

NVIDIA Performance Primitives (NPP)
Version 8.0

January 28, 2016

Contents

1	NVIDIA Performance Primitives	1
1.1	What is NPP?	2
1.2	Documentation	2
1.3	Technical Specifications	3
1.4	Files	3
1.4.1	Header Files	3
1.4.2	Library Files	3
1.5	Supported NVIDIA Hardware	4
2	General API Conventions	5
2.1	Memory Management	6
2.1.1	Scratch Buffer and Host Pointer	6
2.2	Function Naming	7
2.3	Integer Result Scaling	7
2.4	Rounding Modes	8
2.4.1	Rounding Mode Parameter	8
3	Signal-Processing Specific API Conventions	9
3.1	Signal Data	10
3.1.1	Parameter Names for Signal Data	10
3.1.1.1	Source Signal Pointer	10
3.1.1.2	Destination Signal Pointer	10
3.1.1.3	In-Place Signal Pointer	10
3.1.2	Signal Data Alignment Requirements	11
3.1.3	Signal Data Related Error Codes	11
3.2	Signal Length	11
3.2.1	Length Related Error Codes	11
4	Imaging-Processing Specific API Conventions	13

4.1	Function Naming	14
4.2	Image Data	14
4.2.1	Line Step	15
4.2.2	Parameter Names for Image Data	15
4.2.2.1	Passing Source-Image Data	15
4.2.2.2	Passing Destination-Image Data	16
4.2.2.3	Passing In-Place Image Data	18
4.2.2.4	Passing Mask-Image Data	18
4.2.2.5	Passing Channel-of-Interest Data	18
4.2.3	Image Data Alignment Requirements	18
4.2.4	Image Data Related Error Codes	19
4.3	Region-of-Interest (ROI)	19
4.3.1	ROI Related Error Codes	19
4.4	Masked Operation	20
4.5	Channel-of-Interest API	20
4.5.1	Select-Channel Source-Image Pointer	20
4.5.2	Select-Channel Source-Image	20
4.5.3	Select-Channel Destination-Image Pointer	20
4.6	Source-Image Sampling	21
4.6.1	Point-Wise Operations	21
4.6.2	Neighborhood Operations	21
4.6.2.1	Mask-Size Parameter	21
4.6.2.2	Anchor-Point Parameter	22
4.6.2.3	Sampling Beyond Image Boundaries	22
5	Module Index	23
5.1	Modules	23
6	Data Structure Index	25
6.1	Data Structures	25
7	Module Documentation	27
7.1	NPP Core	27
7.1.1	Detailed Description	28
7.1.2	Function Documentation	28
7.1.2.1	nppGetGpuComputeCapability	28
7.1.2.2	nppGetGpuDeviceProperties	28
7.1.2.3	nppGetGpuName	28

7.1.2.4	nppGetGpuNumSMs	28
7.1.2.5	nppGetLibVersion	29
7.1.2.6	nppGetMaxThreadsPerBlock	29
7.1.2.7	nppGetMaxThreadsPerSM	29
7.1.2.8	nppGetStream	29
7.1.2.9	nppGetStreamMaxThreadsPerSM	29
7.1.2.10	nppGetStreamNumSMs	29
7.1.2.11	nppSetStream	30
7.2	NPP Type Definitions and Constants	31
7.2.1	Define Documentation	37
7.2.1.1	NPP_MAX_16S	37
7.2.1.2	NPP_MAX_16U	37
7.2.1.3	NPP_MAX_32S	37
7.2.1.4	NPP_MAX_32U	37
7.2.1.5	NPP_MAX_64S	37
7.2.1.6	NPP_MAX_64U	37
7.2.1.7	NPP_MAX_8S	37
7.2.1.8	NPP_MAX_8U	37
7.2.1.9	NPP_MAXABS_32F	37
7.2.1.10	NPP_MAXABS_64F	37
7.2.1.11	NPP_MIN_16S	38
7.2.1.12	NPP_MIN_16U	38
7.2.1.13	NPP_MIN_32S	38
7.2.1.14	NPP_MIN_32U	38
7.2.1.15	NPP_MIN_64S	38
7.2.1.16	NPP_MIN_64U	38
7.2.1.17	NPP_MIN_8S	38
7.2.1.18	NPP_MIN_8U	38
7.2.1.19	NPP_MINABS_32F	38
7.2.1.20	NPP_MINABS_64F	38
7.2.2	Enumeration Type Documentation	38
7.2.2.1	NppCmpOp	38
7.2.2.2	NppGpuComputeCapability	39
7.2.2.3	NppHintAlgorithm	39
7.2.2.4	NppiAlphaOp	39
7.2.2.5	NppiAxis	40

7.2.2.6	<code>NppiBayerGridPosition</code>	40
7.2.2.7	<code>NppiBorderType</code>	40
7.2.2.8	<code>NppiDifferentialKernel</code>	40
7.2.2.9	<code>NppiHuffmanTableType</code>	41
7.2.2.10	<code>NppiInterpolationMode</code>	41
7.2.2.11	<code>NppiMaskSize</code>	41
7.2.2.12	<code>NppiNorm</code>	42
7.2.2.13	<code>NppRoundMode</code>	42
7.2.2.14	<code>NppStatus</code>	43
7.2.2.15	<code>NppsZCType</code>	45
7.3	Basic NPP Data Types	46
7.3.1	Typedef Documentation	47
7.3.1.1	<code>Npp16s</code>	47
7.3.1.2	<code>Npp16u</code>	47
7.3.1.3	<code>Npp32f</code>	47
7.3.1.4	<code>Npp32fc</code>	47
7.3.1.5	<code>Npp32s</code>	47
7.3.1.6	<code>Npp32sc</code>	48
7.3.1.7	<code>Npp32u</code>	48
7.3.1.8	<code>Npp32uc</code>	48
7.3.1.9	<code>Npp64f</code>	48
7.3.1.10	<code>Npp64fc</code>	48
7.3.1.11	<code>Npp64s</code>	48
7.3.1.12	<code>Npp64sc</code>	48
7.3.1.13	<code>Npp64u</code>	48
7.3.1.14	<code>Npp8s</code>	48
7.3.1.15	<code>Npp8u</code>	48
7.3.2	Function Documentation	48
7.3.2.1	<code>__align__</code>	48
7.3.2.2	<code>__align__</code>	49
7.3.3	Variable Documentation	49
7.3.3.1	<code>Npp16sc</code>	49
7.3.3.2	<code>Npp16uc</code>	49
7.3.3.3	<code>Npp8uc</code>	49
7.4	Arithmetic and Logical Operations	50
7.4.1	Detailed Description	50

7.5	Arithmetic Operations	51
7.6	AddC	53
7.6.1	Detailed Description	58
7.6.2	Function Documentation	58
7.6.2.1	nppiAddC_16s_AC4IRSfs	58
7.6.2.2	nppiAddC_16s_AC4RSfs	58
7.6.2.3	nppiAddC_16s_C1IRSfs	58
7.6.2.4	nppiAddC_16s_C1RSfs	59
7.6.2.5	nppiAddC_16s_C3IRSfs	59
7.6.2.6	nppiAddC_16s_C3RSfs	60
7.6.2.7	nppiAddC_16s_C4IRSfs	60
7.6.2.8	nppiAddC_16s_C4RSfs	60
7.6.2.9	nppiAddC_16sc_AC4IRSfs	61
7.6.2.10	nppiAddC_16sc_AC4RSfs	61
7.6.2.11	nppiAddC_16sc_C1IRSfs	62
7.6.2.12	nppiAddC_16sc_C1RSfs	62
7.6.2.13	nppiAddC_16sc_C3IRSfs	62
7.6.2.14	nppiAddC_16sc_C3RSfs	63
7.6.2.15	nppiAddC_16u_AC4IRSfs	63
7.6.2.16	nppiAddC_16u_AC4RSfs	64
7.6.2.17	nppiAddC_16u_C1IRSfs	64
7.6.2.18	nppiAddC_16u_C1RSfs	64
7.6.2.19	nppiAddC_16u_C3IRSfs	65
7.6.2.20	nppiAddC_16u_C3RSfs	65
7.6.2.21	nppiAddC_16u_C4IRSfs	66
7.6.2.22	nppiAddC_16u_C4RSfs	66
7.6.2.23	nppiAddC_32f_AC4IR	66
7.6.2.24	nppiAddC_32f_AC4R	67
7.6.2.25	nppiAddC_32f_C1IR	67
7.6.2.26	nppiAddC_32f_C1R	67
7.6.2.27	nppiAddC_32f_C3IR	68
7.6.2.28	nppiAddC_32f_C3R	68
7.6.2.29	nppiAddC_32f_C4IR	68
7.6.2.30	nppiAddC_32f_C4R	69
7.6.2.31	nppiAddC_32fc_AC4IR	69
7.6.2.32	nppiAddC_32fc_AC4R	69

7.6.2.33	nppiAddC_32fc_C1IR	70
7.6.2.34	nppiAddC_32fc_C1R	70
7.6.2.35	nppiAddC_32fc_C3IR	70
7.6.2.36	nppiAddC_32fc_C3R	71
7.6.2.37	nppiAddC_32fc_C4IR	71
7.6.2.38	nppiAddC_32fc_C4R	71
7.6.2.39	nppiAddC_32s_C1IRSfs	72
7.6.2.40	nppiAddC_32s_C1RSfs	72
7.6.2.41	nppiAddC_32s_C3IRSfs	72
7.6.2.42	nppiAddC_32s_C3RSfs	73
7.6.2.43	nppiAddC_32sc_AC4IRSfs	73
7.6.2.44	nppiAddC_32sc_AC4RSfs	74
7.6.2.45	nppiAddC_32sc_C1IRSfs	74
7.6.2.46	nppiAddC_32sc_C1RSfs	74
7.6.2.47	nppiAddC_32sc_C3IRSfs	75
7.6.2.48	nppiAddC_32sc_C3RSfs	75
7.6.2.49	nppiAddC_8u_AC4IRSfs	76
7.6.2.50	nppiAddC_8u_AC4RSfs	76
7.6.2.51	nppiAddC_8u_C1IRSfs	76
7.6.2.52	nppiAddC_8u_C1RSfs	77
7.6.2.53	nppiAddC_8u_C3IRSfs	77
7.6.2.54	nppiAddC_8u_C3RSfs	77
7.6.2.55	nppiAddC_8u_C4IRSfs	78
7.6.2.56	nppiAddC_8u_C4RSfs	78
7.7	MulC	79
7.7.1	Detailed Description	84
7.7.2	Function Documentation	84
7.7.2.1	nppiMulC_16s_AC4IRSfs	84
7.7.2.2	nppiMulC_16s_AC4RSfs	84
7.7.2.3	nppiMulC_16s_C1IRSfs	85
7.7.2.4	nppiMulC_16s_C1RSfs	85
7.7.2.5	nppiMulC_16s_C3IRSfs	85
7.7.2.6	nppiMulC_16s_C3RSfs	86
7.7.2.7	nppiMulC_16s_C4IRSfs	86
7.7.2.8	nppiMulC_16s_C4RSfs	86
7.7.2.9	nppiMulC_16sc_AC4IRSfs	87

7.7.2.10	nppiMulC_16sc_AC4RSfs	87
7.7.2.11	nppiMulC_16sc_C1IRSfs	88
7.7.2.12	nppiMulC_16sc_C1RSfs	88
7.7.2.13	nppiMulC_16sc_C3IRSfs	88
7.7.2.14	nppiMulC_16sc_C3RSfs	89
7.7.2.15	nppiMulC_16u_AC4IRSfs	89
7.7.2.16	nppiMulC_16u_AC4RSfs	90
7.7.2.17	nppiMulC_16u_C1IRSfs	90
7.7.2.18	nppiMulC_16u_C1RSfs	90
7.7.2.19	nppiMulC_16u_C3IRSfs	91
7.7.2.20	nppiMulC_16u_C3RSfs	91
7.7.2.21	nppiMulC_16u_C4IRSfs	92
7.7.2.22	nppiMulC_16u_C4RSfs	92
7.7.2.23	nppiMulC_32f_AC4IR	92
7.7.2.24	nppiMulC_32f_AC4R	93
7.7.2.25	nppiMulC_32f_C1IR	93
7.7.2.26	nppiMulC_32f_C1R	93
7.7.2.27	nppiMulC_32f_C3IR	94
7.7.2.28	nppiMulC_32f_C3R	94
7.7.2.29	nppiMulC_32f_C4IR	94
7.7.2.30	nppiMulC_32f_C4R	95
7.7.2.31	nppiMulC_32fc_AC4IR	95
7.7.2.32	nppiMulC_32fc_AC4R	95
7.7.2.33	nppiMulC_32fc_C1IR	96
7.7.2.34	nppiMulC_32fc_C1R	96
7.7.2.35	nppiMulC_32fc_C3IR	96
7.7.2.36	nppiMulC_32fc_C3R	97
7.7.2.37	nppiMulC_32fc_C4IR	97
7.7.2.38	nppiMulC_32fc_C4R	97
7.7.2.39	nppiMulC_32s_C1IRSfs	98
7.7.2.40	nppiMulC_32s_C1RSfs	98
7.7.2.41	nppiMulC_32s_C3IRSfs	98
7.7.2.42	nppiMulC_32s_C3RSfs	99
7.7.2.43	nppiMulC_32sc_AC4IRSfs	99
7.7.2.44	nppiMulC_32sc_AC4RSfs	100
7.7.2.45	nppiMulC_32sc_C1IRSfs	100

7.7.2.46	nppiMulC_32sc_C1RSfs	100
7.7.2.47	nppiMulC_32sc_C3RSfs	101
7.7.2.48	nppiMulC_32sc_C3RSfs	101
7.7.2.49	nppiMulC_8u_AC4RSfs	102
7.7.2.50	nppiMulC_8u_AC4RSfs	102
7.7.2.51	nppiMulC_8u_C1RSfs	102
7.7.2.52	nppiMulC_8u_C1RSfs	103
7.7.2.53	nppiMulC_8u_C3RSfs	103
7.7.2.54	nppiMulC_8u_C3RSfs	103
7.7.2.55	nppiMulC_8u_C4RSfs	104
7.7.2.56	nppiMulC_8u_C4RSfs	104
7.8	MulCScale	105
7.8.1	Detailed Description	106
7.8.2	Function Documentation	106
7.8.2.1	nppiMulCScale_16u_AC4IR	106
7.8.2.2	nppiMulCScale_16u_AC4R	107
7.8.2.3	nppiMulCScale_16u_C1IR	107
7.8.2.4	nppiMulCScale_16u_C1R	107
7.8.2.5	nppiMulCScale_16u_C3IR	108
7.8.2.6	nppiMulCScale_16u_C3R	108
7.8.2.7	nppiMulCScale_16u_C4IR	108
7.8.2.8	nppiMulCScale_16u_C4R	109
7.8.2.9	nppiMulCScale_8u_AC4IR	109
7.8.2.10	nppiMulCScale_8u_AC4R	109
7.8.2.11	nppiMulCScale_8u_C1IR	110
7.8.2.12	nppiMulCScale_8u_C1R	110
7.8.2.13	nppiMulCScale_8u_C3IR	110
7.8.2.14	nppiMulCScale_8u_C3R	111
7.8.2.15	nppiMulCScale_8u_C4IR	111
7.8.2.16	nppiMulCScale_8u_C4R	111
7.9	SubC	112
7.9.1	Detailed Description	117
7.9.2	Function Documentation	117
7.9.2.1	nppiSubC_16s_AC4RSfs	117
7.9.2.2	nppiSubC_16s_AC4RSfs	117
7.9.2.3	nppiSubC_16s_C1RSfs	117

7.9.2.4	nppiSubC_16s_C1RSfs	118
7.9.2.5	nppiSubC_16s_C3RSfs	118
7.9.2.6	nppiSubC_16s_C3RSfs	119
7.9.2.7	nppiSubC_16s_C4RSfs	119
7.9.2.8	nppiSubC_16s_C4RSfs	119
7.9.2.9	nppiSubC_16sc_AC4RSfs	120
7.9.2.10	nppiSubC_16sc_AC4RSfs	120
7.9.2.11	nppiSubC_16sc_C1RSfs	121
7.9.2.12	nppiSubC_16sc_C1RSfs	121
7.9.2.13	nppiSubC_16sc_C3RSfs	121
7.9.2.14	nppiSubC_16sc_C3RSfs	122
7.9.2.15	nppiSubC_16u_AC4RSfs	122
7.9.2.16	nppiSubC_16u_AC4RSfs	123
7.9.2.17	nppiSubC_16u_C1RSfs	123
7.9.2.18	nppiSubC_16u_C1RSfs	123
7.9.2.19	nppiSubC_16u_C3RSfs	124
7.9.2.20	nppiSubC_16u_C3RSfs	124
7.9.2.21	nppiSubC_16u_C4RSfs	125
7.9.2.22	nppiSubC_16u_C4RSfs	125
7.9.2.23	nppiSubC_32f_AC4IR	125
7.9.2.24	nppiSubC_32f_AC4R	126
7.9.2.25	nppiSubC_32f_C1IR	126
7.9.2.26	nppiSubC_32f_C1R	126
7.9.2.27	nppiSubC_32f_C3IR	127
7.9.2.28	nppiSubC_32f_C3R	127
7.9.2.29	nppiSubC_32f_C4IR	127
7.9.2.30	nppiSubC_32f_C4R	128
7.9.2.31	nppiSubC_32fc_AC4IR	128
7.9.2.32	nppiSubC_32fc_AC4R	128
7.9.2.33	nppiSubC_32fc_C1IR	129
7.9.2.34	nppiSubC_32fc_C1R	129
7.9.2.35	nppiSubC_32fc_C3IR	129
7.9.2.36	nppiSubC_32fc_C3R	130
7.9.2.37	nppiSubC_32fc_C4IR	130
7.9.2.38	nppiSubC_32fc_C4R	130
7.9.2.39	nppiSubC_32s_C1RSfs	131

7.9.2.40	nppiSubC_32s_C1RSfs	131
7.9.2.41	nppiSubC_32s_C3RSfs	131
7.9.2.42	nppiSubC_32s_C3RSfs	132
7.9.2.43	nppiSubC_32sc_AC4RSfs	132
7.9.2.44	nppiSubC_32sc_AC4RSfs	133
7.9.2.45	nppiSubC_32sc_C1RSfs	133
7.9.2.46	nppiSubC_32sc_C1RSfs	133
7.9.2.47	nppiSubC_32sc_C3RSfs	134
7.9.2.48	nppiSubC_32sc_C3RSfs	134
7.9.2.49	nppiSubC_8u_AC4RSfs	135
7.9.2.50	nppiSubC_8u_AC4RSfs	135
7.9.2.51	nppiSubC_8u_C1RSfs	135
7.9.2.52	nppiSubC_8u_C1RSfs	136
7.9.2.53	nppiSubC_8u_C3RSfs	136
7.9.2.54	nppiSubC_8u_C3RSfs	136
7.9.2.55	nppiSubC_8u_C4RSfs	137
7.9.2.56	nppiSubC_8u_C4RSfs	137
7.10	DivC	138
7.10.1	Detailed Description	143
7.10.2	Function Documentation	143
7.10.2.1	nppiDivC_16s_AC4RSfs	143
7.10.2.2	nppiDivC_16s_AC4RSfs	143
7.10.2.3	nppiDivC_16s_C1RSfs	144
7.10.2.4	nppiDivC_16s_C1RSfs	144
7.10.2.5	nppiDivC_16s_C3RSfs	144
7.10.2.6	nppiDivC_16s_C3RSfs	145
7.10.2.7	nppiDivC_16s_C4RSfs	145
7.10.2.8	nppiDivC_16s_C4RSfs	145
7.10.2.9	nppiDivC_16sc_AC4RSfs	146
7.10.2.10	nppiDivC_16sc_AC4RSfs	146
7.10.2.11	nppiDivC_16sc_C1RSfs	147
7.10.2.12	nppiDivC_16sc_C1RSfs	147
7.10.2.13	nppiDivC_16sc_C3RSfs	147
7.10.2.14	nppiDivC_16sc_C3RSfs	148
7.10.2.15	nppiDivC_16u_AC4RSfs	148
7.10.2.16	nppiDivC_16u_AC4RSfs	149

7.10.2.17 nppiDivC_16u_C1RSfs	149
7.10.2.18 nppiDivC_16u_C1RSfs	149
7.10.2.19 nppiDivC_16u_C3RSfs	150
7.10.2.20 nppiDivC_16u_C3RSfs	150
7.10.2.21 nppiDivC_16u_C4RSfs	151
7.10.2.22 nppiDivC_16u_C4RSfs	151
7.10.2.23 nppiDivC_32f_AC4IR	151
7.10.2.24 nppiDivC_32f_AC4R	152
7.10.2.25 nppiDivC_32f_C1IR	152
7.10.2.26 nppiDivC_32f_C1R	152
7.10.2.27 nppiDivC_32f_C3IR	153
7.10.2.28 nppiDivC_32f_C3R	153
7.10.2.29 nppiDivC_32f_C4IR	153
7.10.2.30 nppiDivC_32f_C4R	154
7.10.2.31 nppiDivC_32fc_AC4IR	154
7.10.2.32 nppiDivC_32fc_AC4R	154
7.10.2.33 nppiDivC_32fc_C1IR	155
7.10.2.34 nppiDivC_32fc_C1R	155
7.10.2.35 nppiDivC_32fc_C3IR	155
7.10.2.36 nppiDivC_32fc_C3R	156
7.10.2.37 nppiDivC_32fc_C4IR	156
7.10.2.38 nppiDivC_32fc_C4R	156
7.10.2.39 nppiDivC_32s_C1RSfs	157
7.10.2.40 nppiDivC_32s_C1RSfs	157
7.10.2.41 nppiDivC_32s_C3RSfs	157
7.10.2.42 nppiDivC_32s_C3RSfs	158
7.10.2.43 nppiDivC_32sc_AC4RSfs	158
7.10.2.44 nppiDivC_32sc_AC4RSfs	159
7.10.2.45 nppiDivC_32sc_C1RSfs	159
7.10.2.46 nppiDivC_32sc_C1RSfs	159
7.10.2.47 nppiDivC_32sc_C3RSfs	160
7.10.2.48 nppiDivC_32sc_C3RSfs	160
7.10.2.49 nppiDivC_8u_AC4RSfs	161
7.10.2.50 nppiDivC_8u_AC4RSfs	161
7.10.2.51 nppiDivC_8u_C1RSfs	161
7.10.2.52 nppiDivC_8u_C1RSfs	162

7.10.2.53	nppiDivC_8u_C3IRSfs	162
7.10.2.54	nppiDivC_8u_C3RSfs	162
7.10.2.55	nppiDivC_8u_C4IRSfs	163
7.10.2.56	nppiDivC_8u_C4RSfs	163
7.11	AbsDiffC	164
7.11.1	Detailed Description	164
7.11.2	Function Documentation	164
7.11.2.1	nppiAbsDiffC_16u_C1R	164
7.11.2.2	nppiAbsDiffC_32f_C1R	164
7.11.2.3	nppiAbsDiffC_8u_C1R	165
7.12	Add	166
7.12.1	Detailed Description	171
7.12.2	Function Documentation	171
7.12.2.1	nppiAdd_16s_AC4IRSfs	171
7.12.2.2	nppiAdd_16s_AC4RSfs	171
7.12.2.3	nppiAdd_16s_C1IRSfs	172
7.12.2.4	nppiAdd_16s_C1RSfs	172
7.12.2.5	nppiAdd_16s_C3IRSfs	173
7.12.2.6	nppiAdd_16s_C3RSfs	173
7.12.2.7	nppiAdd_16s_C4IRSfs	174
7.12.2.8	nppiAdd_16s_C4RSfs	174
7.12.2.9	nppiAdd_16sc_AC4IRSfs	174
7.12.2.10	nppiAdd_16sc_AC4RSfs	175
7.12.2.11	nppiAdd_16sc_C1IRSfs	175
7.12.2.12	nppiAdd_16sc_C1RSfs	176
7.12.2.13	nppiAdd_16sc_C3IRSfs	176
7.12.2.14	nppiAdd_16sc_C3RSfs	176
7.12.2.15	nppiAdd_16u_AC4IRSfs	177
7.12.2.16	nppiAdd_16u_AC4RSfs	177
7.12.2.17	nppiAdd_16u_C1IRSfs	178
7.12.2.18	nppiAdd_16u_C1RSfs	178
7.12.2.19	nppiAdd_16u_C3IRSfs	179
7.12.2.20	nppiAdd_16u_C3RSfs	179
7.12.2.21	nppiAdd_16u_C4IRSfs	179
7.12.2.22	nppiAdd_16u_C4RSfs	180
7.12.2.23	nppiAdd_32f_AC4IR	180

7.12.2.24 nppiAdd_32f_AC4R	181
7.12.2.25 nppiAdd_32f_C1IR	181
7.12.2.26 nppiAdd_32f_C1R	181
7.12.2.27 nppiAdd_32f_C3IR	182
7.12.2.28 nppiAdd_32f_C3R	182
7.12.2.29 nppiAdd_32f_C4IR	183
7.12.2.30 nppiAdd_32f_C4R	183
7.12.2.31 nppiAdd_32fc_AC4IR	183
7.12.2.32 nppiAdd_32fc_AC4R	184
7.12.2.33 nppiAdd_32fc_C1IR	184
7.12.2.34 nppiAdd_32fc_C1R	184
7.12.2.35 nppiAdd_32fc_C3IR	185
7.12.2.36 nppiAdd_32fc_C3R	185
7.12.2.37 nppiAdd_32fc_C4IR	186
7.12.2.38 nppiAdd_32fc_C4R	186
7.12.2.39 nppiAdd_32s_C1IRSfs	186
7.12.2.40 nppiAdd_32s_C1R	187
7.12.2.41 nppiAdd_32s_C1RSfs	187
7.12.2.42 nppiAdd_32s_C3IRSfs	188
7.12.2.43 nppiAdd_32s_C3RSfs	188
7.12.2.44 nppiAdd_32sc_AC4IRSfs	188
7.12.2.45 nppiAdd_32sc_AC4RSfs	189
7.12.2.46 nppiAdd_32sc_C1IRSfs	189
7.12.2.47 nppiAdd_32sc_C1RSfs	190
7.12.2.48 nppiAdd_32sc_C3IRSfs	190
7.12.2.49 nppiAdd_32sc_C3RSfs	190
7.12.2.50 nppiAdd_8u_AC4IRSfs	191
7.12.2.51 nppiAdd_8u_AC4RSfs	191
7.12.2.52 nppiAdd_8u_C1IRSfs	192
7.12.2.53 nppiAdd_8u_C1RSfs	192
7.12.2.54 nppiAdd_8u_C3IRSfs	193
7.12.2.55 nppiAdd_8u_C3RSfs	193
7.12.2.56 nppiAdd_8u_C4IRSfs	193
7.12.2.57 nppiAdd_8u_C4RSfs	194
7.13 AddSquare	195
7.13.1 Detailed Description	195

7.13.2	Function Documentation	195
7.13.2.1	nppiAddSquare_16u32f_C1IMR	195
7.13.2.2	nppiAddSquare_16u32f_C1IR	196
7.13.2.3	nppiAddSquare_32f_C1IMR	196
7.13.2.4	nppiAddSquare_32f_C1IR	197
7.13.2.5	nppiAddSquare_8u32f_C1IMR	197
7.13.2.6	nppiAddSquare_8u32f_C1IR	197
7.14	AddProduct	198
7.14.1	Detailed Description	198
7.14.2	Function Documentation	198
7.14.2.1	nppiAddProduct_16u32f_C1IMR	198
7.14.2.2	nppiAddProduct_16u32f_C1IR	199
7.14.2.3	nppiAddProduct_32f_C1IMR	199
7.14.2.4	nppiAddProduct_32f_C1IR	200
7.14.2.5	nppiAddProduct_8u32f_C1IMR	200
7.14.2.6	nppiAddProduct_8u32f_C1IR	201
7.15	AddWeighted	202
7.15.1	Detailed Description	202
7.15.2	Function Documentation	202
7.15.2.1	nppiAddWeighted_16u32f_C1IMR	202
7.15.2.2	nppiAddWeighted_16u32f_C1IR	203
7.15.2.3	nppiAddWeighted_32f_C1IMR	203
7.15.2.4	nppiAddWeighted_32f_C1IR	204
7.15.2.5	nppiAddWeighted_8u32f_C1IMR	204
7.15.2.6	nppiAddWeighted_8u32f_C1IR	205
7.16	Mul	206
7.16.1	Detailed Description	211
7.16.2	Function Documentation	211
7.16.2.1	nppiMul_16s_AC4IRSfs	211
7.16.2.2	nppiMul_16s_AC4RSfs	212
7.16.2.3	nppiMul_16s_C1IRSfs	212
7.16.2.4	nppiMul_16s_C1RSfs	212
7.16.2.5	nppiMul_16s_C3IRSfs	213
7.16.2.6	nppiMul_16s_C3RSfs	213
7.16.2.7	nppiMul_16s_C4IRSfs	214
7.16.2.8	nppiMul_16s_C4RSfs	214

7.16.2.9	nppiMul_16sc_AC4IRSfs	214
7.16.2.10	nppiMul_16sc_AC4RSfs	215
7.16.2.11	nppiMul_16sc_C1IRSfs	215
7.16.2.12	nppiMul_16sc_C1RSfs	216
7.16.2.13	nppiMul_16sc_C3IRSfs	216
7.16.2.14	nppiMul_16sc_C3RSfs	216
7.16.2.15	nppiMul_16u_AC4IRSfs	217
7.16.2.16	nppiMul_16u_AC4RSfs	217
7.16.2.17	nppiMul_16u_C1IRSfs	218
7.16.2.18	nppiMul_16u_C1RSfs	218
7.16.2.19	nppiMul_16u_C3IRSfs	219
7.16.2.20	nppiMul_16u_C3RSfs	219
7.16.2.21	nppiMul_16u_C4IRSfs	219
7.16.2.22	nppiMul_16u_C4RSfs	220
7.16.2.23	nppiMul_32f_AC4IR	220
7.16.2.24	nppiMul_32f_AC4R	221
7.16.2.25	nppiMul_32f_C1IR	221
7.16.2.26	nppiMul_32f_C1R	221
7.16.2.27	nppiMul_32f_C3IR	222
7.16.2.28	nppiMul_32f_C3R	222
7.16.2.29	nppiMul_32f_C4IR	223
7.16.2.30	nppiMul_32f_C4R	223
7.16.2.31	nppiMul_32fc_AC4IR	223
7.16.2.32	nppiMul_32fc_AC4R	224
7.16.2.33	nppiMul_32fc_C1IR	224
7.16.2.34	nppiMul_32fc_C1R	224
7.16.2.35	nppiMul_32fc_C3IR	225
7.16.2.36	nppiMul_32fc_C3R	225
7.16.2.37	nppiMul_32fc_C4IR	226
7.16.2.38	nppiMul_32fc_C4R	226
7.16.2.39	nppiMul_32s_C1IRSfs	226
7.16.2.40	nppiMul_32s_C1R	227
7.16.2.41	nppiMul_32s_C1RSfs	227
7.16.2.42	nppiMul_32s_C3IRSfs	228
7.16.2.43	nppiMul_32s_C3RSfs	228
7.16.2.44	nppiMul_32sc_AC4IRSfs	228

7.16.2.45	<code>nppiMul_32sc_AC4RSfs</code>	229
7.16.2.46	<code>nppiMul_32sc_C1IRSfs</code>	229
7.16.2.47	<code>nppiMul_32sc_C1RSfs</code>	230
7.16.2.48	<code>nppiMul_32sc_C3IRSfs</code>	230
7.16.2.49	<code>nppiMul_32sc_C3RSfs</code>	230
7.16.2.50	<code>nppiMul_8u_AC4IRSfs</code>	231
7.16.2.51	<code>nppiMul_8u_AC4RSfs</code>	231
7.16.2.52	<code>nppiMul_8u_C1IRSfs</code>	232
7.16.2.53	<code>nppiMul_8u_C1RSfs</code>	232
7.16.2.54	<code>nppiMul_8u_C3IRSfs</code>	233
7.16.2.55	<code>nppiMul_8u_C3RSfs</code>	233
7.16.2.56	<code>nppiMul_8u_C4IRSfs</code>	233
7.16.2.57	<code>nppiMul_8u_C4RSfs</code>	234
7.17	MulScale	235
7.17.1	Detailed Description	236
7.17.2	Function Documentation	236
7.17.2.1	<code>nppiMulScale_16u_AC4IR</code>	236
7.17.2.2	<code>nppiMulScale_16u_AC4R</code>	237
7.17.2.3	<code>nppiMulScale_16u_C1IR</code>	237
7.17.2.4	<code>nppiMulScale_16u_C1R</code>	238
7.17.2.5	<code>nppiMulScale_16u_C3IR</code>	238
7.17.2.6	<code>nppiMulScale_16u_C3R</code>	238
7.17.2.7	<code>nppiMulScale_16u_C4IR</code>	239
7.17.2.8	<code>nppiMulScale_16u_C4R</code>	239
7.17.2.9	<code>nppiMulScale_8u_AC4IR</code>	240
7.17.2.10	<code>nppiMulScale_8u_AC4R</code>	240
7.17.2.11	<code>nppiMulScale_8u_C1IR</code>	240
7.17.2.12	<code>nppiMulScale_8u_C1R</code>	241
7.17.2.13	<code>nppiMulScale_8u_C3IR</code>	241
7.17.2.14	<code>nppiMulScale_8u_C3R</code>	242
7.17.2.15	<code>nppiMulScale_8u_C4IR</code>	242
7.17.2.16	<code>nppiMulScale_8u_C4R</code>	242
7.18	Sub	244
7.18.1	Detailed Description	249
7.18.2	Function Documentation	249
7.18.2.1	<code>nppiSub_16s_AC4IRSfs</code>	249

7.18.2.2	nppiSub_16s_AC4RSfs	250
7.18.2.3	nppiSub_16s_C1IRSfs	250
7.18.2.4	nppiSub_16s_C1RSfs	251
7.18.2.5	nppiSub_16s_C3IRSfs	251
7.18.2.6	nppiSub_16s_C3RSfs	251
7.18.2.7	nppiSub_16s_C4IRSfs	252
7.18.2.8	nppiSub_16s_C4RSfs	252
7.18.2.9	nppiSub_16sc_AC4IRSfs	253
7.18.2.10	nppiSub_16sc_AC4RSfs	253
7.18.2.11	nppiSub_16sc_C1IRSfs	253
7.18.2.12	nppiSub_16sc_C1RSfs	254
7.18.2.13	nppiSub_16sc_C3IRSfs	254
7.18.2.14	nppiSub_16sc_C3RSfs	255
7.18.2.15	nppiSub_16u_AC4IRSfs	255
7.18.2.16	nppiSub_16u_AC4RSfs	255
7.18.2.17	nppiSub_16u_C1IRSfs	256
7.18.2.18	nppiSub_16u_C1RSfs	256
7.18.2.19	nppiSub_16u_C3IRSfs	257
7.18.2.20	nppiSub_16u_C3RSfs	257
7.18.2.21	nppiSub_16u_C4IRSfs	258
7.18.2.22	nppiSub_16u_C4RSfs	258
7.18.2.23	nppiSub_32f_AC4IR	258
7.18.2.24	nppiSub_32f_AC4R	259
7.18.2.25	nppiSub_32f_C1IR	259
7.18.2.26	nppiSub_32f_C1R	260
7.18.2.27	nppiSub_32f_C3IR	260
7.18.2.28	nppiSub_32f_C3R	260
7.18.2.29	nppiSub_32f_C4IR	261
7.18.2.30	nppiSub_32f_C4R	261
7.18.2.31	nppiSub_32fc_AC4IR	262
7.18.2.32	nppiSub_32fc_AC4R	262
7.18.2.33	nppiSub_32fc_C1IR	262
7.18.2.34	nppiSub_32fc_C1R	263
7.18.2.35	nppiSub_32fc_C3IR	263
7.18.2.36	nppiSub_32fc_C3R	264
7.18.2.37	nppiSub_32fc_C4IR	264

7.18.2.38	nppiSub_32fc_C4R	264
7.18.2.39	nppiSub_32s_C1IRSfs	265
7.18.2.40	nppiSub_32s_C1R	265
7.18.2.41	nppiSub_32s_C1RSfs	266
7.18.2.42	nppiSub_32s_C3IRSfs	266
7.18.2.43	nppiSub_32s_C3RSfs	266
7.18.2.44	nppiSub_32s_C4IRSfs	267
7.18.2.45	nppiSub_32s_C4RSfs	267
7.18.2.46	nppiSub_32sc_AC4IRSfs	268
7.18.2.47	nppiSub_32sc_AC4RSfs	268
7.18.2.48	nppiSub_32sc_C1IRSfs	269
7.18.2.49	nppiSub_32sc_C1RSfs	269
7.18.2.50	nppiSub_32sc_C3IRSfs	269
7.18.2.51	nppiSub_32sc_C3RSfs	270
7.18.2.52	nppiSub_8u_AC4IRSfs	270
7.18.2.53	nppiSub_8u_AC4RSfs	271
7.18.2.54	nppiSub_8u_C1IRSfs	271
7.18.2.55	nppiSub_8u_C1RSfs	271
7.18.2.56	nppiSub_8u_C3IRSfs	272
7.18.2.57	nppiSub_8u_C3RSfs	272
7.18.2.58	nppiSub_8u_C4IRSfs	273
7.18.2.59	nppiSub_8u_C4RSfs	273
7.19	Div	274
7.19.1	Detailed Description	279
7.19.2	Function Documentation	279
7.19.2.1	nppiDiv_16s_AC4IRSfs	279
7.19.2.2	nppiDiv_16s_AC4RSfs	279
7.19.2.3	nppiDiv_16s_C1IRSfs	280
7.19.2.4	nppiDiv_16s_C1RSfs	280
7.19.2.5	nppiDiv_16s_C3IRSfs	281
7.19.2.6	nppiDiv_16s_C3RSfs	281
7.19.2.7	nppiDiv_16s_C4IRSfs	281
7.19.2.8	nppiDiv_16s_C4RSfs	282
7.19.2.9	nppiDiv_16sc_AC4IRSfs	282
7.19.2.10	nppiDiv_16sc_AC4RSfs	283
7.19.2.11	nppiDiv_16sc_C1IRSfs	283

7.19.2.12 nppiDiv_16sc_C1RSfs	283
7.19.2.13 nppiDiv_16sc_C3IRSfs	284
7.19.2.14 nppiDiv_16sc_C3RSfs	284
7.19.2.15 nppiDiv_16u_AC4IRSfs	285
7.19.2.16 nppiDiv_16u_AC4RSfs	285
7.19.2.17 nppiDiv_16u_C1IRSfs	286
7.19.2.18 nppiDiv_16u_C1RSfs	286
7.19.2.19 nppiDiv_16u_C3IRSfs	286
7.19.2.20 nppiDiv_16u_C3RSfs	287
7.19.2.21 nppiDiv_16u_C4IRSfs	287
7.19.2.22 nppiDiv_16u_C4RSfs	288
7.19.2.23 nppiDiv_32f_AC4IR	288
7.19.2.24 nppiDiv_32f_AC4R	288
7.19.2.25 nppiDiv_32f_C1IR	289
7.19.2.26 nppiDiv_32f_C1R	289
7.19.2.27 nppiDiv_32f_C3IR	290
7.19.2.28 nppiDiv_32f_C3R	290
7.19.2.29 nppiDiv_32f_C4IR	290
7.19.2.30 nppiDiv_32f_C4R	291
7.19.2.31 nppiDiv_32fc_AC4IR	291
7.19.2.32 nppiDiv_32fc_AC4R	291
7.19.2.33 nppiDiv_32fc_C1IR	292
7.19.2.34 nppiDiv_32fc_C1R	292
7.19.2.35 nppiDiv_32fc_C3IR	293
7.19.2.36 nppiDiv_32fc_C3R	293
7.19.2.37 nppiDiv_32fc_C4IR	293
7.19.2.38 nppiDiv_32fc_C4R	294
7.19.2.39 nppiDiv_32s_C1IRSfs	294
7.19.2.40 nppiDiv_32s_C1R	294
7.19.2.41 nppiDiv_32s_C1RSfs	295
7.19.2.42 nppiDiv_32s_C3IRSfs	295
7.19.2.43 nppiDiv_32s_C3RSfs	296
7.19.2.44 nppiDiv_32sc_AC4IRSfs	296
7.19.2.45 nppiDiv_32sc_AC4RSfs	296
7.19.2.46 nppiDiv_32sc_C1IRSfs	297
7.19.2.47 nppiDiv_32sc_C1RSfs	297

7.19.2.48	nppiDiv_32sc_C3IRSfs	298
7.19.2.49	nppiDiv_32sc_C3RSfs	298
7.19.2.50	nppiDiv_8u_AC4IRSfs	299
7.19.2.51	nppiDiv_8u_AC4RSfs	299
7.19.2.52	nppiDiv_8u_C1IRSfs	299
7.19.2.53	nppiDiv_8u_C1RSfs	300
7.19.2.54	nppiDiv_8u_C3IRSfs	300
7.19.2.55	nppiDiv_8u_C3RSfs	301
7.19.2.56	nppiDiv_8u_C4IRSfs	301
7.19.2.57	nppiDiv_8u_C4RSfs	301
7.20	Div_Round	303
7.20.1	Detailed Description	305
7.20.2	Function Documentation	305
7.20.2.1	nppiDiv_Round_16s_AC4IRSfs	305
7.20.2.2	nppiDiv_Round_16s_AC4RSfs	306
7.20.2.3	nppiDiv_Round_16s_C1IRSfs	306
7.20.2.4	nppiDiv_Round_16s_C1RSfs	307
7.20.2.5	nppiDiv_Round_16s_C3IRSfs	307
7.20.2.6	nppiDiv_Round_16s_C3RSfs	308
7.20.2.7	nppiDiv_Round_16s_C4IRSfs	308
7.20.2.8	nppiDiv_Round_16s_C4RSfs	309
7.20.2.9	nppiDiv_Round_16u_AC4IRSfs	309
7.20.2.10	nppiDiv_Round_16u_AC4RSfs	310
7.20.2.11	nppiDiv_Round_16u_C1IRSfs	310
7.20.2.12	nppiDiv_Round_16u_C1RSfs	311
7.20.2.13	nppiDiv_Round_16u_C3IRSfs	311
7.20.2.14	nppiDiv_Round_16u_C3RSfs	312
7.20.2.15	nppiDiv_Round_16u_C4IRSfs	312
7.20.2.16	nppiDiv_Round_16u_C4RSfs	313
7.20.2.17	nppiDiv_Round_8u_AC4IRSfs	313
7.20.2.18	nppiDiv_Round_8u_AC4RSfs	314
7.20.2.19	nppiDiv_Round_8u_C1IRSfs	314
7.20.2.20	nppiDiv_Round_8u_C1RSfs	315
7.20.2.21	nppiDiv_Round_8u_C3IRSfs	315
7.20.2.22	nppiDiv_Round_8u_C3RSfs	316
7.20.2.23	nppiDiv_Round_8u_C4IRSfs	316

7.20.2.24	nppiDiv_Round_8u_C4RSfs	317
7.21	Abs	318
7.21.1	Detailed Description	319
7.21.2	Function Documentation	319
7.21.2.1	nppiAbs_16s_AC4IR	319
7.21.2.2	nppiAbs_16s_AC4R	319
7.21.2.3	nppiAbs_16s_C1IR	320
7.21.2.4	nppiAbs_16s_C1R	320
7.21.2.5	nppiAbs_16s_C3IR	320
7.21.2.6	nppiAbs_16s_C3R	321
7.21.2.7	nppiAbs_16s_C4IR	321
7.21.2.8	nppiAbs_16s_C4R	321
7.21.2.9	nppiAbs_32f_AC4IR	322
7.21.2.10	nppiAbs_32f_AC4R	322
7.21.2.11	nppiAbs_32f_C1IR	322
7.21.2.12	nppiAbs_32f_C1R	323
7.21.2.13	nppiAbs_32f_C3IR	323
7.21.2.14	nppiAbs_32f_C3R	323
7.21.2.15	nppiAbs_32f_C4IR	324
7.21.2.16	nppiAbs_32f_C4R	324
7.22	AbsDiff	325
7.22.1	Detailed Description	325
7.22.2	Function Documentation	325
7.22.2.1	nppiAbsDiff_16u_C1R	325
7.22.2.2	nppiAbsDiff_32f_C1R	326
7.22.2.3	nppiAbsDiff_8u_C1R	326
7.22.2.4	nppiAbsDiff_8u_C3R	326
7.22.2.5	nppiAbsDiff_8u_C4R	327
7.23	Sqr	328
7.23.1	Detailed Description	330
7.23.2	Function Documentation	331
7.23.2.1	nppiSqr_16s_AC4IRSfs	331
7.23.2.2	nppiSqr_16s_AC4RSfs	331
7.23.2.3	nppiSqr_16s_C1IRSfs	331
7.23.2.4	nppiSqr_16s_C1RSfs	332
7.23.2.5	nppiSqr_16s_C3IRSfs	332

7.23.2.6	nppiSqr_16s_C3RSfs	332
7.23.2.7	nppiSqr_16s_C4IRSfs	333
7.23.2.8	nppiSqr_16s_C4RSfs	333
7.23.2.9	nppiSqr_16u_AC4IRSfs	333
7.23.2.10	nppiSqr_16u_AC4RSfs	334
7.23.2.11	nppiSqr_16u_C1IRSfs	334
7.23.2.12	nppiSqr_16u_C1RSfs	334
7.23.2.13	nppiSqr_16u_C3IRSfs	335
7.23.2.14	nppiSqr_16u_C3RSfs	335
7.23.2.15	nppiSqr_16u_C4IRSfs	335
7.23.2.16	nppiSqr_16u_C4RSfs	336
7.23.2.17	nppiSqr_32f_AC4IR	336
7.23.2.18	nppiSqr_32f_AC4R	336
7.23.2.19	nppiSqr_32f_C1IR	337
7.23.2.20	nppiSqr_32f_C1R	337
7.23.2.21	nppiSqr_32f_C3IR	337
7.23.2.22	nppiSqr_32f_C3R	338
7.23.2.23	nppiSqr_32f_C4IR	338
7.23.2.24	nppiSqr_32f_C4R	338
7.23.2.25	nppiSqr_8u_AC4IRSfs	339
7.23.2.26	nppiSqr_8u_AC4RSfs	339
7.23.2.27	nppiSqr_8u_C1IRSfs	339
7.23.2.28	nppiSqr_8u_C1RSfs	340
7.23.2.29	nppiSqr_8u_C3IRSfs	340
7.23.2.30	nppiSqr_8u_C3RSfs	340
7.23.2.31	nppiSqr_8u_C4IRSfs	341
7.23.2.32	nppiSqr_8u_C4RSfs	341
7.24	Sqrt	342
7.24.1	Detailed Description	344
7.24.2	Function Documentation	344
7.24.2.1	nppiSqrt_16s_AC4IRSfs	344
7.24.2.2	nppiSqrt_16s_AC4RSfs	345
7.24.2.3	nppiSqrt_16s_C1IRSfs	345
7.24.2.4	nppiSqrt_16s_C1RSfs	345
7.24.2.5	nppiSqrt_16s_C3IRSfs	346
7.24.2.6	nppiSqrt_16s_C3RSfs	346

7.24.2.7	nppiSqrt_16u_AC4IRSfs	346
7.24.2.8	nppiSqrt_16u_AC4RSfs	347
7.24.2.9	nppiSqrt_16u_C1IRSfs	347
7.24.2.10	nppiSqrt_16u_C1RSfs	348
7.24.2.11	nppiSqrt_16u_C3IRSfs	348
7.24.2.12	nppiSqrt_16u_C3RSfs	348
7.24.2.13	nppiSqrt_32f_AC4IR	349
7.24.2.14	nppiSqrt_32f_AC4R	349
7.24.2.15	nppiSqrt_32f_C1IR	349
7.24.2.16	nppiSqrt_32f_C1R	350
7.24.2.17	nppiSqrt_32f_C3IR	350
7.24.2.18	nppiSqrt_32f_C3R	350
7.24.2.19	nppiSqrt_32f_C4IR	351
7.24.2.20	nppiSqrt_32f_C4R	351
7.24.2.21	nppiSqrt_8u_AC4IRSfs	351
7.24.2.22	nppiSqrt_8u_AC4RSfs	352
7.24.2.23	nppiSqrt_8u_C1IRSfs	352
7.24.2.24	nppiSqrt_8u_C1RSfs	352
7.24.2.25	nppiSqrt_8u_C3IRSfs	353
7.24.2.26	nppiSqrt_8u_C3RSfs	353
7.25	Ln	354
7.25.1	Detailed Description	355
7.25.2	Function Documentation	355
7.25.2.1	nppiLn_16s_C1IRSfs	355
7.25.2.2	nppiLn_16s_C1RSfs	356
7.25.2.3	nppiLn_16s_C3IRSfs	356
7.25.2.4	nppiLn_16s_C3RSfs	356
7.25.2.5	nppiLn_16u_C1IRSfs	357
7.25.2.6	nppiLn_16u_C1RSfs	357
7.25.2.7	nppiLn_16u_C3IRSfs	357
7.25.2.8	nppiLn_16u_C3RSfs	358
7.25.2.9	nppiLn_32f_C1IR	358
7.25.2.10	nppiLn_32f_C1R	358
7.25.2.11	nppiLn_32f_C3IR	359
7.25.2.12	nppiLn_32f_C3R	359
7.25.2.13	nppiLn_8u_C1IRSfs	359

7.25.2.14	nppiLn_8u_C1RSfs	360
7.25.2.15	nppiLn_8u_C3RSfs	360
7.25.2.16	nppiLn_8u_C3RSfs	360
7.26	Exp	361
7.26.1	Detailed Description	362
7.26.2	Function Documentation	362
7.26.2.1	nppiExp_16s_C1RSfs	362
7.26.2.2	nppiExp_16s_C1RSfs	363
7.26.2.3	nppiExp_16s_C3RSfs	363
7.26.2.4	nppiExp_16s_C3RSfs	363
7.26.2.5	nppiExp_16u_C1RSfs	364
7.26.2.6	nppiExp_16u_C1RSfs	364
7.26.2.7	nppiExp_16u_C3RSfs	364
7.26.2.8	nppiExp_16u_C3RSfs	365
7.26.2.9	nppiExp_32f_C1IR	365
7.26.2.10	nppiExp_32f_C1R	365
7.26.2.11	nppiExp_32f_C3IR	366
7.26.2.12	nppiExp_32f_C3R	366
7.26.2.13	nppiExp_8u_C1RSfs	366
7.26.2.14	nppiExp_8u_C1RSfs	367
7.26.2.15	nppiExp_8u_C3RSfs	367
7.26.2.16	nppiExp_8u_C3RSfs	367
7.27	Logical Operations	368
7.28	AndC	369
7.28.1	Detailed Description	371
7.28.2	Function Documentation	371
7.28.2.1	nppiAndC_16u_AC4IR	371
7.28.2.2	nppiAndC_16u_AC4R	371
7.28.2.3	nppiAndC_16u_C1IR	371
7.28.2.4	nppiAndC_16u_C1R	372
7.28.2.5	nppiAndC_16u_C3IR	372
7.28.2.6	nppiAndC_16u_C3R	372
7.28.2.7	nppiAndC_16u_C4IR	373
7.28.2.8	nppiAndC_16u_C4R	373
7.28.2.9	nppiAndC_32s_AC4IR	374
7.28.2.10	nppiAndC_32s_AC4R	374

7.28.2.11	nppiAndC_32s_C1IR	374
7.28.2.12	nppiAndC_32s_C1R	375
7.28.2.13	nppiAndC_32s_C3IR	375
7.28.2.14	nppiAndC_32s_C3R	375
7.28.2.15	nppiAndC_32s_C4IR	376
7.28.2.16	nppiAndC_32s_C4R	376
7.28.2.17	nppiAndC_8u_AC4IR	376
7.28.2.18	nppiAndC_8u_AC4R	377
7.28.2.19	nppiAndC_8u_C1IR	377
7.28.2.20	nppiAndC_8u_C1R	377
7.28.2.21	nppiAndC_8u_C3IR	378
7.28.2.22	nppiAndC_8u_C3R	378
7.28.2.23	nppiAndC_8u_C4IR	378
7.28.2.24	nppiAndC_8u_C4R	379
7.29	OrC	380
7.29.1	Detailed Description	382
7.29.2	Function Documentation	382
7.29.2.1	nppiOrC_16u_AC4IR	382
7.29.2.2	nppiOrC_16u_AC4R	382
7.29.2.3	nppiOrC_16u_C1IR	382
7.29.2.4	nppiOrC_16u_C1R	383
7.29.2.5	nppiOrC_16u_C3IR	383
7.29.2.6	nppiOrC_16u_C3R	383
7.29.2.7	nppiOrC_16u_C4IR	384
7.29.2.8	nppiOrC_16u_C4R	384
7.29.2.9	nppiOrC_32s_AC4IR	385
7.29.2.10	nppiOrC_32s_AC4R	385
7.29.2.11	nppiOrC_32s_C1IR	385
7.29.2.12	nppiOrC_32s_C1R	386
7.29.2.13	nppiOrC_32s_C3IR	386
7.29.2.14	nppiOrC_32s_C3R	386
7.29.2.15	nppiOrC_32s_C4IR	387
7.29.2.16	nppiOrC_32s_C4R	387
7.29.2.17	nppiOrC_8u_AC4IR	387
7.29.2.18	nppiOrC_8u_AC4R	388
7.29.2.19	nppiOrC_8u_C1IR	388

7.29.2.20	nppiOrC_8u_C1R	388
7.29.2.21	nppiOrC_8u_C3IR	389
7.29.2.22	nppiOrC_8u_C3R	389
7.29.2.23	nppiOrC_8u_C4IR	389
7.29.2.24	nppiOrC_8u_C4R	390
7.30	XorC	391
7.30.1	Detailed Description	393
7.30.2	Function Documentation	393
7.30.2.1	nppiXorC_16u_AC4IR	393
7.30.2.2	nppiXorC_16u_AC4R	393
7.30.2.3	nppiXorC_16u_C1IR	393
7.30.2.4	nppiXorC_16u_C1R	394
7.30.2.5	nppiXorC_16u_C3IR	394
7.30.2.6	nppiXorC_16u_C3R	394
7.30.2.7	nppiXorC_16u_C4IR	395
7.30.2.8	nppiXorC_16u_C4R	395
7.30.2.9	nppiXorC_32s_AC4IR	396
7.30.2.10	nppiXorC_32s_AC4R	396
7.30.2.11	nppiXorC_32s_C1IR	396
7.30.2.12	nppiXorC_32s_C1R	397
7.30.2.13	nppiXorC_32s_C3IR	397
7.30.2.14	nppiXorC_32s_C3R	397
7.30.2.15	nppiXorC_32s_C4IR	398
7.30.2.16	nppiXorC_32s_C4R	398
7.30.2.17	nppiXorC_8u_AC4IR	398
7.30.2.18	nppiXorC_8u_AC4R	399
7.30.2.19	nppiXorC_8u_C1IR	399
7.30.2.20	nppiXorC_8u_C1R	399
7.30.2.21	nppiXorC_8u_C3IR	400
7.30.2.22	nppiXorC_8u_C3R	400
7.30.2.23	nppiXorC_8u_C4IR	400
7.30.2.24	nppiXorC_8u_C4R	401
7.31	RShiftC	402
7.31.1	Detailed Description	405
7.31.2	Function Documentation	405
7.31.2.1	nppiRShiftC_16s_AC4IR	405

7.31.2.2	nppiRShiftC_16s_AC4R	405
7.31.2.3	nppiRShiftC_16s_C1IR	406
7.31.2.4	nppiRShiftC_16s_C1R	406
7.31.2.5	nppiRShiftC_16s_C3IR	406
7.31.2.6	nppiRShiftC_16s_C3R	407
7.31.2.7	nppiRShiftC_16s_C4IR	407
7.31.2.8	nppiRShiftC_16s_C4R	407
7.31.2.9	nppiRShiftC_16u_AC4IR	408
7.31.2.10	nppiRShiftC_16u_AC4R	408
7.31.2.11	nppiRShiftC_16u_C1IR	409
7.31.2.12	nppiRShiftC_16u_C1R	409
7.31.2.13	nppiRShiftC_16u_C3IR	409
7.31.2.14	nppiRShiftC_16u_C3R	410
7.31.2.15	nppiRShiftC_16u_C4IR	410
7.31.2.16	nppiRShiftC_16u_C4R	410
7.31.2.17	nppiRShiftC_32s_AC4IR	411
7.31.2.18	nppiRShiftC_32s_AC4R	411
7.31.2.19	nppiRShiftC_32s_C1IR	411
7.31.2.20	nppiRShiftC_32s_C1R	412
7.31.2.21	nppiRShiftC_32s_C3IR	412
7.31.2.22	nppiRShiftC_32s_C3R	412
7.31.2.23	nppiRShiftC_32s_C4IR	413
7.31.2.24	nppiRShiftC_32s_C4R	413
7.31.2.25	nppiRShiftC_8s_AC4IR	413
7.31.2.26	nppiRShiftC_8s_AC4R	414
7.31.2.27	nppiRShiftC_8s_C1IR	414
7.31.2.28	nppiRShiftC_8s_C1R	414
7.31.2.29	nppiRShiftC_8s_C3IR	415
7.31.2.30	nppiRShiftC_8s_C3R	415
7.31.2.31	nppiRShiftC_8s_C4IR	415
7.31.2.32	nppiRShiftC_8s_C4R	416
7.31.2.33	nppiRShiftC_8u_AC4IR	416
7.31.2.34	nppiRShiftC_8u_AC4R	416
7.31.2.35	nppiRShiftC_8u_C1IR	417
7.31.2.36	nppiRShiftC_8u_C1R	417
7.31.2.37	nppiRShiftC_8u_C3IR	417

7.31.2.38	nppiRShiftC_8u_C3R	418
7.31.2.39	nppiRShiftC_8u_C4IR	418
7.31.2.40	nppiRShiftC_8u_C4R	418
7.32	LShiftC	419
7.32.1	Detailed Description	421
7.32.2	Function Documentation	421
7.32.2.1	nppiLShiftC_16u_AC4IR	421
7.32.2.2	nppiLShiftC_16u_AC4R	421
7.32.2.3	nppiLShiftC_16u_C1IR	421
7.32.2.4	nppiLShiftC_16u_C1R	422
7.32.2.5	nppiLShiftC_16u_C3IR	422
7.32.2.6	nppiLShiftC_16u_C3R	422
7.32.2.7	nppiLShiftC_16u_C4IR	423
7.32.2.8	nppiLShiftC_16u_C4R	423
7.32.2.9	nppiLShiftC_32s_AC4IR	424
7.32.2.10	nppiLShiftC_32s_AC4R	424
7.32.2.11	nppiLShiftC_32s_C1IR	424
7.32.2.12	nppiLShiftC_32s_C1R	425
7.32.2.13	nppiLShiftC_32s_C3IR	425
7.32.2.14	nppiLShiftC_32s_C3R	425
7.32.2.15	nppiLShiftC_32s_C4IR	426
7.32.2.16	nppiLShiftC_32s_C4R	426
7.32.2.17	nppiLShiftC_8u_AC4IR	426
7.32.2.18	nppiLShiftC_8u_AC4R	427
7.32.2.19	nppiLShiftC_8u_C1IR	427
7.32.2.20	nppiLShiftC_8u_C1R	427
7.32.2.21	nppiLShiftC_8u_C3IR	428
7.32.2.22	nppiLShiftC_8u_C3R	428
7.32.2.23	nppiLShiftC_8u_C4IR	428
7.32.2.24	nppiLShiftC_8u_C4R	429
7.33	And	430
7.33.1	Detailed Description	432
7.33.2	Function Documentation	432
7.33.2.1	nppiAnd_16u_AC4IR	432
7.33.2.2	nppiAnd_16u_AC4R	432
7.33.2.3	nppiAnd_16u_C1IR	432

7.33.2.4	nppiAnd_16u_C1R	433
7.33.2.5	nppiAnd_16u_C3IR	433
7.33.2.6	nppiAnd_16u_C3R	434
7.33.2.7	nppiAnd_16u_C4IR	434
7.33.2.8	nppiAnd_16u_C4R	434
7.33.2.9	nppiAnd_32s_AC4IR	435
7.33.2.10	nppiAnd_32s_AC4R	435
7.33.2.11	nppiAnd_32s_C1IR	436
7.33.2.12	nppiAnd_32s_C1R	436
7.33.2.13	nppiAnd_32s_C3IR	436
7.33.2.14	nppiAnd_32s_C3R	437
7.33.2.15	nppiAnd_32s_C4IR	437
7.33.2.16	nppiAnd_32s_C4R	437
7.33.2.17	nppiAnd_8u_AC4IR	438
7.33.2.18	nppiAnd_8u_AC4R	438
7.33.2.19	nppiAnd_8u_C1IR	439
7.33.2.20	nppiAnd_8u_C1R	439
7.33.2.21	nppiAnd_8u_C3IR	439
7.33.2.22	nppiAnd_8u_C3R	440
7.33.2.23	nppiAnd_8u_C4IR	440
7.33.2.24	nppiAnd_8u_C4R	440
7.34	Or	442
7.34.1	Detailed Description	444
7.34.2	Function Documentation	444
7.34.2.1	nppiOr_16u_AC4IR	444
7.34.2.2	nppiOr_16u_AC4R	444
7.34.2.3	nppiOr_16u_C1IR	444
7.34.2.4	nppiOr_16u_C1R	445
7.34.2.5	nppiOr_16u_C3IR	445
7.34.2.6	nppiOr_16u_C3R	446
7.34.2.7	nppiOr_16u_C4IR	446
7.34.2.8	nppiOr_16u_C4R	446
7.34.2.9	nppiOr_32s_AC4IR	447
7.34.2.10	nppiOr_32s_AC4R	447
7.34.2.11	nppiOr_32s_C1IR	448
7.34.2.12	nppiOr_32s_C1R	448

7.34.2.13	nppiOr_32s_C3IR	448
7.34.2.14	nppiOr_32s_C3R	449
7.34.2.15	nppiOr_32s_C4IR	449
7.34.2.16	nppiOr_32s_C4R	449
7.34.2.17	nppiOr_8u_AC4IR	450
7.34.2.18	nppiOr_8u_AC4R	450
7.34.2.19	nppiOr_8u_C1IR	451
7.34.2.20	nppiOr_8u_C1R	451
7.34.2.21	nppiOr_8u_C3IR	451
7.34.2.22	nppiOr_8u_C3R	452
7.34.2.23	nppiOr_8u_C4IR	452
7.34.2.24	nppiOr_8u_C4R	452
7.35	Xor	454
7.35.1	Detailed Description	456
7.35.2	Function Documentation	456
7.35.2.1	nppiXor_16u_AC4IR	456
7.35.2.2	nppiXor_16u_AC4R	456
7.35.2.3	nppiXor_16u_C1IR	456
7.35.2.4	nppiXor_16u_C1R	457
7.35.2.5	nppiXor_16u_C3IR	457
7.35.2.6	nppiXor_16u_C3R	458
7.35.2.7	nppiXor_16u_C4IR	458
7.35.2.8	nppiXor_16u_C4R	458
7.35.2.9	nppiXor_32s_AC4IR	459
7.35.2.10	nppiXor_32s_AC4R	459
7.35.2.11	nppiXor_32s_C1IR	460
7.35.2.12	nppiXor_32s_C1R	460
7.35.2.13	nppiXor_32s_C3IR	460
7.35.2.14	nppiXor_32s_C3R	461
7.35.2.15	nppiXor_32s_C4IR	461
7.35.2.16	nppiXor_32s_C4R	461
7.35.2.17	nppiXor_8u_AC4IR	462
7.35.2.18	nppiXor_8u_AC4R	462
7.35.2.19	nppiXor_8u_C1IR	463
7.35.2.20	nppiXor_8u_C1R	463
7.35.2.21	nppiXor_8u_C3IR	463

7.35.2.22	nppiXor_8u_C3R	464
7.35.2.23	nppiXor_8u_C4IR	464
7.35.2.24	nppiXor_8u_C4R	464
7.36	Not	466
7.36.1	Detailed Description	466
7.36.2	Function Documentation	466
7.36.2.1	nppiNot_8u_AC4IR	466
7.36.2.2	nppiNot_8u_AC4R	467
7.36.2.3	nppiNot_8u_C1IR	467
7.36.2.4	nppiNot_8u_C1R	467
7.36.2.5	nppiNot_8u_C3IR	468
7.36.2.6	nppiNot_8u_C3R	468
7.36.2.7	nppiNot_8u_C4IR	468
7.36.2.8	nppiNot_8u_C4R	469
7.37	Alpha Composition	470
7.38	AlphaCompC	471
7.38.1	Detailed Description	472
7.38.2	Function Documentation	472
7.38.2.1	nppiAlphaCompC_16s_C1R	472
7.38.2.2	nppiAlphaCompC_16u_AC4R	473
7.38.2.3	nppiAlphaCompC_16u_C1R	473
7.38.2.4	nppiAlphaCompC_16u_C3R	474
7.38.2.5	nppiAlphaCompC_16u_C4R	474
7.38.2.6	nppiAlphaCompC_32f_C1R	475
7.38.2.7	nppiAlphaCompC_32s_C1R	475
7.38.2.8	nppiAlphaCompC_32u_C1R	476
7.38.2.9	nppiAlphaCompC_8s_C1R	476
7.38.2.10	nppiAlphaCompC_8u_AC4R	477
7.38.2.11	nppiAlphaCompC_8u_C1R	477
7.38.2.12	nppiAlphaCompC_8u_C3R	478
7.38.2.13	nppiAlphaCompC_8u_C4R	478
7.39	AlphaPremulC	479
7.39.1	Detailed Description	480
7.39.2	Function Documentation	480
7.39.2.1	nppiAlphaPremulC_16u_AC4IR	480
7.39.2.2	nppiAlphaPremulC_16u_AC4R	480

7.39.2.3	<code>nppiAlphaPremulC_16u_C1IR</code>	481
7.39.2.4	<code>nppiAlphaPremulC_16u_C1R</code>	481
7.39.2.5	<code>nppiAlphaPremulC_16u_C3IR</code>	482
7.39.2.6	<code>nppiAlphaPremulC_16u_C3R</code>	482
7.39.2.7	<code>nppiAlphaPremulC_16u_C4IR</code>	482
7.39.2.8	<code>nppiAlphaPremulC_16u_C4R</code>	483
7.39.2.9	<code>nppiAlphaPremulC_8u_AC4IR</code>	483
7.39.2.10	<code>nppiAlphaPremulC_8u_AC4R</code>	483
7.39.2.11	<code>nppiAlphaPremulC_8u_C1IR</code>	484
7.39.2.12	<code>nppiAlphaPremulC_8u_C1R</code>	484
7.39.2.13	<code>nppiAlphaPremulC_8u_C3IR</code>	484
7.39.2.14	<code>nppiAlphaPremulC_8u_C3R</code>	485
7.39.2.15	<code>nppiAlphaPremulC_8u_C4IR</code>	485
7.39.2.16	<code>nppiAlphaPremulC_8u_C4R</code>	485
7.40	<code>AlphaComp</code>	486
7.40.1	Detailed Description	487
7.40.2	Function Documentation	487
7.40.2.1	<code>nppiAlphaComp_16s_AC1R</code>	487
7.40.2.2	<code>nppiAlphaComp_16u_AC1R</code>	487
7.40.2.3	<code>nppiAlphaComp_16u_AC4R</code>	488
7.40.2.4	<code>nppiAlphaComp_32f_AC1R</code>	488
7.40.2.5	<code>nppiAlphaComp_32f_AC4R</code>	489
7.40.2.6	<code>nppiAlphaComp_32s_AC1R</code>	489
7.40.2.7	<code>nppiAlphaComp_32s_AC4R</code>	490
7.40.2.8	<code>nppiAlphaComp_32u_AC1R</code>	490
7.40.2.9	<code>nppiAlphaComp_32u_AC4R</code>	491
7.40.2.10	<code>nppiAlphaComp_8s_AC1R</code>	491
7.40.2.11	<code>nppiAlphaComp_8u_AC1R</code>	491
7.40.2.12	<code>nppiAlphaComp_8u_AC4R</code>	492
7.41	<code>AlphaPremul</code>	493
7.41.1	Detailed Description	493
7.41.2	Function Documentation	493
7.41.2.1	<code>nppiAlphaPremul_16u_AC4IR</code>	493
7.41.2.2	<code>nppiAlphaPremul_16u_AC4R</code>	494
7.41.2.3	<code>nppiAlphaPremul_8u_AC4IR</code>	494
7.41.2.4	<code>nppiAlphaPremul_8u_AC4R</code>	494

8	Data Structure Documentation	495
8.1	NPP_ALIGN_16 Struct Reference	495
8.1.1	Detailed Description	495
8.1.2	Field Documentation	495
8.1.2.1	im	495
8.1.2.2	im	496
8.1.2.3	re	496
8.1.2.4	re	496
8.2	NPP_ALIGN_8 Struct Reference	497
8.2.1	Detailed Description	497
8.2.2	Field Documentation	497
8.2.2.1	im	497
8.2.2.2	im	497
8.2.2.3	im	497
8.2.2.4	re	498
8.2.2.5	re	498
8.2.2.6	re	498
8.3	NppiHaarBuffer Struct Reference	499
8.3.1	Field Documentation	499
8.3.1.1	haarBuffer	499
8.3.1.2	haarBufferSize	499
8.4	NppiHaarClassifier_32f Struct Reference	500
8.4.1	Field Documentation	500
8.4.1.1	classifiers	500
8.4.1.2	classifierSize	500
8.4.1.3	classifierStep	500
8.4.1.4	counterDevice	500
8.4.1.5	numClassifiers	500
8.5	NppiPoint Struct Reference	501
8.5.1	Detailed Description	501
8.5.2	Field Documentation	501
8.5.2.1	x	501
8.5.2.2	y	501
8.6	NppiRect Struct Reference	502
8.6.1	Detailed Description	502
8.6.2	Field Documentation	502

8.6.2.1	height	502
8.6.2.2	width	502
8.6.2.3	x	502
8.6.2.4	y	502
8.7	NppiSize Struct Reference	503
8.7.1	Detailed Description	503
8.7.2	Field Documentation	503
8.7.2.1	height	503
8.7.2.2	width	503
8.8	NppLibraryVersion Struct Reference	504
8.8.1	Field Documentation	504
8.8.1.1	build	504
8.8.1.2	major	504
8.8.1.3	minor	504

Chapter 1

NVIDIA Performance Primitives

Note: Starting with release 6.5, NPP is also provided as a static library (`libnppc_static.a`, `libnppi_static.a`, and `libnpps_static.a`) on Linux, Android, and Mac OSes in addition to being provided as a shared library. The static NPP libraries depend on a common thread abstraction layer library called `cuLIBOS` (`libculibos.a`) that is now distributed as part of the toolkit. Consequently, `cuLIBOS` must be provided to the linker when the static library is being linked against. The `libnppi` library is becoming quite large so to minimize library loading and CUDA runtime startup times it is recommended to use the static library(s) whenever possible. To improve loading and runtime performance when using dynamic libraries NPP 8.0 now includes the full set of `nppi` sub-libraries in addition to the full sized `nppi` library itself. Linking to only the sub-libraries that contain functions that your application uses can significantly improve load time and runtime startup performance. Some `nppi` functions make calls to other `nppi` and/or `npps` functions internally so you may need to link to a few extra libraries depending on what function calls your application makes. The `nppi` sub-libraries are split into sections corresponding to the way that `nppi` header files are split. There are also static versions of each of the new sub-libraries. The full sized `nppi` library will be deprecated in the next CUDA release. This list of sub-libraries is as follows:

```
nppial arithmetic and logical operation functions in nppi_arithmetic_and_logical_operations.h
nppicc color conversion and sampling functions in nppi_color_conversion.h
nppicom JPEG compression and decompression functions in nppi_compression_functions.h
nppidei data exchange and initialization functions in nppi_data_exchange_and_initialization.h
nppif filtering and computer vision functions in nppi_filter_functions.h
nppig geometry transformation functions found in nppi_geometry_transforms.h
nppim morphological operation functions found in nppi_morphological_operations.h
nppist statistics and linear transform in nppi_statistics_functions.h and nppi_linear_transforms.h
nppisu memory support functions in nppi_support_functions.h
nppitc threshold and compare operation functions in nppi_threshold_and_compare_operations.h
```

For example, on Linux, to compile a small application `foo` using NPP against the dynamic library, the following command can be used:

```
nvcc foo.c -lnppi -o foo
```

Whereas to compile against the static NPP library, the following command has to be used:

```
nvcc foo.c -lnppi_static -lculibos -o foo
```

It is also possible to use the native host C++ compiler. Depending on the host operating system, some additional libraries like `pthread` or `dl` might be needed on the linking line. The following command on Linux is suggested:

```
g++ foo.c -lnppi_static -lculibos -lcudart_static -lpthread -ldl
-I <cuda-toolkit-path>/include -L <cuda-toolkit-path>/lib64 -o foo
```

NPP is a stateless API, as of NPP 6.5 the ONLY state that NPP remembers between function calls is the current stream ID, i.e. the stream ID that was set in the most recent `nppSetStream` call. The default stream ID is 0. If an application intends to use NPP with multiple streams then it is the responsibility of the application to call `nppSetStream` whenever it wishes to change stream IDs. Several NPP functions may call other NPP functions internally to complete their functionality. For this reason it is recommended that `cudaDeviceSynchronize` be called before making an `nppSetStream` call to change to a new stream ID. This will insure that any internal function calls that have not yet occurred will be completed using the current stream ID before it changes to a new ID. Calling `cudaDeviceSynchronize` frequently call kill performance so minimizing the frequency of these calls is critical for good performance. It is not necessary to call `cudaDeviceSynchronize` for stream management while the same stream ID is used for multiple NPP calls. All NPP functions should be thread safe except for the following functions:

```
nppiGraphcut_32s8u - this function has been deprecated in NPP 8.0
nppiGraphcut_32f8u - this function has been deprecated in NPP 8.0
nppiGraphcut8_32s8u - this function has been deprecated in NPP 8.0
nppiGraphcut8_32f8u - this function has been deprecated in NPP 8.0
nppiDCTQuantFwd8x8LS_JPEG_8u16s_C1R
nppiDCTQuantInv8x8LS_JPEG_16s8u_C1R
```

As of NPP version 5.0 and beyond a few parameters for a few pre-5.0 existing image LUT functions have changed from host memory pointers to device memory pointers. Your application will fail (crash or report an error) if you use these functions with host memory pointers. The functions are the `nppiLUT_Linear_8u_xxx` functions.

Also, pre-5.0 function `nppiMeanStdDev8uC1RGetBufferHostSize` has been renamed `nppiMeanStdDevGetBufferHostSize_8u_C1R`.

1.1 What is NPP?

NVIDIA NPP is a library of functions for performing CUDA accelerated processing. The initial set of functionality in the library focuses on imaging and video processing and is widely applicable for developers in these areas. NPP will evolve over time to encompass more of the compute heavy tasks in a variety of problem domains. The NPP library is written to maximize flexibility, while maintaining high performance.

NPP can be used in one of two ways:

- A stand-alone library for adding GPU acceleration to an application with minimal effort. Using this route allows developers to add GPU acceleration to their applications in a matter of hours.
- A cooperative library for interoperating with a developer's GPU code efficiently.

Either route allows developers to harness the massive compute resources of NVIDIA GPUs, while simultaneously reducing development times.

1.2 Documentation

- [General API Conventions](#)

- [Signal-Processing Specific API Conventions](#)
- [Imaging-Processing Specific API Conventions](#)

1.3 Technical Specifications

Supported Platforms:

- Microsoft Windows 7, 8, and 10 (64-bit and 32-bit)
- Microsoft Windows Vista (64-bit and 32-bit)
- Linux (Centos, Ubuntu, and several others) (64-bit and 32-bit)
- Mac OS X (64-bit)
- Android on Arm (32-bit and 64-bit)

1.4 Files

NPP is comprised of the following files:

1.4.1 Header Files

- [nppdefs.h](#)
- [nppcore.h](#)
- [nppi.h](#)
- [npps.h](#)
- [nppversion.h](#)
- [npp.h](#)

All those header files are located in the CUDA Toolkit's

```
/include/
```

directory.

1.4.2 Library Files

Starting with Version 5.5 NPP's functionality is now split up into 3 distinct libraries:

- A core library (NPPC) containing basic functionality from the `npp.h` header files as well as functionality shared by the other two libraries.
- The image processing library NPPI. Any functions from the `nppi.h` header file (or the various header files named "nppi_XXX.h") are bundled into the NPPI library.

- The signal processing library NPPS. Any function from the npps.h header file (or the various header files named "npps_xxx.h" are bundled into the NPPS library.

On the Windows platform the NPP stub libraries are found in the CUDA Toolkit's library directory:

```
/lib/nppc.lib
```

```
/lib/nppi.lib
```

```
/lib/npps.lib
```

The matching DLLs are located in the CUDA Toolkit's binary directory. Example

```
/bin/nppi64_55_<build_no>.dll // Dynamic image-processing library for 64-bit Windows.
```

On Linux and Mac platforms the dynamic libraries are located in the lib directory

```
/lib/libnppc32.so.5.5.<build_no> // NPP 32-bit dynamic core library for Linux
```

```
/lib/libnpps32.5.5.dylib // NPP 32-bit dynamic signal processing library for Mac
```

1.5 Supported NVIDIA Hardware

NPP runs on all CUDA capable NVIDIA hardware. For details please see http://www.nvidia.com/object/cuda_learn_products.html

Chapter 2

General API Conventions

2.1 Memory Management

The design of all the NPP functions follows the same guidelines as other NVIDIA CUDA libraries like cuFFT and cuBLAS. That is that all pointer arguments in those APIs are device pointers.

This convention enables the individual developer to make smart choices about memory management that minimize the number of memory transfers. It also allows the user the maximum flexibility regarding which of the various memory transfer mechanisms offered by the CUDA runtime is used, e.g. synchronous or asynchronous memory transfers, zero-copy and pinned memory, etc.

The most basic steps involved in using NPP for processing data is as follows:

1. Transfer input data from the host to device using

```
cudaMemcpy(...)
```

2. Process data using one or several NPP functions or custom CUDA kernels

3. Transfer the result data from the device to the host using

```
cudaMemcpy(...)
```

2.1.1 Scratch Buffer and Host Pointer

Some primitives of NPP require additional device memory buffers (scratch buffers) for calculations, e.g. signal and image reductions (Sum, Max, Min, MinMax, etc.). In order to give the NPP user maximum control regarding memory allocations and performance, it is the user's responsibility to allocate and delete those temporary buffers. For one this has the benefit that the library will not allocate memory unbeknownst to the user. It also allows developers who invoke the same primitive repeatedly to allocate the scratch only once, improving performance and potential device-memory fragmentation.

Scratch-buffer memory is unstructured and may be passed to the primitive in uninitialized form. This allows for reuse of the same scratch buffers with any primitive require scratch memory, as long as it is sufficiently sized.

The minimum scratch-buffer size for a given primitive (e.g. `nppsSum_32f()`) can be obtained by a companion function (e.g. `nppsSumGetBufferSize_32f()`). The buffer size is returned via a host pointer as allocation of the scratch-buffer is performed via CUDA runtime host code.

An example to invoke signal sum primitive and allocate and free the necessary scratch memory:

```
// pSrc, pSum, pDeviceBuffer are all device pointers.
Npp32f * pSrc;
Npp32f * pSum;
Npp8u * pDeviceBuffer;
int nLength = 1024;

// Allocate the device memroy.
cudaMalloc((void **)(&pSrc), sizeof(Npp32f) * nLength);
nppsSet_32f(1.0f, pSrc, nLength);
cudaMalloc((void **)(&pSum), sizeof(Npp32f) * 1);

// Compute the appropriate size of the scratch-memory buffer
int nBufferSize;
nppsSumGetBufferSize_32f(nLength, &nBufferSize);
// Allocate the scratch buffer
cudaMalloc((void **)(&pDeviceBuffer), nBufferSize);

// Call the primitive with the scratch buffer
```

```

nppsSum_32f(pSrc, nLength, pSum, pDeviceBuffer);
Npp32f nSumHost;
cudaMemcpy(&nSumHost, pSum, sizeof(Npp32f) * 1, cudaMemcpyDeviceToHost);
printf("sum = %f\n", nSumHost); // nSumHost = 1024.0f;

// Free the device memory
cudaFree(pSrc);
cudaFree(pDeviceBuffer);
cudaFree(pSum);

```

2.2 Function Naming

Since NPP is a C API and therefore does not allow for function overloading for different data-types the NPP naming convention addresses the need to differentiate between different flavors of the same algorithm or primitive function but for various data types. This disambiguation of different flavors of a primitive is done via a suffix containing data type and other disambiguating information.

In addition to the flavor suffix, all NPP functions are prefixed with by the letters "npp". Primitives belonging to NPP's image-processing module add the letter "i" to the npp prefix, i.e. are prefixed by "nppi". Similarly signal-processing primitives are prefixed with "npps".

The general naming scheme is:

```
npp<module info><PrimitiveName>_<data-type info>[_<additional flavor info>](<parameter list>)
```

The data-type information uses the same names as the [Basic NPP Data Types](#). For example the data-type information "8u" would imply that the primitive operates on [Npp8u](#) data.

If a primitive consumes different type data from what it produces, both types will be listed in the order of consumed to produced data type.

Details about the "additional flavor information" is provided for each of the NPP modules, since each problem domain uses different flavor information suffixes.

2.3 Integer Result Scaling

NPP signal processing and imaging primitives often operate on integer data. This integer data is usually a fixed point fractional representation of some physical magnitue (e.g. luminance). Because of this fixed-point nature of the representation many numerical operations (e.g. addition or multiplication) tend to produce results exceeding the original fixed-point range if treated as regular integers.

In cases where the results exceed the original range, these functions clamp the result values back to the valid range. E.g. the maximum positive value for a 16-bit unsigned integer is 32767. A multiplication operation of $4 * 10000 = 40000$ would exceed this range. The result would be clamped to be 32767.

To avoid the level of lost information due to clamping most integer primitives allow for result scaling. Primitives with result scaling have the "Sfs" suffix in their name and provide a parameter "nScaleFactor" that controls the amount of scaling. Before the results of an operation are clamped to the valid output-data range by multiplying them with $2^{-nScaleFactor}$.

Example: The primitive `nppsSqr_8u_Sfs()` computes the square of 8-bit unsigned sample values in a signal (1D array of values). The maximum value of a 8-bit value is 255. The square of $255^2 = 65025$ which would be clamped to 255 if no result scaling is performed. In order to map the maximum value of 255 to 255 in the result, one would specify an integer result scaling factor of 8, i.e. multiply each result with $2^{-8} = \frac{1}{2^8} = \frac{1}{256}$. The final result for a signal value of 255 being squared and scaled would be:

$$255^2 \cdot 2^{-8} = 254.00390625$$

which would be rounded to a final result of 254.

A medium gray value of 128 would result in

$$128^2 * 2^{-8} = 64$$

2.4 Rounding Modes

Many NPP functions require converting floating-point values to integers. The [NppRoundMode](#) enum lists NPP's supported rounding modes. Not all primitives in NPP that perform rounding as part of their functionality allow the user to specify the round-mode used. Instead they use NPP's default rounding mode, which is [NPP_RND_FINANCIAL](#).

2.4.1 Rounding Mode Parameter

A subset of NPP functions performing rounding as part of their functionality do allow the user to specify which rounding mode is used through a parameter of the [NppRoundMode](#) type.

Chapter 3

Signal-Processing Specific API Conventions

3.1 Signal Data

Signal data is passed to and from NPPS primitives via a pointer to the signal's data type.

The general idea behind this fairly low-level way of passing signal data is ease-of-adoption into existing software projects:

- Passing the data pointer rather than a higher-level signal struct allows for easy adoption by not requiring a specific signal representation (that could include total signal size offset, or other additional information). This avoids awkward packing and unpacking of signal data from the host application to an NPP specific signal representation.

3.1.1 Parameter Names for Signal Data

There are three general cases of image-data passing throughout NPP detailed in the following sections.

Those are signals consumed by the algorithm.

3.1.1.1 Source Signal Pointer

The source signal data is generally passed via a pointer named

```
pSrc
```

The source signal pointer is generally defined constant, enforcing that the primitive does not change any image data pointed to by that pointer. E.g.

```
nppsPrimitive_32s(const Npp32s * pSrc, ...)
```

In case the primitive consumes multiple signals as inputs the source pointers are numbered like this:

```
pSrc1, pSrc2, ...
```

3.1.1.2 Destination Signal Pointer

The destination signal data is generally passed via a pointer named

```
pDst
```

In case the primitive consumes multiple signals as inputs the source pointers are numbered like this:

```
pDst1, pDst2, ...
```

3.1.1.3 In-Place Signal Pointer

In the case of in-place processing, source and destination are served by the same pointer and thus pointers to in-place signal data are called:

```
pSrcDst
```

3.1.2 Signal Data Alignment Requirements

NPP requires signal sample data to be naturally aligned, i.e. any pointer

```
NppType * p;
```

to a sample in a signal needs to fulfill:

```
assert(p % sizeof(p) == 0);
```

3.1.3 Signal Data Related Error Codes

All NPPI primitives operating on signal data validate the signal-data pointer for proper alignment and test that the point is not null.

Failed validation results in one of the following error codes being returned and the primitive not being executed:

- [NPP_NULL_POINTER_ERROR](#) is returned if the image-data pointer is 0 (NULL).
- [NPP_ALIGNMENT_ERROR](#) if the signal-data pointer address is not a multiple of the signal's data-type size.

3.2 Signal Length

The vast majority of NPPS functions take a

```
nLength
```

parameter that tells the primitive how many of the signal's samples starting from the given data pointer are to be processed.

3.2.1 Length Related Error Codes

All NPPS primitives taking a length parameter validate this input.

Failed validation results in the following error code being returned and the primitive not being executed:

- [NPP_SIZE_ERROR](#) is returned if the length is negative.

Chapter 4

Imaging-Processing Specific API Conventions

4.1 Function Naming

Image processing related functions use a number of suffixes to indicate various different flavors of a primitive beyond just different data types. The flavor suffix uses the following abbreviations:

- "A" if the image is a 4 channel image this indicates the result alpha channel is not affected by the primitive.
- "Cn" the image consists of n channel packed pixels, where n can be 1, 2, 3 or 4.
- "Pn" the image consists of n separate image planes, where n can be 1, 2, 3 or 4.
- "C" (following the channel information) indicates that the primitive only operates on one of the color channels, the "channel-of-interest". All other output channels are not affected by the primitive.
- "I" indicates that the primitive works "in-place". In this case the image-data pointer is usually named "pSrcDst" to indicate that the image data serves as source and destination at the same time.
- "M" indicates "masked operation". These types of primitives have an additional "mask image" as input. Each pixel in the destination image corresponds to a pixel in the mask image. Only pixels with a corresponding non-zero mask pixel are being processed.
- "R" indicates the primitive operates only on a rectangular "region-of-interest" or "ROI". All ROI primitives take an additional input parameter of type [NppiSize](#), which specifies the width and height of the rectangular region that the primitive should process. For details on how primitives operate on ROIs see: [Region-of-Interest \(ROI\)](#).
- "Sfs" indicates the result values are processed by fixed scaling and saturation before they're written out.

The suffixes above always appear in alphabetical order. E.g. a 4 channel primitive not affecting the alpha channel with masked operation, in place and with scaling/saturation and ROI would have the postfix: "AC4IMRSfs".

4.2 Image Data

Image data is passed to and from NPPI primitives via a pair of parameters:

1. A pointer to the image's underlying data type.
2. A line step in bytes (also sometimes called line stride).

The general idea behind this fairly low-level way of passing image data is ease-of-adoption into existing software projects:

- Passing a raw pointer to the underlying pixel data type, rather than structured (by color) channel pixel data allows usage of the function in a wide variety of situations avoiding risky type cast or expensive image data copies.
- Passing the data pointer and line step individually rather than a higher- level image struct again allows for easy adoption by not requiring a specific image representation and thus avoiding awkward packing and unpacking of image data from the host application to an NPP specific image representation.

4.2.1 Line Step

The line step (also called "line stride" or "row step") allows lines of oddly sized images to start on well-aligned addresses by adding a number of unused bytes at the ends of the lines. This type of line padding has been common practice in digital image processing for a long time and is not particular to GPU image processing.

The line step is the number of bytes in a line **including the padding**. An other way to interpret this number is to say that it is the number of bytes between the first pixel of successive rows in the image, or generally the number of bytes between two neighboring pixels in any column of pixels.

The general reason for the existence of the line step it is that uniformly aligned rows of pixel enable optimizations of memory-access patterns.

Even though all functions in NPP will work with arbitrarily aligned images, best performance can only be achieved with well aligned image data. Any image data allocated with the NPP image allocators or the 2D memory allocators in the CUDA runtime, is well aligned.

Particularly on older CUDA capable GPUs it is likely that the performance decrease for misaligned data is substantial (orders of magnitude).

All image data passed to NPPI primitives requires a line step to be provided. It is important to keep in mind that this line step is always specified in terms of bytes, not pixels.

4.2.2 Parameter Names for Image Data

There are three general cases of image-data passing throughout NPP detailed in the following sections.

4.2.2.1 Passing Source-Image Data

Those are images consumed by the algorithm.

4.2.2.1.1 Source-Image Pointer

The source image data is generally passed via a pointer named

```
pSrc
```

The source image pointer is generally defined constant, enforcing that the primitive does not change any image data pointed to by that pointer. E.g.

```
nppiPrimitive_32s_C1R(const Npp32s * pSrc, ...)
```

In case the primitive consumes multiple images as inputs the source pointers are numbered like this:

```
pSrc1, pSrc2, ...
```

4.2.2.1.2 Source-Planar-Image Pointer Array

The planar source image data is generally passed via an array of pointers named

```
pSrc[]
```

The planar source image pointer array is generally defined a constant array of constant pointers, enforcing that the primitive does not change any image data pointed to by those pointers. E.g.

```
nppiPrimitive_8u_P3R(const Npp8u * const pSrc[3], ...)
```

Each pointer in the array points to a different image plane.

4.2.2.1.3 Source-Planar-Image Pointer

The multiple plane source image data is passed via a set of pointers named

```
pSrc1, pSrc2, ...
```

The planar source image pointer is generally defined as one of a set of constant pointers with each pointer pointing to a different input image plane.

4.2.2.1.4 Source-Image Line Step

The source image line step is the number of bytes between successive rows in the image. The source image line step parameter is

```
nSrcStep
```

or in the case of multiple source images

```
nSrcStep1, nSrcStep2, ...
```

4.2.2.1.5 Source-Planar-Image Line Step Array

The source planar image line step array is an array where each element of the array contains the number of bytes between successive rows for a particular plane in the input image. The source planar image line step array parameter is

```
rSrcStep[]
```

4.2.2.1.6 Source-Planar-Image Line Step

The source planar image line step is the number of bytes between successive rows in a particular plane of the multiplane input image. The source planar image line step parameter is

```
nSrcStep1, nSrcStep2, ...
```

4.2.2.2 Passing Destination-Image Data

Those are images produced by the algorithm.

4.2.2.2.1 Destination-Image Pointer

The destination image data is generally passed via a pointer named

```
pDst
```

In case the primitive generates multiple images as outputs the destination pointers are numbered like this:

```
pDst1, pDst2, ...
```

4.2.2.2.2 Destination-Planar-Image Pointer Array

The planar destination image data pointers are generally passed via an array of pointers named

```
pDst[]
```

Each pointer in the array points to a different image plane.

4.2.2.2.3 Destination-Planar-Image Pointer

The destination planar image data is generally passed via a pointer to each plane of a multiplane output image named

```
pDst1, pDst2, ...
```

4.2.2.2.4 Destination-Image Line Step

The destination image line step parameter is

```
nDstStep
```

or in the case of multiple destination images

```
nDstStep1, nDstStep2, ...
```

4.2.2.2.5 Destination-Planar-Image Line Step Array

The destination planar image line step array is an array where each element of the array contains the number of bytes between successive rows for a particular plane in the output image. The destination planar image line step array parameter is

```
rDstStep[]
```

4.2.2.2.6 Destination-Planar-Image Line Step

The destination planar image line step is the number of bytes between successive rows for a particular plane in a multiplane output image. The destination planar image line step parameter is

```
nDstStep1, nDstStep2, ...
```

4.2.2.3 Passing In-Place Image Data

4.2.2.3.1 In-Place Image Pointer

In the case of in-place processing, source and destination are served by the same pointer and thus pointers to in-place image data are called:

```
pSrcDst
```

4.2.2.3.2 In-Place-Image Line Step

The in-place line step parameter is

```
nSrcDstStep
```

4.2.2.4 Passing Mask-Image Data

Some image processing primitives have variants supporting [Masked Operation](#).

4.2.2.4.1 Mask-Image Pointer

The mask-image data is generally passed via a pointer named

```
pMask
```

4.2.2.4.2 Mask-Image Line Step

The mask-image line step parameter is

```
nMaskStep
```

4.2.2.5 Passing Channel-of-Interest Data

Some image processing primitives support [Channel-of-Interest API](#).

4.2.2.5.1 Channel_of_Interest Number

The channel-of-interest data is generally an integer (either 1, 2, or 3):

```
nCOI
```

4.2.3 Image Data Alignment Requirements

NPP requires pixel data to adhere to certain alignment constraints: For 2 and 4 channel images the following alignment requirement holds: `data_pointer % (#channels * sizeof(channel type)) == 0`. E.g. a 4 channel image with underlying type [Npp8u](#) (8-bit unsigned) would require all pixels to fall on addresses that are multiples of 4 (4 channels * 1 byte size).

As a logical consequence of all pixels being aligned to their natural size the image line steps of 2 and 4 channel images also need to be multiples of the pixel size.

1 and 3 channel images only require that pixel pointers are aligned to the underlying data type, i.e. `pData % sizeof(data type) == 0`. And consequentially line steps are also held to this requirement.

4.2.4 Image Data Related Error Codes

All NPPI primitives operating on image data validate the image-data pointer for proper alignment and test that the point is not null. They also validate the line stride for proper alignment and guard against the step being less or equal to 0. Failed validation results in one of the following error codes being returned and the primitive not being executed:

- `NPP_STEP_ERROR` is returned if the data step is 0 or negative.
- `NPP_NOT_EVEN_STEP_ERROR` is returned if the line step is not a multiple of the pixel size for 2 and 4 channel images.
- `NPP_NULL_POINTER_ERROR` is returned if the image-data pointer is 0 (NULL).
- `NPP_ALIGNMENT_ERROR` if the image-data pointer address is not a multiple of the pixel size for 2 and 4 channel images.

4.3 Region-of-Interest (ROI)

In practice processing a rectangular sub-region of an image is often more common than processing complete images. The vast majority of NPPI's image-processing primitives allow for processing of such sub regions also referred to as regions-of-interest or ROIs.

All primitives supporting ROI processing are marked by a "R" in their name suffix. In most cases the ROI is passed as a single `NppiSize` struct, which provides the width and height of the ROI. This raises the question how the primitive knows where in the image this rectangle of (width, height) is located. The "start pixel" of the ROI is implicitly given by the image-data pointer. I.e. instead of explicitly passing a pixel coordinate for the upper-left corner (lowest memory address), the user simply offsets the image-data pointers to point to the first pixel of the ROI.

In practice this means that for an image (`pSrc`, `nSrcStep`) and the start-pixel of the ROI being at location (`x`, `y`), one would pass

```
pSrcOffset = pSrc + y * nSrcStep + x * PixelSize;
```

as the image-data source to the primitive. `PixelSize` is typically computed as

```
PixelSize = NumberOfColorChannels * sizeof(PixelDataType).
```

E.g. for a primitive like `nppiSet_16s_C4R()` we would have

- `NumberOfColorChannels == 4;`
- `sizeof(Npp16s) == 2;`
- and thus `PixelSize = 4 * 2 = 8;`

4.3.1 ROI Related Error Codes

All NPPI primitives operating on ROIs of image data validate the ROI size and image's step size. Failed validation results in one of the following error codes being returned and the primitive not being executed:

- `NPP_SIZE_ERROR` is returned if either the ROI width or ROI height are negative.
- `NPP_STEP_ERROR` is returned if the ROI width exceeds the image's line step. In mathematical terms $(\text{widthROI} * \text{PixelSize}) > \text{nLinStep}$ indicates an error.

4.4 Masked Operation

Some primitive support masked operation. An "M" in the suffix of those variants indicates masked operation. Primitives supporting masked operation consume an additional input image provided via a [Mask-Image Pointer](#) and [Mask-Image Line Step](#). The mask image is interpreted by these primitives as a boolean image. The values of type `Npp8u` are interpreted as boolean values where a values of 0 indicates false, any non-zero values true.

Unless otherwise indicated the operation is only performed on pixels where its spatially corresponding mask pixel is true (non-zero). E.g. a masked copy operation would only copy those pixels in the ROI that have corresponding non-zero mask pixels.

4.5 Channel-of-Interest API

Some primitives allow restricting operations to a single channel of interest within a multi-channel image. These primitives are suffixed with the letter "C" (after the channel information, e.g. `nppiCopy_8u_C3CR(...)`). The channel-of-interest is generally selected by offsetting the image-data pointer to point directly to the channel- of-interest rather than the base of the first pixel in the ROI. Some primitives also explicitly specify the selected channel number and pass it via an integer, e.g. `nppiMean_StdDev_8u_C3CR(...)`.

4.5.1 Select-Channel Source-Image Pointer

This is a pointer to the channel-of-interest within the first pixel of the source image. E.g. if `pSrc` is the pointer to the first pixel inside the ROI of a three channel image. Using the appropriate select-channel copy primitive one could copy the second channel of this source image into the first channel of a destination image given by `pDst` by offsetting the pointer by one:

```
nppiCopy_8u_C3CR(pSrc + 1, nSrcStep, pDst, nDstStep, oSizeROI);
```

4.5.2 Select-Channel Source-Image

Some primitives allow the user to select the channel-of-interest by specifying the channel number (`nCOI`). This approach is typically used in the image statistical functions. For example,

```
nppiMean_StdDev_8u_C3CR(pSrc, nSrcStep, oSizeROI, nCOI, pDeviceBuffer, pMean, pStdDev );
```

The channel-of-interest number can be either 1, 2, or 3.

4.5.3 Select-Channel Destination-Image Pointer

This is a pointer to the channel-of-interest within the first pixel of the destination image. E.g. if `pDst` is the pointer to the first pixel inside the ROI of a three channel image. Using the appropriate select-channel

copy primitive one could copy data into the second channel of this destination image from the first channel of a source image given by pSrc by offsetting the destination pointer by one:

```
nppiCopy_8u_C3CR(pSrc, nSrcStep, pDst + 1, nDstStep, oSizeROI);
```

4.6 Source-Image Sampling

A large number of NPP image-processing functions consume at least one source image and produce an output image (e.g. [nppiAddC_8u_C1RSfs\(\)](#) or [nppiFilterBox_8u_C1R\(\)](#)). All NPP functions falling into this category also operate on ROIs (see [Region-of-Interest \(ROI\)](#)) which for these functions should be considered to describe the destination ROI. In other words the ROI describes a rectangular region in the destination image and all pixels inside of this region are being written by the function in question.

In order to use such functions successfully it is important to understand how the user defined destination ROI affects which pixels in the input image(s) are being read by the algorithms. To simplify the discussion of ROI propagation (i.e. given a destination ROI, what are the ROIs in the source(s)), it makes sense to distinguish two major cases:

1. Point-Wise Operations: These are primitives like [nppiAddC_8u_C1RSfs\(\)](#). Each output pixel requires exactly one input pixel to be read.
2. Neighborhood Operations: These are primitives like [nppiFilterBox_8u_C1R\(\)](#), which require a group of pixels from the source image(s) to be read in order to produce a single output.

4.6.1 Point-Wise Operations

As mentioned above, point-wise operations consume a single pixel from the input image (or a single pixel from each input image, if the operation in question has more than one input image) in order to produce a single output pixel.

4.6.2 Neighborhood Operations

In the case of neighborhood operations a number of input pixels (a "neighborhood" of pixels) is read in the input image (or images) in order to compute a single output pixel. All of the functions for [image_filtering_functions](#) and [image_morphological_operations](#) are neighborhood operations.

Most of these functions have parameters that affect the size and relative location of the neighborhood: a mask-size structure and an anchor-point structure. Both parameters are described in more detail in the next subsections.

4.6.2.1 Mask-Size Parameter

Many NPP neighborhood operations allow the user to specify the size of the neighborhood via a parameter usually named oMaskSize of type [NppiSize](#). In those cases the neighborhood of pixels read from the source(s) is exactly the size of the mask. Assuming the mask is anchored at location (0, 0) (see [Anchor-Point Parameter](#) below) and has a size of (w, h), i.e.

```
assert(oMaskSize.w == w);  
assert(oMaskSize.h == h);  
assert(oAnchor.x == 0);  
assert(oAnchor.y == 0);
```

a neighborhood operation would read the following source pixels in order to compute destination pixel $D_{i,j}$:

$$\begin{array}{cccc}
 S_{i,j} & S_{i,j+1} & \cdots & S_{i,j+w-1} \\
 S_{i+1,j} & S_{i+1,j+1} & \cdots & S_{i+1,j+w-1} \\
 \vdots & \vdots & \ddots & \vdots \\
 S_{i+h-1,j} & S_{i+h-1,j+1} & \cdots & S_{i+h-1,j+w-1}
 \end{array}$$

4.6.2.2 Anchor-Point Parameter

Many NPP primitives performing neighborhood operations allow the user to specify the relative location of the neighborhood via a parameter usually named `oAnchor` of type [NppiPoint](#). Using the anchor a developer can choose the position of the mask (see [Mask-Size Parameter](#)) relative to current pixel index.

Using the same example as in [Mask-Size Parameter](#), but this time with an anchor position of (a, b):

```

assert(oMaskSize.w == w);
assert(oMaskSize.h == h);
assert(oAnchor.x == a);
assert(oAnchor.y == b);

```

the following pixels from the source image would be read:

$$\begin{array}{cccc}
 S_{i-a,j-b} & S_{i-a,j-b+1} & \cdots & S_{i-a,j-b+w-1} \\
 S_{i-a+1,j-b} & S_{i-a+1,j-b+1} & \cdots & S_{i-a+1,j-b+w-1} \\
 \vdots & \vdots & \ddots & \vdots \\
 S_{i-a+h-1,j-b} & S_{i-a+h-1,j-b+1} & \cdots & S_{i-a+h-1,j-b+w-1}
 \end{array}$$

4.6.2.3 Sampling Beyond Image Boundaries

NPP primitives in general and NPP neighborhood operations in particular require that all pixel locations read and written are valid and within the boundaries of the respective images. Sampling outside of the defined image data regions results in undefined behavior and may lead to system instability.

This poses a problem in practice: when processing full-size images one cannot choose the destination ROI to be the same size as the source image. Because neighborhood operations read pixels from an enlarged source ROI, the destination ROI must be shrunk so that the expanded source ROI does not exceed the source image's size.

For cases where this "shrinking" of the destination image size is unacceptable, NPP provides a set of border-expanding Copy primitives. E.g. `nppiCopyConstBorder_8u_C1R()`, `nppiCopyReplicateBorder_8u_C1R()` and `nppiCopyWrapBorder_8u_C1R()`. The user can use these primitives to "expand" the source image's size using one of the three expansion modes. The expanded image can then be safely passed to a neighborhood operation producing a full-size result.

Chapter 5

Module Index

5.1 Modules

Here is a list of all modules:

NPP Core	27
NPP Type Definitions and Constants	31
Basic NPP Data Types	46
Arithmetic and Logical Operations	50
Arithmetic Operations	51
AddC	53
MulC	79
MulCScale	105
SubC	112
DivC	138
AbsDiffC	164
Add	166
AddSquare	195
AddProduct	198
AddWeighted	202
Mul	206
MulScale	235
Sub	244
Div	274
Div_Round	303
Abs	318
AbsDiff	325
Sqr	328
Sqrt	342
Ln	354
Exp	361
Logical Operations	368
AndC	369
OrC	380
XorC	391
RShiftC	402
LShiftC	419
And	430

Or	442
Xor	454
Not	466
Alpha Composition	470
AlphaCompC	471
AlphaPremulC	479
AlphaComp	486
AlphaPremul	493

Chapter 6

Data Structure Index

6.1 Data Structures

Here are the data structures with brief descriptions:

NPP_ALIGN_16 (Complex Number This struct represents a long long complex number)	495
NPP_ALIGN_8 (Complex Number This struct represents an unsigned int complex number) . .	497
NppiHaarBuffer	499
NppiHaarClassifier_32f	500
NppiPoint (2D Point)	501
NppiRect (2D Rectangle This struct contains position and size information of a rectangle in two space)	502
NppiSize (2D Size This struct typically represents the size of a a rectangular region in two space)	503
NppLibraryVersion	504

Chapter 7

Module Documentation

7.1 NPP Core

Basic functions for library management, in particular library version and device property query functions.

Functions

- const [NppLibraryVersion](#) * [nppGetLibVersion](#) (void)
Get the NPP library version.
- [NppGpuComputeCapability](#) [nppGetGpuComputeCapability](#) (void)
What CUDA compute model is supported by the active CUDA device?
- int [nppGetGpuNumSMs](#) (void)
Get the number of Streaming Multiprocessors (SM) on the active CUDA device.
- int [nppGetMaxThreadsPerBlock](#) (void)
Get the maximum number of threads per block on the active CUDA device.
- int [nppGetMaxThreadsPerSM](#) (void)
Get the maximum number of threads per SM for the active GPU.
- int [nppGetGpuDeviceProperties](#) (int *pMaxThreadsPerSM, int *pMaxThreadsPerBlock, int *pNumberOfSMs)
Get the maximum number of threads per SM, maximum threads per block, and number of SMs for the active GPU.
- const char * [nppGetGpuName](#) (void)
Get the name of the active CUDA device.
- cudaStream_t [nppGetStream](#) (void)
Get the NPP CUDA stream.
- unsigned int [nppGetStreamNumSMs](#) (void)
Get the number of SMs on the device associated with the current NPP CUDA stream.

- unsigned int `nppGetStreamMaxThreadsPerSM` (void)
Get the maximum number of threads per SM on the device associated with the current NPP CUDA stream.
- void `nppSetStream` (cudaStream_t hStream)
Set the NPP CUDA stream.

7.1.1 Detailed Description

Basic functions for library management, in particular library version and device property query functions.

7.1.2 Function Documentation

7.1.2.1 `NppGpuComputeCapability nppGetGpuComputeCapability` (void)

What CUDA compute model is supported by the active CUDA device?

Before trying to call any NPP functions, the user should make a call this function to ensure that the current machine has a CUDA capable device.

Returns:

An enum value representing if a CUDA capable device was found and what level of compute capabilities it supports.

7.1.2.2 `int nppGetGpuDeviceProperties` (int * *pMaxThreadsPerSM*, int * *pMaxThreadsPerBlock*, int * *pNumberOfSMs*)

Get the maximum number of threads per SM, maximum threads per block, and number of SMs for the active GPU.

Returns:

`cudaSuccess` for success, -1 for failure

7.1.2.3 `const char* nppGetGpuName` (void)

Get the name of the active CUDA device.

Returns:

Name string of the active graphics-card/compute device in a system.

7.1.2.4 `int nppGetGpuNumSMs` (void)

Get the number of Streaming Multiprocessors (SM) on the active CUDA device.

Returns:

Number of SMs of the default CUDA device.

7.1.2.5 const NppLibraryVersion* nppGetLibVersion (void)

Get the NPP library version.

Returns:

A struct containing separate values for major and minor revision and build number.

7.1.2.6 int nppGetMaxThreadsPerBlock (void)

Get the maximum number of threads per block on the active CUDA device.

Returns:

Maximum number of threads per block on the active CUDA device.

7.1.2.7 int nppGetMaxThreadsPerSM (void)

Get the maximum number of threads per SM for the active GPU.

Returns:

Maximum number of threads per SM for the active GPU

7.1.2.8 cudaStream_t nppGetStream (void)

Get the NPP CUDA stream.

NPP enables concurrent device tasks via a global stream state variable. The NPP stream by default is set to stream 0, i.e. non-concurrent mode. A user can set the NPP stream to any valid CUDA stream. All CUDA commands issued by NPP (e.g. kernels launched by the NPP library) are then issued to that NPP stream.

7.1.2.9 unsigned int nppGetStreamMaxThreadsPerSM (void)

Get the maximum number of threads per SM on the device associated with the current NPP CUDA stream.

NPP enables concurrent device tasks via a global stream state variable. The NPP stream by default is set to stream 0, i.e. non-concurrent mode. A user can set the NPP stream to any valid CUDA stream. All CUDA commands issued by NPP (e.g. kernels launched by the NPP library) are then issued to that NPP stream. This call avoids a cudaGetDeviceProperties() call.

7.1.2.10 unsigned int nppGetStreamNumSMs (void)

Get the number of SMs on the device associated with the current NPP CUDA stream.

NPP enables concurrent device tasks via a global stream state variable. The NPP stream by default is set to stream 0, i.e. non-concurrent mode. A user can set the NPP stream to any valid CUDA stream. All CUDA commands issued by NPP (e.g. kernels launched by the NPP library) are then issued to that NPP stream. This call avoids a cudaGetDeviceProperties() call.

7.1.2.11 void nppSetStream (cudaStream_t *hStream*)

Set the NPP CUDA stream.

See also:

[nppGetStream\(\)](#)

7.2 NPP Type Definitions and Constants

Data Structures

- struct [NppLibraryVersion](#)
- struct [NppiPoint](#)
2D Point
- struct [NppiSize](#)
2D Size This struct typically represents the size of a rectangular region in two space.
- struct [NppiRect](#)
2D Rectangle This struct contains position and size information of a rectangle in two space.
- struct [NppiHaarClassifier_32f](#)
- struct [NppiHaarBuffer](#)

Modules

- [Basic NPP Data Types](#)

Defines

- #define [NPP_MIN_8U](#) (0)
Minimum 8-bit unsigned integer.
- #define [NPP_MAX_8U](#) (255)
Maximum 8-bit unsigned integer.
- #define [NPP_MIN_16U](#) (0)
Minimum 16-bit unsigned integer.
- #define [NPP_MAX_16U](#) (65535)
Maximum 16-bit unsigned integer.
- #define [NPP_MIN_32U](#) (0)
Minimum 32-bit unsigned integer.
- #define [NPP_MAX_32U](#) (4294967295U)
Maximum 32-bit unsigned integer.
- #define [NPP_MIN_64U](#) (0)
Minimum 64-bit unsigned integer.
- #define [NPP_MAX_64U](#) (18446744073709551615ULL)
Maximum 64-bit unsigned integer.
- #define [NPP_MIN_8S](#) (-127 - 1)
Minimum 8-bit signed integer.

- #define `NPP_MAX_8S` (127)
Maximum 8-bit signed integer.
- #define `NPP_MIN_16S` (-32767 - 1)
Minimum 16-bit signed integer.
- #define `NPP_MAX_16S` (32767)
Maximum 16-bit signed integer.
- #define `NPP_MIN_32S` (-2147483647 - 1)
Minimum 32-bit signed integer.
- #define `NPP_MAX_32S` (2147483647)
Maximum 32-bit signed integer.
- #define `NPP_MAX_64S` (9223372036854775807LL)
Maximum 64-bit signed integer.
- #define `NPP_MIN_64S` (-9223372036854775807LL - 1)
Minimum 64-bit signed integer.
- #define `NPP_MINABS_32F` (1.175494351e-38f)
Smallest positive 32-bit floating point value.
- #define `NPP_MAXABS_32F` (3.402823466e+38f)
Largest positive 32-bit floating point value.
- #define `NPP_MINABS_64F` (2.2250738585072014e-308)
Smallest positive 64-bit floating point value.
- #define `NPP_MAXABS_64F` (1.7976931348623158e+308)
Largest positive 64-bit floating point value.

Enumerations

- enum `NppiInterpolationMode` {
`NPPI_INTER_UNDEFINED` = 0,
`NPPI_INTER_NN` = 1,
`NPPI_INTER_LINEAR` = 2,
`NPPI_INTER_CUBIC` = 4,
`NPPI_INTER_CUBIC2P_BSPLINE`,
`NPPI_INTER_CUBIC2P_CATMULLROM`,
`NPPI_INTER_CUBIC2P_B05C03`,
`NPPI_INTER_SUPER` = 8,
`NPPI_INTER_LANCZOS` = 16,
`NPPI_INTER_LANCZOS3_ADVANCED` = 17,
`NPPI_SMOOTH_EDGE` = (1 << 31) }

Filtering methods.

- enum `NppiBayerGridPosition` {
 `NPPI_BAYER_BGGR` = 0,
 `NPPI_BAYER_RGGB` = 1,
 `NPPI_BAYER_GBRG` = 2,
 `NPPI_BAYER_GRBG` = 3 }

Bayer Grid Position Registration.

- enum `NppiMaskSize` {
 `NPP_MASK_SIZE_1_X_3`,
 `NPP_MASK_SIZE_1_X_5`,
 `NPP_MASK_SIZE_3_X_1` = 100,
 `NPP_MASK_SIZE_5_X_1`,
 `NPP_MASK_SIZE_3_X_3` = 200,
 `NPP_MASK_SIZE_5_X_5`,
 `NPP_MASK_SIZE_7_X_7` = 400,
 `NPP_MASK_SIZE_9_X_9` = 500,
 `NPP_MASK_SIZE_11_X_11` = 600,
 `NPP_MASK_SIZE_13_X_13` = 700,
 `NPP_MASK_SIZE_15_X_15` = 800 }

Fixed filter-kernel sizes.

- enum `NppiDifferentialKernel` {
 `NPP_FILTER_SOBEL`,
 `NPP_FILTER_SCHARR` }

Differential Filter types.

- enum `NppStatus` {
 `NPP_NOT_SUPPORTED_MODE_ERROR` = -9999,
 `NPP_INVALID_HOST_POINTER_ERROR` = -1032,
 `NPP_INVALID_DEVICE_POINTER_ERROR` = -1031,
 `NPP_LUT_PALETTE_BITSIZE_ERROR` = -1030,
 `NPP_ZC_MODE_NOT_SUPPORTED_ERROR` = -1028,
 `NPP_NOT_SUFFICIENT_COMPUTE_CAPABILITY` = -1027,
 `NPP_TEXTURE_BIND_ERROR` = -1024,
 `NPP_WRONG_INTERSECTION_ROI_ERROR` = -1020,
 `NPP_HAAR_CLASSIFIER_PIXEL_MATCH_ERROR` = -1006,
 `NPP_MEMFREE_ERROR` = -1005,
 `NPP_MEMSET_ERROR` = -1004,
 `NPP_MEMCPY_ERROR` = -1003,
 `NPP_ALIGNMENT_ERROR` = -1002,
 `NPP_CUDA_KERNEL_EXECUTION_ERROR` = -1000,

NPP_ROUND_MODE_NOT_SUPPORTED_ERROR = -213,
NPP_QUALITY_INDEX_ERROR = -210,
NPP_RESIZE_NO_OPERATION_ERROR = -201,
NPP_OVERFLOW_ERROR = -109,
NPP_NOT_EVEN_STEP_ERROR = -108,
NPP_HISTOGRAM_NUMBER_OF_LEVELS_ERROR = -107,
NPP_LUT_NUMBER_OF_LEVELS_ERROR = -106,
NPP_CORRUPTED_DATA_ERROR = -61,
NPP_CHANNEL_ORDER_ERROR = -60,
NPP_ZERO_MASK_VALUE_ERROR = -59,
NPP_QUADRANGLE_ERROR = -58,
NPP_RECTANGLE_ERROR = -57,
NPP_COEFFICIENT_ERROR = -56,
NPP_NUMBER_OF_CHANNELS_ERROR = -53,
NPP_COI_ERROR = -52,
NPP_DIVISOR_ERROR = -51,
NPP_CHANNEL_ERROR = -47,
NPP_STRIDE_ERROR = -37,
NPP_ANCHOR_ERROR = -34,
NPP_MASK_SIZE_ERROR = -33,
NPP_RESIZE_FACTOR_ERROR = -23,
NPP_INTERPOLATION_ERROR = -22,
NPP_MIRROR_FLIP_ERROR = -21,
NPP_MOMENT_00_ZERO_ERROR = -20,
NPP_THRESHOLD_NEGATIVE_LEVEL_ERROR = -19,
NPP_THRESHOLD_ERROR = -18,
NPP_CONTEXT_MATCH_ERROR = -17,
NPP_FFT_FLAG_ERROR = -16,
NPP_FFT_ORDER_ERROR = -15,
NPP_STEP_ERROR = -14,
NPP_SCALE_RANGE_ERROR = -13,
NPP_DATA_TYPE_ERROR = -12,
NPP_OUT_OFF_RANGE_ERROR = -11,
NPP_DIVIDE_BY_ZERO_ERROR = -10,
NPP_MEMORY_ALLOCATION_ERR = -9,
NPP_NULL_POINTER_ERROR = -8,
NPP_RANGE_ERROR = -7,
NPP_SIZE_ERROR = -6,
NPP_BAD_ARGUMENT_ERROR = -5,
NPP_NO_MEMORY_ERROR = -4,
NPP_NOT_IMPLEMENTED_ERROR = -3,

```
NPP_ERROR = -2,  
NPP_ERROR_RESERVED = -1,  
NPP_NO_ERROR = 0,  
NPP_SUCCESS = NPP_NO_ERROR,  
NPP_NO_OPERATION_WARNING = 1,  
NPP_DIVIDE_BY_ZERO_WARNING = 6,  
NPP_AFFINE_QUAD_INCORRECT_WARNING = 28,  
NPP_WRONG_INTERSECTION_ROI_WARNING = 29,  
NPP_WRONG_INTERSECTION_QUAD_WARNING = 30,  
NPP_DOUBLE_SIZE_WARNING = 35,  
NPP_MISALIGNED_DST_ROI_WARNING = 10000 }
```

Error Status Codes.

- enum NppGpuComputeCapability {
NPP_CUDA_UNKNOWN_VERSION = -1,
NPP_CUDA_NOT_CAPABLE = 0,
NPP_CUDA_1_0 = 100,
NPP_CUDA_1_1 = 110,
NPP_CUDA_1_2 = 120,
NPP_CUDA_1_3 = 130,
NPP_CUDA_2_0 = 200,
NPP_CUDA_2_1 = 210,
NPP_CUDA_3_0 = 300,
NPP_CUDA_3_2 = 320,
NPP_CUDA_3_5 = 350,
NPP_CUDA_3_7 = 370,
NPP_CUDA_5_0 = 500,
NPP_CUDA_5_2 = 520,
NPP_CUDA_5_3 = 530,
NPP_CUDA_6_0 = 600 }
- enum NppiAxis {
NPP_HORIZONTAL_AXIS,
NPP_VERTICAL_AXIS,
NPP_BOTH_AXIS }
- enum NppCmpOp {
NPP_CMP_LESS,
NPP_CMP_LESS_EQ,
NPP_CMP_EQ,
NPP_CMP_GREATER_EQ,
NPP_CMP_GREATER }

- enum `NppRoundMode` {
 - `NPP_RND_NEAR`,
 - `NPP_ROUND_NEAREST_TIES_TO_EVEN` = `NPP_RND_NEAR`,
 - `NPP_RND_FINANCIAL`,
 - `NPP_ROUND_NEAREST_TIES_AWAY_FROM_ZERO` = `NPP_RND_FINANCIAL`,
 - `NPP_RND_ZERO`,
 - `NPP_ROUND_TOWARD_ZERO` = `NPP_RND_ZERO` }

Rounding Modes.
- enum `NppiBorderType` {
 - `NPP_BORDER_UNDEFINED` = 0,
 - `NPP_BORDER_NONE` = `NPP_BORDER_UNDEFINED`,
 - `NPP_BORDER_CONSTANT` = 1,
 - `NPP_BORDER_REPLICATE` = 2,
 - `NPP_BORDER_WRAP` = 3,
 - `NPP_BORDER_MIRROR` = 4 }
- enum `NppHintAlgorithm` {
 - `NPP_ALG_HINT_NONE`,
 - `NPP_ALG_HINT_FAST`,
 - `NPP_ALG_HINT_ACCURATE` }
- enum `NppiAlphaOp` {
 - `NPPI_OP_ALPHA_OVER`,
 - `NPPI_OP_ALPHA_IN`,
 - `NPPI_OP_ALPHA_OUT`,
 - `NPPI_OP_ALPHA_ATOP`,
 - `NPPI_OP_ALPHA_XOR`,
 - `NPPI_OP_ALPHA_PLUS`,
 - `NPPI_OP_ALPHA_OVER_PREMUL`,
 - `NPPI_OP_ALPHA_IN_PREMUL`,
 - `NPPI_OP_ALPHA_OUT_PREMUL`,
 - `NPPI_OP_ALPHA_ATOP_PREMUL`,
 - `NPPI_OP_ALPHA_XOR_PREMUL`,
 - `NPPI_OP_ALPHA_PLUS_PREMUL`,
 - `NPPI_OP_ALPHA_PREMUL` }
- enum `NppsZCTYPE` {
 - `nppZCR`,
 - `nppZCXor`,
 - `nppZCC` }
- enum `NppiHuffmanTableType` {
 - `nppiDCTable`,
 - `nppiACTable` }

- enum `NppiNorm` {
 `nppiNormInf` = 0,
 `nppiNormL1` = 1,
 `nppiNormL2` = 2 }

7.2.1 Define Documentation

7.2.1.1 #define NPP_MAX_16S (32767)

Maximum 16-bit signed integer.

7.2.1.2 #define NPP_MAX_16U (65535)

Maximum 16-bit unsigned integer.

7.2.1.3 #define NPP_MAX_32S (2147483647)

Maximum 32-bit signed integer.

7.2.1.4 #define NPP_MAX_32U (4294967295U)

Maximum 32-bit unsigned integer.

7.2.1.5 #define NPP_MAX_64S (9223372036854775807LL)

Maximum 64-bit signed integer.

7.2.1.6 #define NPP_MAX_64U (18446744073709551615ULL)

Maximum 64-bit unsigned integer.

7.2.1.7 #define NPP_MAX_8S (127)

Maximum 8-bit signed integer.

7.2.1.8 #define NPP_MAX_8U (255)

Maximum 8-bit unsigned integer.

7.2.1.9 #define NPP_MAXABS_32F (3.402823466e+38f)

Largest positive 32-bit floating point value.

7.2.1.10 #define NPP_MAXABS_64F (1.7976931348623158e+308)

Largest positive 64-bit floating point value.

7.2.1.11 #define NPP_MIN_16S (-32767 - 1)

Minimum 16-bit signed integer.

7.2.1.12 #define NPP_MIN_16U (0)

Minimum 16-bit unsigned integer.

7.2.1.13 #define NPP_MIN_32S (-2147483647 - 1)

Minimum 32-bit signed integer.

7.2.1.14 #define NPP_MIN_32U (0)

Minimum 32-bit unsigned integer.

7.2.1.15 #define NPP_MIN_64S (-9223372036854775807LL - 1)

Minimum 64-bit signed integer.

7.2.1.16 #define NPP_MIN_64U (0)

Minimum 64-bit unsigned integer.

7.2.1.17 #define NPP_MIN_8S (-127 - 1)

Minimum 8-bit signed integer.

7.2.1.18 #define NPP_MIN_8U (0)

Minimum 8-bit unsigned integer.

7.2.1.19 #define NPP_MINABS_32F (1.175494351e-38f)

Smallest positive 32-bit floating point value.

7.2.1.20 #define NPP_MINABS_64F (2.2250738585072014e-308)

Smallest positive 64-bit floating point value.

7.2.2 Enumeration Type Documentation**7.2.2.1 enum NppCmpOp**

Enumerator:

NPP_CMP_LESS

NPP_CMP_LESS_EQ
NPP_CMP_EQ
NPP_CMP_GREATER_EQ
NPP_CMP_GREATER

7.2.2.2 enum NppGpuComputeCapability

Enumerator:

NPP_CUDA_UNKNOWN_VERSION Indicates that the compute-capability query failed.
NPP_CUDA_NOT_CAPABLE Indicates that no CUDA capable device was found.
NPP_CUDA_1_0 Indicates that CUDA 1.0 capable device is machine's default device.
NPP_CUDA_1_1 Indicates that CUDA 1.1 capable device is machine's default device.
NPP_CUDA_1_2 Indicates that CUDA 1.2 capable device is machine's default device.
NPP_CUDA_1_3 Indicates that CUDA 1.3 capable device is machine's default device.
NPP_CUDA_2_0 Indicates that CUDA 2.0 capable device is machine's default device.
NPP_CUDA_2_1 Indicates that CUDA 2.1 capable device is machine's default device.
NPP_CUDA_3_0 Indicates that CUDA 3.0 capable device is machine's default device.
NPP_CUDA_3_2 Indicates that CUDA 3.2 capable device is machine's default device.
NPP_CUDA_3_5 Indicates that CUDA 3.5 capable device is machine's default device.
NPP_CUDA_3_7 Indicates that CUDA 3.7 capable device is machine's default device.
NPP_CUDA_5_0 Indicates that CUDA 5.0 capable device is machine's default device.
NPP_CUDA_5_2 Indicates that CUDA 5.2 capable device is machine's default device.
NPP_CUDA_5_3 Indicates that CUDA 5.3 capable device is machine's default device.
NPP_CUDA_6_0 Indicates that CUDA 6.0 or better is machine's default device.

7.2.2.3 enum NppHintAlgorithm

Enumerator:

NPP_ALG_HINT_NONE
NPP_ALG_HINT_FAST
NPP_ALG_HINT_ACCURATE

7.2.2.4 enum NppiAlphaOp

Enumerator:

NPPI_OP_ALPHA_OVER
NPPI_OP_ALPHA_IN
NPPI_OP_ALPHA_OUT
NPPI_OP_ALPHA_ATOP
NPPI_OP_ALPHA_XOR

NPPI_OP_ALPHA_PLUS
NPPI_OP_ALPHA_OVER_PREMUL
NPPI_OP_ALPHA_IN_PREMUL
NPPI_OP_ALPHA_OUT_PREMUL
NPPI_OP_ALPHA_ATOP_PREMUL
NPPI_OP_ALPHA_XOR_PREMUL
NPPI_OP_ALPHA_PLUS_PREMUL
NPPI_OP_ALPHA_PREMUL

7.2.2.5 enum NppiAxis

Enumerator:

NPP_HORIZONTAL_AXIS
NPP_VERTICAL_AXIS
NPP_BOTH_AXIS

7.2.2.6 enum NppiBayerGridPosition

Bayer Grid Position Registration.

Enumerator:

NPPI_BAYER_BGGR Default registration position.
NPPI_BAYER_RGGB
NPPI_BAYER_GBRG
NPPI_BAYER_GRBG

7.2.2.7 enum NppiBorderType

Enumerator:

NPP_BORDER_UNDEFINED
NPP_BORDER_NONE
NPP_BORDER_CONSTANT
NPP_BORDER_REPLICATE
NPP_BORDER_WRAP
NPP_BORDER_MIRROR

7.2.2.8 enum NppiDifferentialKernel

Differential Filter types.

Enumerator:

NPP_FILTER_SOBEL
NPP_FILTER_SCHARR

7.2.2.9 enum NppiHuffmanTableType

Enumerator:

nppiDCTable DC Table.

nppiACTable AC Table.

7.2.2.10 enum NppiInterpolationMode

Filtering methods.

Enumerator:

NPPI_INTER_UNDEFINED

NPPI_INTER_NN Nearest neighbor filtering.

NPPI_INTER_LINEAR Linear interpolation.

NPPI_INTER_CUBIC Cubic interpolation.

NPPI_INTER_CUBIC2P_BSPLINE Two-parameter cubic filter (B=1, C=0).

NPPI_INTER_CUBIC2P_CATMULLROM Two-parameter cubic filter (B=0, C=1/2).

NPPI_INTER_CUBIC2P_B05C03 Two-parameter cubic filter (B=1/2, C=3/10).

NPPI_INTER_SUPER Super sampling.

NPPI_INTER_LANCZOS Lanczos filtering.

NPPI_INTER_LANCZOS3_ADVANCED Generic Lanczos filtering with order 3.

NPPI_SMOOTH_EDGE Smooth edge filtering.

7.2.2.11 enum NppiMaskSize

Fixed filter-kernel sizes.

Enumerator:

NPP_MASK_SIZE_1_X_3

NPP_MASK_SIZE_1_X_5

NPP_MASK_SIZE_3_X_1

NPP_MASK_SIZE_5_X_1

NPP_MASK_SIZE_3_X_3

NPP_MASK_SIZE_5_X_5

NPP_MASK_SIZE_7_X_7

NPP_MASK_SIZE_9_X_9

NPP_MASK_SIZE_11_X_11

NPP_MASK_SIZE_13_X_13

NPP_MASK_SIZE_15_X_15

7.2.2.12 enum NppiNorm

Enumerator:

- nppiNormInf* maximum
- nppiNormL1* sum
- nppiNormL2* square root of sum of squares

7.2.2.13 enum NppRoundMode

Rounding Modes.

The enumerated rounding modes are used by a large number of NPP primitives to allow the user to specify the method by which fractional values are converted to integer values. Also see [Rounding Modes](#).

For NPP release 5.5 new names for the three rounding modes are introduced that are based on the naming conventions for rounding modes set forth in the IEEE-754 floating-point standard. Developers are encouraged to use the new, longer names to be future proof as the legacy names will be deprecated in subsequent NPP releases.

Enumerator:

NPP_RND_NEAR Round to the nearest even integer.

All fractional numbers are rounded to their nearest integer. The ambiguous cases (i.e. $\langle \text{integer} \rangle.5$) are rounded to the closest even integer. E.g.

- `roundNear(0.5) = 0`
- `roundNear(0.6) = 1`
- `roundNear(1.5) = 2`
- `roundNear(-1.5) = -2`

NPP_ROUND_NEAREST_TIES_TO_EVEN Alias name for [NPP_RND_NEAR](#).

NPP_RND_FINANCIAL Round according to financial rule.

All fractional numbers are rounded to their nearest integer. The ambiguous cases (i.e. $\langle \text{integer} \rangle.5$) are rounded away from zero. E.g.

- `roundFinancial(0.4) = 0`
- `roundFinancial(0.5) = 1`
- `roundFinancial(-1.5) = -2`

NPP_ROUND_NEAREST_TIES_AWAY_FROM_ZERO Alias name for [NPP_RND_FINANCIAL](#).

NPP_RND_ZERO Round towards zero (truncation).

All fractional numbers of the form $\langle \text{integer} \rangle.\langle \text{decimals} \rangle$ are truncated to $\langle \text{integer} \rangle$.

- `roundZero(1.5) = 1`
- `roundZero(1.9) = 1`
- `roundZero(-2.5) = -2`

NPP_ROUND_TOWARD_ZERO Alias name for [NPP_RND_ZERO](#).

7.2.2.14 enum NppStatus

Error Status Codes.

Almost all NPP function return error-status information using these return codes. Negative return codes indicate errors, positive return codes indicate warnings, a return code of 0 indicates success.

Enumerator:

NPP_NOT_SUPPORTED_MODE_ERROR

NPP_INVALID_HOST_POINTER_ERROR

NPP_INVALID_DEVICE_POINTER_ERROR

NPP_LUT_PALETTE_BITSIZE_ERROR

NPP_ZC_MODE_NOT_SUPPORTED_ERROR ZeroCrossing mode not supported.

NPP_NOT_SUFFICIENT_COMPUTE_CAPABILITY

NPP_TEXTURE_BIND_ERROR

NPP_WRONG_INTERSECTION_ROI_ERROR

NPP_HAAR_CLASSIFIER_PIXEL_MATCH_ERROR

NPP_MEMFREE_ERROR

NPP_MEMSET_ERROR

NPP_MEMCPY_ERROR

NPP_ALIGNMENT_ERROR

NPP_CUDA_KERNEL_EXECUTION_ERROR

NPP_ROUND_MODE_NOT_SUPPORTED_ERROR Unsupported round mode.

NPP_QUALITY_INDEX_ERROR Image pixels are constant for quality index.

NPP_RESIZE_NO_OPERATION_ERROR One of the output image dimensions is less than 1 pixel.

NPP_OVERFLOW_ERROR Number overflows the upper or lower limit of the data type.

NPP_NOT_EVEN_STEP_ERROR Step value is not pixel multiple.

NPP_HISTOGRAM_NUMBER_OF_LEVELS_ERROR Number of levels for histogram is less than 2.

NPP_LUT_NUMBER_OF_LEVELS_ERROR Number of levels for LUT is less than 2.

NPP_CORRUPTED_DATA_ERROR Processed data is corrupted.

NPP_CHANNEL_ORDER_ERROR Wrong order of the destination channels.

NPP_ZERO_MASK_VALUE_ERROR All values of the mask are zero.

NPP_QUADRANGLE_ERROR The quadrangle is nonconvex or degenerates into triangle, line or point.

NPP_RECTANGLE_ERROR Size of the rectangle region is less than or equal to 1.

NPP_COEFFICIENT_ERROR Unallowable values of the transformation coefficients.

NPP_NUMBER_OF_CHANNELS_ERROR Bad or unsupported number of channels.

NPP_COI_ERROR Channel of interest is not 1, 2, or 3.

NPP_DIVISOR_ERROR Divisor is equal to zero.

NPP_CHANNEL_ERROR Illegal channel index.

NPP_STRIDE_ERROR Stride is less than the row length.

NPP_ANCHOR_ERROR Anchor point is outside mask.

NPP_MASK_SIZE_ERROR Lower bound is larger than upper bound.

NPP_RESIZE_FACTOR_ERROR

NPP_INTERPOLATION_ERROR

NPP_MIRROR_FLIP_ERROR

NPP_MOMENT_00_ZERO_ERROR

NPP_THRESHOLD_NEGATIVE_LEVEL_ERROR

NPP_THRESHOLD_ERROR

NPP_CONTEXT_MATCH_ERROR

NPP_FFT_FLAG_ERROR

NPP_FFT_ORDER_ERROR

NPP_STEP_ERROR Step is less or equal zero.

NPP_SCALE_RANGE_ERROR

NPP_DATA_TYPE_ERROR

NPP_OUT_OFF_RANGE_ERROR

NPP_DIVIDE_BY_ZERO_ERROR

NPP_MEMORY_ALLOCATION_ERR

NPP_NULL_POINTER_ERROR

NPP_RANGE_ERROR

NPP_SIZE_ERROR

NPP_BAD_ARGUMENT_ERROR

NPP_NO_MEMORY_ERROR

NPP_NOT_IMPLEMENTED_ERROR

NPP_ERROR

NPP_ERROR_RESERVED

NPP_NO_ERROR Error free operation.

NPP_SUCCESS Successful operation (same as ***NPP_NO_ERROR***).

NPP_NO_OPERATION_WARNING Indicates that no operation was performed.

NPP_DIVIDE_BY_ZERO_WARNING Divisor is zero however does not terminate the execution.

NPP_AFFINE_QUAD_INCORRECT_WARNING Indicates that the quadrangle passed to one of affine warping functions doesn't have necessary properties.
First 3 vertices are used, the fourth vertex discarded.

NPP_WRONG_INTERSECTION_ROI_WARNING The given ROI has no intersection with either the source or destination ROI.
Thus no operation was performed.

NPP_WRONG_INTERSECTION_QUAD_WARNING The given quadrangle has no intersection with either the source or destination ROI.
Thus no operation was performed.

NPP_DOUBLE_SIZE_WARNING Image size isn't multiple of two.
Indicates that in case of 422/411/420 sampling the ROI width/height was modified for proper processing.

NPP_MISALIGNED_DST_ROI_WARNING Speed reduction due to uncoalesced memory accesses warning.

7.2.2.15 enum NppsZCType**Enumerator:**

nppZCR sign change
nppZCxor sign change XOR
nppZCC sign change count_0

7.3 Basic NPP Data Types

Data Structures

- struct [NPP_ALIGN_8](#)
Complex Number This struct represents an unsigned int complex number.
- struct [NPP_ALIGN_16](#)
Complex Number This struct represents a long long complex number.

Typedefs

- typedef unsigned char [Npp8u](#)
8-bit unsigned chars
- typedef signed char [Npp8s](#)
8-bit signed chars
- typedef unsigned short [Npp16u](#)
16-bit unsigned integers
- typedef short [Npp16s](#)
16-bit signed integers
- typedef unsigned int [Npp32u](#)
32-bit unsigned integers
- typedef int [Npp32s](#)
32-bit signed integers
- typedef unsigned long long [Npp64u](#)
64-bit unsigned integers
- typedef long long [Npp64s](#)
64-bit signed integers
- typedef float [Npp32f](#)
32-bit (IEEE) floating-point numbers
- typedef double [Npp64f](#)
64-bit floating-point numbers
- typedef struct [NPP_ALIGN_8](#) [Npp32uc](#)
Complex Number This struct represents an unsigned int complex number.
- typedef struct [NPP_ALIGN_8](#) [Npp32sc](#)
Complex Number This struct represents a signed int complex number.

- typedef struct [NPP_ALIGN_8 Npp32fc](#)
Complex Number This struct represents a single floating-point complex number.
- typedef struct [NPP_ALIGN_16 Npp64sc](#)
Complex Number This struct represents a long long complex number.
- typedef struct [NPP_ALIGN_16 Npp64fc](#)
Complex Number This struct represents a double floating-point complex number.

Functions

- struct [__align__](#) (2)
Complex Number This struct represents an unsigned char complex number.
- struct [__align__](#) (4)
Complex Number This struct represents an unsigned short complex number.

Variables

- [Npp8uc](#)
- [Npp16uc](#)
- [Npp16sc](#)

7.3.1 Typedef Documentation

7.3.1.1 typedef short Npp16s

16-bit signed integers

7.3.1.2 typedef unsigned short Npp16u

16-bit unsigned integers

7.3.1.3 typedef float Npp32f

32-bit (IEEE) floating-point numbers

7.3.1.4 typedef struct NPP_ALIGN_8 Npp32fc

Complex Number This struct represents a single floating-point complex number.

7.3.1.5 typedef int Npp32s

32-bit signed integers

7.3.1.6 typedef struct NPP_ALIGN_8 Npp32sc

Complex Number This struct represents a signed int complex number.

7.3.1.7 typedef unsigned int Npp32u

32-bit unsigned integers

7.3.1.8 typedef struct NPP_ALIGN_8 Npp32uc

Complex Number This struct represents an unsigned int complex number.

7.3.1.9 typedef double Npp64f

64-bit floating-point numbers

7.3.1.10 typedef struct NPP_ALIGN_16 Npp64fc

Complex Number This struct represents a double floating-point complex number.

7.3.1.11 typedef long long Npp64s

64-bit signed integers

7.3.1.12 typedef struct NPP_ALIGN_16 Npp64sc

Complex Number This struct represents a long long complex number.

7.3.1.13 typedef unsigned long long Npp64u

64-bit unsigned integers

7.3.1.14 typedef signed char Npp8s

8-bit signed chars

7.3.1.15 typedef unsigned char Npp8u

8-bit unsigned chars

7.3.2 Function Documentation**7.3.2.1 struct __align__ (4) [read]**

Complex Number This struct represents an unsigned short complex number.

Complex Number This struct represents a short complex number.

< Real part

< Imaginary part

< Real part

< Imaginary part

7.3.2.2 `struct __align__(2)` [read]

Complex Number This struct represents an unsigned char complex number.

< Real part

< Imaginary part

7.3.3 Variable Documentation

7.3.3.1 `Npp16sc`

7.3.3.2 `Npp16uc`

7.3.3.3 `Npp8uc`

7.4 Arithmetic and Logical Operations

These functions can be found in either the nppi or nppial libraries.

Modules

- [Arithmetic Operations](#)
- [Logical Operations](#)
- [Alpha Composition](#)

7.4.1 Detailed Description

These functions can be found in either the nppi or nppial libraries.

Linking to only the sub-libraries that you use can significantly save link time, application load time, and CUDA runtime startup time when using dynamic libraries.

7.5 Arithmetic Operations

Modules

- **AddC**
Adds a constant value to each pixel of an image.
- **MulC**
Multiplies each pixel of an image by a constant value.
- **MulCScale**
Multiplies each pixel of an image by a constant value then scales the result by the maximum value for the data bit width.
- **SubC**
Subtracts a constant value from each pixel of an image.
- **DivC**
Divides each pixel of an image by a constant value.
- **AbsDiffC**
Determines absolute difference between each pixel of an image and a constant value.
- **Add**
Pixel by pixel addition of two images.
- **AddSquare**
Pixel by pixel addition of squared pixels from source image to floating point pixel values of destination image.
- **AddProduct**
Pixel by pixel addition of product of pixels from two source images to floating point pixel values of destination image.
- **AddWeighted**
Pixel by pixel addition of alpha weighted pixel values from a source image to floating point pixel values of destination image.
- **Mul**
Pixel by pixel multiply of two images.
- **MulScale**
Pixel by pixel multiplies each pixel of two images then scales the result by the maximum value for the data bit width.
- **Sub**
Pixel by pixel subtraction of two images.
- **Div**
Pixel by pixel division of two images.

- [Div_Round](#)
Pixel by pixel division of two images using result rounding modes.
- [Abs](#)
Absolute value of each pixel value in an image.
- [AbsDiff](#)
Pixel by pixel absolute difference between two images.
- [Sqr](#)
Square each pixel in an image.
- [Sqrt](#)
Pixel by pixel square root of each pixel in an image.
- [Ln](#)
Pixel by pixel natural logarithm of each pixel in an image.
- [Exp](#)
Exponential value of each pixel in an image.

7.6 AddC

Adds a constant value to each pixel of an image.

Functions

- `NppStatus nppiAddC_8u_C1RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` nConstant, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_8u_C1IRSfs` (const `Npp8u` nConstant, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_8u_C3RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` aConstants[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_8u_C3IRSfs` (const `Npp8u` aConstants[3], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel 8-bit unsigned char in place image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_8u_AC4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` aConstants[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_8u_AC4IRSfs` (const `Npp8u` aConstants[3], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_8u_C4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` aConstants[4], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_8u_C4IRSfs` (const `Npp8u` aConstants[4], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel in place image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_16u_C1RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` nConstant, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_16u_C1IRSfs` (const `Npp16u` nConstant, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel in place image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_16u_C3RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16u_C3IRSfs` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16u_AC4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16u_AC4IRSfs` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16u_C4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[4], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16u_C4IRSfs` (const `Npp16u` aConstants[4], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16s_C1RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` nConstant, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16s_C1IRSfs` (const `Npp16s` nConstant, `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16s_C3RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[3], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16s_C3IRSfs` (const `Npp16s` aConstants[3], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16s_AC4RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[3], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16s_AC4IRSfs` (const `Npp16s` aConstants[3], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16s_C4RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[4], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16s_C4IRSfs` (const `Npp16s` aConstants[4], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16sc_C1RSfs` (const `Npp16sc` *pSrc1, int nSrc1Step, const `Npp16sc` nConstant, `Npp16sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16sc_C1IRSfs` (const `Npp16sc` nConstant, `Npp16sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16sc_C3RSfs` (const `Npp16sc` *pSrc1, int nSrc1Step, const `Npp16sc` aConstants[3], `Npp16sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16sc_C3IRSfs` (const `Npp16sc` aConstants[3], `Npp16sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16sc_AC4RSfs` (const `Npp16sc` *pSrc1, int nSrc1Step, const `Npp16sc` aConstants[3], `Npp16sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_16sc_AC4IRSfs` (const `Npp16sc` aConstants[3], `Npp16sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_32s_C1RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` nConstant, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_32s_C1IRSfs` (const `Npp32s` nConstant, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_32s_C3RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_32s_C3IRSfs` (const `Npp32s` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel in place image add constant, scale, then clamp to saturated value.

- `NppStatus nppiAddC_32sc_C1RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc nConstant`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_32sc_C1IRSfs` (const `Npp32sc nConstant`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_32sc_C3RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc aConstants[3]`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_32sc_C3IRSfs` (const `Npp32sc aConstants[3]`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_32sc_AC4RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc aConstants[3]`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_32sc_AC4IRSfs` (const `Npp32sc aConstants[3]`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.
- `NppStatus nppiAddC_32f_C1R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f nConstant`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel image add constant.
- `NppStatus nppiAddC_32f_C1IR` (const `Npp32f nConstant`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel in place image add constant.
- `NppStatus nppiAddC_32f_C3R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f aConstants[3]`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel image add constant.
- `NppStatus nppiAddC_32f_C3IR` (const `Npp32f aConstants[3]`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel in place image add constant.
- `NppStatus nppiAddC_32f_AC4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f aConstants[3]`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel with unmodified alpha image add constant.
- `NppStatus nppiAddC_32f_AC4IR` (const `Npp32f aConstants[3]`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 32-bit floating point channel with unmodified alpha in place image add constant.

- **NppStatus nppiAddC_32f_C4R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** aConstants[4], **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)

Four 32-bit floating point channel image add constant.

- **NppStatus nppiAddC_32f_C4IR** (const **Npp32f** aConstants[4], **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

Four 32-bit floating point channel in place image add constant.

- **NppStatus nppiAddC_32fc_C1R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** nConstant, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image add constant.

- **NppStatus nppiAddC_32fc_C1IR** (const **Npp32fc** nConstant, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image add constant.

- **NppStatus nppiAddC_32fc_C3R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** aConstants[3], **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image add constant.

- **NppStatus nppiAddC_32fc_C3IR** (const **Npp32fc** aConstants[3], **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image add constant.

- **NppStatus nppiAddC_32fc_AC4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** aConstants[3], **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha image add constant.

- **NppStatus nppiAddC_32fc_AC4IR** (const **Npp32fc** aConstants[3], **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha in place image add constant.

- **NppStatus nppiAddC_32fc_C4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** aConstants[4], **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image add constant.

- **NppStatus nppiAddC_32fc_C4IR** (const **Npp32fc** aConstants[4], **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image add constant.

7.6.1 Detailed Description

Adds a constant value to each pixel of an image.

7.6.2 Function Documentation

7.6.2.1 `NppStatus nppiAddC_16s_AC4IRSfs (const Npp16s aConstants[3], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.2 `NppStatus nppiAddC_16s_AC4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha image add constant, scale, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.3 `NppStatus nppiAddC_16s_C1IRSfs (const Npp16s nConstant, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel in place image add constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.4 NppStatus nppiAddC_16s_C1RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s nConstant, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.5 NppStatus nppiAddC_16s_C3IRSfs (const Npp16s aConstants[3], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.6 `NppStatus nppiAddC_16s_C3RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.7 `NppStatus nppiAddC_16s_C4IRSfs (const Npp16s aConstants[4], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.8 `NppStatus nppiAddC_16s_C4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[4], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.9 NppStatus nppiAddC_16sc_AC4IRSfs (const Npp16sc aConstants[3], Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.10 NppStatus nppiAddC_16sc_AC4RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc aConstants[3], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.11 `NppStatus nppiAddC_16sc_C1IRSfs (const Npp16sc nConstant, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image add constant, scale, then clamp to saturated value.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.12 `NppStatus nppiAddC_16sc_C1RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc nConstant, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image add constant, scale, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nConstant* Constant.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.13 `NppStatus nppiAddC_16sc_C3IRSfs (const Npp16sc aConstants[3], Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image add constant, scale, then clamp to saturated value.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.14 NppStatus nppiAddC_16sc_C3RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc aConstants[3], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.15 NppStatus nppiAddC_16u_AC4IRSfs (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.16 NppStatus nppiAddC_16u_AC4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image add constant, scale, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.17 NppStatus nppiAddC_16u_C1IRSfs (const Npp16u nConstant, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image add constant, scale, then clamp to saturated value.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.18 NppStatus nppiAddC_16u_C1RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image add constant, scale, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nConstant* Constant.
- pDst* Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.19 NppStatus nppiAddC_16u_C3IRSfs (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.20 NppStatus nppiAddC_16u_C3RSfs (const Npp16u * pSrcI, int nSrcIStep, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrcI Source-Image Pointer.

nSrcIStep Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.21 `NppStatus nppiAddC_16u_C4IRSfs (const Npp16u aConstants[4], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.22 `NppStatus nppiAddC_16u_C4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.23 `NppStatus nppiAddC_32f_AC4IR (const Npp32f aConstants[3], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha in place image add constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.24 NppStatus nppiAddC_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[3], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel with unmodified alpha image add constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.25 NppStatus nppiAddC_32f_C1IR (const Npp32f nConstant, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel in place image add constant.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.26 NppStatus nppiAddC_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f nConstant, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image add constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.27 NppStatus nppiAddC_32f_C3IR (const Npp32f aConstants[3], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel in place image add constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.28 NppStatus nppiAddC_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[3], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image add constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.29 NppStatus nppiAddC_32f_C4IR (const Npp32f aConstants[4], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image add constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.30 NppStatus nppiAddC_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[4], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image add constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.31 NppStatus nppiAddC_32fc_AC4IR (const Npp32fc aConstants[3], Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha in place image add constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.32 NppStatus nppiAddC_32fc_AC4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[3], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha image add constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.33 `NppStatus nppiAddC_32fc_C1IR (const Npp32fc nConstant, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image add constant.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.34 `NppStatus nppiAddC_32fc_C1R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc nConstant, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image add constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.35 `NppStatus nppiAddC_32fc_C3IR (const Npp32fc aConstants[3], Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image add constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.36 `NppStatus nppiAddC_32fc_C3R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[3], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image add constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.37 `NppStatus nppiAddC_32fc_C4IR (const Npp32fc aConstants[4], Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image add constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.38 `NppStatus nppiAddC_32fc_C4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[4], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image add constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.39 `NppStatus nppiAddC_32s_C1IRSfs (const Npp32s nConstant, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel in place image add constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.40 `NppStatus nppiAddC_32s_C1RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s nConstant, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.41 `NppStatus nppiAddC_32s_C3IRSfs (const Npp32s aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.42 **NppStatus nppiAddC_32s_C3RSfs** (const Npp32s * *pSrc1*, int *nSrc1Step*, const Npp32s *aConstants*[3], Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Three 32-bit signed integer channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.43 **NppStatus nppiAddC_32sc_AC4IRSfs** (const Npp32sc *aConstants*[3], Npp32sc * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.44 `NppStatus nppiAddC_32sc_AC4RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc aConstants[3], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha image add constant, scale, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.45 `NppStatus nppiAddC_32sc_C1IRSfs (const Npp32sc nConstant, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image add constant, scale, then clamp to saturated value.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.46 `NppStatus nppiAddC_32sc_C1RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc nConstant, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image add constant, scale, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.

nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.47 NppStatus nppiAddC_32sc_C3IRSfs (const Npp32sc aConstants[3], Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.48 NppStatus nppiAddC_32sc_C3RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc aConstants[3], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.49 `NppStatus nppiAddC_8u_AC4IRSfs (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha in place image add constant, scale, then clamp to saturated value.

Parameters:

- aConstants* fixed size array of constant values, one per channel..
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.50 `NppStatus nppiAddC_8u_AC4RSfs (const Npp8u * pSrcI, int nSrcIStep, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha image add constant, scale, then clamp to saturated value.

Parameters:

- pSrcI* Source-Image Pointer.
- nSrcIStep* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel..
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.51 `NppStatus nppiAddC_8u_C1IRSfs (const Npp8u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image add constant, scale, then clamp to saturated value.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.52 `NppStatus nppiAddC_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.53 `NppStatus nppiAddC_8u_C3RSfs (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel 8-bit unsigned char in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel..
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.6.2.54 `NppStatus nppiAddC_8u_C3RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel..
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.55 `NppStatus nppiAddC_8u_C4IRSfs (const Npp8u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel in place image add constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.6.2.56 `NppStatus nppiAddC_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel image add constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel..
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7 MulC

Multiplies each pixel of an image by a constant value.

Functions

- **NppStatus nppiMulC_8u_C1RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** nConstant, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_8u_C1IRSfs** (const **Npp8u** nConstant, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_8u_C3RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_8u_C3IRSfs** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel 8-bit unsigned char in place image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_8u_AC4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_8u_AC4IRSfs** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_8u_C4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[4], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_8u_C4IRSfs** (const **Npp8u** aConstants[4], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel in place image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_16u_C1RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** nConstant, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_16u_C1IRSfs** (const **Npp16u** nConstant, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel in place image multiply by constant, scale, then clamp to saturated value.
- **NppStatus nppiMulC_16u_C3RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** aConstants[3], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16u_C3IRSfs` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16u_AC4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16u_AC4IRSfs` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16u_C4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[4], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16u_C4IRSfs` (const `Npp16u` aConstants[4], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16s_C1RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` nConstant, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16s_C1IRSfs` (const `Npp16s` nConstant, `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16s_C3RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[3], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16s_C3IRSfs` (const `Npp16s` aConstants[3], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16s_AC4RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[3], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16s_AC4IRSfs` (const `Npp16s` aConstants[3], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_16s_C4RSfs` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp16s aConstants[4]`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 16-bit signed short channel image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_16s_C4IRSfs` (const `Npp16s aConstants[4]`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 16-bit signed short channel in place image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_16sc_C1RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc nConstant`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_16sc_C1IRSfs` (const `Npp16sc nConstant`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_16sc_C3RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc aConstants[3]`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_16sc_C3IRSfs` (const `Npp16sc aConstants[3]`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_16sc_AC4RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc aConstants[3]`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_16sc_AC4IRSfs` (const `Npp16sc aConstants[3]`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32s_C1RSfs` (const `Npp32s *pSrc1`, int `nSrc1Step`, const `Npp32s nConstant`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 32-bit signed integer channel image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32s_C1IRSfs` (const `Npp32s nConstant`, `Npp32s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 32-bit signed integer channel in place image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32s_C3RSfs` (const `Npp32s *pSrc1`, int `nSrc1Step`, const `Npp32s aConstants[3]`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 32-bit signed integer channel image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32s_C3IRSfs` (const `Npp32s aConstants[3]`, `Npp32s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 32-bit signed integer channel in place image multiply by constant, scale, then clamp to saturated value.

- `NppStatus nppiMulC_32sc_C1RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc nConstant`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32sc_C1IRSfs` (const `Npp32sc nConstant`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32sc_C3RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc aConstants[3]`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32sc_C3IRSfs` (const `Npp32sc aConstants[3]`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32sc_AC4RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc aConstants[3]`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32sc_AC4IRSfs` (const `Npp32sc aConstants[3]`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.
- `NppStatus nppiMulC_32f_C1R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f nConstant`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel image multiply by constant.
- `NppStatus nppiMulC_32f_C1IR` (const `Npp32f nConstant`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel in place image multiply by constant.
- `NppStatus nppiMulC_32f_C3R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f aConstants[3]`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel image multiply by constant.
- `NppStatus nppiMulC_32f_C3IR` (const `Npp32f aConstants[3]`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel in place image multiply by constant.
- `NppStatus nppiMulC_32f_AC4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f aConstants[3]`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel with unmodified alpha image multiply by constant.

- **NppStatus nppiMulC_32f_AC4IR** (const **Npp32f** aConstants[3], **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel with unmodified alpha in place image multiply by constant.
- **NppStatus nppiMulC_32f_C4R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** aConstants[4], **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel image multiply by constant.
- **NppStatus nppiMulC_32f_C4IR** (const **Npp32f** aConstants[4], **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel in place image multiply by constant.
- **NppStatus nppiMulC_32fc_C1R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** nConstant, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image multiply by constant.
- **NppStatus nppiMulC_32fc_C1IR** (const **Npp32fc** nConstant, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image multiply by constant.
- **NppStatus nppiMulC_32fc_C3R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** aConstants[3], **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image multiply by constant.
- **NppStatus nppiMulC_32fc_C3IR** (const **Npp32fc** aConstants[3], **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image multiply by constant.
- **NppStatus nppiMulC_32fc_AC4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** aConstants[3], **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha image multiply by constant.
- **NppStatus nppiMulC_32fc_AC4IR** (const **Npp32fc** aConstants[3], **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha in place image multiply by constant.
- **NppStatus nppiMulC_32fc_C4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** aConstants[4], **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image multiply by constant.
- **NppStatus nppiMulC_32fc_C4IR** (const **Npp32fc** aConstants[4], **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image multiply by constant.

7.7.1 Detailed Description

Multiplies each pixel of an image by a constant value.

7.7.2 Function Documentation

7.7.2.1 `NppStatus nppiMulC_16s_AC4IRSfs (const Npp16s aConstants[3], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.2 `NppStatus nppiMulC_16s_AC4RSfs (const Npp16s * pSrcI, int nSrcIStep, const Npp16s aConstants[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrcI [Source-Image Pointer](#).

nSrcIStep [Source-Image Line Step](#).

aConstants fixed size array of constant values, one per channel.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.3 NppStatus nppiMulC_16s_C1IRSfs (const Npp16s *nConstant*, Npp16s * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

One 16-bit signed short channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.4 NppStatus nppiMulC_16s_C1RSfs (const Npp16s * *pSrc1*, int *nSrc1Step*, const Npp16s *nConstant*, Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

One 16-bit signed short channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.5 NppStatus nppiMulC_16s_C3IRSfs (const Npp16s *aConstants*[3], Npp16s * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Three 16-bit signed short channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.6 `NppStatus nppiMulC_16s_C3RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.7 `NppStatus nppiMulC_16s_C4IRSfs (const Npp16s aConstants[4], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.8 `NppStatus nppiMulC_16s_C4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[4], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.9 NppStatus nppiMulC_16sc_AC4IRSfs (const Npp16sc aConstants[3], Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.10 NppStatus nppiMulC_16sc_AC4RSfs (const Npp16sc * pSrcI, int nSrcIStep, const Npp16sc aConstants[3], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrcI Source-Image Pointer.

nSrcIStep Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.11 NppStatus nppiMulC_16sc_C1IRSfs (const Npp16sc nConstant, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.12 NppStatus nppiMulC_16sc_C1RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc nConstant, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.13 NppStatus nppiMulC_16sc_C3IRSfs (const Npp16sc aConstants[3], Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.14 NppStatus nppiMulC_16sc_C3RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc aConstants[3], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.15 NppStatus nppiMulC_16u_AC4IRSfs (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.16 NppStatus nppiMulC_16u_AC4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.17 NppStatus nppiMulC_16u_C1IRSfs (const Npp16u nConstant, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.18 NppStatus nppiMulC_16u_C1RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.19 NppStatus nppiMulC_16u_C3IRSfs (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.20 NppStatus nppiMulC_16u_C3RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.21 `NppStatus nppiMulC_16u_C4IRSfs (const Npp16u aConstants[4], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.22 `NppStatus nppiMulC_16u_C4RSfs (const Npp16u * pSrcI, int nSrcIStep, const Npp16u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

- pSrcI* Source-Image Pointer.
- nSrcIStep* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.23 `NppStatus nppiMulC_32f_AC4IR (const Npp32f aConstants[3], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha in place image multiply by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.24 NppStatus nppiMulC_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[3], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel with unmodified alpha image multiply by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.25 NppStatus nppiMulC_32f_C1IR (const Npp32f nConstant, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel in place image multiply by constant.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.26 NppStatus nppiMulC_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f nConstant, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image multiply by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.27 NppStatus nppiMulC_32f_C3IR (const Npp32f aConstants[3], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel in place image multiply by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.28 NppStatus nppiMulC_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[3], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image multiply by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.29 NppStatus nppiMulC_32f_C4IR (const Npp32f aConstants[4], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image multiply by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.30 NppStatus nppiMulC_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[4], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image multiply by constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.31 NppStatus nppiMulC_32fc_AC4IR (const Npp32fc aConstants[3], Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha in place image multiply by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.32 NppStatus nppiMulC_32fc_AC4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[3], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha image multiply by constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.33 NppStatus nppiMulC_32fc_C1IR (const Npp32fc *nConstant*, Npp32fc * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image multiply by constant.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.34 NppStatus nppiMulC_32fc_C1R (const Npp32fc * *pSrc1*, int *nSrc1Step*, const Npp32fc *nConstant*, Npp32fc * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image multiply by constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.35 NppStatus nppiMulC_32fc_C3IR (const Npp32fc *aConstants*[3], Npp32fc * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image multiply by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.36 NppStatus nppiMulC_32fc_C3R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[3], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image multiply by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.37 NppStatus nppiMulC_32fc_C4IR (const Npp32fc aConstants[4], Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image multiply by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.38 NppStatus nppiMulC_32fc_C4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[4], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image multiply by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.39 NppStatus nppiMulC_32s_C1RSfs (const Npp32s nConstant, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.40 NppStatus nppiMulC_32s_C1RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s nConstant, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 32-bit signed integer channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.41 NppStatus nppiMulC_32s_C3IRSfs (const Npp32s aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.42 NppStatus nppiMulC_32s_C3RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.43 NppStatus nppiMulC_32sc_AC4IRSfs (const Npp32sc aConstants[3], Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.44 `NppStatus nppiMulC_32sc_AC4RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc aConstants[3], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.45 `NppStatus nppiMulC_32sc_C1IRSfs (const Npp32sc nConstant, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.46 `NppStatus nppiMulC_32sc_C1RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc nConstant, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.47 NppStatus nppiMulC_32sc_C3IRSfs (const Npp32sc aConstants[3], Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.48 NppStatus nppiMulC_32sc_C3RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc aConstants[3], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.49 `NppStatus nppiMulC_8u_AC4IRSfs (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.50 `NppStatus nppiMulC_8u_AC4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.51 `NppStatus nppiMulC_8u_C1IRSfs (const Npp8u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.52 `NppStatus nppiMulC_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.53 `NppStatus nppiMulC_8u_C3IRSfs (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel 8-bit unsigned char in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.7.2.54 `NppStatus nppiMulC_8u_C3RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.55 `NppStatus nppiMulC_8u_C4IRSfs (const Npp8u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel in place image multiply by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.7.2.56 `NppStatus nppiMulC_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel image multiply by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8 MulCScale

Multiplies each pixel of an image by a constant value then scales the result by the maximum value for the data bit width.

Functions

- **NppStatus nppiMulCScale_8u_C1R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** nConstant, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel image multiply by constant and scale by max bit width value.
- **NppStatus nppiMulCScale_8u_C1IR** (const **Npp8u** nConstant, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel in place image multiply by constant and scale by max bit width value.
- **NppStatus nppiMulCScale_8u_C3R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel image multiply by constant and scale by max bit width value.
- **NppStatus nppiMulCScale_8u_C3IR** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel 8-bit unsigned char in place image multiply by constant and scale by max bit width value.
- **NppStatus nppiMulCScale_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel with unmodified alpha image multiply by constant and scale by max bit width value.
- **NppStatus nppiMulCScale_8u_AC4IR** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel with unmodified alpha in place image multiply by constant, scale and scale by max bit width value.
- **NppStatus nppiMulCScale_8u_C4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[4], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image multiply by constant and scale by max bit width value.
- **NppStatus nppiMulCScale_8u_C4IR** (const **Npp8u** aConstants[4], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image multiply by constant and scale by max bit width value.
- **NppStatus nppiMulCScale_16u_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** nConstant, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image multiply by constant and scale by max bit width value.
- **NppStatus nppiMulCScale_16u_C1IR** (const **Npp16u** nConstant, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel in place image multiply by constant and scale by max bit width value.

- `NppStatus nppiMulCScale_16u_C3R` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u aConstants[3]`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 16-bit unsigned short channel image multiply by constant and scale by max bit width value.
- `NppStatus nppiMulCScale_16u_C3IR` (const `Npp16u aConstants[3]`, `Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Three 16-bit unsigned short channel in place image multiply by constant and scale by max bit width value.
- `NppStatus nppiMulCScale_16u_AC4R` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u aConstants[3]`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 16-bit unsigned short channel with unmodified alpha image multiply by constant and scale by max bit width value.
- `NppStatus nppiMulCScale_16u_AC4IR` (const `Npp16u aConstants[3]`, `Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 16-bit unsigned short channel with unmodified alpha in place image multiply by constant and scale by max bit width value.
- `NppStatus nppiMulCScale_16u_C4R` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u aConstants[4]`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 16-bit unsigned short channel image multiply by constant and scale by max bit width value.
- `NppStatus nppiMulCScale_16u_C4IR` (const `Npp16u aConstants[4]`, `Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 16-bit unsigned short channel in place image multiply by constant and scale by max bit width value.

7.8.1 Detailed Description

Multiplies each pixel of an image by a constant value then scales the result by the maximum value for the data bit width.

7.8.2 Function Documentation

7.8.2.1 `NppStatus nppiMulCScale_16u_AC4IR` (const `Npp16u aConstants[3]`, `Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 16-bit unsigned short channel with unmodified alpha in place image multiply by constant and scale by max bit width value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.2 NppStatus nppiMulCScale_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel with unmodified alpha image multiply by constant and scale by max bit width value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.3 NppStatus nppiMulCScale_16u_C1IR (const Npp16u nConstant, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel in place image multiply by constant and scale by max bit width value.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.4 NppStatus nppiMulCScale_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel image multiply by constant and scale by max bit width value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nConstant* Constant.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.5 `NppStatus nppiMulCScale_16u_C3IR` (`const Npp16u aConstants[3]`, `Npp16u * pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)

Three 16-bit unsigned short channel in place image multiply by constant and scale by max bit width value.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.6 `NppStatus nppiMulCScale_16u_C3R` (`const Npp16u * pSrc1`, `int nSrc1Step`, `const Npp16u aConstants[3]`, `Npp16u * pDst`, `int nDstStep`, `NppiSize oSizeROI`)

Three 16-bit unsigned short channel image multiply by constant and scale by max bit width value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.7 `NppStatus nppiMulCScale_16u_C4IR` (`const Npp16u aConstants[4]`, `Npp16u * pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)

Four 16-bit unsigned short channel in place image multiply by constant and scale by max bit width value.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.8 NppStatus nppiMulCScale_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image multiply by constant and scale by max bit width value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.9 NppStatus nppiMulCScale_8u_AC4IR (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel with unmodified alpha in place image multiply by constant, scale and scale by max bit width value.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.10 NppStatus nppiMulCScale_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel with unmodified alpha image multiply by constant and scale by max bit width value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.11 `NppStatus nppiMulCScale_8u_C1IR (const Npp8u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel in place image multiply by constant and scale by max bit width value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.12 `NppStatus nppiMulCScale_8u_C1R (const Npp8u * pSrcI, int nSrcIStep, const Npp8u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel image multiply by constant and scale by max bit width value.

Parameters:

pSrcI Source-Image Pointer.
nSrcIStep Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.13 `NppStatus nppiMulCScale_8u_C3IR (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 8-bit unsigned char channel 8-bit unsigned char in place image multiply by constant and scale by max bit width value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.8.2.14 NppStatus nppiMulCScale_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel image multiply by constant and scale by max bit width value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.15 NppStatus nppiMulCScale_8u_C4IR (const Npp8u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel in place image multiply by constant and scale by max bit width value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.8.2.16 NppStatus nppiMulCScale_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel image multiply by constant and scale by max bit width value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9 SubC

Subtracts a constant value from each pixel of an image.

Functions

- `NppStatus nppiSubC_8u_C1RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` nConstant, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_8u_C1IRSfs` (const `Npp8u` nConstant, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_8u_C3RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` aConstants[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_8u_C3IRSfs` (const `Npp8u` aConstants[3], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel 8-bit unsigned char in place image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_8u_AC4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` aConstants[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_8u_AC4IRSfs` (const `Npp8u` aConstants[3], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_8u_C4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` aConstants[4], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_8u_C4IRSfs` (const `Npp8u` aConstants[4], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel in place image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_16u_C1RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` nConstant, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_16u_C1IRSfs` (const `Npp16u` nConstant, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel in place image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_16u_C3RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16u_C3IRSfs` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16u_AC4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16u_AC4IRSfs` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16u_C4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[4], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16u_C4IRSfs` (const `Npp16u` aConstants[4], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16s_C1RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` nConstant, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16s_C1IRSfs` (const `Npp16s` nConstant, `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16s_C3RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[3], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16s_C3IRSfs` (const `Npp16s` aConstants[3], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16s_AC4RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[3], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16s_AC4IRSfs` (const `Npp16s` aConstants[3], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16s_C4RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[4], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16s_C4IRSfs` (const `Npp16s` aConstants[4], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16sc_C1RSfs` (const `Npp16sc` *pSrc1, int nSrc1Step, const `Npp16sc` nConstant, `Npp16sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16sc_C1IRSfs` (const `Npp16sc` nConstant, `Npp16sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16sc_C3RSfs` (const `Npp16sc` *pSrc1, int nSrc1Step, const `Npp16sc` aConstants[3], `Npp16sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16sc_C3IRSfs` (const `Npp16sc` aConstants[3], `Npp16sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16sc_AC4RSfs` (const `Npp16sc` *pSrc1, int nSrc1Step, const `Npp16sc` aConstants[3], `Npp16sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_16sc_AC4IRSfs` (const `Npp16sc` aConstants[3], `Npp16sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_32s_C1RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` nConstant, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_32s_C1IRSfs` (const `Npp32s` nConstant, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_32s_C3RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_32s_C3IRSfs` (const `Npp32s` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel in place image subtract constant, scale, then clamp to saturated value.

- `NppStatus nppiSubC_32sc_C1RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc nConstant`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_32sc_C1IRSfs` (const `Npp32sc nConstant`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_32sc_C3RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc aConstants[3]`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_32sc_C3IRSfs` (const `Npp32sc aConstants[3]`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_32sc_AC4RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc aConstants[3]`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_32sc_AC4IRSfs` (const `Npp32sc aConstants[3]`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.
- `NppStatus nppiSubC_32f_C1R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f nConstant`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel image subtract constant.
- `NppStatus nppiSubC_32f_C1IR` (const `Npp32f nConstant`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel in place image subtract constant.
- `NppStatus nppiSubC_32f_C3R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f aConstants[3]`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel image subtract constant.
- `NppStatus nppiSubC_32f_C3IR` (const `Npp32f aConstants[3]`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel in place image subtract constant.
- `NppStatus nppiSubC_32f_AC4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f aConstants[3]`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel with unmodified alpha image subtract constant.
- `NppStatus nppiSubC_32f_AC4IR` (const `Npp32f aConstants[3]`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 32-bit floating point channel with unmodified alpha in place image subtract constant.

- `NppStatus nppiSubC_32f_C4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f aConstants[4]`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four 32-bit floating point channel image subtract constant.

- `NppStatus nppiSubC_32f_C4IR` (const `Npp32f aConstants[4]`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 32-bit floating point channel in place image subtract constant.

- `NppStatus nppiSubC_32fc_C1R` (const `Npp32fc *pSrc1`, int `nSrc1Step`, const `Npp32fc nConstant`, `Npp32fc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image subtract constant.

- `NppStatus nppiSubC_32fc_C1IR` (const `Npp32fc nConstant`, `Npp32fc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image subtract constant.

- `NppStatus nppiSubC_32fc_C3R` (const `Npp32fc *pSrc1`, int `nSrc1Step`, const `Npp32fc aConstants[3]`, `Npp32fc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image subtract constant.

- `NppStatus nppiSubC_32fc_C3IR` (const `Npp32fc aConstants[3]`, `Npp32fc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image subtract constant.

- `NppStatus nppiSubC_32fc_AC4R` (const `Npp32fc *pSrc1`, int `nSrc1Step`, const `Npp32fc aConstants[3]`, `Npp32fc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha image subtract constant.

- `NppStatus nppiSubC_32fc_AC4IR` (const `Npp32fc aConstants[3]`, `Npp32fc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha in place image subtract constant.

- `NppStatus nppiSubC_32fc_C4R` (const `Npp32fc *pSrc1`, int `nSrc1Step`, const `Npp32fc aConstants[4]`, `Npp32fc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image subtract constant.

- `NppStatus nppiSubC_32fc_C4IR` (const `Npp32fc aConstants[4]`, `Npp32fc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image subtract constant.

7.9.1 Detailed Description

Subtracts a constant value from each pixel of an image.

7.9.2 Function Documentation

7.9.2.1 `NppStatus nppiSubC_16s_AC4IRSfs (const Npp16s aConstants[3], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.2 `NppStatus nppiSubC_16s_AC4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.3 `NppStatus nppiSubC_16s_C1IRSfs (const Npp16s nConstant, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.4 `NppStatus nppiSubC_16s_C1RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s nConstant, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.5 `NppStatus nppiSubC_16s_C3IRSfs (const Npp16s aConstants[3], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.6 NppStatus nppiSubC_16s_C3RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.7 NppStatus nppiSubC_16s_C4IRSfs (const Npp16s aConstants[4], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.8 NppStatus nppiSubC_16s_C4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[4], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI [Region-of-Interest \(ROI\)](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.9 `NppStatus nppiSubC_16sc_AC4IRSfs (const Npp16sc aConstants[3], Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.10 `NppStatus nppiSubC_16sc_AC4RSfs (const Npp16sc * pSrcI, int nSrcIStep, const Npp16sc aConstants[3], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrcI [Source-Image Pointer](#).

nSrcIStep [Source-Image Line Step](#).

aConstants fixed size array of constant values, one per channel.

pDst [Destination-Image Pointer](#).

nDstStep [Destination-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.11 NppStatus nppiSubC_16sc_C1IRSfs (const Npp16sc nConstant, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.12 NppStatus nppiSubC_16sc_C1RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc nConstant, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.13 NppStatus nppiSubC_16sc_C3IRSfs (const Npp16sc aConstants[3], Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.14 NppStatus nppiSubC_16sc_C3RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc aConstants[3], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.15 NppStatus nppiSubC_16u_AC4IRSfs (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.16 NppStatus nppiSubC_16u_AC4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.17 NppStatus nppiSubC_16u_C1IRSfs (const Npp16u nConstant, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.18 NppStatus nppiSubC_16u_C1RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.19 `NppStatus nppiSubC_16u_C3IRSfs (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.20 `NppStatus nppiSubC_16u_C3RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.21 `NppStatus nppiSubC_16u_C4IRSfs (const Npp16u aConstants[4], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.22 `NppStatus nppiSubC_16u_C4RSfs (const Npp16u * pSrcI, int nSrcIStep, const Npp16u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrcI Source-Image Pointer.

nSrcIStep Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.23 `NppStatus nppiSubC_32f_AC4IR (const Npp32f aConstants[3], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha in place image subtract constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.24 **NppStatus nppiSubC_32f_AC4R** (const Npp32f * *pSrc1*, int *nSrc1Step*, const Npp32f *aConstants*[3], Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Four 32-bit floating point channel with unmodified alpha image subtract constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.25 **NppStatus nppiSubC_32f_C1IR** (const Npp32f *nConstant*, Npp32f * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 32-bit floating point channel in place image subtract constant.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.26 **NppStatus nppiSubC_32f_C1R** (const Npp32f * *pSrc1*, int *nSrc1Step*, const Npp32f *nConstant*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

One 32-bit floating point channel image subtract constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.27 NppStatus nppiSubC_32f_C3IR (const Npp32f aConstants[3], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel in place image subtract constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.28 NppStatus nppiSubC_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[3], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image subtract constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.29 NppStatus nppiSubC_32f_C4IR (const Npp32f aConstants[4], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image subtract constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.30 NppStatus nppiSubC_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[4], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image subtract constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.31 NppStatus nppiSubC_32fc_AC4IR (const Npp32fc aConstants[3], Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha in place image subtract constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.32 NppStatus nppiSubC_32fc_AC4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[3], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha image subtract constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.33 NppStatus nppiSubC_32fc_C1IR (const Npp32fc *nConstant*, Npp32fc * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image subtract constant.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.34 NppStatus nppiSubC_32fc_C1R (const Npp32fc * *pSrc1*, int *nSrc1Step*, const Npp32fc *nConstant*, Npp32fc * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image subtract constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.35 NppStatus nppiSubC_32fc_C3IR (const Npp32fc *aConstants*[3], Npp32fc * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image subtract constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.36 NppStatus nppiSubC_32fc_C3R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[3], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image subtract constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.37 NppStatus nppiSubC_32fc_C4IR (const Npp32fc aConstants[4], Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image subtract constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.38 NppStatus nppiSubC_32fc_C4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[4], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image subtract constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.39 `NppStatus nppiSubC_32s_C1IRSfs (const Npp32s nConstant, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.40 `NppStatus nppiSubC_32s_C1RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s nConstant, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.41 `NppStatus nppiSubC_32s_C3IRSfs (const Npp32s aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.42 `NppStatus nppiSubC_32s_C3RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.43 `NppStatus nppiSubC_32sc_AC4IRSfs (const Npp32sc aConstants[3], Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.44 `NppStatus nppiSubC_32sc_AC4RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc aConstants[3], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.45 `NppStatus nppiSubC_32sc_C1RSfs (const Npp32sc nConstant, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.46 `NppStatus nppiSubC_32sc_C1RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc nConstant, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.47 `NppStatus nppiSubC_32sc_C3IRSfs (const Npp32sc aConstants[3], Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.48 `NppStatus nppiSubC_32sc_C3RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc aConstants[3], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.49 `NppStatus nppiSubC_8u_AC4IRSfs (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha in place image subtract constant, scale, then clamp to saturated value.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.50 `NppStatus nppiSubC_8u_AC4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha image subtract constant, scale, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.9.2.51 `NppStatus nppiSubC_8u_C1IRSfs (const Npp8u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.52 `NppStatus nppiSubC_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.53 `NppStatus nppiSubC_8u_C3IRSfs (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel 8-bit unsigned char in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.54 `NppStatus nppiSubC_8u_C3RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.55 `NppStatus nppiSubC_8u_C4IRSfs (const Npp8u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel in place image subtract constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.9.2.56 `NppStatus nppiSubC_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel image subtract constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10 DivC

Divides each pixel of an image by a constant value.

Functions

- **NppStatus nppiDivC_8u_C1RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** nConstant, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel image divided by constant, scale, then clamp to saturated value.
- **NppStatus nppiDivC_8u_C1IRSfs** (const **Npp8u** nConstant, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image divided by constant, scale, then clamp to saturated value.
- **NppStatus nppiDivC_8u_C3RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel image divided by constant, scale, then clamp to saturated value.
- **NppStatus nppiDivC_8u_C3IRSfs** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel 8-bit unsigned char in place image divided by constant, scale, then clamp to saturated value.
- **NppStatus nppiDivC_8u_AC4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.
- **NppStatus nppiDivC_8u_AC4IRSfs** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.
- **NppStatus nppiDivC_8u_C4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[4], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel image divided by constant, scale, then clamp to saturated value.
- **NppStatus nppiDivC_8u_C4IRSfs** (const **Npp8u** aConstants[4], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel in place image divided by constant, scale, then clamp to saturated value.
- **NppStatus nppiDivC_16u_C1RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** nConstant, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel image divided by constant, scale, then clamp to saturated value.
- **NppStatus nppiDivC_16u_C1IRSfs** (const **Npp16u** nConstant, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel in place image divided by constant, scale, then clamp to saturated value.
- **NppStatus nppiDivC_16u_C3RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** aConstants[3], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16u_C3IRSfs` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16u_AC4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16u_AC4IRSfs` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16u_C4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[4], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16u_C4IRSfs` (const `Npp16u` aConstants[4], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16s_C1RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` nConstant, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16s_C1IRSfs` (const `Npp16s` nConstant, `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16s_C3RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[3], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16s_C3IRSfs` (const `Npp16s` aConstants[3], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16s_AC4RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` aConstants[3], `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16s_AC4IRSfs` (const `Npp16s` aConstants[3], `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_16s_C4RSfs` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp16s aConstants[4]`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 16-bit signed short channel image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_16s_C4IRSfs` (const `Npp16s aConstants[4]`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 16-bit signed short channel in place image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_16sc_C1RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc nConstant`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_16sc_C1IRSfs` (const `Npp16sc nConstant`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_16sc_C3RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc aConstants[3]`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_16sc_C3IRSfs` (const `Npp16sc aConstants[3]`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_16sc_AC4RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc aConstants[3]`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_16sc_AC4IRSfs` (const `Npp16sc aConstants[3]`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_32s_C1RSfs` (const `Npp32s *pSrc1`, int `nSrc1Step`, const `Npp32s nConstant`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 32-bit signed integer channel image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_32s_C1IRSfs` (const `Npp32s nConstant`, `Npp32s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
One 32-bit signed integer channel in place image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_32s_C3RSfs` (const `Npp32s *pSrc1`, int `nSrc1Step`, const `Npp32s aConstants[3]`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Three 32-bit signed integer channel image divided by constant, scale, then clamp to saturated value.
- `NppStatus nppiDivC_32s_C3IRSfs` (const `Npp32s aConstants[3]`, `Npp32s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 32-bit signed integer channel in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_32sc_C1RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc nConstant`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_32sc_C1IRSfs` (const `Npp32sc nConstant`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_32sc_C3RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc aConstants[3]`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_32sc_C3IRSfs` (const `Npp32sc aConstants[3]`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_32sc_AC4RSfs` (const `Npp32sc *pSrc1`, int `nSrc1Step`, const `Npp32sc aConstants[3]`, `Npp32sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_32sc_AC4IRSfs` (const `Npp32sc aConstants[3]`, `Npp32sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.

- `NppStatus nppiDivC_32f_C1R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f nConstant`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

One 32-bit floating point channel image divided by constant.

- `NppStatus nppiDivC_32f_C1IR` (const `Npp32f nConstant`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

One 32-bit floating point channel in place image divided by constant.

- `NppStatus nppiDivC_32f_C3R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f aConstants[3]`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Three 32-bit floating point channel image divided by constant.

- `NppStatus nppiDivC_32f_C3IR` (const `Npp32f aConstants[3]`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Three 32-bit floating point channel in place image divided by constant.

- `NppStatus nppiDivC_32f_AC4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f aConstants[3]`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four 32-bit floating point channel with unmodified alpha image divided by constant.

- **NppStatus nppiDivC_32f_AC4R** (const **Npp32f** aConstants[3], **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel with unmodified alpha in place image divided by constant.
- **NppStatus nppiDivC_32f_C4R** (const **Npp32f** *pSrc1, int nSrc1Step, const **Npp32f** aConstants[4], **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel image divided by constant.
- **NppStatus nppiDivC_32f_C4IR** (const **Npp32f** aConstants[4], **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel in place image divided by constant.
- **NppStatus nppiDivC_32fc_C1R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** nConstant, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image divided by constant.
- **NppStatus nppiDivC_32fc_C1IR** (const **Npp32fc** nConstant, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image divided by constant.
- **NppStatus nppiDivC_32fc_C3R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** aConstants[3], **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image divided by constant.
- **NppStatus nppiDivC_32fc_C3IR** (const **Npp32fc** aConstants[3], **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image divided by constant.
- **NppStatus nppiDivC_32fc_AC4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** aConstants[3], **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha image divided by constant.
- **NppStatus nppiDivC_32fc_AC4IR** (const **Npp32fc** aConstants[3], **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha in place image divided by constant.
- **NppStatus nppiDivC_32fc_C4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** aConstants[4], **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image divided by constant.
- **NppStatus nppiDivC_32fc_C4IR** (const **Npp32fc** aConstants[4], **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image divided by constant.

7.10.1 Detailed Description

Divides each pixel of an image by a constant value.

7.10.2 Function Documentation

7.10.2.1 `NppStatus nppiDivC_16s_AC4IRSfs (const Npp16s aConstants[3], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.2 `NppStatus nppiDivC_16s_AC4RSfs (const Npp16s * pSrcI, int nSrcIStep, const Npp16s aConstants[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrcI Source-Image Pointer.

nSrcIStep Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.3 `NppStatus nppiDivC_16s_C1IRSfs (const Npp16s nConstant, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.4 `NppStatus nppiDivC_16s_C1RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s nConstant, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.5 `NppStatus nppiDivC_16s_C3IRSfs (const Npp16s aConstants[3], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.6 NppStatus nppiDivC_16s_C3RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.7 NppStatus nppiDivC_16s_C4IRSfs (const Npp16s aConstants[4], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.8 NppStatus nppiDivC_16s_C4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s aConstants[4], Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.9 NppStatus nppiDivC_16sc_AC4IRSfs (const Npp16sc aConstants[3], Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.10 NppStatus nppiDivC_16sc_AC4RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc aConstants[3], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.11 NppStatus nppiDivC_16sc_C1IRSfs (const Npp16sc nConstant, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.12 NppStatus nppiDivC_16sc_C1RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc nConstant, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.13 NppStatus nppiDivC_16sc_C3IRSfs (const Npp16sc aConstants[3], Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.14 `NppStatus nppiDivC_16sc_C3RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc aConstants[3], Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.15 `NppStatus nppiDivC_16u_AC4IRSfs (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.16 `NppStatus nppiDivC_16u_AC4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.17 `NppStatus nppiDivC_16u_C1IRSfs (const Npp16u nConstant, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit unsigned short channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.18 `NppStatus nppiDivC_16u_C1RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit unsigned short channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.19 `NppStatus nppiDivC_16u_C3IRSfs (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.20 `NppStatus nppiDivC_16u_C3RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.21 `NppStatus nppiDivC_16u_C4IRSfs (const Npp16u aConstants[4], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.22 `NppStatus nppiDivC_16u_C4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.23 `NppStatus nppiDivC_32f_AC4IR (const Npp32f aConstants[3], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha in place image divided by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.24 `NppStatus nppiDivC_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[3], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha image divided by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.25 `NppStatus nppiDivC_32f_C1IR (const Npp32f nConstant, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel in place image divided by constant.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.26 `NppStatus nppiDivC_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f nConstant, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel image divided by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.27 NppStatus nppiDivC_32f_C3IR (const Npp32f aConstants[3], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel in place image divided by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.28 NppStatus nppiDivC_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[3], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image divided by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.29 NppStatus nppiDivC_32f_C4IR (const Npp32f aConstants[4], Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image divided by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.30 `NppStatus nppiDivC_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f aConstants[4], Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel image divided by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.31 `NppStatus nppiDivC_32fc_AC4IR (const Npp32fc aConstants[3], Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha in place image divided by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.32 `NppStatus nppiDivC_32fc_AC4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[3], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel with unmodified alpha image divided by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.33 `NppStatus nppiDivC_32fc_C1IR` (`const Npp32fc nConstant`, `Npp32fc * pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image divided by constant.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.34 `NppStatus nppiDivC_32fc_C1R` (`const Npp32fc * pSrc1`, `int nSrc1Step`, `const Npp32fc nConstant`, `Npp32fc * pDst`, `int nDstStep`, `NppiSize oSizeROI`)

One 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image divided by constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.35 `NppStatus nppiDivC_32fc_C3IR` (`const Npp32fc aConstants[3]`, `Npp32fc * pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image divided by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.36 `NppStatus nppiDivC_32fc_C3R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[3], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image divided by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.37 `NppStatus nppiDivC_32fc_C4IR (const Npp32fc aConstants[4], Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel in place image divided by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.38 `NppStatus nppiDivC_32fc_C4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc aConstants[4], Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit complex floating point (32-bit floating point real, 32-bit floating point imaginary) channel image divided by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.39 `NppStatus nppiDivC_32s_C1RSfs (const Npp32s nConstant, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.40 `NppStatus nppiDivC_32s_C1RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s nConstant, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.41 `NppStatus nppiDivC_32s_C3IRSfs (const Npp32s aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.42 `NppStatus nppiDivC_32s_C3RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.43 `NppStatus nppiDivC_32sc_AC4IRSfs (const Npp32sc aConstants[3], Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.44 `NppStatus nppiDivC_32sc_AC4RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc aConstants[3], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.45 `NppStatus nppiDivC_32sc_C1IRSfs (const Npp32sc nConstant, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.46 `NppStatus nppiDivC_32sc_C1RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc nConstant, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.47 `NppStatus nppiDivC_32sc_C3IRSfs (const Npp32sc aConstants[3], Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.48 `NppStatus nppiDivC_32sc_C3RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc aConstants[3], Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed complex integer (32-bit real, 32-bit imaginary) channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.49 `NppStatus nppiDivC_8u_AC4IRSfs (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.50 `NppStatus nppiDivC_8u_AC4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.10.2.51 `NppStatus nppiDivC_8u_C1IRSfs (const Npp8u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.52 `NppStatus nppiDivC_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.53 `NppStatus nppiDivC_8u_C3RSfs (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel 8-bit unsigned char in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.54 `NppStatus nppiDivC_8u_C3RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.55 `NppStatus nppiDivC_8u_C4IRSfs (const Npp8u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel in place image divided by constant, scale, then clamp to saturated value.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.10.2.56 `NppStatus nppiDivC_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel image divided by constant, scale, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11 AbsDiffC

Determines absolute difference between each pixel of an image and a constant value.

Functions

- `NppStatus nppiAbsDiffC_8u_C1R` (const `Npp8u *pSrc1`, int `nSrc1Step`, `Npp8u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `Npp8u nConstant`)
One 8-bit unsigned char channel image absolute difference with constant.
- `NppStatus nppiAbsDiffC_16u_C1R` (const `Npp16u *pSrc1`, int `nSrc1Step`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `Npp16u nConstant`)
One 16-bit unsigned short channel image absolute difference with constant.
- `NppStatus nppiAbsDiffC_32f_C1R` (const `Npp32f *pSrc1`, int `nSrc1Step`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `Npp32f nConstant`)
One 32-bit floating point channel image absolute difference with constant.

7.11.1 Detailed Description

Determines absolute difference between each pixel of an image and a constant value.

7.11.2 Function Documentation

7.11.2.1 `NppStatus nppiAbsDiffC_16u_C1R` (const `Npp16u *pSrc1`, int `nSrc1Step`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `Npp16u nConstant`)

One 16-bit unsigned short channel image absolute difference with constant.

Parameters:

- `pSrc1` Source-Image Pointer.
- `nSrc1Step` Source-Image Line Step.
- `nConstant` Constant.
- `pDst` Destination-Image Pointer.
- `nDstStep` Destination-Image Line Step.
- `oSizeROI` Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.11.2.2 `NppStatus nppiAbsDiffC_32f_C1R` (const `Npp32f *pSrc1`, int `nSrc1Step`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `Npp32f nConstant`)

One 32-bit floating point channel image absolute difference with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.11.2.3 NppStatus nppiAbsDiffC_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, Npp8u nConstant)

One 8-bit unsigned char channel image absolute difference with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12 Add

Pixel by pixel addition of two images.

Functions

- `NppStatus nppiAdd_8u_C1RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_8u_C1IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_8u_C3RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_8u_C3IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_8u_AC4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel with unmodified alpha image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_8u_AC4IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel with unmodified alpha in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_8u_C4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_8u_C4IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16u_C1RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16u_C1IRSfs` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16u_C3RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16u_C3IRSfs` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16u_AC4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16u_AC4IRSfs` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16u_C4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16u_C4IRSfs` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16s_C1RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` *pSrc2, int nSrc2Step, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16s_C1IRSfs` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16s_C3RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` *pSrc2, int nSrc2Step, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_16s_C3IRSfs` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16s_AC4RSfs` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp16s *pSrc2`, int `nSrc2Step`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel with unmodified alpha image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16s_AC4RSfs` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel with unmodified alpha in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16s_C4RSfs` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp16s *pSrc2`, int `nSrc2Step`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16s_C4IRSfs` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16sc_C1RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc *pSrc2`, int `nSrc2Step`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16sc_C1IRSfs` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16sc_C3RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc *pSrc2`, int `nSrc2Step`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16sc_C3IRSfs` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16sc_AC4RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc *pSrc2`, int `nSrc2Step`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_16sc_AC4IRSfs` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiAdd_32s_C1RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

Note: This function is to be deprecated in future NPP releases, use the function above with a scale factor of 0 instead.
- `NppStatus nppiAdd_32s_C1IRSfs` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_32s_C3RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_32s_C3IRSfs` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_32sc_C1RSfs` (const `Npp32sc` *pSrc1, int nSrc1Step, const `Npp32sc` *pSrc2, int nSrc2Step, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_32sc_C1IRSfs` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_32sc_C3RSfs` (const `Npp32sc` *pSrc1, int nSrc1Step, const `Npp32sc` *pSrc2, int nSrc2Step, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_32sc_C3IRSfs` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_32sc_AC4RSfs` (const `Npp32sc` *pSrc1, int nSrc1Step, const `Npp32sc` *pSrc2, int nSrc2Step, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiAdd_32sc_AC4IRSfs` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image addition, scale by $2^{-nScaleFactor}$, then clamp to saturated value.

- `NppStatus nppiAdd_32f_C1R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel image addition.
- `NppStatus nppiAdd_32f_C1IR` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel in place image addition.
- `NppStatus nppiAdd_32f_C3R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel image addition.
- `NppStatus nppiAdd_32f_C3IR` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel in place image addition.
- `NppStatus nppiAdd_32f_AC4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel with unmodified alpha image addition.
- `NppStatus nppiAdd_32f_AC4IR` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel with unmodified alpha in place image addition.
- `NppStatus nppiAdd_32f_C4R` (const `Npp32f *pSrc1`, int `nSrc1Step`, const `Npp32f *pSrc2`, int `nSrc2Step`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel image addition.
- `NppStatus nppiAdd_32f_C4IR` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel in place image addition.
- `NppStatus nppiAdd_32fc_C1R` (const `Npp32fc *pSrc1`, int `nSrc1Step`, const `Npp32fc *pSrc2`, int `nSrc2Step`, `Npp32fc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image addition.
- `NppStatus nppiAdd_32fc_C1IR` (const `Npp32fc *pSrc`, int `nSrcStep`, `Npp32fc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image addition.
- `NppStatus nppiAdd_32fc_C3R` (const `Npp32fc *pSrc1`, int `nSrc1Step`, const `Npp32fc *pSrc2`, int `nSrc2Step`, `Npp32fc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image addition.
- `NppStatus nppiAdd_32fc_C3IR` (const `Npp32fc *pSrc`, int `nSrcStep`, `Npp32fc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image addition.

- **NppStatus nppiAdd_32fc_AC4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** *pSrc2, int nSrc2Step, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image addition.
- **NppStatus nppiAdd_32fc_AC4IR** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image addition.
- **NppStatus nppiAdd_32fc_C4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** *pSrc2, int nSrc2Step, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image addition.
- **NppStatus nppiAdd_32fc_C4IR** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image addition.

7.12.1 Detailed Description

Pixel by pixel addition of two images.

7.12.2 Function Documentation

7.12.2.1 **NppStatus nppiAdd_16s_AC4IRSfs** (const **Npp16s** * pSrc, int nSrcStep, **Npp16s** * pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.12.2.2 **NppStatus nppiAdd_16s_AC4RSfs** (const **Npp16s** * pSrc1, int nSrc1Step, const **Npp16s** * pSrc2, int nSrc2Step, **Npp16s** * pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.3 NppStatus nppiAdd_16s_C1IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.4 NppStatus nppiAdd_16s_C1RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.5 NppStatus nppiAdd_16s_C3IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.6 NppStatus nppiAdd_16s_C3RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.7 `NppStatus nppiAdd_16s_C4IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.8 `NppStatus nppiAdd_16s_C4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.9 `NppStatus nppiAdd_16sc_AC4IRSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.10 NppStatus nppiAdd_16sc_AC4RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.11 NppStatus nppiAdd_16sc_C1IRSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.12 NppStatus nppiAdd_16sc_C1RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.12.2.13 NppStatus nppiAdd_16sc_C3RSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.12.2.14 NppStatus nppiAdd_16sc_C3RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.15 **NppStatus nppiAdd_16u_AC4IRSfs** (const Npp16u * *pSrc*, int *nSrcStep*, Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 16-bit unsigned short channel with unmodified alpha in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.16 **NppStatus nppiAdd_16u_AC4RSfs** (const Npp16u * *pSrc1*, int *nSrc1Step*, const Npp16u * *pSrc2*, int *nSrc2Step*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 16-bit unsigned short channel with unmodified alpha image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.17 NppStatus nppiAdd_16u_C1RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image addition, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.18 NppStatus nppiAdd_16u_C1RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image addition, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.19 `NppStatus nppiAdd_16u_C3IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.12.2.20 `NppStatus nppiAdd_16u_C3RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.12.2.21 `NppStatus nppiAdd_16u_C4IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.22 `NppStatus nppiAdd_16u_C4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.23 `NppStatus nppiAdd_32f_AC4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha in place image addition.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.24 `NppStatus nppiAdd_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha image addition.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.12.2.25 `NppStatus nppiAdd_32f_C1IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel in place image addition.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.12.2.26 `NppStatus nppiAdd_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel image addition.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.27 NppStatus nppiAdd_32f_C3IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel in place image addition.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.28 NppStatus nppiAdd_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image addition.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.29 `NppStatus nppiAdd_32f_C4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel in place image addition.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.30 `NppStatus nppiAdd_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel image addition.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.31 `NppStatus nppiAdd_32fc_AC4IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image addition.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.32 `NppStatus nppiAdd_32fc_AC4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image addition.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.12.2.33 `NppStatus nppiAdd_32fc_C1IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image addition.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.12.2.34 `NppStatus nppiAdd_32fc_C1R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image addition.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.35 `NppStatus nppiAdd_32fc_C3IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image addition.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.36 `NppStatus nppiAdd_32fc_C3R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image addition.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.37 `NppStatus nppiAdd_32fc_C4IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image addition.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.38 `NppStatus nppiAdd_32fc_C4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image addition.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.39 `NppStatus nppiAdd_32s_C1IRSfs (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.40 NppStatus nppiAdd_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Note: This function is to be deprecated in future NPP releases, use the function above with a scale factor of 0 instead.

32-bit image add. Add the pixel values of corresponding pixels in the ROI and write them to the output image.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.41 NppStatus nppiAdd_32s_C1RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 32-bit signed integer channel image addition, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.42 `NppStatus nppiAdd_32s_C3IRSfs (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.12.2.43 `NppStatus nppiAdd_32s_C3RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.12.2.44 `NppStatus nppiAdd_32sc_AC4IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.45 NppStatus nppiAdd_32sc_AC4RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image addition, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.46 NppStatus nppiAdd_32sc_C1IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image addition, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.47 `NppStatus nppiAdd_32sc_C1RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image addition, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.12.2.48 `NppStatus nppiAdd_32sc_C3RSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image addition, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.12.2.49 `NppStatus nppiAdd_32sc_C3RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image addition, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.50 `NppStatus nppiAdd_8u_AC4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.51 `NppStatus nppiAdd_8u_AC4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.52 `NppStatus nppiAdd_8u_C1IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.53 `NppStatus nppiAdd_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.54 `NppStatus nppiAdd_8u_C3IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.55 `NppStatus nppiAdd_8u_C3RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.56 `NppStatus nppiAdd_8u_C4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel in place image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.12.2.57 `NppStatus nppiAdd_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel image addition, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.13 AddSquare

Pixel by pixel addition of squared pixels from source image to floating point pixel values of destination image.

Functions

- **NppStatus nppiAddSquare_8u32f_C1IMR** (const **Npp8u** *pSrc, int nSrcStep, const **Npp8u** *pMask, int nMaskStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel image squared then added to in place floating point destination image using filter mask (updates destination when mask is non-zero).
- **NppStatus nppiAddSquare_8u32f_C1IR** (const **Npp8u** *pSrc, int nSrcStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel image squared then added to in place floating point destination image.
- **NppStatus nppiAddSquare_16u32f_C1IMR** (const **Npp16u** *pSrc, int nSrcStep, const **Npp8u** *pMask, int nMaskStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image squared then added to in place floating point destination image using filter mask (updates destination when mask is non-zero).
- **NppStatus nppiAddSquare_16u32f_C1IR** (const **Npp16u** *pSrc, int nSrcStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image squared then added to in place floating point destination image.
- **NppStatus nppiAddSquare_32f_C1IMR** (const **Npp32f** *pSrc, int nSrcStep, const **Npp8u** *pMask, int nMaskStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit floating point channel image squared then added to in place floating point destination image using filter mask (updates destination when mask is non-zero).
- **NppStatus nppiAddSquare_32f_C1IR** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit floating point channel image squared then added to in place floating point destination image.

7.13.1 Detailed Description

Pixel by pixel addition of squared pixels from source image to floating point pixel values of destination image.

7.13.2 Function Documentation

7.13.2.1 **NppStatus nppiAddSquare_16u32f_C1IMR** (const **Npp16u** *pSrc, int nSrcStep, const **Npp8u** *pMask, int nMaskStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

One 16-bit unsigned short channel image squared then added to in place floating point destination image using filter mask (updates destination when mask is non-zero).

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.13.2.2 `NppStatus nppiAddSquare_16u32f_C1IR (const Npp16u * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 16-bit unsigned short channel image squared then added to in place floating point destination image.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.13.2.3 `NppStatus nppiAddSquare_32f_C1IMR (const Npp32f * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel image squared then added to in place floating point destination image using filter mask (updates destination when mask is non-zero).

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.13.2.4 NppStatus nppiAddSquare_32f_C1IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image squared then added to in place floating point destination image.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.13.2.5 NppStatus nppiAddSquare_8u32f_C1IMR (const Npp8u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel image squared then added to in place floating point destination image using filter mask (updates destination when mask is non-zero).

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.13.2.6 NppStatus nppiAddSquare_8u32f_C1IR (const Npp8u * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel image squared then added to in place floating point destination image.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.14 AddProduct

Pixel by pixel addition of product of pixels from two source images to floating point pixel values of destination image.

Functions

- `NppStatus nppiAddProduct_8u32f_C1IMR` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, const `Npp8u` *pMask, int nMaskStep, `Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel image product added to in place floating point destination image using filter mask (updates destination when mask is non-zero).
- `NppStatus nppiAddProduct_8u32f_C1IR` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel image product added to in place floating point destination image.
- `NppStatus nppiAddProduct_16u32f_C1IMR` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, const `Npp8u` *pMask, int nMaskStep, `Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel image product added to in place floating point destination image using filter mask (updates destination when mask is non-zero).
- `NppStatus nppiAddProduct_16u32f_C1IR` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel image product added to in place floating point destination image.
- `NppStatus nppiAddProduct_32f_C1IMR` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, const `Npp8u` *pMask, int nMaskStep, `Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit floating point channel image product added to in place floating point destination image using filter mask (updates destination when mask is non-zero).
- `NppStatus nppiAddProduct_32f_C1IR` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, `Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit floating point channel image product added to in place floating point destination image.

7.14.1 Detailed Description

Pixel by pixel addition of product of pixels from two source images to floating point pixel values of destination image.

7.14.2 Function Documentation

- 7.14.2.1 `NppStatus nppiAddProduct_16u32f_C1IMR`** (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, const `Npp8u` *pMask, int nMaskStep, `Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)

One 16-bit unsigned short channel image product added to in place floating point destination image using filter mask (updates destination when mask is non-zero).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.14.2.2 NppStatus nppiAddProduct_16u32f_C11R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel image product added to in place floating point destination image.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.14.2.3 NppStatus nppiAddProduct_32f_C11MR (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image product added to in place floating point destination image using filter mask (updates destination when mask is non-zero).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.

pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.14.2.4 **NppStatus nppiAddProduct_32f_C1IR (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)**

One 32-bit floating point channel image product added to in place floating point destination image.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.14.2.5 **NppStatus nppiAddProduct_8u32f_C1IMR (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, const Npp8u * pMask, int nMaskStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)**

One 8-bit unsigned char channel image product added to in place floating point destination image using filter mask (updates destination when mask is non-zero).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.14.2.6 NppStatus nppiAddProduct_8u32f_C1IR (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel image product added to in place floating point destination image.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.15 AddWeighted

Pixel by pixel addition of alpha weighted pixel values from a source image to floating point pixel values of destination image.

Functions

- **NppStatus nppiAddWeighted_8u32f_C1IMR** (const **Npp8u** *pSrc, int nSrcStep, const **Npp8u** *pMask, int nMaskStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **Npp32f** nAlpha)
One 8-bit unsigned char channel alpha weighted image added to in place floating point destination image using filter mask (updates destination when mask is non-zero).
- **NppStatus nppiAddWeighted_8u32f_C1IR** (const **Npp8u** *pSrc, int nSrcStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **Npp32f** nAlpha)
One 8-bit unsigned char channel alpha weighted image added to in place floating point destination image.
- **NppStatus nppiAddWeighted_16u32f_C1IMR** (const **Npp16u** *pSrc, int nSrcStep, const **Npp8u** *pMask, int nMaskStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **Npp32f** nAlpha)
One 16-bit unsigned short channel alpha weighted image added to in place floating point destination image using filter mask (updates destination when mask is non-zero).
- **NppStatus nppiAddWeighted_16u32f_C1IR** (const **Npp16u** *pSrc, int nSrcStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **Npp32f** nAlpha)
One 16-bit unsigned short channel alpha weighted image added to in place floating point destination image.
- **NppStatus nppiAddWeighted_32f_C1IMR** (const **Npp32f** *pSrc, int nSrcStep, const **Npp8u** *pMask, int nMaskStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **Npp32f** nAlpha)
One 32-bit floating point channel alpha weighted image added to in place floating point destination image using filter mask (updates destination when mask is non-zero).
- **NppStatus nppiAddWeighted_32f_C1IR** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **Npp32f** nAlpha)
One 32-bit floating point channel alpha weighted image added to in place floating point destination image.

7.15.1 Detailed Description

Pixel by pixel addition of alpha weighted pixel values from a source image to floating point pixel values of destination image.

7.15.2 Function Documentation

7.15.2.1 NppStatus nppiAddWeighted_16u32f_C1IMR (const Npp16u *pSrc, int nSrcStep, const Npp8u *pMask, int nMaskStep, Npp32f *pSrcDst, int nSrcDstStep, NppiSize oSizeROI, Npp32f nAlpha)

One 16-bit unsigned short channel alpha weighted image added to in place floating point destination image using filter mask (updates destination when mask is non-zero).

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nAlpha Alpha weight to be applied to source image pixels (0.0F to 1.0F)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.15.2.2 `NppStatus nppiAddWeighted_16u32f_C1IR (const Npp16u * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, Npp32f nAlpha)`

One 16-bit unsigned short channel alpha weighted image added to in place floating point destination image.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nAlpha Alpha weight to be applied to source image pixels (0.0F to 1.0F)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.15.2.3 `NppStatus nppiAddWeighted_32f_C1IMR (const Npp32f * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, Npp32f nAlpha)`

One 32-bit floating point channel alpha weighted image added to in place floating point destination image using filter mask (updates destination when mask is non-zero).

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pMask Mask-Image Pointer.
nMaskStep Mask-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nAlpha Alpha weight to be applied to source image pixels (0.0F to 1.0F)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.15.2.4 NppStatus nppiAddWeighted_32f_C1IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, Npp32f nAlpha)

One 32-bit floating point channel alpha weighted image added to in place floating point destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nAlpha Alpha weight to be applied to source image pixels (0.0F to 1.0F)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.15.2.5 NppStatus nppiAddWeighted_8u32f_C1IMR (const Npp8u * pSrc, int nSrcStep, const Npp8u * pMask, int nMaskStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, Npp32f nAlpha)

One 8-bit unsigned char channel alpha weighted image added to in place floating point destination image using filter mask (updates destination when mask is non-zero).

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pMask Mask-Image Pointer.

nMaskStep Mask-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nAlpha Alpha weight to be applied to source image pixels (0.0F to 1.0F)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.15.2.6 NppStatus nppiAddWeighted_8u32f_C1IR (const Npp8u * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, Npp32f nAlpha)

One 8-bit unsigned char channel alpha weighted image added to in place floating point destination image.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nAlpha Alpha weight to be applied to source image pixels (0.0F to 1.0F)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16 Mul

Pixel by pixel multiply of two images.

Functions

- **NppStatus nppiMul_8u_C1RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiMul_8u_C1IRSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiMul_8u_C3RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiMul_8u_C3IRSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiMul_8u_AC4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiMul_8u_AC4IRSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiMul_8u_C4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiMul_8u_C4IRSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiMul_16u_C1RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16u_C1RSfs` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16u_C3RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 16-bit unsigned short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16u_C3RSfs` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 16-bit unsigned short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16u_AC4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 16-bit unsigned short channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16u_AC4RSfs` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 16-bit unsigned short channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16u_C4RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 16-bit unsigned short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16u_C4RSfs` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 16-bit unsigned short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16s_C1RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` *pSrc2, int nSrc2Step, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 16-bit signed short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16s_C1RSfs` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 16-bit signed short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16s_C3RSfs` (const `Npp16s` *pSrc1, int nSrc1Step, const `Npp16s` *pSrc2, int nSrc2Step, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 16-bit signed short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_16s_C3RSfs` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16s_AC4RSfs` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp16s *pSrc2`, int `nSrc2Step`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16s_AC4RSfs` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16s_C4RSfs` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp16s *pSrc2`, int `nSrc2Step`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16s_C4RSfs` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16sc_C1RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc *pSrc2`, int `nSrc2Step`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16sc_C1RSfs` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16sc_C3RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc *pSrc2`, int `nSrc2Step`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16sc_C3RSfs` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16sc_AC4RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc *pSrc2`, int `nSrc2Step`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_16sc_AC4RSfs` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_32s_C1RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

Note: This function is to be deprecated in future NPP releases, use the function above with a scale factor of 0 instead.
- `NppStatus nppiMul_32s_C1IRSfs` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_32s_C3RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_32s_C3IRSfs` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_32sc_C1RSfs` (const `Npp32sc` *pSrc1, int nSrc1Step, const `Npp32sc` *pSrc2, int nSrc2Step, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_32sc_C1IRSfs` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_32sc_C3RSfs` (const `Npp32sc` *pSrc1, int nSrc1Step, const `Npp32sc` *pSrc2, int nSrc2Step, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_32sc_C3IRSfs` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_32sc_AC4RSfs` (const `Npp32sc` *pSrc1, int nSrc1Step, const `Npp32sc` *pSrc2, int nSrc2Step, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiMul_32sc_AC4IRSfs` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiMul_32f_C1R` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit floating point channel image multiplication.
- `NppStatus nppiMul_32f_C1IR` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit floating point channel in place image multiplication.
- `NppStatus nppiMul_32f_C3R` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 32-bit floating point channel image multiplication.
- `NppStatus nppiMul_32f_C3IR` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 32-bit floating point channel in place image multiplication.
- `NppStatus nppiMul_32f_AC4R` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit floating point channel with unmodified alpha image multiplication.
- `NppStatus nppiMul_32f_AC4IR` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit floating point channel with unmodified alpha in place image multiplication.
- `NppStatus nppiMul_32f_C4R` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit floating point channel image multiplication.
- `NppStatus nppiMul_32f_C4IR` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit floating point channel in place image multiplication.
- `NppStatus nppiMul_32fc_C1R` (const `Npp32fc` *pSrc1, int nSrc1Step, const `Npp32fc` *pSrc2, int nSrc2Step, `Npp32fc` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image multiplication.
- `NppStatus nppiMul_32fc_C1IR` (const `Npp32fc` *pSrc, int nSrcStep, `Npp32fc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image multiplication.
- `NppStatus nppiMul_32fc_C3R` (const `Npp32fc` *pSrc1, int nSrc1Step, const `Npp32fc` *pSrc2, int nSrc2Step, `Npp32fc` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image multiplication.

- **NppStatus nppiMul_32fc_C3IR** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image multiplication.
- **NppStatus nppiMul_32fc_AC4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** *pSrc2, int nSrc2Step, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image multiplication.
- **NppStatus nppiMul_32fc_AC4IR** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image multiplication.
- **NppStatus nppiMul_32fc_C4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** *pSrc2, int nSrc2Step, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image multiplication.
- **NppStatus nppiMul_32fc_C4IR** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image multiplication.

7.16.1 Detailed Description

Pixel by pixel multiply of two images.

7.16.2 Function Documentation

7.16.2.1 **NppStatus nppiMul_16s_AC4IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.2 `NppStatus nppiMul_16s_AC4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.3 `NppStatus nppiMul_16s_C1IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.4 `NppStatus nppiMul_16s_C1RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.5 `NppStatus nppiMul_16s_C3IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.6 `NppStatus nppiMul_16s_C3RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.7 **NppStatus nppiMul_16s_C4IRSfs** (const Npp16s * *pSrc*, int *nSrcStep*, Npp16s * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 16-bit signed short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.8 **NppStatus nppiMul_16s_C4RSfs** (const Npp16s * *pSrc1*, int *nSrc1Step*, const Npp16s * *pSrc2*, int *nSrc2Step*, Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 16-bit signed short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.9 **NppStatus nppiMul_16sc_AC4IRSfs** (const Npp16sc * *pSrc*, int *nSrcStep*, Npp16sc * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.10 **NppStatus nppiMul_16sc_AC4RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)**

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.11 **NppStatus nppiMul_16sc_C1IRSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)**

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.12 NppStatus nppiMul_16sc_C1RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.13 NppStatus nppiMul_16sc_C3RSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.14 NppStatus nppiMul_16sc_C3RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.15 `NppStatus nppiMul_16u_AC4IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.16 `NppStatus nppiMul_16u_AC4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.17 NppStatus nppiMul_16u_C1IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.18 NppStatus nppiMul_16u_C1RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.19 `NppStatus nppiMul_16u_C3IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.20 `NppStatus nppiMul_16u_C3RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.21 `NppStatus nppiMul_16u_C4IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.22 `NppStatus nppiMul_16u_C4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel image multiplication, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.23 `NppStatus nppiMul_32f_AC4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha in place image multiplication.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.24 `NppStatus nppiMul_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha image multiplication.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.25 `NppStatus nppiMul_32f_C1IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel in place image multiplication.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.26 `NppStatus nppiMul_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel image multiplication.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.27 `NppStatus nppiMul_32f_C3IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 32-bit floating point channel in place image multiplication.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.28 `NppStatus nppiMul_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit floating point channel image multiplication.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.29 `NppStatus nppiMul_32f_C4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel in place image multiplication.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.30 `NppStatus nppiMul_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel image multiplication.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.31 `NppStatus nppiMul_32fc_AC4IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image multiplication.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.32 `NppStatus nppiMul_32fc_AC4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image multiplication.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.33 `NppStatus nppiMul_32fc_C1IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image multiplication.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.34 `NppStatus nppiMul_32fc_C1R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image multiplication.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.35 NppStatus nppiMul_32fc_C3IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image multiplication.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.36 NppStatus nppiMul_32fc_C3R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image multiplication.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.37 `NppStatus nppiMul_32fc_C4IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image multiplication.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.38 `NppStatus nppiMul_32fc_C4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image multiplication.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.39 `NppStatus nppiMul_32s_C1IRSfs (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.40 NppStatus nppiMul_32s_C1R (const Npp32s * *pSrc1*, int *nSrc1Step*, const Npp32s * *pSrc2*, int *nSrc2Step*, Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Note: This function is to be deprecated in future NPP releases, use the function above with a scale factor of 0 instead.

1 channel 32-bit image multiplication. Multiply corresponding pixels in ROI.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.41 NppStatus nppiMul_32s_C1RSfs (const Npp32s * *pSrc1*, int *nSrc1Step*, const Npp32s * *pSrc2*, int *nSrc2Step*, Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

One 32-bit signed integer channel image multiplication, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.42 `NppStatus nppiMul_32s_C3IRSfs (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.43 `NppStatus nppiMul_32s_C3RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.44 `NppStatus nppiMul_32sc_AC4IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.45 `NppStatus nppiMul_32sc_AC4RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.46 `NppStatus nppiMul_32sc_C1IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.47 `NppStatus nppiMul_32sc_C1RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image multiplication, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.48 `NppStatus nppiMul_32sc_C3IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image multiplication, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.16.2.49 `NppStatus nppiMul_32sc_C3RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image multiplication, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.50 `NppStatus nppiMul_8u_AC4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.51 `NppStatus nppiMul_8u_AC4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.52 `NppStatus nppiMul_8u_C1RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.53 `NppStatus nppiMul_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.54 `NppStatus nppiMul_8u_C3IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.55 `NppStatus nppiMul_8u_C3RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.56 `NppStatus nppiMul_8u_C4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel in place image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.16.2.57 `NppStatus nppiMul_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel image multiplication, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17 MulScale

Pixel by pixel multiplies each pixel of two images then scales the result by the maximum value for the data bit width.

Functions

- `NppStatus nppiMulScale_8u_C1R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel image multiplication then scale by maximum value for pixel bit width.
- `NppStatus nppiMulScale_8u_C1IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel in place image multiplication then scale by maximum value for pixel bit width.
- `NppStatus nppiMulScale_8u_C3R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel image multiplication then scale by maximum value for pixel bit width.
- `NppStatus nppiMulScale_8u_C3IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel in place image multiplication then scale by maximum value for pixel bit width.
- `NppStatus nppiMulScale_8u_AC4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel with unmodified alpha image multiplication then scale by maximum value for pixel bit width.
- `NppStatus nppiMulScale_8u_AC4IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel with unmodified alpha in place image multiplication then scale by maximum value for pixel bit width.
- `NppStatus nppiMulScale_8u_C4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image multiplication then scale by maximum value for pixel bit width.
- `NppStatus nppiMulScale_8u_C4IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image multiplication then scale by maximum value for pixel bit width.
- `NppStatus nppiMulScale_16u_C1R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel image multiplication then scale by maximum value for pixel bit width.
- `NppStatus nppiMulScale_16u_C1IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)

One 16-bit unsigned short channel in place image multiplication then scale by maximum value for pixel bit width.

- `NppStatus nppiMulScale_16u_C3R` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u *pSrc2`, int `nSrc2Step`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Three 16-bit unsigned short channel image multiplication then scale by maximum value for pixel bit width.

- `NppStatus nppiMulScale_16u_C3IR` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Three 16-bit unsigned short channel in place image multiplication then scale by maximum value for pixel bit width.

- `NppStatus nppiMulScale_16u_AC4R` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u *pSrc2`, int `nSrc2Step`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four 16-bit unsigned short channel with unmodified alpha image multiplication then scale by maximum value for pixel bit width.

- `NppStatus nppiMulScale_16u_AC4IR` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 16-bit unsigned short channel with unmodified alpha in place image multiplication then scale by maximum value for pixel bit width.

- `NppStatus nppiMulScale_16u_C4R` (const `Npp16u *pSrc1`, int `nSrc1Step`, const `Npp16u *pSrc2`, int `nSrc2Step`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four 16-bit unsigned short channel image multiplication then scale by maximum value for pixel bit width.

- `NppStatus nppiMulScale_16u_C4IR` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 16-bit unsigned short channel in place image multiplication then scale by maximum value for pixel bit width.

7.17.1 Detailed Description

Pixel by pixel multiplies each pixel of two images then scales the result by the maximum value for the data bit width.

7.17.2 Function Documentation

7.17.2.1 `NppStatus nppiMulScale_16u_AC4IR` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)

Four 16-bit unsigned short channel with unmodified alpha in place image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.2 NppStatus nppiMulScale_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel with unmodified alpha image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.3 NppStatus nppiMulScale_16u_C11R (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel in place image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.4 `NppStatus nppiMulScale_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

One 16-bit unsigned short channel image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.5 `NppStatus nppiMulScale_16u_C3IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 16-bit unsigned short channel in place image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.6 `NppStatus nppiMulScale_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

Three 16-bit unsigned short channel image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.7 NppStatus nppiMulScale_16u_C4IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel in place image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.8 NppStatus nppiMulScale_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.9 `NppStatus nppiMulScale_8u_AC4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel with unmodified alpha in place image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.10 `NppStatus nppiMulScale_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel with unmodified alpha image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.11 `NppStatus nppiMulScale_8u_C1IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel in place image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.12 `NppStatus nppiMulScale_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.13 `NppStatus nppiMulScale_8u_C3IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 8-bit unsigned char channel in place image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.17.2.14 `NppStatus nppiMulScale_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Three 8-bit unsigned char channel image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.15 `NppStatus nppiMulScale_8u_C4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.17.2.16 `NppStatus nppiMulScale_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image multiplication then scale by maximum value for pixel bit width.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18 Sub

Pixel by pixel subtraction of two images.

Functions

- `NppStatus nppiSub_8u_C1RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSub_8u_C1IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSub_8u_C3RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSub_8u_C3IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSub_8u_AC4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSub_8u_AC4IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSub_8u_C4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSub_8u_C4IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSub_16u_C1RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiSub_16u_C1IRSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16u_C3RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit unsigned short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16u_C3IRSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit unsigned short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16u_AC4RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 16-bit unsigned short channel with unmodified alpha image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16u_AC4IRSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 16-bit unsigned short channel with unmodified alpha in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16u_C4RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 16-bit unsigned short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16u_C4IRSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 16-bit unsigned short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16s_C1RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit signed short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16s_C1IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit signed short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16s_C3RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit signed short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_16s_C3IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSub_16s_AC4RSfs` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp16s *pSrc2`, int `nSrc2Step`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel with unmodified alpha image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSub_16s_AC4IRSfs` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel with unmodified alpha in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSub_16s_C4RSfs` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp16s *pSrc2`, int `nSrc2Step`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSub_16s_C4IRSfs` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSub_16sc_C1RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc *pSrc2`, int `nSrc2Step`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSub_16sc_C1IRSfs` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSub_16sc_C3RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc *pSrc2`, int `nSrc2Step`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSub_16sc_C3IRSfs` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSub_16sc_AC4RSfs` (const `Npp16sc *pSrc1`, int `nSrc1Step`, const `Npp16sc *pSrc2`, int `nSrc2Step`, `Npp16sc *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSub_16sc_AC4IRSfs` (const `Npp16sc *pSrc`, int `nSrcStep`, `Npp16sc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiSub_32s_C1RSfs** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 32-bit signed integer channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_32s_C1R** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)

Note: This function is to be deprecated in future NPP releases, use the function above with a scale factor of 0 instead.
- **NppStatus nppiSub_32s_C1IRSfs** (const **Npp32s** *pSrc, int nSrcStep, **Npp32s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_32s_C3RSfs** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_32s_C3IRSfs** (const **Npp32s** *pSrc, int nSrcStep, **Npp32s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_32s_C4RSfs** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 32-bit signed integer channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_32s_C4IRSfs** (const **Npp32s** *pSrc, int nSrcStep, **Npp32s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 32-bit signed integer channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_32sc_C1RSfs** (const **Npp32sc** *pSrc1, int nSrc1Step, const **Npp32sc** *pSrc2, int nSrc2Step, **Npp32sc** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_32sc_C1IRSfs** (const **Npp32sc** *pSrc, int nSrcStep, **Npp32sc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSub_32sc_C3RSfs** (const **Npp32sc** *pSrc1, int nSrc1Step, const **Npp32sc** *pSrc2, int nSrc2Step, **Npp32sc** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- [NppStatus nppiSub_32sc_C3IRSfs](#) (const [Npp32sc](#) *pSrc, int nSrcStep, [Npp32sc](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI, int nScaleFactor)
Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- [NppStatus nppiSub_32sc_AC4RSfs](#) (const [Npp32sc](#) *pSrc1, int nSrc1Step, const [Npp32sc](#) *pSrc2, int nSrc2Step, [Npp32sc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, int nScaleFactor)
Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- [NppStatus nppiSub_32sc_AC4IRSfs](#) (const [Npp32sc](#) *pSrc, int nSrcStep, [Npp32sc](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI, int nScaleFactor)
Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- [NppStatus nppiSub_32f_C1R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
One 32-bit floating point channel image subtraction.
- [NppStatus nppiSub_32f_C1IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
One 32-bit floating point channel in place image subtraction.
- [NppStatus nppiSub_32f_C3R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Three 32-bit floating point channel image subtraction.
- [NppStatus nppiSub_32f_C3IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
Three 32-bit floating point channel in place image subtraction.
- [NppStatus nppiSub_32f_AC4R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four 32-bit floating point channel with unmodified alpha image subtraction.
- [NppStatus nppiSub_32f_AC4IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
Four 32-bit floating point channel with unmodified alpha in place image subtraction.
- [NppStatus nppiSub_32f_C4R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four 32-bit floating point channel image subtraction.
- [NppStatus nppiSub_32f_C4IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
Four 32-bit floating point channel in place image subtraction.
- [NppStatus nppiSub_32fc_C1R](#) (const [Npp32fc](#) *pSrc1, int nSrc1Step, const [Npp32fc](#) *pSrc2, int nSrc2Step, [Npp32fc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image subtraction.

- `NppStatus nppiSub_32fc_C1IR` (const `Npp32fc *pSrc`, int `nSrcStep`, `Npp32fc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image subtraction.
- `NppStatus nppiSub_32fc_C3R` (const `Npp32fc *pSrc1`, int `nSrc1Step`, const `Npp32fc *pSrc2`, int `nSrc2Step`, `Npp32fc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image subtraction.
- `NppStatus nppiSub_32fc_C3IR` (const `Npp32fc *pSrc`, int `nSrcStep`, `Npp32fc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image subtraction.
- `NppStatus nppiSub_32fc_AC4R` (const `Npp32fc *pSrc1`, int `nSrc1Step`, const `Npp32fc *pSrc2`, int `nSrc2Step`, `Npp32fc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image subtraction.
- `NppStatus nppiSub_32fc_AC4IR` (const `Npp32fc *pSrc`, int `nSrcStep`, `Npp32fc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image subtraction.
- `NppStatus nppiSub_32fc_C4R` (const `Npp32fc *pSrc1`, int `nSrc1Step`, const `Npp32fc *pSrc2`, int `nSrc2Step`, `Npp32fc *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image subtraction.
- `NppStatus nppiSub_32fc_C4IR` (const `Npp32fc *pSrc`, int `nSrcStep`, `Npp32fc *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image subtraction.

7.18.1 Detailed Description

Pixel by pixel subtraction of two images.

7.18.2 Function Documentation

7.18.2.1 `NppStatus nppiSub_16s_AC4IRSfs` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit signed short channel with unmodified alpha in place image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

- `pSrc` Source-Image Pointer.
- `nSrcStep` Source-Image Line Step.
- `pSrcDst` In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.2 `NppStatus nppiSub_16s_AC4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel with unmodified alpha image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.3 `NppStatus nppiSub_16s_C1IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.4 NppStatus nppiSub_16s_C1RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.5 NppStatus nppiSub_16s_C3RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.6 NppStatus nppiSub_16s_C3RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.7 **NppStatus nppiSub_16s_C4IRSfs** (const Npp16s * *pSrc*, int *nSrcStep*, Npp16s * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 16-bit signed short channel in place image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.8 **NppStatus nppiSub_16s_C4RSfs** (const Npp16s * *pSrc1*, int *nSrc1Step*, const Npp16s * *pSrc2*, int *nSrc2Step*, Npp16s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 16-bit signed short channel image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.9 NppStatus nppiSub_16sc_AC4IRSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.10 NppStatus nppiSub_16sc_AC4RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.11 NppStatus nppiSub_16sc_C1IRSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.12 `NppStatus nppiSub_16sc_C1RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.13 `NppStatus nppiSub_16sc_C3IRSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.14 `NppStatus nppiSub_16sc_C3RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.15 `NppStatus nppiSub_16u_AC4IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel with unmodified alpha in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.16 `NppStatus nppiSub_16u_AC4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel with unmodified alpha image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.17 **NppStatus nppiSub_16u_C1RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)**

One 16-bit unsigned short channel in place image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.18 **NppStatus nppiSub_16u_C1RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)**

One 16-bit unsigned short channel image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.19 NppStatus nppiSub_16u_C3IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.20 NppStatus nppiSub_16u_C3RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.21 NppStatus nppiSub_16u_C4IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.22 NppStatus nppiSub_16u_C4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.23 NppStatus nppiSub_32f_AC4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel with unmodified alpha in place image subtraction.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.24 **NppStatus nppiSub_32f_AC4R** (const Npp32f * *pSrc1*, int *nSrc1Step*, const Npp32f * *pSrc2*, int *nSrc2Step*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Four 32-bit floating point channel with unmodified alpha image subtraction.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.25 **NppStatus nppiSub_32f_C1IR** (const Npp32f * *pSrc*, int *nSrcStep*, Npp32f * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 32-bit floating point channel in place image subtraction.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.26 `NppStatus nppiSub_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel image subtraction.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.27 `NppStatus nppiSub_32f_C3IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 32-bit floating point channel in place image subtraction.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.28 `NppStatus nppiSub_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit floating point channel image subtraction.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.29 `NppStatus nppiSub_32f_C4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel in place image subtraction.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.30 `NppStatus nppiSub_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel image subtraction.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.31 `NppStatus nppiSub_32fc_AC4IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image subtraction.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.32 `NppStatus nppiSub_32fc_AC4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image subtraction.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.33 `NppStatus nppiSub_32fc_C1IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image subtraction.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.34 `NppStatus nppiSub_32fc_C1R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image subtraction.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.35 `NppStatus nppiSub_32fc_C3IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image subtraction.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.36 `NppStatus nppiSub_32fc_C3R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image subtraction.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.37 `NppStatus nppiSub_32fc_C4IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image subtraction.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.38 `NppStatus nppiSub_32fc_C4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image subtraction.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.39 NppStatus nppiSub_32s_C1IRSfs (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.40 NppStatus nppiSub_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Note: This function is to be deprecated in future NPP releases, use the function above with a scale factor of 0 instead.

32-bit image subtraction. Subtract pSrc1's pixels from corresponding pixels in pSrc2.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.41 `NppStatus nppiSub_32s_C1RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.42 `NppStatus nppiSub_32s_C3IRSfs (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.43 `NppStatus nppiSub_32s_C3RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.44 NppStatus nppiSub_32s_C4IRSfs (const Npp32s * *pSrc*, int *nSrcStep*, Npp32s * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 32-bit signed integer channel in place image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.45 NppStatus nppiSub_32s_C4RSfs (const Npp32s * *pSrc1*, int *nSrc1Step*, const Npp32s * *pSrc2*, int *nSrc2Step*, Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Four 32-bit signed integer channel image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.46 NppStatus nppiSub_32sc_AC4IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.47 NppStatus nppiSub_32sc_AC4RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.48 `NppStatus nppiSub_32sc_C1IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.49 `NppStatus nppiSub_32sc_C1RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.50 `NppStatus nppiSub_32sc_C3IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.51 `NppStatus nppiSub_32sc_C3RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.52 `NppStatus nppiSub_8u_AC4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha in place image subtraction, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.53 `NppStatus nppiSub_8u_AC4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.54 `NppStatus nppiSub_8u_C1IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.55 `NppStatus nppiSub_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.56 NppStatus nppiSub_8u_C3IRSfs (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Three 8-bit unsigned char channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.57 NppStatus nppiSub_8u_C3RSfs (const Npp8u * *pSrc1*, int *nSrc1Step*, const Npp8u * *pSrc2*, int *nSrc2Step*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, int *nScaleFactor*)

Three 8-bit unsigned char channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.18.2.58 `NppStatus nppiSub_8u_C4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel in place image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.18.2.59 `NppStatus nppiSub_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel image subtraction, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19 Div

Pixel by pixel division of two images.

Functions

- `NppStatus nppiDiv_8u_C1RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_8u_C1IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_8u_C3RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_8u_C3IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_8u_AC4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_8u_AC4IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel with unmodified alpha in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_8u_C4RSfs` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_8u_C4IRSfs` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_16u_C1RSfs` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiDiv_16u_C1IRSfs` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16u_C3RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16u_C3IRSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16u_AC4RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16u_AC4IRSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16u_C4RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16u_C4IRSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16s_C1RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16s_C1IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16s_C3RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16s_C3IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_16s_AC4RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_16s_AC4IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_16s_C4RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_16s_C4IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_16sc_C1RSfs** (const **Npp16sc** *pSrc1, int nSrc1Step, const **Npp16sc** *pSrc2, int nSrc2Step, **Npp16sc** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_16sc_C1IRSfs** (const **Npp16sc** *pSrc, int nSrcStep, **Npp16sc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_16sc_C3RSfs** (const **Npp16sc** *pSrc1, int nSrc1Step, const **Npp16sc** *pSrc2, int nSrc2Step, **Npp16sc** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_16sc_C3IRSfs** (const **Npp16sc** *pSrc, int nSrcStep, **Npp16sc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_16sc_AC4RSfs** (const **Npp16sc** *pSrc1, int nSrc1Step, const **Npp16sc** *pSrc2, int nSrc2Step, **Npp16sc** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_16sc_AC4IRSfs** (const **Npp16sc** *pSrc, int nSrcStep, **Npp16sc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_32s_C1RSfs** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 32-bit signed integer channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)

Note: This function is to be deprecated in future NPP releases, use the function above with a scale factor of 0 instead.

- `NppStatus nppiDiv_32s_C1IRSfs` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_32s_C3RSfs` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_32s_C3IRSfs` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_32sc_C1RSfs` (const `Npp32sc` *pSrc1, int nSrc1Step, const `Npp32sc` *pSrc2, int nSrc2Step, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_32sc_C1IRSfs` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_32sc_C3RSfs` (const `Npp32sc` *pSrc1, int nSrc1Step, const `Npp32sc` *pSrc2, int nSrc2Step, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_32sc_C3IRSfs` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_32sc_AC4RSfs` (const `Npp32sc` *pSrc1, int nSrc1Step, const `Npp32sc` *pSrc2, int nSrc2Step, `Npp32sc` *pDst, int nDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiDiv_32sc_AC4IRSfs` (const `Npp32sc` *pSrc, int nSrcStep, `Npp32sc` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI, int nScaleFactor)

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- [NppStatus nppiDiv_32f_C1R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
One 32-bit floating point channel image division.
- [NppStatus nppiDiv_32f_C1IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
One 32-bit floating point channel in place image division.
- [NppStatus nppiDiv_32f_C3R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Three 32-bit floating point channel image division.
- [NppStatus nppiDiv_32f_C3IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
Three 32-bit floating point channel in place image division.
- [NppStatus nppiDiv_32f_AC4R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four 32-bit floating point channel with unmodified alpha image division.
- [NppStatus nppiDiv_32f_AC4IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
Four 32-bit floating point channel with unmodified alpha in place image division.
- [NppStatus nppiDiv_32f_C4R](#) (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Four 32-bit floating point channel image division.
- [NppStatus nppiDiv_32f_C4IR](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
Four 32-bit floating point channel in place image division.
- [NppStatus nppiDiv_32fc_C1R](#) (const [Npp32fc](#) *pSrc1, int nSrc1Step, const [Npp32fc](#) *pSrc2, int nSrc2Step, [Npp32fc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image division.
- [NppStatus nppiDiv_32fc_C1IR](#) (const [Npp32fc](#) *pSrc, int nSrcStep, [Npp32fc](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image division.
- [NppStatus nppiDiv_32fc_C3R](#) (const [Npp32fc](#) *pSrc1, int nSrc1Step, const [Npp32fc](#) *pSrc2, int nSrc2Step, [Npp32fc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)
Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image division.
- [NppStatus nppiDiv_32fc_C3IR](#) (const [Npp32fc](#) *pSrc, int nSrcStep, [Npp32fc](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)
Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image division.
- [NppStatus nppiDiv_32fc_AC4R](#) (const [Npp32fc](#) *pSrc1, int nSrc1Step, const [Npp32fc](#) *pSrc2, int nSrc2Step, [Npp32fc](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image division.

- **NppStatus nppiDiv_32fc_AC4IR** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image division.

- **NppStatus nppiDiv_32fc_C4R** (const **Npp32fc** *pSrc1, int nSrc1Step, const **Npp32fc** *pSrc2, int nSrc2Step, **Npp32fc** *pDst, int nDstStep, **NppiSize** oSizeROI)

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image division.

- **NppStatus nppiDiv_32fc_C4IR** (const **Npp32fc** *pSrc, int nSrcStep, **Npp32fc** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image division.

7.19.1 Detailed Description

Pixel by pixel division of two images.

7.19.2 Function Documentation

7.19.2.1 **NppStatus nppiDiv_16s_AC4IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc** Source-Image Pointer.
- nSrcStep** Source-Image Line Step.
- pSrcDst** In-Place Image Pointer.
- nSrcDstStep** In-Place-Image Line Step.
- oSizeROI** Region-of-Interest (ROI).
- nScaleFactor** Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.2 **NppStatus nppiDiv_16s_AC4RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel with unmodified alpha image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc1** Source-Image Pointer.

nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.3 NppStatus nppiDiv_16s_C1IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.4 NppStatus nppiDiv_16s_C1RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short channel image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.5 NppStatus nppiDiv_16s_C3IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.6 NppStatus nppiDiv_16s_C3RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.7 NppStatus nppiDiv_16s_C4IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.8 `NppStatus nppiDiv_16s_C4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.9 `NppStatus nppiDiv_16sc_AC4IRSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.10 NppStatus nppiDiv_16sc_AC4RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel with unmodified alpha image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.11 NppStatus nppiDiv_16sc_C1IRSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.12 NppStatus nppiDiv_16sc_C1RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.13 `NppStatus nppiDiv_16sc_C3IRSfs (const Npp16sc * pSrc, int nSrcStep, Npp16sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.14 `NppStatus nppiDiv_16sc_C3RSfs (const Npp16sc * pSrc1, int nSrc1Step, const Npp16sc * pSrc2, int nSrc2Step, Npp16sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short complex number (16-bit real, 16-bit imaginary) channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.15 NppStatus nppiDiv_16u_AC4IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.16 NppStatus nppiDiv_16u_AC4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel with unmodified alpha image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.17 `NppStatus nppiDiv_16u_C1IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.18 `NppStatus nppiDiv_16u_C1RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.19 `NppStatus nppiDiv_16u_C3IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.20 NppStatus nppiDiv_16u_C3RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.21 NppStatus nppiDiv_16u_C4IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.22 `NppStatus nppiDiv_16u_C4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.23 `NppStatus nppiDiv_32f_AC4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha in place image division.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.24 `NppStatus nppiDiv_32f_AC4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel with unmodified alpha image division.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.25 NppStatus nppiDiv_32f_C1IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel in place image division.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.26 NppStatus nppiDiv_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image division.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.27 NppStatus nppiDiv_32f_C3IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel in place image division.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.28 NppStatus nppiDiv_32f_C3R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image division.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.29 NppStatus nppiDiv_32f_C4IR (const Npp32f * pSrc, int nSrcStep, Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image division.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.30 `NppStatus nppiDiv_32f_C4R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel image division.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.31 `NppStatus nppiDiv_32fc_AC4IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image division.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.32 `NppStatus nppiDiv_32fc_AC4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image division.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.33 `NppStatus nppiDiv_32fc_C1IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image division.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.34 `NppStatus nppiDiv_32fc_C1R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image division.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.35 `NppStatus nppiDiv_32fc_C3IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image division.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.36 `NppStatus nppiDiv_32fc_C3R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image division.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.37 `NppStatus nppiDiv_32fc_C4IR (const Npp32fc * pSrc, int nSrcStep, Npp32fc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel in place image division.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.38 `NppStatus nppiDiv_32fc_C4R (const Npp32fc * pSrc1, int nSrc1Step, const Npp32fc * pSrc2, int nSrc2Step, Npp32fc * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point complex number (32-bit real, 32-bit imaginary) channel image division.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.39 `NppStatus nppiDiv_32s_C1IRSfs (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.40 `NppStatus nppiDiv_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Note: This function is to be deprecated in future NPP releases, use the function above with a scale factor of 0 instead.

32-bit image division. Divide pixels in pSrc2 by pSrc1's pixels.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.41 `NppStatus nppiDiv_32s_C1RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.42 `NppStatus nppiDiv_32s_C3IRSfs (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.43 `NppStatus nppiDiv_32s_C3RSfs (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 32-bit signed integer channel image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.44 `NppStatus nppiDiv_32sc_AC4IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha in place image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.45 `NppStatus nppiDiv_32sc_AC4RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel with unmodified alpha image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.46 `NppStatus nppiDiv_32sc_C1RSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.47 `NppStatus nppiDiv_32sc_C1RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.48 NppStatus nppiDiv_32sc_C3IRSfs (const Npp32sc * pSrc, int nSrcStep, Npp32sc * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel in place image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.49 NppStatus nppiDiv_32sc_C3RSfs (const Npp32sc * pSrc1, int nSrc1Step, const Npp32sc * pSrc2, int nSrc2Step, Npp32sc * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 32-bit signed integer complex number (32-bit real, 32-bit imaginary) channel image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.50 `NppStatus nppiDiv_8u_AC4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.51 `NppStatus nppiDiv_8u_AC4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel with unmodified alpha image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.52 `NppStatus nppiDiv_8u_C1IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.53 `NppStatus nppiDiv_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.54 `NppStatus nppiDiv_8u_C3IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.19.2.55 `NppStatus nppiDiv_8u_C3RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.56 `NppStatus nppiDiv_8u_C4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.19.2.57 `NppStatus nppiDiv_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20 Div_Round

Pixel by pixel division of two images using result rounding modes.

Functions

- **NppStatus nppiDiv_Round_8u_C1RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
One 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_8u_C1IRSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
One 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_8u_C3RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Three 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_8u_C3IRSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Three 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_8u_AC4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Four 8-bit unsigned char channel image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_8u_AC4IRSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Four 8-bit unsigned char channel in place image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_8u_C4RSfs** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Four 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_8u_C4IRSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Four 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_16u_C1RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

One 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16u_C1RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

One 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16u_C3RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

Three 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16u_C3RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

Three 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16u_AC4RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

Four 16-bit unsigned short channel image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16u_AC4RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

Four 16-bit unsigned short channel in place image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16u_C4RSfs** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

Four 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16u_C4RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

Four 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16s_C1RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

One 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16s_C1RSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

One 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiDiv_Round_16s_C3RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Three 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_16s_C3IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Three 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_16s_AC4RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Four 16-bit signed short channel image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_16s_AC4IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Four 16-bit signed short channel in place image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_16s_C4RSfs** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Four 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiDiv_Round_16s_C4IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)
Four 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

7.20.1 Detailed Description

Pixel by pixel division of two images using result rounding modes.

7.20.2 Function Documentation

7.20.2.1 **NppStatus nppiDiv_Round_16s_AC4IRSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, **NppRoundMode** rndMode, int nScaleFactor)

Four 16-bit signed short channel in place image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc** Source-Image Pointer.
- nSrcStep** Source-Image Line Step.
- pSrcDst** In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.2 NppStatus nppiDiv_Round_16s_AC4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

Four 16-bit signed short channel image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.3 NppStatus nppiDiv_Round_16s_C1IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

One 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.4 NppStatus nppiDiv_Round_16s_C1RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

One 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.5 NppStatus nppiDiv_Round_16s_C3IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

Three 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.6 NppStatus nppiDiv_Round_16s_C3RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

Three 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.7 NppStatus nppiDiv_Round_16s_C4IRSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

Four 16-bit signed short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.8 NppStatus nppiDiv_Round_16s_C4RSfs (const Npp16s * pSrc1, int nSrc1Step, const Npp16s * pSrc2, int nSrc2Step, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

Four 16-bit signed short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.9 NppStatus nppiDiv_Round_16u_AC4IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

Four 16-bit unsigned short channel in place image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.10 `NppStatus nppiDiv_Round_16u_AC4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

Four 16-bit unsigned short channel image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.11 `NppStatus nppiDiv_Round_16u_C1IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

One 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.12 NppStatus nppiDiv_Round_16u_C1RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

One 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.13 NppStatus nppiDiv_Round_16u_C3IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

Three 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.20.2.14 `NppStatus nppiDiv_Round_16u_C3RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

Three 16-bit unsigned short channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.15 `NppStatus nppiDiv_Round_16u_C4IRSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

Four 16-bit unsigned short channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.16 `NppStatus nppiDiv_Round_16u_C4RSfs (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

Four 16-bit unsigned short channel image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.17 `NppStatus nppiDiv_Round_8u_AC4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

Four 8-bit unsigned char channel in place image division with unmodified alpha, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.18 `NppStatus nppiDiv_Round_8u_AC4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

Four 8-bit unsigned char channel image division with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.19 `NppStatus nppiDiv_Round_8u_C1IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

One 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.20 `NppStatus nppiDiv_Round_8u_C1RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

One 8-bit unsigned char channel image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.21 `NppStatus nppiDiv_Round_8u_C3IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

Three 8-bit unsigned char channel in place image division, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.22 NppStatus nppiDiv_Round_8u_C3RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

Three 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.23 NppStatus nppiDiv_Round_8u_C4IRSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)

Four 8-bit unsigned char channel in place image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.20.2.24 `NppStatus nppiDiv_Round_8u_C4RSfs (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppRoundMode rndMode, int nScaleFactor)`

Four 8-bit unsigned char channel image division, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

rndMode Result Rounding mode to be used (NPP_RND_ZERO, NPP_RND_NEAR, or NP_RND_FINANCIAL)

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21 Abs

Absolute value of each pixel value in an image.

Functions

- `NppStatus nppiAbs_16s_C1R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 16-bit signed short channel image absolute value.
- `NppStatus nppiAbs_16s_C1IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 16-bit signed short channel in place image absolute value.
- `NppStatus nppiAbs_16s_C3R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 16-bit signed short channel image absolute value.
- `NppStatus nppiAbs_16s_C3IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 16-bit signed short channel in place image absolute value.
- `NppStatus nppiAbs_16s_AC4R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit signed short channel image absolute value with unmodified alpha.
- `NppStatus nppiAbs_16s_AC4IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit signed short channel in place image absolute value with unmodified alpha.
- `NppStatus nppiAbs_16s_C4R` (const `Npp16s` *pSrc, int nSrcStep, `Npp16s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit signed short channel image absolute value.
- `NppStatus nppiAbs_16s_C4IR` (`Npp16s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit signed short channel in place image absolute value.
- `NppStatus nppiAbs_32f_C1R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit floating point channel image absolute value.
- `NppStatus nppiAbs_32f_C1IR` (`Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit floating point channel in place image absolute value.
- `NppStatus nppiAbs_32f_C3R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 32-bit floating point channel image absolute value.
- `NppStatus nppiAbs_32f_C3IR` (`Npp32f` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 32-bit floating point channel in place image absolute value.
- `NppStatus nppiAbs_32f_AC4R` (const `Npp32f` *pSrc, int nSrcStep, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four 32-bit floating point channel image absolute value with unmodified alpha.

- **NppStatus nppiAbs_32f_AC4IR** (**Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel in place image absolute value with unmodified alpha.
- **NppStatus nppiAbs_32f_C4R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel image absolute value.
- **NppStatus nppiAbs_32f_C4IR** (**Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit floating point channel in place image absolute value.

7.21.1 Detailed Description

Absolute value of each pixel value in an image.

7.21.2 Function Documentation

7.21.2.1 NppStatus nppiAbs_16s_AC4IR (Npp16s *pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit signed short channel in place image absolute value with unmodified alpha.

Parameters:

- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.2 NppStatus nppiAbs_16s_AC4R (const Npp16s *pSrc, int nSrcStep, Npp16s *pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit signed short channel image absolute value with unmodified alpha.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.3 NppStatus nppiAbs_16s_C1IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 16-bit signed short channel in place image absolute value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.4 NppStatus nppiAbs_16s_C1R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit signed short channel image absolute value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.5 NppStatus nppiAbs_16s_C3IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 16-bit signed short channel in place image absolute value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.6 NppStatus nppiAbs_16s_C3R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Three 16-bit signed short channel image absolute value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.7 NppStatus nppiAbs_16s_C4IR (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit signed short channel in place image absolute value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.8 NppStatus nppiAbs_16s_C4R (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit signed short channel image absolute value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.9 NppStatus nppiAbs_32f_AC4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image absolute value with unmodified alpha.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.10 NppStatus nppiAbs_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image absolute value with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.11 NppStatus nppiAbs_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel in place image absolute value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.12 NppStatus nppiAbs_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image absolute value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.13 NppStatus nppiAbs_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel in place image absolute value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.14 NppStatus nppiAbs_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image absolute value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.15 NppStatus nppiAbs_32f_C4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image absolute value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.21.2.16 NppStatus nppiAbs_32f_C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image absolute value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.22 AbsDiff

Pixel by pixel absolute difference between two images.

Functions

- `NppStatus nppiAbsDiff_8u_C1R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel absolute difference of image1 minus image2.
- `NppStatus nppiAbsDiff_8u_C3R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channels absolute difference of image1 minus image2.
- `NppStatus nppiAbsDiff_8u_C4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channels absolute difference of image1 minus image2.
- `NppStatus nppiAbsDiff_16u_C1R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel absolute difference of image1 minus image2.
- `NppStatus nppiAbsDiff_32f_C1R` (const `Npp32f` *pSrc1, int nSrc1Step, const `Npp32f` *pSrc2, int nSrc2Step, `Npp32f` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit floating point channel absolute difference of image1 minus image2.

7.22.1 Detailed Description

Pixel by pixel absolute difference between two images.

7.22.2 Function Documentation

7.22.2.1 `NppStatus nppiAbsDiff_16u_C1R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)

One 16-bit unsigned short channel absolute difference of image1 minus image2.

Parameters:

- `pSrc1` Source-Image Pointer.
- `nSrc1Step` Source-Image Line Step.
- `pSrc2` Source-Image Pointer.
- `nSrc2Step` Source-Image Line Step.
- `pDst` Destination-Image Pointer.
- `nDstStep` Destination-Image Line Step.
- `oSizeROI` Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.22.2.2 `NppStatus nppiAbsDiff_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit floating point channel absolute difference of image1 minus image2.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.22.2.3 `NppStatus nppiAbsDiff_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel absolute difference of image1 minus image2.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.22.2.4 `NppStatus nppiAbsDiff_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Three 8-bit unsigned char channels absolute difference of image1 minus image2.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.22.2.5 NppStatus nppiAbsDiff_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channels absolute difference of image1 minus image2.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23 Sqr

Square each pixel in an image.

Functions

- **NppStatus nppiSqr_8u_C1RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqr_8u_C1IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqr_8u_C3RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqr_8u_C3IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqr_8u_AC4RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqr_8u_AC4IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel in place image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqr_8u_C4RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqr_8u_C4IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqr_16u_C1RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqr_16u_C1IRSfs** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

One 16-bit unsigned short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16u_C3RSfs` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 16-bit unsigned short channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16u_C3IRSfs` (`Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 16-bit unsigned short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16u_AC4RSfs` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit unsigned short channel image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16u_AC4IRSfs` (`Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit unsigned short channel in place image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16u_C4RSfs` (const `Npp16u *pSrc`, int `nSrcStep`, `Npp16u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit unsigned short channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16u_C4IRSfs` (`Npp16u *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Four 16-bit unsigned short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16s_C1RSfs` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 16-bit signed short channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16s_C1IRSfs` (`Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

One 16-bit signed short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16s_C3RSfs` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 16-bit signed short channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16s_C3IRSfs` (`Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)

Three 16-bit signed short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- `NppStatus nppiSqr_16s_AC4RSfs` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 16-bit signed short channel image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSqr_16s_AC4IRSfs` (`Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 16-bit signed short channel in place image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSqr_16s_C4RSfs` (const `Npp16s *pSrc`, int `nSrcStep`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 16-bit signed short channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSqr_16s_C4IRSfs` (`Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`, int `nScaleFactor`)
Four 16-bit signed short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- `NppStatus nppiSqr_32f_C1R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel image squared.
- `NppStatus nppiSqr_32f_C1IR` (`Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
One 32-bit floating point channel in place image squared.
- `NppStatus nppiSqr_32f_C3R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel image squared.
- `NppStatus nppiSqr_32f_C3IR` (`Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Three 32-bit floating point channel in place image squared.
- `NppStatus nppiSqr_32f_AC4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel image squared with unmodified alpha.
- `NppStatus nppiSqr_32f_AC4IR` (`Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel in place image squared with unmodified alpha.
- `NppStatus nppiSqr_32f_C4R` (const `Npp32f *pSrc`, int `nSrcStep`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel image squared.
- `NppStatus nppiSqr_32f_C4IR` (`Npp32f *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 32-bit floating point channel in place image squared.

7.23.1 Detailed Description

Square each pixel in an image.

7.23.2 Function Documentation

7.23.2.1 `NppStatus nppiSqr_16s_AC4IRSfs (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel in place image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.23.2.2 `NppStatus nppiSqr_16s_AC4RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit signed short channel image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.23.2.3 `NppStatus nppiSqr_16s_C1IRSfs (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.23.2.4 `NppStatus nppiSqr_16s_C1RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 16-bit signed short channel image squared, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.5 `NppStatus nppiSqr_16s_C3IRSfs (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short channel in place image squared, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.6 `NppStatus nppiSqr_16s_C3RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit signed short channel image squared, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.7 NppStatus nppiSqr_16s_C4IRSfs (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.23.2.8 NppStatus nppiSqr_16s_C4RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.23.2.9 NppStatus nppiSqr_16u_AC4IRSfs (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.23.2.10 NppStatus nppiSqr_16u_AC4RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.11 NppStatus nppiSqr_16u_C1IRSfs (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.12 NppStatus nppiSqr_16u_C1RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.13 `NppStatus nppiSqr_16u_C3IRSfs (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.14 `NppStatus nppiSqr_16u_C3RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 16-bit unsigned short channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.15 `NppStatus nppiSqr_16u_C4IRSfs (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.16 `NppStatus nppiSqr_16u_C4RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 16-bit unsigned short channel image squared, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.17 `NppStatus nppiSqr_32f_AC4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel in place image squared with unmodified alpha.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.18 `NppStatus nppiSqr_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit floating point channel image squared with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.19 NppStatus nppiSqr_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel in place image squared.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.20 NppStatus nppiSqr_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image squared.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.21 NppStatus nppiSqr_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel in place image squared.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.22 NppStatus nppiSqr_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image squared.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.23 NppStatus nppiSqr_32f_C4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image squared.

Parameters:

- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.24 NppStatus nppiSqr_32f_C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image squared.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.25 NppStatus nppiSqr_8u_AC4IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel in place image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.26 NppStatus nppiSqr_8u_AC4RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel image squared with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.27 NppStatus nppiSqr_8u_C1IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.28 `NppStatus nppiSqr_8u_C1RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.29 `NppStatus nppiSqr_8u_C3IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.30 `NppStatus nppiSqr_8u_C3RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.31 NppStatus nppiSqr_8u_C4IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel in place image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.23.2.32 NppStatus nppiSqr_8u_C4RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel image squared, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24 Sqrt

Pixel by pixel square root of each pixel in an image.

Functions

- **NppStatus nppiSqrt_8u_C1RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_8u_C1IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_8u_C3RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_8u_C3IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_8u_AC4RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_8u_AC4IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Four 8-bit unsigned char channel in place image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16u_C1RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16u_C1IRSfs** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16u_C3RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit unsigned short channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiSqrt_16u_C3IRSfs** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16u_AC4RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16u_AC4IRSfs** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16s_C1RSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16s_C1IRSfs** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16s_C3RSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16s_C3IRSfs** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16s_AC4RSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_16s_AC4IRSfs** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiSqrt_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)

One 32-bit floating point channel image square root.
- **NppStatus nppiSqrt_32f_C1IR** (**Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

One 32-bit floating point channel in place image square root.

- [NppStatus nppiSqrt_32f_C3R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)

Three 32-bit floating point channel image square root.

- [NppStatus nppiSqrt_32f_C3IR](#) ([Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

Three 32-bit floating point channel in place image square root.

- [NppStatus nppiSqrt_32f_AC4R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)

Four 32-bit floating point channel image square root with unmodified alpha.

- [NppStatus nppiSqrt_32f_AC4IR](#) ([Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

Four 32-bit floating point channel in place image square root with unmodified alpha.

- [NppStatus nppiSqrt_32f_C4R](#) (const [Npp32f](#) *pSrc, int nSrcStep, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI)

Four 32-bit floating point channel image square root.

- [NppStatus nppiSqrt_32f_C4IR](#) ([Npp32f](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI)

Four 32-bit floating point channel in place image square root.

7.24.1 Detailed Description

Pixel by pixel square root of each pixel in an image.

7.24.2 Function Documentation

7.24.2.1 [NppStatus nppiSqrt_16s_AC4IRSfs](#) ([Npp16s](#) *pSrcDst, int nSrcDstStep, [NppiSize](#) oSizeROI, int nScaleFactor)

Four 16-bit signed short channel in place image square root with unmodified alpha, scale by $2^{-(nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst [In-Place Image Pointer](#).

nSrcDstStep [In-Place-Image Line Step](#).

oSizeROI [Region-of-Interest \(ROI\)](#).

nScaleFactor [Integer Result Scaling](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.24.2.2 NppStatus nppiSqrt_16s_AC4RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit signed short channel image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.3 NppStatus nppiSqrt_16s_C1IRSfs (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.4 NppStatus nppiSqrt_16s_C1RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.24.2.5 NppStatus nppiSqrt_16s_C3IRSfs (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.24.2.6 NppStatus nppiSqrt_16s_C3RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.24.2.7 NppStatus nppiSqrt_16u_AC4IRSfs (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel in place image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.8 NppStatus nppiSqrt_16u_AC4RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 16-bit unsigned short channel image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.9 NppStatus nppiSqrt_16u_C1IRSfs (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.10 NppStatus nppiSqrt_16u_C1RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.24.2.11 NppStatus nppiSqrt_16u_C3IRSfs (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.24.2.12 NppStatus nppiSqrt_16u_C3RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.24.2.13 NppStatus nppiSqrt_32f_AC4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image square root with unmodified alpha.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.14 NppStatus nppiSqrt_32f_AC4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image square root with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.15 NppStatus nppiSqrt_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel in place image square root.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.16 NppStatus nppiSqrt_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image square root.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.17 NppStatus nppiSqrt_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel in place image square root.

Parameters:

- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.18 NppStatus nppiSqrt_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image square root.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.19 NppStatus nppiSqrt_32f_C4IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel in place image square root.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.20 NppStatus nppiSqrt_32f_C4R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit floating point channel image square root.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.21 NppStatus nppiSqrt_8u_AC4IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Four 8-bit unsigned char channel in place image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.22 `NppStatus nppiSqrt_8u_AC4RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Four 8-bit unsigned char channel image square root with unmodified alpha, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.23 `NppStatus nppiSqrt_8u_C1IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.24 `NppStatus nppiSqrt_8u_C1RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.25 `NppStatus nppiSqrt_8u_C3IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel in place image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.24.2.26 `NppStatus nppiSqrt_8u_C3RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel image square root, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25 Ln

Pixel by pixel natural logarithm of each pixel in an image.

Functions

- **NppStatus nppiLn_8u_C1RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_8u_C1IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_8u_C3RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_8u_C3IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_16u_C1RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_16u_C1IRSfs** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_16u_C3RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_16u_C3IRSfs** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_16s_C1RSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiLn_16s_C1IRSfs** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit signed short channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_16s_C3RSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit signed short channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_16s_C3IRSfs** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit signed short channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiLn_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 32-bit floating point channel image natural logarithm.
- **NppStatus nppiLn_32f_C1IR** (**Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit floating point channel in place image natural logarithm.
- **NppStatus nppiLn_32f_C3R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 32-bit floating point channel image natural logarithm.
- **NppStatus nppiLn_32f_C3IR** (**Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 32-bit floating point channel in place image natural logarithm.

7.25.1 Detailed Description

Pixel by pixel natural logarithm of each pixel in an image.

7.25.2 Function Documentation

7.25.2.1 **NppStatus nppiLn_16s_C1IRSfs** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrcDst** In-Place Image Pointer.
- nSrcDstStep** In-Place-Image Line Step.
- oSizeROI** Region-of-Interest (ROI).
- nScaleFactor** Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.2 **NppStatus nppiLn_16s_C1RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)**

One 16-bit signed short channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.3 **NppStatus nppiLn_16s_C3IRSfs (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)**

Three 16-bit signed short channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.4 **NppStatus nppiLn_16s_C3RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)**

Three 16-bit signed short channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.5 **NppStatus nppiLn_16u_C1IRSfs** (**Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor**)

One 16-bit unsigned short channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.25.2.6 **NppStatus nppiLn_16u_C1RSfs** (**const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor**)

One 16-bit unsigned short channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.25.2.7 **NppStatus nppiLn_16u_C3IRSfs** (**Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor**)

Three 16-bit unsigned short channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.25.2.8 NppStatus nppiLn_16u_C3RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- nScaleFactor* Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.9 NppStatus nppiLn_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel in place image natural logarithm.

Parameters:

- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.10 NppStatus nppiLn_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image natural logarithm.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.25.2.11 NppStatus nppiLn_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel in place image natural logarithm.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.25.2.12 NppStatus nppiLn_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit floating point channel image natural logarithm.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.25.2.13 NppStatus nppiLn_8u_C1IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.25.2.14 `NppStatus nppiLn_8u_C1RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.25.2.15 `NppStatus nppiLn_8u_C3IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel in place image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.25.2.16 `NppStatus nppiLn_8u_C3RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)`

Three 8-bit unsigned char channel image natural logarithm, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.26 Exp

Exponential value of each pixel in an image.

Functions

- **NppStatus nppiExp_8u_C1RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_8u_C1IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 8-bit unsigned char channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_8u_C3RSfs** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_8u_C3IRSfs** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 8-bit unsigned char channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_16u_C1RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_16u_C1IRSfs** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit unsigned short channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_16u_C3RSfs** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit unsigned short channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_16u_C3IRSfs** (**Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit unsigned short channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_16s_C1RSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit signed short channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

- **NppStatus nppiExp_16s_C1IRSfs** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
One 16-bit signed short channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_16s_C3RSfs** (const **Npp16s** *pSrc, int nSrcStep, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit signed short channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_16s_C3IRSfs** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)
Three 16-bit signed short channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.
- **NppStatus nppiExp_32f_C1R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 32-bit floating point channel image exponential.
- **NppStatus nppiExp_32f_C1IR** (**Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit floating point channel in place image exponential.
- **NppStatus nppiExp_32f_C3R** (const **Npp32f** *pSrc, int nSrcStep, **Npp32f** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 32-bit floating point channel image exponential.
- **NppStatus nppiExp_32f_C3IR** (**Npp32f** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 32-bit floating point channel in place image exponential.

7.26.1 Detailed Description

Exponential value of each pixel in an image.

7.26.2 Function Documentation

7.26.2.1 **NppStatus nppiExp_16s_C1IRSfs** (**Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI, int nScaleFactor)

One 16-bit signed short channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

- pSrcDst** In-Place Image Pointer.
- nSrcDstStep** In-Place-Image Line Step.
- oSizeROI** Region-of-Interest (ROI).
- nScaleFactor** Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.26.2.2 NppStatus nppiExp_16s_C1RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit signed short channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.26.2.3 NppStatus nppiExp_16s_C3IRSfs (Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.26.2.4 NppStatus nppiExp_16s_C3RSfs (const Npp16s * pSrc, int nSrcStep, Npp16s * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit signed short channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.26.2.5 NppStatus nppiExp_16u_C1IRSfs (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.26.2.6 NppStatus nppiExp_16u_C1RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 16-bit unsigned short channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.26.2.7 NppStatus nppiExp_16u_C3IRSfs (Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.26.2.8 NppStatus nppiExp_16u_C3RSfs (const Npp16u * pSrc, int nSrcStep, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 16-bit unsigned short channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.26.2.9 NppStatus nppiExp_32f_C1IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit floating point channel in place image exponential.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.26.2.10 NppStatus nppiExp_32f_C1R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit floating point channel image exponential.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.26.2.11 `NppStatus nppiExp_32f_C3IR (Npp32f * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 32-bit floating point channel in place image exponential.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.26.2.12 `NppStatus nppiExp_32f_C3R (const Npp32f * pSrc, int nSrcStep, Npp32f * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit floating point channel image exponential.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.26.2.13 `NppStatus nppiExp_8u_C1IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)`

One 8-bit unsigned char channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

nScaleFactor Integer Result Scaling.

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.26.2.14 NppStatus nppiExp_8u_C1RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

One 8-bit unsigned char channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.26.2.15 NppStatus nppiExp_8u_C3IRSfs (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel in place image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.26.2.16 NppStatus nppiExp_8u_C3RSfs (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, int nScaleFactor)

Three 8-bit unsigned char channel image exponential, scale by $2^{(-nScaleFactor)}$, then clamp to saturated value.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
nScaleFactor Integer Result Scaling.

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.27 Logical Operations

Modules

- [AndC](#)
Pixel by pixel logical and of an image with a constant.
- [OrC](#)
Pixel by pixel logical or of an image with a constant.
- [XorC](#)
Pixel by pixel logical exclusive or of an image with a constant.
- [RShiftC](#)
Pixel by pixel right shift of an image by a constant value.
- [LShiftC](#)
Pixel by pixel left shift of an image by a constant value.
- [And](#)
Pixel by pixel logical and of images.
- [Or](#)
Pixel by pixel logical or of images.
- [Xor](#)
Pixel by pixel logical exclusive or of images.
- [Not](#)
Pixel by pixel logical not of image.

7.28 AndC

Pixel by pixel logical and of an image with a constant.

Functions

- **NppStatus nppiAndC_8u_C1R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** nConstant, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel image logical and with constant.
- **NppStatus nppiAndC_8u_C1IR** (const **Npp8u** nConstant, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel in place image logical and with constant.
- **NppStatus nppiAndC_8u_C3R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel image logical and with constant.
- **NppStatus nppiAndC_8u_C3IR** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel in place image logical and with constant.
- **NppStatus nppiAndC_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image logical and with constant with unmodified alpha.
- **NppStatus nppiAndC_8u_AC4IR** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image logical and with constant with unmodified alpha.
- **NppStatus nppiAndC_8u_C4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[4], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image logical and with constant.
- **NppStatus nppiAndC_8u_C4IR** (const **Npp8u** aConstants[4], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image logical and with constant.
- **NppStatus nppiAndC_16u_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** nConstant, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image logical and with constant.
- **NppStatus nppiAndC_16u_C1IR** (const **Npp16u** nConstant, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel in place image logical and with constant.
- **NppStatus nppiAndC_16u_C3R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** aConstants[3], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 16-bit unsigned short channel image logical and with constant.

- `NppStatus nppiAndC_16u_C3IR` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel in place image logical and with constant.
- `NppStatus nppiAndC_16u_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical and with constant with unmodified alpha.
- `NppStatus nppiAndC_16u_AC4IR` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical and with constant with unmodified alpha.
- `NppStatus nppiAndC_16u_C4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[4], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical and with constant.
- `NppStatus nppiAndC_16u_C4IR` (const `Npp16u` aConstants[4], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical and with constant.
- `NppStatus nppiAndC_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` nConstant, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel image logical and with constant.
- `NppStatus nppiAndC_32s_C1IR` (const `Npp32s` nConstant, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel in place image logical and with constant.
- `NppStatus nppiAndC_32s_C3R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel image logical and with constant.
- `NppStatus nppiAndC_32s_C3IR` (const `Npp32s` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel in place image logical and with constant.
- `NppStatus nppiAndC_32s_AC4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical and with constant with unmodified alpha.
- `NppStatus nppiAndC_32s_AC4IR` (const `Npp32s` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical and with constant with unmodified alpha.
- `NppStatus nppiAndC_32s_C4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[4], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical and with constant.
- `NppStatus nppiAndC_32s_C4IR` (const `Npp32s` aConstants[4], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical and with constant.

7.28.1 Detailed Description

Pixel by pixel logical and of an image with a constant.

7.28.2 Function Documentation

7.28.2.1 `NppStatus nppiAndC_16u_AC4IR (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel in place image logical and with constant with unmodified alpha.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.28.2.2 `NppStatus nppiAndC_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel image logical and with constant with unmodified alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.28.2.3 `NppStatus nppiAndC_16u_C1IR (const Npp16u nConstant, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 16-bit unsigned short channel in place image logical and with constant.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.28.2.4 NppStatus nppiAndC_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel image logical and with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.28.2.5 NppStatus nppiAndC_16u_C3IR (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel in place image logical and with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.28.2.6 NppStatus nppiAndC_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel image logical and with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.28.2.7 NppStatus nppiAndC_16u_C4IR (const Npp16u aConstants[4], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel in place image logical and with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.28.2.8 NppStatus nppiAndC_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image logical and with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.28.2.9 NppStatus nppiAndC_32s_AC4IR (const Npp32s aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel in place image logical and with constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.28.2.10 NppStatus nppiAndC_32s_AC4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel image logical and with constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.28.2.11 NppStatus nppiAndC_32s_C1IR (const Npp32s nConstant, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel in place image logical and with constant.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.28.2.12 NppStatus nppiAndC_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s nConstant, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel image logical and with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.28.2.13 NppStatus nppiAndC_32s_C3IR (const Npp32s aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit signed integer channel in place image logical and with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.28.2.14 NppStatus nppiAndC_32s_C3R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit signed integer channel image logical and with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.28.2.15 `NppStatus nppiAndC_32s_C4IR (const Npp32s aConstants[4], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel in place image logical and with constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* [In-Place Image Pointer](#).
- nSrcDstStep* [In-Place-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.28.2.16 `NppStatus nppiAndC_32s_C4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[4], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel image logical and with constant.

Parameters:

- pSrc1* [Source-Image Pointer](#).
- nSrc1Step* [Source-Image Line Step](#).
- aConstants* fixed size array of constant values, one per channel.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.28.2.17 `NppStatus nppiAndC_8u_AC4IR (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image logical and with constant with unmodified alpha.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* [In-Place Image Pointer](#).
- nSrcDstStep* [In-Place-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.28.2.18 `NppStatus nppiAndC_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical and with constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.28.2.19 `NppStatus nppiAndC_8u_C1IR (const Npp8u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel in place image logical and with constant.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.28.2.20 `NppStatus nppiAndC_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel image logical and with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.28.2.21 NppStatus nppiAndC_8u_C3IR (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel in place image logical and with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.28.2.22 NppStatus nppiAndC_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel image logical and with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.28.2.23 NppStatus nppiAndC_8u_C4IR (const Npp8u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel in place image logical and with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.28.2.24 `NppStatus nppiAndC_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical and with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29 OrC

Pixel by pixel logical or of an image with a constant.

Functions

- `NppStatus nppiOrC_8u_C1R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` nConstant, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel image logical or with constant.
- `NppStatus nppiOrC_8u_C1IR` (const `Npp8u` nConstant, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel in place image logical or with constant.
- `NppStatus nppiOrC_8u_C3R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` aConstants[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel image logical or with constant.
- `NppStatus nppiOrC_8u_C3IR` (const `Npp8u` aConstants[3], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel in place image logical or with constant.
- `NppStatus nppiOrC_8u_AC4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` aConstants[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image logical or with constant with unmodified alpha.
- `NppStatus nppiOrC_8u_AC4IR` (const `Npp8u` aConstants[3], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image logical or with constant with unmodified alpha.
- `NppStatus nppiOrC_8u_C4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` aConstants[4], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image logical or with constant.
- `NppStatus nppiOrC_8u_C4IR` (const `Npp8u` aConstants[4], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image logical or with constant.
- `NppStatus nppiOrC_16u_C1R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` nConstant, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel image logical or with constant.
- `NppStatus nppiOrC_16u_C1IR` (const `Npp16u` nConstant, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel in place image logical or with constant.
- `NppStatus nppiOrC_16u_C3R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel image logical or with constant.

- `NppStatus nppiOrC_16u_C3IR` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel in place image logical or with constant.
- `NppStatus nppiOrC_16u_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical or with constant with unmodified alpha.
- `NppStatus nppiOrC_16u_AC4IR` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical or with constant with unmodified alpha.
- `NppStatus nppiOrC_16u_C4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[4], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical or with constant.
- `NppStatus nppiOrC_16u_C4IR` (const `Npp16u` aConstants[4], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical or with constant.
- `NppStatus nppiOrC_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` nConstant, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel image logical or with constant.
- `NppStatus nppiOrC_32s_C1IR` (const `Npp32s` nConstant, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel in place image logical or with constant.
- `NppStatus nppiOrC_32s_C3R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel image logical or with constant.
- `NppStatus nppiOrC_32s_C3IR` (const `Npp32s` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel in place image logical or with constant.
- `NppStatus nppiOrC_32s_AC4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical or with constant with unmodified alpha.
- `NppStatus nppiOrC_32s_AC4IR` (const `Npp32s` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical or with constant with unmodified alpha.
- `NppStatus nppiOrC_32s_C4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[4], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical or with constant.
- `NppStatus nppiOrC_32s_C4IR` (const `Npp32s` aConstants[4], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical or with constant.

7.29.1 Detailed Description

Pixel by pixel logical or of an image with a constant.

7.29.2 Function Documentation

7.29.2.1 `NppStatus nppiOrC_16u_AC4IR (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel in place image logical or with constant with unmodified alpha.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.2 `NppStatus nppiOrC_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel image logical or with constant with unmodified alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.3 `NppStatus nppiOrC_16u_C1IR (const Npp16u nConstant, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 16-bit unsigned short channel in place image logical or with constant.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.4 NppStatus nppiOrC_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel image logical or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.5 NppStatus nppiOrC_16u_C3IR (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel in place image logical or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.6 NppStatus nppiOrC_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel image logical or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.7 NppStatus nppiOrC_16u_C4IR (const Npp16u aConstants[4], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel in place image logical or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.8 NppStatus nppiOrC_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image logical or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.9 NppStatus nppiOrC_32s_AC4IR (const Npp32s aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel in place image logical or with constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.10 NppStatus nppiOrC_32s_AC4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel image logical or with constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.11 NppStatus nppiOrC_32s_C1IR (const Npp32s nConstant, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel in place image logical or with constant.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.12 NppStatus nppiOrC_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s nConstant, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel image logical or with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.13 NppStatus nppiOrC_32s_C3IR (const Npp32s aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit signed integer channel in place image logical or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.14 NppStatus nppiOrC_32s_C3R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit signed integer channel image logical or with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.15 NppStatus nppiOrC_32s_C4IR (const Npp32s aConstants[4], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel in place image logical or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.16 NppStatus nppiOrC_32s_C4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[4], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel image logical or with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.17 NppStatus nppiOrC_8u_AC4IR (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel in place image logical or with constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.18 `NppStatus nppiOrC_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical or with constant with unmodified alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.19 `NppStatus nppiOrC_8u_C1IR (const Npp8u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel in place image logical or with constant.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.20 `NppStatus nppiOrC_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel image logical or with constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nConstant* Constant.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.29.2.21 NppStatus nppiOrC_8u_C3IR (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel in place image logical or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.22 NppStatus nppiOrC_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel image logical or with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.23 NppStatus nppiOrC_8u_C4IR (const Npp8u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel in place image logical or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.29.2.24 NppStatus nppiOrC_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel image logical or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30 XorC

Pixel by pixel logical exclusive or of an image with a constant.

Functions

- **NppStatus nppiXorC_8u_C1R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** nConstant, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel image logical exclusive or with constant.
- **NppStatus nppiXorC_8u_C1IR** (const **Npp8u** nConstant, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel in place image logical exclusive or with constant.
- **NppStatus nppiXorC_8u_C3R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel image logical exclusive or with constant.
- **NppStatus nppiXorC_8u_C3IR** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel in place image logical exclusive or with constant.
- **NppStatus nppiXorC_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image logical exclusive or with constant with unmodified alpha.
- **NppStatus nppiXorC_8u_AC4IR** (const **Npp8u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image logical exclusive or with constant with unmodified alpha.
- **NppStatus nppiXorC_8u_C4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** aConstants[4], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image logical exclusive or with constant.
- **NppStatus nppiXorC_8u_C4IR** (const **Npp8u** aConstants[4], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image logical exclusive or with constant.
- **NppStatus nppiXorC_16u_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** nConstant, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image logical exclusive or with constant.
- **NppStatus nppiXorC_16u_C1IR** (const **Npp16u** nConstant, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel in place image logical exclusive or with constant.
- **NppStatus nppiXorC_16u_C3R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** aConstants[3], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 16-bit unsigned short channel image logical exclusive or with constant.

- `NppStatus nppiXorC_16u_C3IR` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel in place image logical exclusive or with constant.
- `NppStatus nppiXorC_16u_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical exclusive or with constant with unmodified alpha.
- `NppStatus nppiXorC_16u_AC4IR` (const `Npp16u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical exclusive or with constant with unmodified alpha.
- `NppStatus nppiXorC_16u_C4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` aConstants[4], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical exclusive or with constant.
- `NppStatus nppiXorC_16u_C4IR` (const `Npp16u` aConstants[4], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical exclusive or with constant.
- `NppStatus nppiXorC_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` nConstant, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel image logical exclusive or with constant.
- `NppStatus nppiXorC_32s_C1IR` (const `Npp32s` nConstant, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel in place image logical exclusive or with constant.
- `NppStatus nppiXorC_32s_C3R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel image logical exclusive or with constant.
- `NppStatus nppiXorC_32s_C3IR` (const `Npp32s` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel in place image logical exclusive or with constant.
- `NppStatus nppiXorC_32s_AC4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical exclusive or with constant with unmodified alpha.
- `NppStatus nppiXorC_32s_AC4IR` (const `Npp32s` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical exclusive or with constant with unmodified alpha.
- `NppStatus nppiXorC_32s_C4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` aConstants[4], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical exclusive or with constant.
- `NppStatus nppiXorC_32s_C4IR` (const `Npp32s` aConstants[4], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical exclusive or with constant.

7.30.1 Detailed Description

Pixel by pixel logical exclusive or of an image with a constant.

7.30.2 Function Documentation

7.30.2.1 NppStatus nppiXorC_16u_AC4IR (const Npp16u *aConstants*[3], Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Four 16-bit unsigned short channel in place image logical exclusive or with constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.2 NppStatus nppiXorC_16u_AC4R (const Npp16u * *pSrc1*, int *nSrc1Step*, const Npp16u *aConstants*[3], Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Four 16-bit unsigned short channel image logical exclusive or with constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.3 NppStatus nppiXorC_16u_C1IR (const Npp16u *nConstant*, Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 16-bit unsigned short channel in place image logical exclusive or with constant.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.4 NppStatus nppiXorC_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel image logical exclusive or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.5 NppStatus nppiXorC_16u_C3IR (const Npp16u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel in place image logical exclusive or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.6 NppStatus nppiXorC_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel image logical exclusive or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.7 NppStatus nppiXorC_16u_C4IR (const Npp16u aConstants[4], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel in place image logical exclusive or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.8 NppStatus nppiXorC_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image logical exclusive or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.9 NppStatus nppiXorC_32s_AC4IR (const Npp32s *aConstants*[3], Npp32s * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Four 32-bit signed integer channel in place image logical exclusive or with constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.10 NppStatus nppiXorC_32s_AC4R (const Npp32s * *pSrc1*, int *nSrc1Step*, const Npp32s *aConstants*[3], Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Four 32-bit signed integer channel image logical exclusive or with constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.11 NppStatus nppiXorC_32s_C1IR (const Npp32s *nConstant*, Npp32s * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 32-bit signed integer channel in place image logical exclusive or with constant.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.12 NppStatus nppiXorC_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s nConstant, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel image logical exclusive or with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.13 NppStatus nppiXorC_32s_C3IR (const Npp32s aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit signed integer channel in place image logical exclusive or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.14 NppStatus nppiXorC_32s_C3R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Three 32-bit signed integer channel image logical exclusive or with constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.15 `NppStatus nppiXorC_32s_C4IR (const Npp32s aConstants[4], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel in place image logical exclusive or with constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* [In-Place Image Pointer](#).
- nSrcDstStep* [In-Place-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.16 `NppStatus nppiXorC_32s_C4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s aConstants[4], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel image logical exclusive or with constant.

Parameters:

- pSrc1* [Source-Image Pointer](#).
- nSrc1Step* [Source-Image Line Step](#).
- aConstants* fixed size array of constant values, one per channel.
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.17 `NppStatus nppiXorC_8u_AC4IR (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image logical exclusive or with constant with unmodified alpha.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* [In-Place Image Pointer](#).
- nSrcDstStep* [In-Place-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.18 `NppStatus nppiXorC_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical exclusive or with constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.19 `NppStatus nppiXorC_8u_C1IR (const Npp8u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel in place image logical exclusive or with constant.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.20 `NppStatus nppiXorC_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel image logical exclusive or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.30.2.21 NppStatus nppiXorC_8u_C3IR (const Npp8u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel in place image logical exclusive or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.22 NppStatus nppiXorC_8u_C3R (const Npp8u * pSrcI, int nSrcIStep, const Npp8u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel image logical exclusive or with constant.

Parameters:

pSrcI Source-Image Pointer.
nSrcIStep Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.23 NppStatus nppiXorC_8u_C4IR (const Npp8u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel in place image logical exclusive or with constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.30.2.24 NppStatus nppiXorC_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u aConstants[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel image logical exclusive or with constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31 RShiftC

Pixel by pixel right shift of an image by a constant value.

Functions

- `NppStatus nppiRShiftC_8u_C1R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp32u` nConstant, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel image right shift by constant.
- `NppStatus nppiRShiftC_8u_C1IR` (const `Npp32u` nConstant, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel in place image right shift by constant.
- `NppStatus nppiRShiftC_8u_C3R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp32u` aConstants[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel image right shift by constant.
- `NppStatus nppiRShiftC_8u_C3IR` (const `Npp32u` aConstants[3], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel in place image right shift by constant.
- `NppStatus nppiRShiftC_8u_AC4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp32u` aConstants[3], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image right shift by constant with unmodified alpha.
- `NppStatus nppiRShiftC_8u_AC4IR` (const `Npp32u` aConstants[3], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image right shift by constant with unmodified alpha.
- `NppStatus nppiRShiftC_8u_C4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp32u` aConstants[4], `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image right shift by constant.
- `NppStatus nppiRShiftC_8u_C4IR` (const `Npp32u` aConstants[4], `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image right shift by constant.
- `NppStatus nppiRShiftC_8s_C1R` (const `Npp8s` *pSrc1, int nSrc1Step, const `Npp32u` nConstant, `Npp8s` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 8-bit signed char channel image right shift by constant.
- `NppStatus nppiRShiftC_8s_C1IR` (const `Npp32u` nConstant, `Npp8s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 8-bit signed char channel in place image right shift by constant.
- `NppStatus nppiRShiftC_8s_C3R` (const `Npp8s` *pSrc1, int nSrc1Step, const `Npp32u` aConstants[3], `Npp8s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 8-bit signed char channel image right shift by constant.

- **NppStatus nppiRShiftC_8s_C3IR** (const **Npp32u** aConstants[3], **Npp8s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 8-bit signed char channel in place image right shift by constant.
- **NppStatus nppiRShiftC_8s_AC4R** (const **Npp8s** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[3], **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit signed char channel image right shift by constant with unmodified alpha.
- **NppStatus nppiRShiftC_8s_AC4IR** (const **Npp32u** aConstants[3], **Npp8s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit signed char channel in place image right shift by constant with unmodified alpha.
- **NppStatus nppiRShiftC_8s_C4R** (const **Npp8s** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[4], **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit signed char channel image right shift by constant.
- **NppStatus nppiRShiftC_8s_C4IR** (const **Npp32u** aConstants[4], **Npp8s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit signed char channel in place image right shift by constant.
- **NppStatus nppiRShiftC_16u_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp32u** nConstant, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image right shift by constant.
- **NppStatus nppiRShiftC_16u_C1IR** (const **Npp32u** nConstant, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel in place image right shift by constant.
- **NppStatus nppiRShiftC_16u_C3R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[3], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 16-bit unsigned short channel image right shift by constant.
- **NppStatus nppiRShiftC_16u_C3IR** (const **Npp32u** aConstants[3], **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 16-bit unsigned short channel in place image right shift by constant.
- **NppStatus nppiRShiftC_16u_AC4R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[3], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 16-bit unsigned short channel image right shift by constant with unmodified alpha.
- **NppStatus nppiRShiftC_16u_AC4IR** (const **Npp32u** aConstants[3], **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 16-bit unsigned short channel in place image right shift by constant with unmodified alpha.
- **NppStatus nppiRShiftC_16u_C4R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[4], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 16-bit unsigned short channel image right shift by constant.
- **NppStatus nppiRShiftC_16u_C4IR** (const **Npp32u** aConstants[4], **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 16-bit unsigned short channel in place image right shift by constant.

- `NppStatus nppiRShiftC_16s_C1R` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp32u nConstant`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
One 16-bit signed short channel image right shift by constant.
- `NppStatus nppiRShiftC_16s_C1IR` (const `Npp32u nConstant`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
One 16-bit signed short channel in place image right shift by constant.
- `NppStatus nppiRShiftC_16s_C3R` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp32u aConstants[3]`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 16-bit signed short channel image right shift by constant.
- `NppStatus nppiRShiftC_16s_C3IR` (const `Npp32u aConstants[3]`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Three 16-bit signed short channel in place image right shift by constant.
- `NppStatus nppiRShiftC_16s_AC4R` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp32u aConstants[3]`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 16-bit signed short channel image right shift by constant with unmodified alpha.
- `NppStatus nppiRShiftC_16s_AC4IR` (const `Npp32u aConstants[3]`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 16-bit signed short channel in place image right shift by constant with unmodified alpha.
- `NppStatus nppiRShiftC_16s_C4R` (const `Npp16s *pSrc1`, int `nSrc1Step`, const `Npp32u aConstants[4]`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Four 16-bit signed short channel image right shift by constant.
- `NppStatus nppiRShiftC_16s_C4IR` (const `Npp32u aConstants[4]`, `Npp16s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Four 16-bit signed short channel in place image right shift by constant.
- `NppStatus nppiRShiftC_32s_C1R` (const `Npp32s *pSrc1`, int `nSrc1Step`, const `Npp32u nConstant`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
One 32-bit signed integer channel image right shift by constant.
- `NppStatus nppiRShiftC_32s_C1IR` (const `Npp32u nConstant`, `Npp32s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
One 32-bit signed integer channel in place image right shift by constant.
- `NppStatus nppiRShiftC_32s_C3R` (const `Npp32s *pSrc1`, int `nSrc1Step`, const `Npp32u aConstants[3]`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)
Three 32-bit signed integer channel image right shift by constant.
- `NppStatus nppiRShiftC_32s_C3IR` (const `Npp32u aConstants[3]`, `Npp32s *pSrcDst`, int `nSrcDstStep`, `NppiSize oSizeROI`)
Three 32-bit signed integer channel in place image right shift by constant.
- `NppStatus nppiRShiftC_32s_AC4R` (const `Npp32s *pSrc1`, int `nSrc1Step`, const `Npp32u aConstants[3]`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`)

Four 32-bit signed integer channel image right shift by constant with unmodified alpha.

- **NppStatus nppiRShiftC_32s_AC4IR** (const **Npp32u** aConstants[3], **Npp32s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

Four 32-bit signed integer channel in place image right shift by constant with unmodified alpha.

- **NppStatus nppiRShiftC_32s_C4R** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[4], **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)

Four 32-bit signed integer channel image right shift by constant.

- **NppStatus nppiRShiftC_32s_C4IR** (const **Npp32u** aConstants[4], **Npp32s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

Four 32-bit signed integer channel in place image right shift by constant.

7.31.1 Detailed Description

Pixel by pixel right shift of an image by a constant value.

7.31.2 Function Documentation

7.31.2.1 **NppStatus nppiRShiftC_16s_AC4IR** (const **Npp32u** aConstants[3], **Npp16s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

Four 16-bit signed short channel in place image right shift by constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.2 **NppStatus nppiRShiftC_16s_AC4R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[3], **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI)

Four 16-bit signed short channel image right shift by constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.3 NppStatus nppiRShiftC_16s_C1IR (const Npp32u nConstant, Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 16-bit signed short channel in place image right shift by constant.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.4 NppStatus nppiRShiftC_16s_C1R (const Npp16s * pSrc1, int nSrc1Step, const Npp32u nConstant, Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit signed short channel image right shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.5 NppStatus nppiRShiftC_16s_C3IR (const Npp32u aConstants[3], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 16-bit signed short channel in place image right shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.6 NppStatus nppiRShiftC_16s_C3R (const Npp16s * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Three 16-bit signed short channel image right shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.7 NppStatus nppiRShiftC_16s_C4IR (const Npp32u aConstants[4], Npp16s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit signed short channel in place image right shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.8 NppStatus nppiRShiftC_16s_C4R (const Npp16s * pSrc1, int nSrc1Step, const Npp32u aConstants[4], Npp16s * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit signed short channel image right shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.9 NppStatus nppiRShiftC_16u_AC4IR (const Npp32u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel in place image right shift by constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.10 NppStatus nppiRShiftC_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image right shift by constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.11 NppStatus nppiRShiftC_16u_C1IR (const Npp32u *nConstant*, Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 16-bit unsigned short channel in place image right shift by constant.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.12 NppStatus nppiRShiftC_16u_C1R (const Npp16u * *pSrc1*, int *nSrc1Step*, const Npp32u *nConstant*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

One 16-bit unsigned short channel image right shift by constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.13 NppStatus nppiRShiftC_16u_C3IR (const Npp32u *aConstants*[3], Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Three 16-bit unsigned short channel in place image right shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.14 `NppStatus nppiRShiftC_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

Three 16-bit unsigned short channel image right shift by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.15 `NppStatus nppiRShiftC_16u_C4IR (const Npp32u aConstants[4], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel in place image right shift by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.16 `NppStatus nppiRShiftC_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp32u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel image right shift by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.17 NppStatus nppiRShiftC_32s_AC4IR (const Npp32u *aConstants*[3], Npp32s * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Four 32-bit signed integer channel in place image right shift by constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.18 NppStatus nppiRShiftC_32s_AC4R (const Npp32s * *pSrcI*, int *nSrcIStep*, const Npp32u *aConstants*[3], Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Four 32-bit signed integer channel image right shift by constant with unmodified alpha.

Parameters:

pSrcI Source-Image Pointer.
nSrcIStep Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.19 NppStatus nppiRShiftC_32s_C1IR (const Npp32u *nConstant*, Npp32s * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 32-bit signed integer channel in place image right shift by constant.

Parameters:

nConstant Constant.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.20 `NppStatus nppiRShiftC_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32u nConstant, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit signed integer channel image right shift by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nConstant* Constant.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.21 `NppStatus nppiRShiftC_32s_C3IR (const Npp32u aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 32-bit signed integer channel in place image right shift by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.22 `NppStatus nppiRShiftC_32s_C3R (const Npp32s * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit signed integer channel image right shift by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.23 NppStatus nppiRShiftC_32s_C4IR (const Npp32u aConstants[4], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel in place image right shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.24 NppStatus nppiRShiftC_32s_C4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32u aConstants[4], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel image right shift by constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.25 NppStatus nppiRShiftC_8s_AC4IR (const Npp32u aConstants[3], Npp8s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit signed char channel in place image right shift by constant with unmodified alpha.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.31.2.26 `NppStatus nppiRShiftC_8s_AC4R (const Npp8s * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp8s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit signed char channel image right shift by constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.27 `NppStatus nppiRShiftC_8s_C1IR (const Npp32u nConstant, Npp8s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 8-bit signed char channel in place image right shift by constant.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.28 `NppStatus nppiRShiftC_8s_C1R (const Npp8s * pSrc1, int nSrc1Step, const Npp32u nConstant, Npp8s * pDst, int nDstStep, NppiSize oSizeROI)`

One 8-bit signed char channel image right shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.29 NppStatus nppiRShiftC_8s_C3IR (const Npp32u aConstants[3], Npp8s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 8-bit signed char channel in place image right shift by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.30 NppStatus nppiRShiftC_8s_C3R (const Npp8s * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp8s * pDst, int nDstStep, NppiSize oSizeROI)

Three 8-bit signed char channel image right shift by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.31 NppStatus nppiRShiftC_8s_C4IR (const Npp32u aConstants[4], Npp8s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit signed char channel in place image right shift by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.32 `NppStatus nppiRShiftC_8s_C4R (const Npp8s * pSrc1, int nSrc1Step, const Npp32u aConstants[4], Npp8s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit signed char channel image right shift by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.33 `NppStatus nppiRShiftC_8u_AC4IR (const Npp32u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image right shift by constant with unmodified alpha.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.34 `NppStatus nppiRShiftC_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image right shift by constant with unmodified alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.35 NppStatus nppiRShiftC_8u_C1IR (const Npp32u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel in place image right shift by constant.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.36 NppStatus nppiRShiftC_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp32u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel image right shift by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nConstant* Constant.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.37 NppStatus nppiRShiftC_8u_C3IR (const Npp32u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel in place image right shift by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.38 `NppStatus nppiRShiftC_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Three 8-bit unsigned char channel image right shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.39 `NppStatus nppiRShiftC_8u_C4IR (const Npp32u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image right shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.31.2.40 `NppStatus nppiRShiftC_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp32u aConstants[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image right shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32 LShiftC

Pixel by pixel left shift of an image by a constant value.

Functions

- **NppStatus nppiLShiftC_8u_C1R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp32u** nConstant, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel image left shift by constant.
- **NppStatus nppiLShiftC_8u_C1IR** (const **Npp32u** nConstant, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel in place image left shift by constant.
- **NppStatus nppiLShiftC_8u_C3R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel image left shift by constant.
- **NppStatus nppiLShiftC_8u_C3IR** (const **Npp32u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel in place image left shift by constant.
- **NppStatus nppiLShiftC_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[3], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image left shift by constant with unmodified alpha.
- **NppStatus nppiLShiftC_8u_AC4IR** (const **Npp32u** aConstants[3], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image left shift by constant with unmodified alpha.
- **NppStatus nppiLShiftC_8u_C4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[4], **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image left shift by constant.
- **NppStatus nppiLShiftC_8u_C4IR** (const **Npp32u** aConstants[4], **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image left shift by constant.
- **NppStatus nppiLShiftC_16u_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp32u** nConstant, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image left shift by constant.
- **NppStatus nppiLShiftC_16u_C1IR** (const **Npp32u** nConstant, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel in place image left shift by constant.
- **NppStatus nppiLShiftC_16u_C3R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp32u** aConstants[3], **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 16-bit unsigned short channel image left shift by constant.

- `NppStatus nppiLShiftC_16u_C3IR` (const `Npp32u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel in place image left shift by constant.
- `NppStatus nppiLShiftC_16u_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp32u` aConstants[3], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image left shift by constant with unmodified alpha.
- `NppStatus nppiLShiftC_16u_AC4IR` (const `Npp32u` aConstants[3], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image left shift by constant with unmodified alpha.
- `NppStatus nppiLShiftC_16u_C4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp32u` aConstants[4], `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image left shift by constant.
- `NppStatus nppiLShiftC_16u_C4IR` (const `Npp32u` aConstants[4], `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image left shift by constant.
- `NppStatus nppiLShiftC_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32u` nConstant, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel image left shift by constant.
- `NppStatus nppiLShiftC_32s_C1IR` (const `Npp32u` nConstant, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel in place image left shift by constant.
- `NppStatus nppiLShiftC_32s_C3R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32u` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel image left shift by constant.
- `NppStatus nppiLShiftC_32s_C3IR` (const `Npp32u` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel in place image left shift by constant.
- `NppStatus nppiLShiftC_32s_AC4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32u` aConstants[3], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image left shift by constant with unmodified alpha.
- `NppStatus nppiLShiftC_32s_AC4IR` (const `Npp32u` aConstants[3], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image left shift by constant with unmodified alpha.
- `NppStatus nppiLShiftC_32s_C4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32u` aConstants[4], `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image left shift by constant.
- `NppStatus nppiLShiftC_32s_C4IR` (const `Npp32u` aConstants[4], `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image left shift by constant.

7.32.1 Detailed Description

Pixel by pixel left shift of an image by a constant value.

7.32.2 Function Documentation

7.32.2.1 NppStatus nppiLShiftC_16u_AC4IR (const Npp32u *aConstants*[3], Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Four 16-bit unsigned short channel in place image left shift by constant with unmodified alpha.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.2 NppStatus nppiLShiftC_16u_AC4R (const Npp16u * *pSrc1*, int *nSrc1Step*, const Npp32u *aConstants*[3], Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Four 16-bit unsigned short channel image left shift by constant with unmodified alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.3 NppStatus nppiLShiftC_16u_C1IR (const Npp32u *nConstant*, Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 16-bit unsigned short channel in place image left shift by constant.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.4 `NppStatus nppiLShiftC_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp32u nConstant, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

One 16-bit unsigned short channel image left shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.5 `NppStatus nppiLShiftC_16u_C3IR (const Npp32u aConstants[3], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 16-bit unsigned short channel in place image left shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.6 `NppStatus nppiLShiftC_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

Three 16-bit unsigned short channel image left shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.7 NppStatus nppiLShiftC_16u_C4IR (const Npp32u aConstants[4], Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel in place image left shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.8 NppStatus nppiLShiftC_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp32u aConstants[4], Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image left shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.9 NppStatus nppiLShiftC_32s_AC4IR (const Npp32u aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel in place image left shift by constant with unmodified alpha.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.10 NppStatus nppiLShiftC_32s_AC4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel image left shift by constant with unmodified alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.11 NppStatus nppiLShiftC_32s_C1IR (const Npp32u nConstant, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel in place image left shift by constant.

Parameters:

- nConstant* Constant.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.12 `NppStatus nppiLShiftC_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32u nConstant, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

One 32-bit signed integer channel image left shift by constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nConstant Constant.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.13 `NppStatus nppiLShiftC_32s_C3IR (const Npp32u aConstants[3], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 32-bit signed integer channel in place image left shift by constant.

Parameters:

aConstants fixed size array of constant values, one per channel.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.14 `NppStatus nppiLShiftC_32s_C3R (const Npp32s * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit signed integer channel image left shift by constant.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
aConstants fixed size array of constant values, one per channel.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.15 `NppStatus nppiLShiftC_32s_C4IR (const Npp32u aConstants[4], Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel in place image left shift by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.16 `NppStatus nppiLShiftC_32s_C4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32u aConstants[4], Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel image left shift by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.17 `NppStatus nppiLShiftC_8u_AC4IR (const Npp32u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image left shift by constant with unmodified alpha.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.18 `NppStatus nppiLShiftC_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image left shift by constant with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.19 `NppStatus nppiLShiftC_8u_C1IR (const Npp32u nConstant, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel in place image left shift by constant.

Parameters:

nConstant Constant.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.20 `NppStatus nppiLShiftC_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp32u nConstant, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel image left shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nConstant Constant.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.32.2.21 `NppStatus nppiLShiftC_8u_C3IR (const Npp32u aConstants[3], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 8-bit unsigned char channel in place image left shift by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.22 `NppStatus nppiLShiftC_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp32u aConstants[3], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Three 8-bit unsigned char channel image left shift by constant.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- aConstants* fixed size array of constant values, one per channel.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.23 `NppStatus nppiLShiftC_8u_C4IR (const Npp32u aConstants[4], Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image left shift by constant.

Parameters:

- aConstants* fixed size array of constant values, one per channel.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.32.2.24 `NppStatus nppiLShiftC_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp32u aConstants[4], Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image left shift by constant.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

aConstants fixed size array of constant values, one per channel.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33 And

Pixel by pixel logical and of images.

Functions

- `NppStatus nppiAnd_8u_C1R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel image logical and.
- `NppStatus nppiAnd_8u_C1IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel in place image logical and.
- `NppStatus nppiAnd_8u_C3R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel image logical and.
- `NppStatus nppiAnd_8u_C3IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel in place image logical and.
- `NppStatus nppiAnd_8u_AC4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image logical and with unmodified alpha.
- `NppStatus nppiAnd_8u_AC4IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image logical and with unmodified alpha.
- `NppStatus nppiAnd_8u_C4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image logical and.
- `NppStatus nppiAnd_8u_C4IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image logical and.
- `NppStatus nppiAnd_16u_C1R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel image logical and.
- `NppStatus nppiAnd_16u_C1IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel in place image logical and.
- `NppStatus nppiAnd_16u_C3R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel image logical and.

- `NppStatus nppiAnd_16u_C3IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel in place image logical and.
- `NppStatus nppiAnd_16u_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical and with unmodified alpha.
- `NppStatus nppiAnd_16u_AC4IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical and with unmodified alpha.
- `NppStatus nppiAnd_16u_C4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical and.
- `NppStatus nppiAnd_16u_C4IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical and.
- `NppStatus nppiAnd_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel image logical and.
- `NppStatus nppiAnd_32s_C1IR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel in place image logical and.
- `NppStatus nppiAnd_32s_C3R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel image logical and.
- `NppStatus nppiAnd_32s_C3IR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel in place image logical and.
- `NppStatus nppiAnd_32s_AC4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical and with unmodified alpha.
- `NppStatus nppiAnd_32s_AC4IR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical and with unmodified alpha.
- `NppStatus nppiAnd_32s_C4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical and.
- `NppStatus nppiAnd_32s_C4IR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical and.

7.33.1 Detailed Description

Pixel by pixel logical and of images.

7.33.2 Function Documentation

7.33.2.1 `NppStatus nppiAnd_16u_AC4IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel in place image logical and with unmodified alpha.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.2 `NppStatus nppiAnd_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel image logical and with unmodified alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.3 `NppStatus nppiAnd_16u_C1IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 16-bit unsigned short channel in place image logical and.

Parameters:

- pSrc* Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.4 NppStatus nppiAnd_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel image logical and.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.5 NppStatus nppiAnd_16u_C3IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel in place image logical and.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.6 NppStatus nppiAnd_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel image logical and.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.7 NppStatus nppiAnd_16u_C4IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel in place image logical and.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.8 NppStatus nppiAnd_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image logical and.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.9 NppStatus nppiAnd_32s_AC4IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel in place image logical and with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.10 NppStatus nppiAnd_32s_AC4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

Four 32-bit signed integer channel image logical and with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.11 NppStatus nppiAnd_32s_C1IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel in place image logical and.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.12 NppStatus nppiAnd_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel image logical and.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.13 NppStatus nppiAnd_32s_C3IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit signed integer channel in place image logical and.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.14 `NppStatus nppiAnd_32s_C3R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit signed integer channel image logical and.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.15 `NppStatus nppiAnd_32s_C4IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel in place image logical and.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.16 `NppStatus nppiAnd_32s_C4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel image logical and.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.17 `NppStatus nppiAnd_8u_AC4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image logical and with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.18 `NppStatus nppiAnd_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical and with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.33.2.19 NppStatus nppiAnd_8u_C1IR (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

One 8-bit unsigned char channel in place image logical and.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.20 NppStatus nppiAnd_8u_C1R (const Npp8u * *pSrc1*, int *nSrc1Step*, const Npp8u * *pSrc2*, int *nSrc2Step*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

One 8-bit unsigned char channel image logical and.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.21 NppStatus nppiAnd_8u_C3IR (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Three 8-bit unsigned char channel in place image logical and.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.22 `NppStatus nppiAnd_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Three 8-bit unsigned char channel image logical and.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.23 `NppStatus nppiAnd_8u_C4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image logical and.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.33.2.24 `NppStatus nppiAnd_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical and.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34 Or

Pixel by pixel logical or of images.

Functions

- `NppStatus nppiOr_8u_C1R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel image logical or.
- `NppStatus nppiOr_8u_C1IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel in place image logical or.
- `NppStatus nppiOr_8u_C3R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel image logical or.
- `NppStatus nppiOr_8u_C3IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel in place image logical or.
- `NppStatus nppiOr_8u_AC4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image logical or with unmodified alpha.
- `NppStatus nppiOr_8u_AC4IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image logical or with unmodified alpha.
- `NppStatus nppiOr_8u_C4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image logical or.
- `NppStatus nppiOr_8u_C4IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image logical or.
- `NppStatus nppiOr_16u_C1R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel image logical or.
- `NppStatus nppiOr_16u_C1IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel in place image logical or.
- `NppStatus nppiOr_16u_C3R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel image logical or.

- `NppStatus nppiOr_16u_C3IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel in place image logical or.
- `NppStatus nppiOr_16u_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical or with unmodified alpha.
- `NppStatus nppiOr_16u_AC4IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical or with unmodified alpha.
- `NppStatus nppiOr_16u_C4R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel image logical or.
- `NppStatus nppiOr_16u_C4IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 16-bit unsigned short channel in place image logical or.
- `NppStatus nppiOr_32s_C1R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel image logical or.
- `NppStatus nppiOr_32s_C1IR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 32-bit signed integer channel in place image logical or.
- `NppStatus nppiOr_32s_C3R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel image logical or.
- `NppStatus nppiOr_32s_C3IR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 32-bit signed integer channel in place image logical or.
- `NppStatus nppiOr_32s_AC4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical or with unmodified alpha.
- `NppStatus nppiOr_32s_AC4IR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical or with unmodified alpha.
- `NppStatus nppiOr_32s_C4R` (const `Npp32s` *pSrc1, int nSrc1Step, const `Npp32s` *pSrc2, int nSrc2Step, `Npp32s` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel image logical or.
- `NppStatus nppiOr_32s_C4IR` (const `Npp32s` *pSrc, int nSrcStep, `Npp32s` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 32-bit signed integer channel in place image logical or.

7.34.1 Detailed Description

Pixel by pixel logical or of images.

7.34.2 Function Documentation

7.34.2.1 `NppStatus nppiOr_16u_AC4IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel in place image logical or with unmodified alpha.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.2 `NppStatus nppiOr_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel image logical or with unmodified alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.3 `NppStatus nppiOr_16u_C1IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 16-bit unsigned short channel in place image logical or.

Parameters:

- pSrc* Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.4 NppStatus nppiOr_16u_C1R (const Npp16u * *pSrc1*, int *nSrc1Step*, const Npp16u * *pSrc2*, int *nSrc2Step*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

One 16-bit unsigned short channel image logical or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.5 NppStatus nppiOr_16u_C3IR (const Npp16u * *pSrc*, int *nSrcStep*, Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Three 16-bit unsigned short channel in place image logical or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.6 NppStatus nppiOr_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel image logical or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.7 NppStatus nppiOr_16u_C4IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel in place image logical or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.8 NppStatus nppiOr_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image logical or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.9 `NppStatus nppiOr_32s_AC4IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel in place image logical or with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.10 `NppStatus nppiOr_32s_AC4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel image logical or with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.11 NppStatus nppiOr_32s_C1IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel in place image logical or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.12 NppStatus nppiOr_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel image logical or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.13 NppStatus nppiOr_32s_C3IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit signed integer channel in place image logical or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.14 `NppStatus nppiOr_32s_C3R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit signed integer channel image logical or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.15 `NppStatus nppiOr_32s_C4IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel in place image logical or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.16 `NppStatus nppiOr_32s_C4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel image logical or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.17 `NppStatus nppiOr_8u_AC4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image logical or with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.18 `NppStatus nppiOr_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical or with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.19 NppStatus nppiOr_8u_C1IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel in place image logical or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.20 NppStatus nppiOr_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel image logical or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.21 NppStatus nppiOr_8u_C3IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel in place image logical or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.34.2.22 `NppStatus nppiOr_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Three 8-bit unsigned char channel image logical or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.23 `NppStatus nppiOr_8u_C4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image logical or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.34.2.24 `NppStatus nppiOr_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35 Xor

Pixel by pixel logical exclusive or of images.

Functions

- `NppStatus nppiXor_8u_C1R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel image logical exclusive or.
- `NppStatus nppiXor_8u_C1IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 8-bit unsigned char channel in place image logical exclusive or.
- `NppStatus nppiXor_8u_C3R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel image logical exclusive or.
- `NppStatus nppiXor_8u_C3IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Three 8-bit unsigned char channel in place image logical exclusive or.
- `NppStatus nppiXor_8u_AC4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image logical exclusive or with unmodified alpha.
- `NppStatus nppiXor_8u_AC4IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image logical exclusive or with unmodified alpha.
- `NppStatus nppiXor_8u_C4R` (const `Npp8u` *pSrc1, int nSrc1Step, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel image logical exclusive or.
- `NppStatus nppiXor_8u_C4IR` (const `Npp8u` *pSrc, int nSrcStep, `Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
Four 8-bit unsigned char channel in place image logical exclusive or.
- `NppStatus nppiXor_16u_C1R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel image logical exclusive or.
- `NppStatus nppiXor_16u_C1IR` (const `Npp16u` *pSrc, int nSrcStep, `Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)
One 16-bit unsigned short channel in place image logical exclusive or.
- `NppStatus nppiXor_16u_C3R` (const `Npp16u` *pSrc1, int nSrc1Step, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)
Three 16-bit unsigned short channel image logical exclusive or.

- **NppStatus nppiXor_16u_C3IR** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 16-bit unsigned short channel in place image logical exclusive or.
- **NppStatus nppiXor_16u_AC4R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 16-bit unsigned short channel image logical exclusive or with unmodified alpha.
- **NppStatus nppiXor_16u_AC4IR** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 16-bit unsigned short channel in place image logical exclusive or with unmodified alpha.
- **NppStatus nppiXor_16u_C4R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 16-bit unsigned short channel image logical exclusive or.
- **NppStatus nppiXor_16u_C4IR** (const **Npp16u** *pSrc, int nSrcStep, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 16-bit unsigned short channel in place image logical exclusive or.
- **NppStatus nppiXor_32s_C1R** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 32-bit signed integer channel image logical exclusive or.
- **NppStatus nppiXor_32s_C1IR** (const **Npp32s** *pSrc, int nSrcStep, **Npp32s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 32-bit signed integer channel in place image logical exclusive or.
- **NppStatus nppiXor_32s_C3R** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 32-bit signed integer channel image logical exclusive or.
- **NppStatus nppiXor_32s_C3IR** (const **Npp32s** *pSrc, int nSrcStep, **Npp32s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 32-bit signed integer channel in place image logical exclusive or.
- **NppStatus nppiXor_32s_AC4R** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit signed integer channel image logical exclusive or with unmodified alpha.
- **NppStatus nppiXor_32s_AC4IR** (const **Npp32s** *pSrc, int nSrcStep, **Npp32s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit signed integer channel in place image logical exclusive or with unmodified alpha.
- **NppStatus nppiXor_32s_C4R** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 32-bit signed integer channel image logical exclusive or.
- **NppStatus nppiXor_32s_C4IR** (const **Npp32s** *pSrc, int nSrcStep, **Npp32s** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 32-bit signed integer channel in place image logical exclusive or.

7.35.1 Detailed Description

Pixel by pixel logical exclusive or of images.

7.35.2 Function Documentation

7.35.2.1 `NppStatus nppiXor_16u_AC4IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel in place image logical exclusive or with unmodified alpha.

Parameters:

- pSrc* Source-Image Pointer.
- nSrcStep* Source-Image Line Step.
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.2 `NppStatus nppiXor_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 16-bit unsigned short channel image logical exclusive or with unmodified alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.3 `NppStatus nppiXor_16u_C1IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 16-bit unsigned short channel in place image logical exclusive or.

Parameters:

- pSrc* Source-Image Pointer.

nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.4 NppStatus nppiXor_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel image logical exclusive or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.5 NppStatus nppiXor_16u_C3IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel in place image logical exclusive or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.6 NppStatus nppiXor_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Three 16-bit unsigned short channel image logical exclusive or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.7 NppStatus nppiXor_16u_C4IR (const Npp16u * pSrc, int nSrcStep, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel in place image logical exclusive or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.8 NppStatus nppiXor_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image logical exclusive or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.9 `NppStatus nppiXor_32s_AC4IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel in place image logical exclusive or with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.10 `NppStatus nppiXor_32s_AC4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel image logical exclusive or with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.11 NppStatus nppiXor_32s_C1IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel in place image logical exclusive or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.12 NppStatus nppiXor_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)

One 32-bit signed integer channel image logical exclusive or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.13 NppStatus nppiXor_32s_C3IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 32-bit signed integer channel in place image logical exclusive or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.14 `NppStatus nppiXor_32s_C3R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Three 32-bit signed integer channel image logical exclusive or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.15 `NppStatus nppiXor_32s_C4IR (const Npp32s * pSrc, int nSrcStep, Npp32s * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel in place image logical exclusive or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.16 `NppStatus nppiXor_32s_C4R (const Npp32s * pSrc1, int nSrc1Step, const Npp32s * pSrc2, int nSrc2Step, Npp32s * pDst, int nDstStep, NppiSize oSizeROI)`

Four 32-bit signed integer channel image logical exclusive or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.17 `NppStatus nppiXor_8u_AC4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image logical exclusive or with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.18 `NppStatus nppiXor_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical exclusive or with unmodified alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.35.2.19 NppStatus nppiXor_8u_C1IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel in place image logical exclusive or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.20 NppStatus nppiXor_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

One 8-bit unsigned char channel image logical exclusive or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.21 NppStatus nppiXor_8u_C3IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel in place image logical exclusive or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.22 `NppStatus nppiXor_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Three 8-bit unsigned char channel image logical exclusive or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.23 `NppStatus nppiXor_8u_C4IR (const Npp8u * pSrc, int nSrcStep, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel in place image logical exclusive or.

Parameters:

pSrc Source-Image Pointer.
nSrcStep Source-Image Line Step.
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.35.2.24 `NppStatus nppiXor_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical exclusive or.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36 Not

Pixel by pixel logical not of image.

Functions

- **NppStatus nppiNot_8u_C1R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel image logical not.
- **NppStatus nppiNot_8u_C1IR** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel in place image logical not.
- **NppStatus nppiNot_8u_C3R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel image logical not.
- **NppStatus nppiNot_8u_C3IR** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel in place image logical not.
- **NppStatus nppiNot_8u_AC4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image logical not with unmodified alpha.
- **NppStatus nppiNot_8u_AC4IR** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image logical not with unmodified alpha.
- **NppStatus nppiNot_8u_C4R** (const **Npp8u** *pSrc, int nSrcStep, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image logical not.
- **NppStatus nppiNot_8u_C4IR** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image logical not.

7.36.1 Detailed Description

Pixel by pixel logical not of image.

7.36.2 Function Documentation

7.36.2.1 **NppStatus nppiNot_8u_AC4IR** (**Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)

Four 8-bit unsigned char channel in place image logical not with unmodified alpha.

Parameters:

pSrcDst **In-Place Image Pointer.**

nSrcDstStep **In-Place-Image Line Step.**

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.2 `NppStatus nppiNot_8u_AC4R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

Four 8-bit unsigned char channel image logical not with unmodified alpha.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.3 `NppStatus nppiNot_8u_C1IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel in place image logical not.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.4 `NppStatus nppiNot_8u_C1R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel image logical not.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.5 NppStatus nppiNot_8u_C3IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel in place image logical not.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.6 NppStatus nppiNot_8u_C3R (const Npp8u * pSrc, int nSrcStep, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel image logical not.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.7 NppStatus nppiNot_8u_C4IR (Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel in place image logical not.

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.36.2.8 NppStatus nppiNot_8u_C4R (const Npp8u * *pSrc*, int *nSrcStep*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Four 8-bit unsigned char channel image logical not.

Parameters:

pSrc Source-Image Pointer.

nSrcStep Source-Image Line Step.

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.37 Alpha Composition

Modules

- [AlphaCompC](#)
Composite two images using constant alpha values.
- [AlphaPremulC](#)
Premultiplies pixels of an image using a constant alpha value.
- [AlphaComp](#)
Composite two images using alpha opacity values contained in each image.
- [AlphaPremul](#)
Premultiplies image pixels by image alpha opacity values.

7.38 AlphaCompC

Composite two images using constant alpha values.

Functions

- `NppStatus nppiAlphaCompC_8u_C1R` (const `Npp8u` *pSrc1, int nSrc1Step, `Npp8u` nAlpha1, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` nAlpha2, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
One 8-bit unsigned char channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_8u_C3R` (const `Npp8u` *pSrc1, int nSrc1Step, `Npp8u` nAlpha1, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` nAlpha2, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
Three 8-bit unsigned char channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_8u_C4R` (const `Npp8u` *pSrc1, int nSrc1Step, `Npp8u` nAlpha1, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` nAlpha2, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
Four 8-bit unsigned char channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_8u_AC4R` (const `Npp8u` *pSrc1, int nSrc1Step, `Npp8u` nAlpha1, const `Npp8u` *pSrc2, int nSrc2Step, `Npp8u` nAlpha2, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
Four 8-bit unsigned char channel image composition with alpha using constant source alpha.
- `NppStatus nppiAlphaCompC_8s_C1R` (const `Npp8s` *pSrc1, int nSrc1Step, `Npp8s` nAlpha1, const `Npp8s` *pSrc2, int nSrc2Step, `Npp8s` nAlpha2, `Npp8s` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
One 8-bit signed char channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_16u_C1R` (const `Npp16u` *pSrc1, int nSrc1Step, `Npp16u` nAlpha1, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` nAlpha2, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
One 16-bit unsigned short channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_16u_C3R` (const `Npp16u` *pSrc1, int nSrc1Step, `Npp16u` nAlpha1, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` nAlpha2, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
Three 16-bit unsigned short channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_16u_C4R` (const `Npp16u` *pSrc1, int nSrc1Step, `Npp16u` nAlpha1, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` nAlpha2, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
Four 16-bit unsigned short channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_16u_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, `Npp16u` nAlpha1, const `Npp16u` *pSrc2, int nSrc2Step, `Npp16u` nAlpha2, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI, `NppiAlphaOp` eAlphaOp)
Four 16-bit unsigned short channel image composition with alpha using constant source alpha.

- `NppStatus nppiAlphaCompC_16s_C1R` (const `Npp16s *pSrc1`, int `nSrc1Step`, `Npp16s nAlpha1`, const `Npp16s *pSrc2`, int `nSrc2Step`, `Npp16s nAlpha2`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppiAlphaOp eAlphaOp`)
One 16-bit signed short channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_32u_C1R` (const `Npp32u *pSrc1`, int `nSrc1Step`, `Npp32u nAlpha1`, const `Npp32u *pSrc2`, int `nSrc2Step`, `Npp32u nAlpha2`, `Npp32u *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppiAlphaOp eAlphaOp`)
One 32-bit unsigned integer channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_32s_C1R` (const `Npp32s *pSrc1`, int `nSrc1Step`, `Npp32s nAlpha1`, const `Npp32s *pSrc2`, int `nSrc2Step`, `Npp32s nAlpha2`, `Npp32s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppiAlphaOp eAlphaOp`)
One 32-bit signed integer channel image composition using constant alpha.
- `NppStatus nppiAlphaCompC_32f_C1R` (const `Npp32f *pSrc1`, int `nSrc1Step`, `Npp32f nAlpha1`, const `Npp32f *pSrc2`, int `nSrc2Step`, `Npp32f nAlpha2`, `Npp32f *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppiAlphaOp eAlphaOp`)
One 32-bit floating point channel image composition using constant alpha.

7.38.1 Detailed Description

Composite two images using constant alpha values.

7.38.2 Function Documentation

7.38.2.1 `NppStatus nppiAlphaCompC_16s_C1R` (const `Npp16s *pSrc1`, int `nSrc1Step`, `Npp16s nAlpha1`, const `Npp16s *pSrc2`, int `nSrc2Step`, `Npp16s nAlpha2`, `Npp16s *pDst`, int `nDstStep`, `NppiSize oSizeROI`, `NppiAlphaOp eAlphaOp`)

One 16-bit signed short channel image composition using constant alpha.

Parameters:

- `pSrc1` Source-Image Pointer.
- `nSrc1Step` Source-Image Line Step.
- `nAlpha1` Image alpha opacity (0 - max channel pixel value).
- `pSrc2` Source-Image Pointer.
- `nSrc2Step` Source-Image Line Step.
- `nAlpha2` Image alpha opacity (0 - max channel pixel value).
- `pDst` Destination-Image Pointer.
- `nDstStep` Destination-Image Line Step.
- `oSizeROI` Region-of-Interest (ROI).
- `eAlphaOp` alpha-blending operation..

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.38.2.2 NppStatus nppiAlphaCompC_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, Npp16u nAlpha1, const Npp16u * pSrc2, int nSrc2Step, Npp16u nAlpha2, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

Four 16-bit unsigned short channel image composition with alpha using constant source alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.38.2.3 NppStatus nppiAlphaCompC_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, Npp16u nAlpha1, const Npp16u * pSrc2, int nSrc2Step, Npp16u nAlpha2, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

One 16-bit unsigned short channel image composition using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.38.2.4 NppStatus nppiAlphaCompC_16u_C3R (const Npp16u * pSrc1, int nSrc1Step, Npp16u nAlpha1, const Npp16u * pSrc2, int nSrc2Step, Npp16u nAlpha2, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

Three 16-bit unsigned short channel image composition using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.38.2.5 NppStatus nppiAlphaCompC_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, Npp16u nAlpha1, const Npp16u * pSrc2, int nSrc2Step, Npp16u nAlpha2, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

Four 16-bit unsigned short channel image composition using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.38.2.6 NppStatus nppiAlphaCompC_32f_C1R (const Npp32f * pSrc1, int nSrc1Step, Npp32f nAlpha1, const Npp32f * pSrc2, int nSrc2Step, Npp32f nAlpha2, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

One 32-bit floating point channel image composition using constant alpha.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nAlpha1 Image alpha opacity (0.0 - 1.0).
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
nAlpha2 Image alpha opacity (0.0 - 1.0).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.38.2.7 NppStatus nppiAlphaCompC_32s_C1R (const Npp32s * pSrc1, int nSrc1Step, Npp32s nAlpha1, const Npp32s * pSrc2, int nSrc2Step, Npp32s nAlpha2, Npp32s * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

One 32-bit signed integer channel image composition using constant alpha.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nAlpha1 Image alpha opacity (0 - max channel pixel value).
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
nAlpha2 Image alpha opacity (0 - max channel pixel value).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.38.2.8 NppStatus nppiAlphaCompC_32u_C1R (const Npp32u * pSrc1, int nSrc1Step, Npp32u nAlpha1, const Npp32u * pSrc2, int nSrc2Step, Npp32u nAlpha2, Npp32u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

One 32-bit unsigned integer channel image composition using constant alpha.

Parameters:

- pSrc1* [Source-Image Pointer](#).
- nSrc1Step* [Source-Image Line Step](#).
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* [Source-Image Pointer](#).
- nSrc2Step* [Source-Image Line Step](#).
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).
- eAlphaOp* [alpha-blending operation..](#)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.38.2.9 NppStatus nppiAlphaCompC_8s_C1R (const Npp8s * pSrc1, int nSrc1Step, Npp8s nAlpha1, const Npp8s * pSrc2, int nSrc2Step, Npp8s nAlpha2, Npp8s * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

One 8-bit signed char channel image composition using constant alpha.

Parameters:

- pSrc1* [Source-Image Pointer](#).
- nSrc1Step* [Source-Image Line Step](#).
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* [Source-Image Pointer](#).
- nSrc2Step* [Source-Image Line Step](#).
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).
- eAlphaOp* [alpha-blending operation..](#)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.38.2.10 `NppStatus nppiAlphaCompC_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, Npp8u nAlpha1, const Npp8u * pSrc2, int nSrc2Step, Npp8u nAlpha2, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)`

Four 8-bit unsigned char channel image composition with alpha using constant source alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.38.2.11 `NppStatus nppiAlphaCompC_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, Npp8u nAlpha1, const Npp8u * pSrc2, int nSrc2Step, Npp8u nAlpha2, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)`

One 8-bit unsigned char channel image composition using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.38.2.12 NppStatus nppiAlphaCompC_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, Npp8u nAlpha1, const Npp8u * pSrc2, int nSrc2Step, Npp8u nAlpha2, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

Three 8-bit unsigned char channel image composition using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.38.2.13 NppStatus nppiAlphaCompC_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, Npp8u nAlpha1, const Npp8u * pSrc2, int nSrc2Step, Npp8u nAlpha2, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

Four 8-bit unsigned char channel image composition using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- nAlpha2* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39 AlphaPremulC

Premultiplies pixels of an image using a constant alpha value.

Functions

- **NppStatus nppiAlphaPremulC_8u_C1R** (const **Npp8u** *pSrc1, int nSrc1Step, **Npp8u** nAlpha1, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel image premultiplication using constant alpha.
- **NppStatus nppiAlphaPremulC_8u_C1IR** (**Npp8u** nAlpha1, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 8-bit unsigned char channel in place image premultiplication using constant alpha.
- **NppStatus nppiAlphaPremulC_8u_C3R** (const **Npp8u** *pSrc1, int nSrc1Step, **Npp8u** nAlpha1, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel image premultiplication using constant alpha.
- **NppStatus nppiAlphaPremulC_8u_C3IR** (**Npp8u** nAlpha1, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Three 8-bit unsigned char channel in place image premultiplication using constant alpha.
- **NppStatus nppiAlphaPremulC_8u_C4R** (const **Npp8u** *pSrc1, int nSrc1Step, **Npp8u** nAlpha1, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image premultiplication using constant alpha.
- **NppStatus nppiAlphaPremulC_8u_C4IR** (**Npp8u** nAlpha1, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image premultiplication using constant alpha.
- **NppStatus nppiAlphaPremulC_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, **Npp8u** nAlpha1, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel image premultiplication with alpha using constant alpha.
- **NppStatus nppiAlphaPremulC_8u_AC4IR** (**Npp8u** nAlpha1, **Npp8u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
Four 8-bit unsigned char channel in place image premultiplication with alpha using constant alpha.
- **NppStatus nppiAlphaPremulC_16u_C1R** (const **Npp16u** *pSrc1, int nSrc1Step, **Npp16u** nAlpha1, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel image premultiplication using constant alpha.
- **NppStatus nppiAlphaPremulC_16u_C1IR** (**Npp16u** nAlpha1, **Npp16u** *pSrcDst, int nSrcDstStep, **NppiSize** oSizeROI)
One 16-bit unsigned short channel in place image premultiplication using constant alpha.
- **NppStatus nppiAlphaPremulC_16u_C3R** (const **Npp16u** *pSrc1, int nSrc1Step, **Npp16u** nAlpha1, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI)
Three 16-bit unsigned short channel image premultiplication using constant alpha.

- `NppStatus nppiAlphaPremulC_16u_C3IR` (`Npp16u nAlpha1`, `Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)
Three 16-bit unsigned short channel in place image premultiplication using constant alpha.
- `NppStatus nppiAlphaPremulC_16u_C4R` (`const Npp16u *pSrc1`, `int nSrc1Step`, `Npp16u nAlpha1`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`)
Four 16-bit unsigned short channel image premultiplication using constant alpha.
- `NppStatus nppiAlphaPremulC_16u_C4IR` (`Npp16u nAlpha1`, `Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)
Four 16-bit unsigned short channel in place image premultiplication using constant alpha.
- `NppStatus nppiAlphaPremulC_16u_AC4R` (`const Npp16u *pSrc1`, `int nSrc1Step`, `Npp16u nAlpha1`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`)
Four 16-bit unsigned short channel image premultiplication with alpha using constant alpha.
- `NppStatus nppiAlphaPremulC_16u_AC4IR` (`Npp16u nAlpha1`, `Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)
Four 16-bit unsigned short channel in place image premultiplication with alpha using constant alpha.

7.39.1 Detailed Description

Premultiplies pixels of an image using a constant alpha value.

7.39.2 Function Documentation

7.39.2.1 `NppStatus nppiAlphaPremulC_16u_AC4IR` (`Npp16u nAlpha1`, `Npp16u *pSrcDst`, `int nSrcDstStep`, `NppiSize oSizeROI`)

Four 16-bit unsigned short channel in place image premultiplication with alpha using constant alpha.

Parameters:

nAlpha1 Image alpha opacity (0 - max channel pixel value).

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.39.2.2 `NppStatus nppiAlphaPremulC_16u_AC4R` (`const Npp16u *pSrc1`, `int nSrc1Step`, `Npp16u nAlpha1`, `Npp16u *pDst`, `int nDstStep`, `NppiSize oSizeROI`)

Four 16-bit unsigned short channel image premultiplication with alpha using constant alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nAlpha1 Image alpha opacity (0 - max channel pixel value).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.39.2.3 NppStatus nppiAlphaPremulC_16u_C1IR (Npp16u nAlpha1, Npp16u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel in place image premultiplication using constant alpha.

Parameters:

nAlpha1 Image alpha opacity (0 - max channel pixel value).

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.39.2.4 NppStatus nppiAlphaPremulC_16u_C1R (const Npp16u * pSrc1, int nSrc1Step, Npp16u nAlpha1, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

One 16-bit unsigned short channel image premultiplication using constant alpha.

Parameters:

pSrc1 Source-Image Pointer.

nSrc1Step Source-Image Line Step.

nAlpha1 Image alpha opacity (0 - max channel pixel value).

pDst Destination-Image Pointer.

nDstStep Destination-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.39.2.5 **NppStatus nppiAlphaPremulC_16u_C3IR (Npp16u *nAlpha1*, Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)**

Three 16-bit unsigned short channel in place image premultiplication using constant alpha.

Parameters:

nAlpha1 Image alpha opacity (0 - max channel pixel value).
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.6 **NppStatus nppiAlphaPremulC_16u_C3R (const Npp16u * *pSrc1*, int *nSrc1Step*, Npp16u *nAlpha1*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)**

Three 16-bit unsigned short channel image premultiplication using constant alpha.

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
nAlpha1 Image alpha opacity (0 - max channel pixel value).
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.7 **NppStatus nppiAlphaPremulC_16u_C4IR (Npp16u *nAlpha1*, Npp16u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)**

Four 16-bit unsigned short channel in place image premultiplication using constant alpha.

Parameters:

nAlpha1 Image alpha opacity (0 - max channel pixel value).
pSrcDst In-Place Image Pointer.
nSrcDstStep In-Place-Image Line Step.
oSizeROI Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.8 NppStatus nppiAlphaPremulC_16u_C4R (const Npp16u * pSrc1, int nSrc1Step, Npp16u nAlpha1, Npp16u * pDst, int nDstStep, NppiSize oSizeROI)

Four 16-bit unsigned short channel image premultiplication using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.9 NppStatus nppiAlphaPremulC_8u_AC4IR (Npp8u nAlpha1, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel in place image premultiplication with alpha using constant alpha.

Parameters:

- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.10 NppStatus nppiAlphaPremulC_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, Npp8u nAlpha1, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel image premultiplication with alpha using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.11 `NppStatus nppiAlphaPremulC_8u_C1IR (Npp8u nAlpha1, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel in place image premultiplication using constant alpha.

Parameters:

- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.12 `NppStatus nppiAlphaPremulC_8u_C1R (const Npp8u * pSrc1, int nSrc1Step, Npp8u nAlpha1, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)`

One 8-bit unsigned char channel image premultiplication using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.13 `NppStatus nppiAlphaPremulC_8u_C3IR (Npp8u nAlpha1, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)`

Three 8-bit unsigned char channel in place image premultiplication using constant alpha.

Parameters:

- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.14 NppStatus nppiAlphaPremulC_8u_C3R (const Npp8u * pSrc1, int nSrc1Step, Npp8u nAlpha1, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Three 8-bit unsigned char channel image premultiplication using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.15 NppStatus nppiAlphaPremulC_8u_C4IR (Npp8u nAlpha1, Npp8u * pSrcDst, int nSrcDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel in place image premultiplication using constant alpha.

Parameters:

- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.39.2.16 NppStatus nppiAlphaPremulC_8u_C4R (const Npp8u * pSrc1, int nSrc1Step, Npp8u nAlpha1, Npp8u * pDst, int nDstStep, NppiSize oSizeROI)

Four 8-bit unsigned char channel image premultiplication using constant alpha.

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- nAlpha1* Image alpha opacity (0 - max channel pixel value).
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40 AlphaComp

Composite two images using alpha opacity values contained in each image.

Functions

- **NppStatus nppiAlphaComp_8u_AC1R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppiAlphaOp** eAlphaOp)
One 8-bit unsigned char channel image composition using image alpha values (0 - max channel pixel value).
- **NppStatus nppiAlphaComp_8u_AC4R** (const **Npp8u** *pSrc1, int nSrc1Step, const **Npp8u** *pSrc2, int nSrc2Step, **Npp8u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppiAlphaOp** eAlphaOp)
Four 8-bit unsigned char channel image composition using image alpha values (0 - max channel pixel value).
- **NppStatus nppiAlphaComp_8s_AC1R** (const **Npp8s** *pSrc1, int nSrc1Step, const **Npp8s** *pSrc2, int nSrc2Step, **Npp8s** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppiAlphaOp** eAlphaOp)
One 8-bit signed char channel image composition using image alpha values (0 - max channel pixel value).
- **NppStatus nppiAlphaComp_16u_AC1R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppiAlphaOp** eAlphaOp)
One 16-bit unsigned short channel image composition using image alpha values (0 - max channel pixel value).
- **NppStatus nppiAlphaComp_16u_AC4R** (const **Npp16u** *pSrc1, int nSrc1Step, const **Npp16u** *pSrc2, int nSrc2Step, **Npp16u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppiAlphaOp** eAlphaOp)
Four 16-bit unsigned short channel image composition using image alpha values (0 - max channel pixel value).
- **NppStatus nppiAlphaComp_16s_AC1R** (const **Npp16s** *pSrc1, int nSrc1Step, const **Npp16s** *pSrc2, int nSrc2Step, **Npp16s** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppiAlphaOp** eAlphaOp)
One 16-bit signed short channel image composition using image alpha values (0 - max channel pixel value).
- **NppStatus nppiAlphaComp_32u_AC1R** (const **Npp32u** *pSrc1, int nSrc1Step, const **Npp32u** *pSrc2, int nSrc2Step, **Npp32u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppiAlphaOp** eAlphaOp)
One 32-bit unsigned integer channel image composition using image alpha values (0 - max channel pixel value).
- **NppStatus nppiAlphaComp_32u_AC4R** (const **Npp32u** *pSrc1, int nSrc1Step, const **Npp32u** *pSrc2, int nSrc2Step, **Npp32u** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppiAlphaOp** eAlphaOp)
Four 32-bit unsigned integer channel image composition using image alpha values (0 - max channel pixel value).
- **NppStatus nppiAlphaComp_32s_AC1R** (const **Npp32s** *pSrc1, int nSrc1Step, const **Npp32s** *pSrc2, int nSrc2Step, **Npp32s** *pDst, int nDstStep, **NppiSize** oSizeROI, **NppiAlphaOp** eAlphaOp)
One 32-bit signed integer channel image composition using image alpha values (0 - max channel pixel value).

- **NppStatus nppiAlphaComp_32s_AC4R** (const [Npp32s](#) *pSrc1, int nSrc1Step, const [Npp32s](#) *pSrc2, int nSrc2Step, [Npp32s](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppiAlphaOp](#) eAlphaOp)
Four 32-bit signed integer channel image composition using image alpha values (0 - max channel pixel value).
- **NppStatus nppiAlphaComp_32f_AC1R** (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppiAlphaOp](#) eAlphaOp)
One 32-bit floating point channel image composition using image alpha values (0.0 - 1.0).
- **NppStatus nppiAlphaComp_32f_AC4R** (const [Npp32f](#) *pSrc1, int nSrc1Step, const [Npp32f](#) *pSrc2, int nSrc2Step, [Npp32f](#) *pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppiAlphaOp](#) eAlphaOp)
Four 32-bit floating point channel image composition using image alpha values (0.0 - 1.0).

7.40.1 Detailed Description

Composite two images using alpha opacity values contained in each image.

7.40.2 Function Documentation

7.40.2.1 NppStatus nppiAlphaComp_16s_AC1R (const [Npp16s](#) * pSrc1, int nSrc1Step, const [Npp16s](#) * pSrc2, int nSrc2Step, [Npp16s](#) * pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppiAlphaOp](#) eAlphaOp)

One 16-bit signed short channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

- pSrc1* [Source-Image Pointer](#).
- nSrc1Step* [Source-Image Line Step](#).
- pSrc2* [Source-Image Pointer](#).
- nSrc2Step* [Source-Image Line Step](#).
- pDst* [Destination-Image Pointer](#).
- nDstStep* [Destination-Image Line Step](#).
- oSizeROI* [Region-of-Interest \(ROI\)](#).
- eAlphaOp* [alpha-blending operation..](#)

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.2 NppStatus nppiAlphaComp_16u_AC1R (const [Npp16u](#) * pSrc1, int nSrc1Step, const [Npp16u](#) * pSrc2, int nSrc2Step, [Npp16u](#) * pDst, int nDstStep, [NppiSize](#) oSizeROI, [NppiAlphaOp](#) eAlphaOp)

One 16-bit unsigned short channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.3 NppStatus nppiAlphaComp_16u_AC4R (const Npp16u * pSrc1, int nSrc1Step, const Npp16u * pSrc2, int nSrc2Step, Npp16u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

Four 16-bit unsigned short channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.4 NppStatus nppiAlphaComp_32f_AC1R (const Npp32f * pSrc1, int nSrc1Step, const Npp32f * pSrc2, int nSrc2Step, Npp32f * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)

One 32-bit floating point channel image composition using image alpha values (0.0 - 1.0).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.

nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.5 **NppStatus nppiAlphaComp_32f_AC4R** (const Npp32f * *pSrc1*, int *nSrc1Step*, const Npp32f * *pSrc2*, int *nSrc2Step*, Npp32f * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, NppiAlphaOp *eAlphaOp*)

Four 32-bit floating point channel image composition using image alpha values (0.0 - 1.0).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.6 **NppStatus nppiAlphaComp_32s_AC1R** (const Npp32s * *pSrc1*, int *nSrc1Step*, const Npp32s * *pSrc2*, int *nSrc2Step*, Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, NppiAlphaOp *eAlphaOp*)

One 32-bit signed integer channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.7 NppStatus nppiAlphaComp_32s_AC4R (const Npp32s * *pSrc1*, int *nSrc1Step*, const Npp32s * *pSrc2*, int *nSrc2Step*, Npp32s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, NppiAlphaOp *eAlphaOp*)

Four 32-bit signed integer channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.8 NppStatus nppiAlphaComp_32u_AC1R (const Npp32u * *pSrc1*, int *nSrc1Step*, const Npp32u * *pSrc2*, int *nSrc2Step*, Npp32u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, NppiAlphaOp *eAlphaOp*)

One 32-bit unsigned integer channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pSrc2* Source-Image Pointer.
- nSrc2Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).
- eAlphaOp* alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.9 NppStatus nppiAlphaComp_32u_AC4R (const Npp32u * *pSrc1*, int *nSrc1Step*, const Npp32u * *pSrc2*, int *nSrc2Step*, Npp32u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, NppiAlphaOp *eAlphaOp*)

Four 32-bit unsigned integer channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.10 NppStatus nppiAlphaComp_8s_AC1R (const Npp8s * *pSrc1*, int *nSrc1Step*, const Npp8s * *pSrc2*, int *nSrc2Step*, Npp8s * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, NppiAlphaOp *eAlphaOp*)

One 8-bit signed char channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.11 NppStatus nppiAlphaComp_8u_AC1R (const Npp8u * *pSrc1*, int *nSrc1Step*, const Npp8u * *pSrc2*, int *nSrc2Step*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*, NppiAlphaOp *eAlphaOp*)

One 8-bit unsigned char channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.40.2.12 `NppStatus nppiAlphaComp_8u_AC4R (const Npp8u * pSrc1, int nSrc1Step, const Npp8u * pSrc2, int nSrc2Step, Npp8u * pDst, int nDstStep, NppiSize oSizeROI, NppiAlphaOp eAlphaOp)`

Four 8-bit unsigned char channel image composition using image alpha values (0 - max channel pixel value).

Parameters:

pSrc1 Source-Image Pointer.
nSrc1Step Source-Image Line Step.
pSrc2 Source-Image Pointer.
nSrc2Step Source-Image Line Step.
pDst Destination-Image Pointer.
nDstStep Destination-Image Line Step.
oSizeROI Region-of-Interest (ROI).
eAlphaOp alpha-blending operation..

Returns:

[Image Data Related Error Codes](#), [ROI Related Error Codes](#)

7.41 AlphaPremul

Premultiplies image pixels by image alpha opacity values.

Functions

- `NppStatus nppiAlphaPremul_8u_AC4R` (const `Npp8u` *pSrc1, int nSrc1Step, `Npp8u` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four 8-bit unsigned char channel image premultiplication with pixel alpha (0 - max channel pixel value).

- `NppStatus nppiAlphaPremul_8u_AC4IR` (`Npp8u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)

Four 8-bit unsigned char channel in place image premultiplication with pixel alpha (0 - max channel pixel value).

- `NppStatus nppiAlphaPremul_16u_AC4R` (const `Npp16u` *pSrc1, int nSrc1Step, `Npp16u` *pDst, int nDstStep, `NppiSize` oSizeROI)

Four 16-bit unsigned short channel image premultiplication with pixel alpha (0 - max channel pixel value).

- `NppStatus nppiAlphaPremul_16u_AC4IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)

Four 16-bit unsigned short channel in place image premultiplication with pixel alpha (0 - max channel pixel value).

7.41.1 Detailed Description

Premultiplies image pixels by image alpha opacity values.

7.41.2 Function Documentation

7.41.2.1 `NppStatus nppiAlphaPremul_16u_AC4IR` (`Npp16u` *pSrcDst, int nSrcDstStep, `NppiSize` oSizeROI)

Four 16-bit unsigned short channel in place image premultiplication with pixel alpha (0 - max channel pixel value).

Parameters:

pSrcDst In-Place Image Pointer.

nSrcDstStep In-Place-Image Line Step.

oSizeROI Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.41.2.2 **NppStatus nppiAlphaPremul_16u_AC4R** (const Npp16u * *pSrc1*, int *nSrc1Step*, Npp16u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Four 16-bit unsigned short channel image premultiplication with pixel alpha (0 - max channel pixel value).

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.41.2.3 **NppStatus nppiAlphaPremul_8u_AC4IR** (Npp8u * *pSrcDst*, int *nSrcDstStep*, NppiSize *oSizeROI*)

Four 8-bit unsigned char channel in place image premultiplication with pixel alpha (0 - max channel pixel value).

Parameters:

- pSrcDst* In-Place Image Pointer.
- nSrcDstStep* In-Place-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

7.41.2.4 **NppStatus nppiAlphaPremul_8u_AC4R** (const Npp8u * *pSrc1*, int *nSrc1Step*, Npp8u * *pDst*, int *nDstStep*, NppiSize *oSizeROI*)

Four 8-bit unsigned char channel image premultiplication with pixel alpha (0 - max channel pixel value).

Parameters:

- pSrc1* Source-Image Pointer.
- nSrc1Step* Source-Image Line Step.
- pDst* Destination-Image Pointer.
- nDstStep* Destination-Image Line Step.
- oSizeROI* Region-of-Interest (ROI).

Returns:

Image Data Related Error Codes, ROI Related Error Codes

Chapter 8

Data Structure Documentation

8.1 NPP_ALIGN_16 Struct Reference

Complex Number This struct represents a long long complex number.

```
#include <nppdefs.h>
```

Data Fields

- [Npp64s re](#)
Real part.
- [Npp64s im](#)
Imaginary part.
- [Npp64f re](#)
Real part.
- [Npp64f im](#)
Imaginary part.

8.1.1 Detailed Description

Complex Number This struct represents a long long complex number.

Complex Number This struct represents a double floating-point complex number.

8.1.2 Field Documentation

8.1.2.1 Npp64f NPP_ALIGN_16::im

Imaginary part.

8.1.2.2 Npp64s NPP_ALIGN_16::im

Imaginary part.

8.1.2.3 Npp64f NPP_ALIGN_16::re

Real part.

8.1.2.4 Npp64s NPP_ALIGN_16::re

Real part.

The documentation for this struct was generated from the following file:

- C:/src/sw/rel/gpgpu/toolkit/r8.0/NPP/npp/include/nppdefs.h

8.2 NPP_ALIGN_8 Struct Reference

Complex Number This struct represents an unsigned int complex number.

```
#include <nppdefs.h>
```

Data Fields

- [Npp32u re](#)
Real part.
- [Npp32u im](#)
Imaginary part.
- [Npp32s re](#)
Real part.
- [Npp32s im](#)
Imaginary part.
- [Npp32f re](#)
Real part.
- [Npp32f im](#)
Imaginary part.

8.2.1 Detailed Description

Complex Number This struct represents an unsigned int complex number.

Complex Number This struct represents a single floating-point complex number.

Complex Number This struct represents a signed int complex number.

8.2.2 Field Documentation

8.2.2.1 Npp32f NPP_ALIGN_8::im

Imaginary part.

8.2.2.2 Npp32s NPP_ALIGN_8::im

Imaginary part.

8.2.2.3 Npp32u NPP_ALIGN_8::im

Imaginary part.

8.2.2.4 Npp32f NPP_ALIGN_8::re

Real part.

8.2.2.5 Npp32s NPP_ALIGN_8::re

Real part.

8.2.2.6 Npp32u NPP_ALIGN_8::re

Real part.

The documentation for this struct was generated from the following file:

- C:/src/sw/rel/gpgpu/toolkit/r8.0/NPP/npp/include/nppdefs.h

8.3 NppiHaarBuffer Struct Reference

```
#include <nppdefs.h>
```

Data Fields

- int `haarBufferSize`
size of the buffer
- `Npp32s * haarBuffer`
buffer

8.3.1 Field Documentation

8.3.1.1 `Npp32s* NppiHaarBuffer::haarBuffer`

`buffer`

8.3.1.2 `int NppiHaarBuffer::haarBufferSize`

size of the buffer

The documentation for this struct was generated from the following file:

- `C:/src/sw/rel/gpgpu/toolkit/r8.0/NPP/npp/include/nppdefs.h`

8.4 NppiHaarClassifier_32f Struct Reference

```
#include <nppdefs.h>
```

Data Fields

- int `numClassifiers`
number of classifiers
- `Npp32s * classifiers`
packed classifier data 40 bytes each
- `size_t classifierStep`
- `NppiSize classifierSize`
- `Npp32s * counterDevice`

8.4.1 Field Documentation

8.4.1.1 `Npp32s* NppiHaarClassifier_32f::classifiers`

packed classifier data 40 bytes each

8.4.1.2 `NppiSize NppiHaarClassifier_32f::classifierSize`

8.4.1.3 `size_t NppiHaarClassifier_32f::classifierStep`

8.4.1.4 `Npp32s* NppiHaarClassifier_32f::counterDevice`

8.4.1.5 `int NppiHaarClassifier_32f::numClassifiers`

number of classifiers

The documentation for this struct was generated from the following file:

- `C:/src/sw/rel/gpgpu/toolkit/r8.0/NPP/npp/include/nppdefs.h`

8.5 NppiPoint Struct Reference

2D Point

```
#include <nppdefs.h>
```

Data Fields

- `int x`
x-coordinate.
- `int y`
y-coordinate.

8.5.1 Detailed Description

2D Point

8.5.2 Field Documentation

8.5.2.1 `int NppiPoint::x`

x-coordinate.

8.5.2.2 `int NppiPoint::y`

y-coordinate.

The documentation for this struct was generated from the following file:

- `C:/src/sw/rel/gpgpu/toolkit/r8.0/NPP/npp/include/nppdefs.h`

8.6 NppiRect Struct Reference

2D Rectangle This struct contains position and size information of a rectangle in two space.

```
#include <nppdefs.h>
```

Data Fields

- `int x`
x-coordinate of upper left corner (lowest memory address).
- `int y`
y-coordinate of upper left corner (lowest memory address).
- `int width`
Rectangle width.
- `int height`
Rectangle height.

8.6.1 Detailed Description

2D Rectangle This struct contains position and size information of a rectangle in two space.

The rectangle's position is usually signified by the coordinate of its upper-left corner.

8.6.2 Field Documentation

8.6.2.1 `int NppiRect::height`

Rectangle height.

8.6.2.2 `int NppiRect::width`

Rectangle width.

8.6.2.3 `int NppiRect::x`

x-coordinate of upper left corner (lowest memory address).

8.6.2.4 `int NppiRect::y`

y-coordinate of upper left corner (lowest memory address).

The documentation for this struct was generated from the following file:

- `C:/src/sw/rel/gpgpu/toolkit/r8.0/NPP/npp/include/nppdefs.h`

8.7 NppiSize Struct Reference

2D Size This struct typically represents the size of a rectangular region in two space.

```
#include <nppdefs.h>
```

Data Fields

- `int width`
Rectangle width.
- `int height`
Rectangle height.

8.7.1 Detailed Description

2D Size This struct typically represents the size of a rectangular region in two space.

8.7.2 Field Documentation

8.7.2.1 `int NppiSize::height`

Rectangle height.

8.7.2.2 `int NppiSize::width`

Rectangle width.

The documentation for this struct was generated from the following file:

- `C:/src/sw/rel/gpgpu/toolkit/r8.0/NPP/npp/include/nppdefs.h`

8.8 NppLibraryVersion Struct Reference

```
#include <nppdefs.h>
```

Data Fields

- int `major`
Major version number.
- int `minor`
Minor version number.
- int `build`
Build number.

8.8.1 Field Documentation

8.8.1.1 int NppLibraryVersion::build

Build number.

This reflects the nightly build this release was made from.

8.8.1.2 int NppLibraryVersion::major

Major version number.

8.8.1.3 int NppLibraryVersion::minor

Minor version number.

The documentation for this struct was generated from the following file:

- `C:/src/sw/rel/gpgpu/toolkit/r8.0/NPP/npp/include/nppdefs.h`

Index

- `__align__`
 - `npp_basic_types`, 48, 49
- Abs, 318
- AbsDiff, 325
- AbsDiffC, 164
- Add, 166
- AddC, 53
- AddProduct, 198
- AddSquare, 195
- AddWeighted, 202
- Alpha Composition, 470
- AlphaComp, 486
- AlphaCompC, 471
- AlphaPremul, 493
- AlphaPremulC, 479
- And, 430
- AndC, 369
- Arithmetic and Logical Operations, 50
- Arithmetic Operations, 51
- Basic NPP Data Types, 46
- build
 - `NppLibraryVersion`, 504
- classifiers
 - `NppiHaarClassifier_32f`, 500
- classifierSize
 - `NppiHaarClassifier_32f`, 500
- classifierStep
 - `NppiHaarClassifier_32f`, 500
- core_npp
 - `nppGetGpuComputeCapability`, 28
 - `nppGetGpuDeviceProperties`, 28
 - `nppGetGpuName`, 28
 - `nppGetGpuNumSMs`, 28
 - `nppGetLibVersion`, 28
 - `nppGetMaxThreadsPerBlock`, 29
 - `nppGetMaxThreadsPerSM`, 29
 - `nppGetStream`, 29
 - `nppGetStreamMaxThreadsPerSM`, 29
 - `nppGetStreamNumSMs`, 29
 - `nppSetStream`, 29
- counterDevice
 - `NppiHaarClassifier_32f`, 500
- Div, 274
- Div_Round, 303
- DivC, 138
- Exp, 361
- haarBuffer
 - `NppiHaarBuffer`, 499
- haarBufferSize
 - `NppiHaarBuffer`, 499
- height
 - `NppiRect`, 502
 - `NppiSize`, 503
- im
 - `NPP_ALIGN_16`, 495
 - `NPP_ALIGN_8`, 497
- image_abs
 - `nppiAbs_16s_AC4IR`, 319
 - `nppiAbs_16s_AC4R`, 319
 - `nppiAbs_16s_C1IR`, 319
 - `nppiAbs_16s_C1R`, 320
 - `nppiAbs_16s_C3IR`, 320
 - `nppiAbs_16s_C3R`, 320
 - `nppiAbs_16s_C4IR`, 321
 - `nppiAbs_16s_C4R`, 321
 - `nppiAbs_32f_AC4IR`, 321
 - `nppiAbs_32f_AC4R`, 322
 - `nppiAbs_32f_C1IR`, 322
 - `nppiAbs_32f_C1R`, 322
 - `nppiAbs_32f_C3IR`, 323
 - `nppiAbs_32f_C3R`, 323
 - `nppiAbs_32f_C4IR`, 323
 - `nppiAbs_32f_C4R`, 324
- image_absdiff
 - `nppiAbsDiff_16u_C1R`, 325
 - `nppiAbsDiff_32f_C1R`, 326
 - `nppiAbsDiff_8u_C1R`, 326
 - `nppiAbsDiff_8u_C3R`, 326
 - `nppiAbsDiff_8u_C4R`, 327
- image_absdiffc
 - `nppiAbsDiffC_16u_C1R`, 164
 - `nppiAbsDiffC_32f_C1R`, 164
 - `nppiAbsDiffC_8u_C1R`, 165
- image_add

- nppiAdd_16s_AC4IRSfs, 171
- nppiAdd_16s_AC4RSfs, 171
- nppiAdd_16s_C1IRSfs, 172
- nppiAdd_16s_C1RSfs, 172
- nppiAdd_16s_C3IRSfs, 173
- nppiAdd_16s_C3RSfs, 173
- nppiAdd_16s_C4IRSfs, 173
- nppiAdd_16s_C4RSfs, 174
- nppiAdd_16sc_AC4IRSfs, 174
- nppiAdd_16sc_AC4RSfs, 175
- nppiAdd_16sc_C1IRSfs, 175
- nppiAdd_16sc_C1RSfs, 175
- nppiAdd_16sc_C3IRSfs, 176
- nppiAdd_16sc_C3RSfs, 176
- nppiAdd_16u_AC4IRSfs, 177
- nppiAdd_16u_AC4RSfs, 177
- nppiAdd_16u_C1IRSfs, 178
- nppiAdd_16u_C1RSfs, 178
- nppiAdd_16u_C3IRSfs, 178
- nppiAdd_16u_C3RSfs, 179
- nppiAdd_16u_C4IRSfs, 179
- nppiAdd_16u_C4RSfs, 180
- nppiAdd_32f_AC4IR, 180
- nppiAdd_32f_AC4R, 180
- nppiAdd_32f_C1IR, 181
- nppiAdd_32f_C1R, 181
- nppiAdd_32f_C3IR, 182
- nppiAdd_32f_C3R, 182
- nppiAdd_32f_C4IR, 182
- nppiAdd_32f_C4R, 183
- nppiAdd_32fc_AC4IR, 183
- nppiAdd_32fc_AC4R, 183
- nppiAdd_32fc_C1IR, 184
- nppiAdd_32fc_C1R, 184
- nppiAdd_32fc_C3IR, 185
- nppiAdd_32fc_C3R, 185
- nppiAdd_32fc_C4IR, 185
- nppiAdd_32fc_C4R, 186
- nppiAdd_32s_C1IRSfs, 186
- nppiAdd_32s_C1R, 187
- nppiAdd_32s_C1RSfs, 187
- nppiAdd_32s_C3IRSfs, 187
- nppiAdd_32s_C3RSfs, 188
- nppiAdd_32sc_AC4IRSfs, 188
- nppiAdd_32sc_AC4RSfs, 189
- nppiAdd_32sc_C1IRSfs, 189
- nppiAdd_32sc_C1RSfs, 189
- nppiAdd_32sc_C3IRSfs, 190
- nppiAdd_32sc_C3RSfs, 190
- nppiAdd_8u_AC4IRSfs, 191
- nppiAdd_8u_AC4RSfs, 191
- nppiAdd_8u_C1IRSfs, 192
- nppiAdd_8u_C1RSfs, 192
- nppiAdd_8u_C3IRSfs, 192
- nppiAdd_8u_C3RSfs, 193
- nppiAdd_8u_C4IRSfs, 193
- nppiAdd_8u_C4RSfs, 194
- image_addc
 - nppiAddC_16s_AC4IRSfs, 58
 - nppiAddC_16s_AC4RSfs, 58
 - nppiAddC_16s_C1IRSfs, 58
 - nppiAddC_16s_C1RSfs, 59
 - nppiAddC_16s_C3IRSfs, 59
 - nppiAddC_16s_C3RSfs, 59
 - nppiAddC_16s_C4IRSfs, 60
 - nppiAddC_16s_C4RSfs, 60
 - nppiAddC_16sc_AC4IRSfs, 61
 - nppiAddC_16sc_AC4RSfs, 61
 - nppiAddC_16sc_C1IRSfs, 61
 - nppiAddC_16sc_C1RSfs, 62
 - nppiAddC_16sc_C3IRSfs, 62
 - nppiAddC_16sc_C3RSfs, 63
 - nppiAddC_16u_AC4IRSfs, 63
 - nppiAddC_16u_AC4RSfs, 63
 - nppiAddC_16u_C1IRSfs, 64
 - nppiAddC_16u_C1RSfs, 64
 - nppiAddC_16u_C3IRSfs, 65
 - nppiAddC_16u_C3RSfs, 65
 - nppiAddC_16u_C4IRSfs, 65
 - nppiAddC_16u_C4RSfs, 66
 - nppiAddC_32f_AC4IR, 66
 - nppiAddC_32f_AC4R, 66
 - nppiAddC_32f_C1IR, 67
 - nppiAddC_32f_C1R, 67
 - nppiAddC_32f_C3IR, 67
 - nppiAddC_32f_C3R, 68
 - nppiAddC_32f_C4IR, 68
 - nppiAddC_32f_C4R, 68
 - nppiAddC_32fc_AC4IR, 69
 - nppiAddC_32fc_AC4R, 69
 - nppiAddC_32fc_C1IR, 69
 - nppiAddC_32fc_C1R, 70
 - nppiAddC_32fc_C3IR, 70
 - nppiAddC_32fc_C3R, 70
 - nppiAddC_32fc_C4IR, 71
 - nppiAddC_32fc_C4R, 71
 - nppiAddC_32s_C1IRSfs, 72
 - nppiAddC_32s_C1RSfs, 72
 - nppiAddC_32s_C3IRSfs, 72
 - nppiAddC_32s_C3RSfs, 73
 - nppiAddC_32sc_AC4IRSfs, 73
 - nppiAddC_32sc_AC4RSfs, 73
 - nppiAddC_32sc_C1IRSfs, 74
 - nppiAddC_32sc_C1RSfs, 74
 - nppiAddC_32sc_C3IRSfs, 75
 - nppiAddC_32sc_C3RSfs, 75
 - nppiAddC_8u_AC4IRSfs, 75
 - nppiAddC_8u_AC4RSfs, 76

- nppiAddC_8u_C1RSfs, 76
- nppiAddC_8u_C1RSfs, 77
- nppiAddC_8u_C3RSfs, 77
- nppiAddC_8u_C3RSfs, 77
- nppiAddC_8u_C4RSfs, 78
- nppiAddC_8u_C4RSfs, 78
- image_addproduct
 - nppiAddProduct_16u32f_C1IMR, 198
 - nppiAddProduct_16u32f_C1IR, 199
 - nppiAddProduct_32f_C1IMR, 199
 - nppiAddProduct_32f_C1IR, 200
 - nppiAddProduct_8u32f_C1IMR, 200
 - nppiAddProduct_8u32f_C1IR, 200
- image_addsquare
 - nppiAddSquare_16u32f_C1IMR, 195
 - nppiAddSquare_16u32f_C1IR, 196
 - nppiAddSquare_32f_C1IMR, 196
 - nppiAddSquare_32f_C1IR, 196
 - nppiAddSquare_8u32f_C1IMR, 197
 - nppiAddSquare_8u32f_C1IR, 197
- image_addweighted
 - nppiAddWeighted_16u32f_C1IMR, 202
 - nppiAddWeighted_16u32f_C1IR, 203
 - nppiAddWeighted_32f_C1IMR, 203
 - nppiAddWeighted_32f_C1IR, 204
 - nppiAddWeighted_8u32f_C1IMR, 204
 - nppiAddWeighted_8u32f_C1IR, 204
- image_alphacomp
 - nppiAlphaComp_16s_AC1R, 487
 - nppiAlphaComp_16u_AC1R, 487
 - nppiAlphaComp_16u_AC4R, 488
 - nppiAlphaComp_32f_AC1R, 488
 - nppiAlphaComp_32f_AC4R, 489
 - nppiAlphaComp_32s_AC1R, 489
 - nppiAlphaComp_32s_AC4R, 489
 - nppiAlphaComp_32u_AC1R, 490
 - nppiAlphaComp_32u_AC4R, 490
 - nppiAlphaComp_8s_AC1R, 491
 - nppiAlphaComp_8u_AC1R, 491
 - nppiAlphaComp_8u_AC4R, 492
- image_alphacompC
 - nppiAlphaCompC_16s_C1R, 472
 - nppiAlphaCompC_16u_AC4R, 472
 - nppiAlphaCompC_16u_C1R, 473
 - nppiAlphaCompC_16u_C3R, 473
 - nppiAlphaCompC_16u_C4R, 474
 - nppiAlphaCompC_32f_C1R, 474
 - nppiAlphaCompC_32s_C1R, 475
 - nppiAlphaCompC_32u_C1R, 475
 - nppiAlphaCompC_8s_C1R, 476
 - nppiAlphaCompC_8u_AC4R, 476
 - nppiAlphaCompC_8u_C1R, 477
 - nppiAlphaCompC_8u_C3R, 477
 - nppiAlphaCompC_8u_C4R, 478
- image_alphapremul
 - nppiAlphaPremul_16u_AC4IR, 493
 - nppiAlphaPremul_16u_AC4R, 493
 - nppiAlphaPremul_8u_AC4IR, 494
 - nppiAlphaPremul_8u_AC4R, 494
- image_alphapremulC
 - nppiAlphaPremulC_16u_AC4IR, 480
 - nppiAlphaPremulC_16u_AC4R, 480
 - nppiAlphaPremulC_16u_C1IR, 481
 - nppiAlphaPremulC_16u_C1R, 481
 - nppiAlphaPremulC_16u_C3IR, 481
 - nppiAlphaPremulC_16u_C3R, 482
 - nppiAlphaPremulC_16u_C4IR, 482
 - nppiAlphaPremulC_16u_C4R, 482
 - nppiAlphaPremulC_8u_AC4IR, 483
 - nppiAlphaPremulC_8u_AC4R, 483
 - nppiAlphaPremulC_8u_C1IR, 483
 - nppiAlphaPremulC_8u_C1R, 484
 - nppiAlphaPremulC_8u_C3IR, 484
 - nppiAlphaPremulC_8u_C3R, 484
 - nppiAlphaPremulC_8u_C4IR, 485
 - nppiAlphaPremulC_8u_C4R, 485
- image_and
 - nppiAnd_16u_AC4IR, 432
 - nppiAnd_16u_AC4R, 432
 - nppiAnd_16u_C1IR, 432
 - nppiAnd_16u_C1R, 433
 - nppiAnd_16u_C3IR, 433
 - nppiAnd_16u_C3R, 433
 - nppiAnd_16u_C4IR, 434
 - nppiAnd_16u_C4R, 434
 - nppiAnd_32s_AC4IR, 435
 - nppiAnd_32s_AC4R, 435
 - nppiAnd_32s_C1IR, 435
 - nppiAnd_32s_C1R, 436
 - nppiAnd_32s_C3IR, 436
 - nppiAnd_32s_C3R, 436
 - nppiAnd_32s_C4IR, 437
 - nppiAnd_32s_C4R, 437
 - nppiAnd_8u_AC4IR, 438
 - nppiAnd_8u_AC4R, 438
 - nppiAnd_8u_C1IR, 438
 - nppiAnd_8u_C1R, 439
 - nppiAnd_8u_C3IR, 439
 - nppiAnd_8u_C3R, 439
 - nppiAnd_8u_C4IR, 440
 - nppiAnd_8u_C4R, 440
- image_andc
 - nppiAndC_16u_AC4IR, 371
 - nppiAndC_16u_AC4R, 371
 - nppiAndC_16u_C1IR, 371
 - nppiAndC_16u_C1R, 372
 - nppiAndC_16u_C3IR, 372
 - nppiAndC_16u_C3R, 372

- nppiAndC_16u_C4IR, 373
- nppiAndC_16u_C4R, 373
- nppiAndC_32s_AC4IR, 373
- nppiAndC_32s_AC4R, 374
- nppiAndC_32s_C1IR, 374
- nppiAndC_32s_C1R, 374
- nppiAndC_32s_C3IR, 375
- nppiAndC_32s_C3R, 375
- nppiAndC_32s_C4IR, 375
- nppiAndC_32s_C4R, 376
- nppiAndC_8u_AC4IR, 376
- nppiAndC_8u_AC4R, 376
- nppiAndC_8u_C1IR, 377
- nppiAndC_8u_C1R, 377
- nppiAndC_8u_C3IR, 377
- nppiAndC_8u_C3R, 378
- nppiAndC_8u_C4IR, 378
- nppiAndC_8u_C4R, 378
- image_div
 - nppiDiv_16s_AC4IRSfs, 279
 - nppiDiv_16s_AC4RSfs, 279
 - nppiDiv_16s_C1IRSfs, 280
 - nppiDiv_16s_C1RSfs, 280
 - nppiDiv_16s_C3IRSfs, 280
 - nppiDiv_16s_C3RSfs, 281
 - nppiDiv_16s_C4IRSfs, 281
 - nppiDiv_16s_C4RSfs, 282
 - nppiDiv_16sc_AC4IRSfs, 282
 - nppiDiv_16sc_AC4RSfs, 282
 - nppiDiv_16sc_C1IRSfs, 283
 - nppiDiv_16sc_C1RSfs, 283
 - nppiDiv_16sc_C3IRSfs, 284
 - nppiDiv_16sc_C3RSfs, 284
 - nppiDiv_16u_AC4IRSfs, 285
 - nppiDiv_16u_AC4RSfs, 285
 - nppiDiv_16u_C1IRSfs, 285
 - nppiDiv_16u_C1RSfs, 286
 - nppiDiv_16u_C3IRSfs, 286
 - nppiDiv_16u_C3RSfs, 287
 - nppiDiv_16u_C4IRSfs, 287
 - nppiDiv_16u_C4RSfs, 287
 - nppiDiv_32f_AC4IR, 288
 - nppiDiv_32f_AC4R, 288
 - nppiDiv_32f_C1IR, 289
 - nppiDiv_32f_C1R, 289
 - nppiDiv_32f_C3IR, 289
 - nppiDiv_32f_C3R, 290
 - nppiDiv_32f_C4IR, 290
 - nppiDiv_32f_C4R, 290
 - nppiDiv_32fc_AC4IR, 291
 - nppiDiv_32fc_AC4R, 291
 - nppiDiv_32fc_C1IR, 292
 - nppiDiv_32fc_C1R, 292
 - nppiDiv_32fc_C3IR, 292
 - nppiDiv_32fc_C3R, 293
 - nppiDiv_32fc_C4IR, 293
 - nppiDiv_32fc_C4R, 293
 - nppiDiv_32s_C1IRSfs, 294
 - nppiDiv_32s_C1R, 294
 - nppiDiv_32s_C1RSfs, 295
 - nppiDiv_32s_C3IRSfs, 295
 - nppiDiv_32s_C3RSfs, 295
 - nppiDiv_32sc_AC4IRSfs, 296
 - nppiDiv_32sc_AC4RSfs, 296
 - nppiDiv_32sc_C1IRSfs, 297
 - nppiDiv_32sc_C1RSfs, 297
 - nppiDiv_32sc_C3IRSfs, 298
 - nppiDiv_32sc_C3RSfs, 298
 - nppiDiv_8u_AC4IRSfs, 298
 - nppiDiv_8u_AC4RSfs, 299
 - nppiDiv_8u_C1IRSfs, 299
 - nppiDiv_8u_C1RSfs, 300
 - nppiDiv_8u_C3IRSfs, 300
 - nppiDiv_8u_C3RSfs, 300
 - nppiDiv_8u_C4IRSfs, 301
 - nppiDiv_8u_C4RSfs, 301
- image_divc
 - nppiDivC_16s_AC4IRSfs, 143
 - nppiDivC_16s_AC4RSfs, 143
 - nppiDivC_16s_C1IRSfs, 143
 - nppiDivC_16s_C1RSfs, 144
 - nppiDivC_16s_C3IRSfs, 144
 - nppiDivC_16s_C3RSfs, 144
 - nppiDivC_16s_C4IRSfs, 145
 - nppiDivC_16s_C4RSfs, 145
 - nppiDivC_16sc_AC4IRSfs, 146
 - nppiDivC_16sc_AC4RSfs, 146
 - nppiDivC_16sc_C1IRSfs, 146
 - nppiDivC_16sc_C1RSfs, 147
 - nppiDivC_16sc_C3IRSfs, 147
 - nppiDivC_16sc_C3RSfs, 148
 - nppiDivC_16u_AC4IRSfs, 148
 - nppiDivC_16u_AC4RSfs, 148
 - nppiDivC_16u_C1IRSfs, 149
 - nppiDivC_16u_C1RSfs, 149
 - nppiDivC_16u_C3IRSfs, 150
 - nppiDivC_16u_C3RSfs, 150
 - nppiDivC_16u_C4IRSfs, 150
 - nppiDivC_16u_C4RSfs, 151
 - nppiDivC_32f_AC4IR, 151
 - nppiDivC_32f_AC4R, 151
 - nppiDivC_32f_C1IR, 152
 - nppiDivC_32f_C1R, 152
 - nppiDivC_32f_C3IR, 152
 - nppiDivC_32f_C3R, 153
 - nppiDivC_32f_C4IR, 153
 - nppiDivC_32f_C4R, 153
 - nppiDivC_32fc_AC4IR, 154

- nppiDivC_32fc_AC4R, 154
- nppiDivC_32fc_C1IR, 154
- nppiDivC_32fc_C1R, 155
- nppiDivC_32fc_C3IR, 155
- nppiDivC_32fc_C3R, 155
- nppiDivC_32fc_C4IR, 156
- nppiDivC_32fc_C4R, 156
- nppiDivC_32s_C1IRSfs, 157
- nppiDivC_32s_C1RSfs, 157
- nppiDivC_32s_C3IRSfs, 157
- nppiDivC_32s_C3RSfs, 158
- nppiDivC_32sc_AC4IRSfs, 158
- nppiDivC_32sc_AC4RSfs, 158
- nppiDivC_32sc_C1IRSfs, 159
- nppiDivC_32sc_C1RSfs, 159
- nppiDivC_32sc_C3IRSfs, 160
- nppiDivC_32sc_C3RSfs, 160
- nppiDivC_8u_AC4IRSfs, 160
- nppiDivC_8u_AC4RSfs, 161
- nppiDivC_8u_C1IRSfs, 161
- nppiDivC_8u_C1RSfs, 162
- nppiDivC_8u_C3IRSfs, 162
- nppiDivC_8u_C3RSfs, 162
- nppiDivC_8u_C4IRSfs, 163
- nppiDivC_8u_C4RSfs, 163
- image_divround
 - nppiDiv_Round_16s_AC4IRSfs, 305
 - nppiDiv_Round_16s_AC4RSfs, 306
 - nppiDiv_Round_16s_C1IRSfs, 306
 - nppiDiv_Round_16s_C1RSfs, 307
 - nppiDiv_Round_16s_C3IRSfs, 307
 - nppiDiv_Round_16s_C3RSfs, 307
 - nppiDiv_Round_16s_C4IRSfs, 308
 - nppiDiv_Round_16s_C4RSfs, 308
 - nppiDiv_Round_16u_AC4IRSfs, 309
 - nppiDiv_Round_16u_AC4RSfs, 309
 - nppiDiv_Round_16u_C1IRSfs, 310
 - nppiDiv_Round_16u_C1RSfs, 310
 - nppiDiv_Round_16u_C3IRSfs, 311
 - nppiDiv_Round_16u_C3RSfs, 311
 - nppiDiv_Round_16u_C4IRSfs, 312
 - nppiDiv_Round_16u_C4RSfs, 312
 - nppiDiv_Round_8u_AC4IRSfs, 313
 - nppiDiv_Round_8u_AC4RSfs, 313
 - nppiDiv_Round_8u_C1IRSfs, 314
 - nppiDiv_Round_8u_C1RSfs, 314
 - nppiDiv_Round_8u_C3IRSfs, 315
 - nppiDiv_Round_8u_C3RSfs, 315
 - nppiDiv_Round_8u_C4IRSfs, 316
 - nppiDiv_Round_8u_C4RSfs, 316
- image_exp
 - nppiExp_16s_C1IRSfs, 362
 - nppiExp_16s_C1RSfs, 362
 - nppiExp_16s_C3IRSfs, 363
 - nppiExp_16s_C3RSfs, 363
 - nppiExp_16u_C1IRSfs, 363
 - nppiExp_16u_C1RSfs, 364
 - nppiExp_16u_C3IRSfs, 364
 - nppiExp_16u_C3RSfs, 364
 - nppiExp_32f_C1IR, 365
 - nppiExp_32f_C1R, 365
 - nppiExp_32f_C3IR, 365
 - nppiExp_32f_C3R, 366
 - nppiExp_8u_C1IRSfs, 366
 - nppiExp_8u_C1RSfs, 366
 - nppiExp_8u_C3IRSfs, 367
 - nppiExp_8u_C3RSfs, 367
- image_ln
 - nppiLn_16s_C1IRSfs, 355
 - nppiLn_16s_C1RSfs, 355
 - nppiLn_16s_C3IRSfs, 356
 - nppiLn_16s_C3RSfs, 356
 - nppiLn_16u_C1IRSfs, 356
 - nppiLn_16u_C1RSfs, 357
 - nppiLn_16u_C3IRSfs, 357
 - nppiLn_16u_C3RSfs, 357
 - nppiLn_32f_C1IR, 358
 - nppiLn_32f_C1R, 358
 - nppiLn_32f_C3IR, 358
 - nppiLn_32f_C3R, 359
 - nppiLn_8u_C1IRSfs, 359
 - nppiLn_8u_C1RSfs, 359
 - nppiLn_8u_C3IRSfs, 360
 - nppiLn_8u_C3RSfs, 360
- image_lshiftc
 - nppiLShiftC_16u_AC4IR, 421
 - nppiLShiftC_16u_AC4R, 421
 - nppiLShiftC_16u_C1IR, 421
 - nppiLShiftC_16u_C1R, 422
 - nppiLShiftC_16u_C3IR, 422
 - nppiLShiftC_16u_C3R, 422
 - nppiLShiftC_16u_C4IR, 423
 - nppiLShiftC_16u_C4R, 423
 - nppiLShiftC_32s_AC4IR, 423
 - nppiLShiftC_32s_AC4R, 424
 - nppiLShiftC_32s_C1IR, 424
 - nppiLShiftC_32s_C1R, 424
 - nppiLShiftC_32s_C3IR, 425
 - nppiLShiftC_32s_C3R, 425
 - nppiLShiftC_32s_C4IR, 425
 - nppiLShiftC_32s_C4R, 426
 - nppiLShiftC_8u_AC4IR, 426
 - nppiLShiftC_8u_AC4R, 426
 - nppiLShiftC_8u_C1IR, 427
 - nppiLShiftC_8u_C1R, 427
 - nppiLShiftC_8u_C3IR, 427
 - nppiLShiftC_8u_C3R, 428
 - nppiLShiftC_8u_C4IR, 428

nppiLShiftC_8u_C4R, 428
 image_mul
 nppiMul_16s_AC4IRSfs, 211
 nppiMul_16s_AC4RSfs, 211
 nppiMul_16s_C1IRSfs, 212
 nppiMul_16s_C1RSfs, 212
 nppiMul_16s_C3IRSfs, 213
 nppiMul_16s_C3RSfs, 213
 nppiMul_16s_C4IRSfs, 213
 nppiMul_16s_C4RSfs, 214
 nppiMul_16sc_AC4IRSfs, 214
 nppiMul_16sc_AC4RSfs, 215
 nppiMul_16sc_C1IRSfs, 215
 nppiMul_16sc_C1RSfs, 215
 nppiMul_16sc_C3IRSfs, 216
 nppiMul_16sc_C3RSfs, 216
 nppiMul_16u_AC4IRSfs, 217
 nppiMul_16u_AC4RSfs, 217
 nppiMul_16u_C1IRSfs, 218
 nppiMul_16u_C1RSfs, 218
 nppiMul_16u_C3IRSfs, 218
 nppiMul_16u_C3RSfs, 219
 nppiMul_16u_C4IRSfs, 219
 nppiMul_16u_C4RSfs, 220
 nppiMul_32f_AC4IR, 220
 nppiMul_32f_AC4R, 220
 nppiMul_32f_C1IR, 221
 nppiMul_32f_C1R, 221
 nppiMul_32f_C3IR, 222
 nppiMul_32f_C3R, 222
 nppiMul_32f_C4IR, 222
 nppiMul_32f_C4R, 223
 nppiMul_32fc_AC4IR, 223
 nppiMul_32fc_AC4R, 223
 nppiMul_32fc_C1IR, 224
 nppiMul_32fc_C1R, 224
 nppiMul_32fc_C3IR, 225
 nppiMul_32fc_C3R, 225
 nppiMul_32fc_C4IR, 225
 nppiMul_32fc_C4R, 226
 nppiMul_32s_C1IRSfs, 226
 nppiMul_32s_C1R, 227
 nppiMul_32s_C1RSfs, 227
 nppiMul_32s_C3IRSfs, 227
 nppiMul_32s_C3RSfs, 228
 nppiMul_32sc_AC4IRSfs, 228
 nppiMul_32sc_AC4RSfs, 229
 nppiMul_32sc_C1IRSfs, 229
 nppiMul_32sc_C1RSfs, 229
 nppiMul_32sc_C3IRSfs, 230
 nppiMul_32sc_C3RSfs, 230
 nppiMul_8u_AC4IRSfs, 231
 nppiMul_8u_AC4RSfs, 231
 nppiMul_8u_C1IRSfs, 232

 nppiMul_8u_C1RSfs, 232
 nppiMul_8u_C3IRSfs, 232
 nppiMul_8u_C3RSfs, 233
 nppiMul_8u_C4IRSfs, 233
 nppiMul_8u_C4RSfs, 234
 image_mulc
 nppiMulC_16s_AC4IRSfs, 84
 nppiMulC_16s_AC4RSfs, 84
 nppiMulC_16s_C1IRSfs, 84
 nppiMulC_16s_C1RSfs, 85
 nppiMulC_16s_C3IRSfs, 85
 nppiMulC_16s_C3RSfs, 85
 nppiMulC_16s_C4IRSfs, 86
 nppiMulC_16s_C4RSfs, 86
 nppiMulC_16sc_AC4IRSfs, 87
 nppiMulC_16sc_AC4RSfs, 87
 nppiMulC_16sc_C1IRSfs, 87
 nppiMulC_16sc_C1RSfs, 88
 nppiMulC_16sc_C3IRSfs, 88
 nppiMulC_16sc_C3RSfs, 89
 nppiMulC_16u_AC4IRSfs, 89
 nppiMulC_16u_AC4RSfs, 89
 nppiMulC_16u_C1IRSfs, 90
 nppiMulC_16u_C1RSfs, 90
 nppiMulC_16u_C3IRSfs, 91
 nppiMulC_16u_C3RSfs, 91
 nppiMulC_16u_C4IRSfs, 91
 nppiMulC_16u_C4RSfs, 92
 nppiMulC_32f_AC4IR, 92
 nppiMulC_32f_AC4R, 92
 nppiMulC_32f_C1IR, 93
 nppiMulC_32f_C1R, 93
 nppiMulC_32f_C3IR, 93
 nppiMulC_32f_C3R, 94
 nppiMulC_32f_C4IR, 94
 nppiMulC_32f_C4R, 94
 nppiMulC_32fc_AC4IR, 95
 nppiMulC_32fc_AC4R, 95
 nppiMulC_32fc_C1IR, 95
 nppiMulC_32fc_C1R, 96
 nppiMulC_32fc_C3IR, 96
 nppiMulC_32fc_C3R, 96
 nppiMulC_32fc_C4IR, 97
 nppiMulC_32fc_C4R, 97
 nppiMulC_32s_C1IRSfs, 98
 nppiMulC_32s_C1RSfs, 98
 nppiMulC_32s_C3IRSfs, 98
 nppiMulC_32s_C3RSfs, 99
 nppiMulC_32sc_AC4IRSfs, 99
 nppiMulC_32sc_AC4RSfs, 99
 nppiMulC_32sc_C1IRSfs, 100
 nppiMulC_32sc_C1RSfs, 100
 nppiMulC_32sc_C3IRSfs, 101
 nppiMulC_32sc_C3RSfs, 101

- nppiMulC_8u_AC4IRSfs, 101
- nppiMulC_8u_AC4RSfs, 102
- nppiMulC_8u_C1IRSfs, 102
- nppiMulC_8u_C1RSfs, 103
- nppiMulC_8u_C3IRSfs, 103
- nppiMulC_8u_C3RSfs, 103
- nppiMulC_8u_C4IRSfs, 104
- nppiMulC_8u_C4RSfs, 104
- image_mulcscale
 - nppiMulCScale_16u_AC4IR, 106
 - nppiMulCScale_16u_AC4R, 106
 - nppiMulCScale_16u_C1IR, 107
 - nppiMulCScale_16u_C1R, 107
 - nppiMulCScale_16u_C3IR, 107
 - nppiMulCScale_16u_C3R, 108
 - nppiMulCScale_16u_C4IR, 108
 - nppiMulCScale_16u_C4R, 108
 - nppiMulCScale_8u_AC4IR, 109
 - nppiMulCScale_8u_AC4R, 109
 - nppiMulCScale_8u_C1IR, 109
 - nppiMulCScale_8u_C1R, 110
 - nppiMulCScale_8u_C3IR, 110
 - nppiMulCScale_8u_C3R, 110
 - nppiMulCScale_8u_C4IR, 111
 - nppiMulCScale_8u_C4R, 111
- image_mulscale
 - nppiMulScale_16u_AC4IR, 236
 - nppiMulScale_16u_AC4R, 237
 - nppiMulScale_16u_C1IR, 237
 - nppiMulScale_16u_C1R, 237
 - nppiMulScale_16u_C3IR, 238
 - nppiMulScale_16u_C3R, 238
 - nppiMulScale_16u_C4IR, 239
 - nppiMulScale_16u_C4R, 239
 - nppiMulScale_8u_AC4IR, 239
 - nppiMulScale_8u_AC4R, 240
 - nppiMulScale_8u_C1IR, 240
 - nppiMulScale_8u_C1R, 241
 - nppiMulScale_8u_C3IR, 241
 - nppiMulScale_8u_C3R, 241
 - nppiMulScale_8u_C4IR, 242
 - nppiMulScale_8u_C4R, 242
- image_not
 - nppiNot_8u_AC4IR, 466
 - nppiNot_8u_AC4R, 467
 - nppiNot_8u_C1IR, 467
 - nppiNot_8u_C1R, 467
 - nppiNot_8u_C3IR, 467
 - nppiNot_8u_C3R, 468
 - nppiNot_8u_C4IR, 468
 - nppiNot_8u_C4R, 468
- image_or
 - nppiOr_16u_AC4IR, 444
 - nppiOr_16u_AC4R, 444
 - nppiOr_16u_C1IR, 444
 - nppiOr_16u_C1R, 445
 - nppiOr_16u_C3IR, 445
 - nppiOr_16u_C3R, 445
 - nppiOr_16u_C4IR, 446
 - nppiOr_16u_C4R, 446
 - nppiOr_32s_AC4IR, 447
 - nppiOr_32s_AC4R, 447
 - nppiOr_32s_C1IR, 447
 - nppiOr_32s_C1R, 448
 - nppiOr_32s_C3IR, 448
 - nppiOr_32s_C3R, 448
 - nppiOr_32s_C4IR, 449
 - nppiOr_32s_C4R, 449
 - nppiOr_8u_AC4IR, 450
 - nppiOr_8u_AC4R, 450
 - nppiOr_8u_C1IR, 450
 - nppiOr_8u_C1R, 451
 - nppiOr_8u_C3IR, 451
 - nppiOr_8u_C3R, 451
 - nppiOr_8u_C4IR, 452
 - nppiOr_8u_C4R, 452
- image_orc
 - nppiOrC_16u_AC4IR, 382
 - nppiOrC_16u_AC4R, 382
 - nppiOrC_16u_C1IR, 382
 - nppiOrC_16u_C1R, 383
 - nppiOrC_16u_C3IR, 383
 - nppiOrC_16u_C3R, 383
 - nppiOrC_16u_C4IR, 384
 - nppiOrC_16u_C4R, 384
 - nppiOrC_32s_AC4IR, 384
 - nppiOrC_32s_AC4R, 385
 - nppiOrC_32s_C1IR, 385
 - nppiOrC_32s_C1R, 385
 - nppiOrC_32s_C3IR, 386
 - nppiOrC_32s_C3R, 386
 - nppiOrC_32s_C4IR, 386
 - nppiOrC_32s_C4R, 387
 - nppiOrC_8u_AC4IR, 387
 - nppiOrC_8u_AC4R, 387
 - nppiOrC_8u_C1IR, 388
 - nppiOrC_8u_C1R, 388
 - nppiOrC_8u_C3IR, 388
 - nppiOrC_8u_C3R, 389
 - nppiOrC_8u_C4IR, 389
 - nppiOrC_8u_C4R, 389
- image_rshiftc
 - nppiRShiftC_16s_AC4IR, 405
 - nppiRShiftC_16s_AC4R, 405
 - nppiRShiftC_16s_C1IR, 406
 - nppiRShiftC_16s_C1R, 406
 - nppiRShiftC_16s_C3IR, 406
 - nppiRShiftC_16s_C3R, 407

- nppiRShiftC_16s_C4IR, 407
- nppiRShiftC_16s_C4R, 407
- nppiRShiftC_16u_AC4IR, 408
- nppiRShiftC_16u_AC4R, 408
- nppiRShiftC_16u_C1IR, 408
- nppiRShiftC_16u_C1R, 409
- nppiRShiftC_16u_C3IR, 409
- nppiRShiftC_16u_C3R, 409
- nppiRShiftC_16u_C4IR, 410
- nppiRShiftC_16u_C4R, 410
- nppiRShiftC_32s_AC4IR, 410
- nppiRShiftC_32s_AC4R, 411
- nppiRShiftC_32s_C1IR, 411
- nppiRShiftC_32s_C1R, 411
- nppiRShiftC_32s_C3IR, 412
- nppiRShiftC_32s_C3R, 412
- nppiRShiftC_32s_C4IR, 412
- nppiRShiftC_32s_C4R, 413
- nppiRShiftC_8s_AC4IR, 413
- nppiRShiftC_8s_AC4R, 413
- nppiRShiftC_8s_C1IR, 414
- nppiRShiftC_8s_C1R, 414
- nppiRShiftC_8s_C3IR, 414
- nppiRShiftC_8s_C3R, 415
- nppiRShiftC_8s_C4IR, 415
- nppiRShiftC_8s_C4R, 415
- nppiRShiftC_8u_AC4IR, 416
- nppiRShiftC_8u_AC4R, 416
- nppiRShiftC_8u_C1IR, 416
- nppiRShiftC_8u_C1R, 417
- nppiRShiftC_8u_C3IR, 417
- nppiRShiftC_8u_C3R, 417
- nppiRShiftC_8u_C4IR, 418
- nppiRShiftC_8u_C4R, 418
- image_sqr
 - nppiSqr_16s_AC4IRSfs, 331
 - nppiSqr_16s_AC4RSfs, 331
 - nppiSqr_16s_C1IRSfs, 331
 - nppiSqr_16s_C1RSfs, 331
 - nppiSqr_16s_C3IRSfs, 332
 - nppiSqr_16s_C3RSfs, 332
 - nppiSqr_16s_C4IRSfs, 332
 - nppiSqr_16s_C4RSfs, 333
 - nppiSqr_16u_AC4IRSfs, 333
 - nppiSqr_16u_AC4RSfs, 333
 - nppiSqr_16u_C1IRSfs, 334
 - nppiSqr_16u_C1RSfs, 334
 - nppiSqr_16u_C3IRSfs, 335
 - nppiSqr_16u_C3RSfs, 335
 - nppiSqr_16u_C4IRSfs, 335
 - nppiSqr_16u_C4RSfs, 336
 - nppiSqr_32f_AC4IR, 336
 - nppiSqr_32f_AC4R, 336
 - nppiSqr_32f_C1IR, 337
 - nppiSqr_32f_C1R, 337
 - nppiSqr_32f_C3IR, 337
 - nppiSqr_32f_C3R, 337
 - nppiSqr_32f_C4IR, 338
 - nppiSqr_32f_C4R, 338
 - nppiSqr_8u_AC4IRSfs, 338
 - nppiSqr_8u_AC4RSfs, 339
 - nppiSqr_8u_C1IRSfs, 339
 - nppiSqr_8u_C1RSfs, 339
 - nppiSqr_8u_C3IRSfs, 340
 - nppiSqr_8u_C3RSfs, 340
 - nppiSqr_8u_C4IRSfs, 340
 - nppiSqr_8u_C4RSfs, 341
- image_sqrt
 - nppiSqrt_16s_AC4IRSfs, 344
 - nppiSqrt_16s_AC4RSfs, 344
 - nppiSqrt_16s_C1IRSfs, 345
 - nppiSqrt_16s_C1RSfs, 345
 - nppiSqrt_16s_C3IRSfs, 346
 - nppiSqrt_16s_C3RSfs, 346
 - nppiSqrt_16u_AC4IRSfs, 346
 - nppiSqrt_16u_AC4RSfs, 347
 - nppiSqrt_16u_C1IRSfs, 347
 - nppiSqrt_16u_C1RSfs, 347
 - nppiSqrt_16u_C3IRSfs, 348
 - nppiSqrt_16u_C3RSfs, 348
 - nppiSqrt_32f_AC4IR, 348
 - nppiSqrt_32f_AC4R, 349
 - nppiSqrt_32f_C1IR, 349
 - nppiSqrt_32f_C1R, 349
 - nppiSqrt_32f_C3IR, 350
 - nppiSqrt_32f_C3R, 350
 - nppiSqrt_32f_C4IR, 350
 - nppiSqrt_32f_C4R, 351
 - nppiSqrt_8u_AC4IRSfs, 351
 - nppiSqrt_8u_AC4RSfs, 351
 - nppiSqrt_8u_C1IRSfs, 352
 - nppiSqrt_8u_C1RSfs, 352
 - nppiSqrt_8u_C3IRSfs, 353
 - nppiSqrt_8u_C3RSfs, 353
- image_sub
 - nppiSub_16s_AC4IRSfs, 249
 - nppiSub_16s_AC4RSfs, 250
 - nppiSub_16s_C1IRSfs, 250
 - nppiSub_16s_C1RSfs, 250
 - nppiSub_16s_C3IRSfs, 251
 - nppiSub_16s_C3RSfs, 251
 - nppiSub_16s_C4IRSfs, 252
 - nppiSub_16s_C4RSfs, 252
 - nppiSub_16sc_AC4IRSfs, 252
 - nppiSub_16sc_AC4RSfs, 253
 - nppiSub_16sc_C1IRSfs, 253
 - nppiSub_16sc_C1RSfs, 254
 - nppiSub_16sc_C3IRSfs, 254

- nppiSub_16sc_C3RSfs, 254
- nppiSub_16u_AC4IRSfs, 255
- nppiSub_16u_AC4RSfs, 255
- nppiSub_16u_C1IRSfs, 256
- nppiSub_16u_C1RSfs, 256
- nppiSub_16u_C3IRSfs, 257
- nppiSub_16u_C3RSfs, 257
- nppiSub_16u_C4IRSfs, 257
- nppiSub_16u_C4RSfs, 258
- nppiSub_32f_AC4IR, 258
- nppiSub_32f_AC4R, 259
- nppiSub_32f_C1IR, 259
- nppiSub_32f_C1R, 259
- nppiSub_32f_C3IR, 260
- nppiSub_32f_C3R, 260
- nppiSub_32f_C4IR, 261
- nppiSub_32f_C4R, 261
- nppiSub_32fc_AC4IR, 261
- nppiSub_32fc_AC4R, 262
- nppiSub_32fc_C1IR, 262
- nppiSub_32fc_C1R, 263
- nppiSub_32fc_C3IR, 263
- nppiSub_32fc_C3R, 263
- nppiSub_32fc_C4IR, 264
- nppiSub_32fc_C4R, 264
- nppiSub_32s_C1IRSfs, 265
- nppiSub_32s_C1R, 265
- nppiSub_32s_C1RSfs, 265
- nppiSub_32s_C3IRSfs, 266
- nppiSub_32s_C3RSfs, 266
- nppiSub_32s_C4IRSfs, 267
- nppiSub_32s_C4RSfs, 267
- nppiSub_32sc_AC4IRSfs, 268
- nppiSub_32sc_AC4RSfs, 268
- nppiSub_32sc_C1IRSfs, 268
- nppiSub_32sc_C1RSfs, 269
- nppiSub_32sc_C3IRSfs, 269
- nppiSub_32sc_C3RSfs, 270
- nppiSub_8u_AC4IRSfs, 270
- nppiSub_8u_AC4RSfs, 270
- nppiSub_8u_C1IRSfs, 271
- nppiSub_8u_C1RSfs, 271
- nppiSub_8u_C3IRSfs, 272
- nppiSub_8u_C3RSfs, 272
- nppiSub_8u_C4IRSfs, 272
- nppiSub_8u_C4RSfs, 273
- image_subc
 - nppiSubC_16s_AC4IRSfs, 117
 - nppiSubC_16s_AC4RSfs, 117
 - nppiSubC_16s_C1IRSfs, 117
 - nppiSubC_16s_C1RSfs, 118
 - nppiSubC_16s_C3IRSfs, 118
 - nppiSubC_16s_C3RSfs, 118
 - nppiSubC_16s_C4IRSfs, 119
- nppiSubC_16s_C4RSfs, 119
- nppiSubC_16sc_AC4IRSfs, 120
- nppiSubC_16sc_AC4RSfs, 120
- nppiSubC_16sc_C1IRSfs, 120
- nppiSubC_16sc_C1RSfs, 121
- nppiSubC_16sc_C3IRSfs, 121
- nppiSubC_16sc_C3RSfs, 122
- nppiSubC_16u_AC4IRSfs, 122
- nppiSubC_16u_AC4RSfs, 122
- nppiSubC_16u_C1IRSfs, 123
- nppiSubC_16u_C1RSfs, 123
- nppiSubC_16u_C3IRSfs, 124
- nppiSubC_16u_C3RSfs, 124
- nppiSubC_16u_C4IRSfs, 124
- nppiSubC_16u_C4RSfs, 125
- nppiSubC_32f_AC4IR, 125
- nppiSubC_32f_AC4R, 125
- nppiSubC_32f_C1IR, 126
- nppiSubC_32f_C1R, 126
- nppiSubC_32f_C3IR, 126
- nppiSubC_32f_C3R, 127
- nppiSubC_32f_C4IR, 127
- nppiSubC_32f_C4R, 127
- nppiSubC_32fc_AC4IR, 128
- nppiSubC_32fc_AC4R, 128
- nppiSubC_32fc_C1IR, 128
- nppiSubC_32fc_C1R, 129
- nppiSubC_32fc_C3IR, 129
- nppiSubC_32fc_C3R, 129
- nppiSubC_32fc_C4IR, 130
- nppiSubC_32fc_C4R, 130
- nppiSubC_32s_C1IRSfs, 131
- nppiSubC_32s_C1RSfs, 131
- nppiSubC_32s_C3IRSfs, 131
- nppiSubC_32s_C3RSfs, 132
- nppiSubC_32sc_AC4IRSfs, 132
- nppiSubC_32sc_AC4RSfs, 132
- nppiSubC_32sc_C1IRSfs, 133
- nppiSubC_32sc_C1RSfs, 133
- nppiSubC_32sc_C3IRSfs, 134
- nppiSubC_32sc_C3RSfs, 134
- nppiSubC_8u_AC4IRSfs, 134
- nppiSubC_8u_AC4RSfs, 135
- nppiSubC_8u_C1IRSfs, 135
- nppiSubC_8u_C1RSfs, 136
- nppiSubC_8u_C3IRSfs, 136
- nppiSubC_8u_C3RSfs, 136
- nppiSubC_8u_C4IRSfs, 137
- nppiSubC_8u_C4RSfs, 137
- image_xor
 - nppiXor_16u_AC4IR, 456
 - nppiXor_16u_AC4R, 456
 - nppiXor_16u_C1IR, 456
 - nppiXor_16u_C1R, 457

- nppiXor_16u_C3IR, 457
- nppiXor_16u_C3R, 457
- nppiXor_16u_C4IR, 458
- nppiXor_16u_C4R, 458
- nppiXor_32s_AC4IR, 459
- nppiXor_32s_AC4R, 459
- nppiXor_32s_C1IR, 459
- nppiXor_32s_C1R, 460
- nppiXor_32s_C3IR, 460
- nppiXor_32s_C3R, 460
- nppiXor_32s_C4IR, 461
- nppiXor_32s_C4R, 461
- nppiXor_8u_AC4IR, 462
- nppiXor_8u_AC4R, 462
- nppiXor_8u_C1IR, 462
- nppiXor_8u_C1R, 463
- nppiXor_8u_C3IR, 463
- nppiXor_8u_C3R, 463
- nppiXor_8u_C4IR, 464
- nppiXor_8u_C4R, 464
- image_xorc
 - nppiXorC_16u_AC4IR, 393
 - nppiXorC_16u_AC4R, 393
 - nppiXorC_16u_C1IR, 393
 - nppiXorC_16u_C1R, 394
 - nppiXorC_16u_C3IR, 394
 - nppiXorC_16u_C3R, 394
 - nppiXorC_16u_C4IR, 395
 - nppiXorC_16u_C4R, 395
 - nppiXorC_32s_AC4IR, 395
 - nppiXorC_32s_AC4R, 396
 - nppiXorC_32s_C1IR, 396
 - nppiXorC_32s_C1R, 396
 - nppiXorC_32s_C3IR, 397
 - nppiXorC_32s_C3R, 397
 - nppiXorC_32s_C4IR, 397
 - nppiXorC_32s_C4R, 398
 - nppiXorC_8u_AC4IR, 398
 - nppiXorC_8u_AC4R, 398
 - nppiXorC_8u_C1IR, 399
 - nppiXorC_8u_C1R, 399
 - nppiXorC_8u_C3IR, 399
 - nppiXorC_8u_C3R, 400
 - nppiXorC_8u_C4IR, 400
 - nppiXorC_8u_C4R, 400
- Ln, 354
- Logical Operations, 368
- LShiftC, 419
- major
 - NppLibraryVersion, 504
- minor
 - NppLibraryVersion, 504
- Mul, 206
- MulC, 79
- MulCScale, 105
- MulScale, 235
- Not, 466
- NPP Core, 27
- NPP Type Definitions and Constants, 31
- Npp16s
 - npp_basic_types, 47
- Npp16sc
 - npp_basic_types, 49
- Npp16u
 - npp_basic_types, 47
- Npp16uc
 - npp_basic_types, 49
- Npp32f
 - npp_basic_types, 47
- Npp32fc
 - npp_basic_types, 47
- Npp32s
 - npp_basic_types, 47
- Npp32sc
 - npp_basic_types, 47
- Npp32u
 - npp_basic_types, 48
- Npp32uc
 - npp_basic_types, 48
- Npp64f
 - npp_basic_types, 48
- Npp64fc
 - npp_basic_types, 48
- Npp64s
 - npp_basic_types, 48
- Npp64sc
 - npp_basic_types, 48
- Npp64u
 - npp_basic_types, 48
- Npp8s
 - npp_basic_types, 48
- Npp8u
 - npp_basic_types, 48
- Npp8uc
 - npp_basic_types, 49
- NPP_AFFINE_QUAD_INCORRECT_WARNING
 - typedefs_npp, 44
- NPP_ALG_HINT_ACCURATE
 - typedefs_npp, 39
- NPP_ALG_HINT_FAST
 - typedefs_npp, 39
- NPP_ALG_HINT_NONE
 - typedefs_npp, 39
- NPP_ALIGNMENT_ERROR
 - typedefs_npp, 43

- NPP_ANCHOR_ERROR
typedefs_npp, 43
- NPP_BAD_ARGUMENT_ERROR
typedefs_npp, 44
- NPP_BORDER_CONSTANT
typedefs_npp, 40
- NPP_BORDER_MIRROR
typedefs_npp, 40
- NPP_BORDER_NONE
typedefs_npp, 40
- NPP_BORDER_REPLICATE
typedefs_npp, 40
- NPP_BORDER_UNDEFINED
typedefs_npp, 40
- NPP_BORDER_WRAP
typedefs_npp, 40
- NPP_BOTH_AXIS
typedefs_npp, 40
- NPP_CHANNEL_ERROR
typedefs_npp, 43
- NPP_CHANNEL_ORDER_ERROR
typedefs_npp, 43
- NPP_CMP_EQ
typedefs_npp, 39
- NPP_CMP_GREATER
typedefs_npp, 39
- NPP_CMP_GREATER_EQ
typedefs_npp, 39
- NPP_CMP_LESS
typedefs_npp, 38
- NPP_CMP_LESS_EQ
typedefs_npp, 38
- NPP_COEFFICIENT_ERROR
typedefs_npp, 43
- NPP_COI_ERROR
typedefs_npp, 43
- NPP_CONTEXT_MATCH_ERROR
typedefs_npp, 44
- NPP_CORRUPTED_DATA_ERROR
typedefs_npp, 43
- NPP_CUDA_1_0
typedefs_npp, 39
- NPP_CUDA_1_1
typedefs_npp, 39
- NPP_CUDA_1_2
typedefs_npp, 39
- NPP_CUDA_1_3
typedefs_npp, 39
- NPP_CUDA_2_0
typedefs_npp, 39
- NPP_CUDA_2_1
typedefs_npp, 39
- NPP_CUDA_3_0
typedefs_npp, 39
- NPP_CUDA_3_2
typedefs_npp, 39
- NPP_CUDA_3_5
typedefs_npp, 39
- NPP_CUDA_3_7
typedefs_npp, 39
- NPP_CUDA_5_0
typedefs_npp, 39
- NPP_CUDA_5_2
typedefs_npp, 39
- NPP_CUDA_5_3
typedefs_npp, 39
- NPP_CUDA_6_0
typedefs_npp, 39
- NPP_CUDA_KERNEL_EXECUTION_ERROR
typedefs_npp, 43
- NPP_CUDA_NOT_CAPABLE
typedefs_npp, 39
- NPP_CUDA_UNKNOWN_VERSION
typedefs_npp, 39
- NPP_DATA_TYPE_ERROR
typedefs_npp, 44
- NPP_DIVIDE_BY_ZERO_ERROR
typedefs_npp, 44
- NPP_DIVIDE_BY_ZERO_WARNING
typedefs_npp, 44
- NPP_DIVISOR_ERROR
typedefs_npp, 43
- NPP_DOUBLE_SIZE_WARNING
typedefs_npp, 44
- NPP_ERROR
typedefs_npp, 44
- NPP_ERROR_RESERVED
typedefs_npp, 44
- NPP_FFT_FLAG_ERROR
typedefs_npp, 44
- NPP_FFT_ORDER_ERROR
typedefs_npp, 44
- NPP_FILTER_SCHARR
typedefs_npp, 40
- NPP_FILTER_SOBEL
typedefs_npp, 40
- NPP_HAAR_CLASSIFIER_PIXEL_MATCH_-
ERROR
typedefs_npp, 43
- NPP_HISTOGRAM_NUMBER_OF_LEVELS_-
ERROR
typedefs_npp, 43
- NPP_HORIZONTAL_AXIS
typedefs_npp, 40
- NPP_INTERPOLATION_ERROR
typedefs_npp, 44
- NPP_INVALID_DEVICE_POINTER_ERROR
typedefs_npp, 43

- NPP_INVALID_HOST_POINTER_ERROR
typedefs_npp, 43
- NPP_LUT_NUMBER_OF_LEVELS_ERROR
typedefs_npp, 43
- NPP_LUT_PALETTE_BITSIZE_ERROR
typedefs_npp, 43
- NPP_MASK_SIZE_11_X_11
typedefs_npp, 41
- NPP_MASK_SIZE_13_X_13
typedefs_npp, 41
- NPP_MASK_SIZE_15_X_15
typedefs_npp, 41
- NPP_MASK_SIZE_1_X_3
typedefs_npp, 41
- NPP_MASK_SIZE_1_X_5
typedefs_npp, 41
- NPP_MASK_SIZE_3_X_1
typedefs_npp, 41
- NPP_MASK_SIZE_3_X_3
typedefs_npp, 41
- NPP_MASK_SIZE_5_X_1
typedefs_npp, 41
- NPP_MASK_SIZE_5_X_5
typedefs_npp, 41
- NPP_MASK_SIZE_7_X_7
typedefs_npp, 41
- NPP_MASK_SIZE_9_X_9
typedefs_npp, 41
- NPP_MASK_SIZE_ERROR
typedefs_npp, 43
- NPP_MEMCPY_ERROR
typedefs_npp, 43
- NPP_MEMFREE_ERROR
typedefs_npp, 43
- NPP_MEMORY_ALLOCATION_ERR
typedefs_npp, 44
- NPP_MEMSET_ERROR
typedefs_npp, 43
- NPP_MIRROR_FLIP_ERROR
typedefs_npp, 44
- NPP_MISALIGNED_DST_ROI_WARNING
typedefs_npp, 44
- NPP_MOMENT_00_ZERO_ERROR
typedefs_npp, 44
- NPP_NO_ERROR
typedefs_npp, 44
- NPP_NO_MEMORY_ERROR
typedefs_npp, 44
- NPP_NO_OPERATION_WARNING
typedefs_npp, 44
- NPP_NOT_EVEN_STEP_ERROR
typedefs_npp, 43
- NPP_NOT_IMPLEMENTED_ERROR
typedefs_npp, 44
- NPP_NOT_SUFFICIENT_COMPUTE_-
CAPABILITY
typedefs_npp, 43
- NPP_NOT_SUPPORTED_MODE_ERROR
typedefs_npp, 43
- NPP_NULL_POINTER_ERROR
typedefs_npp, 44
- NPP_NUMBER_OF_CHANNELS_ERROR
typedefs_npp, 43
- NPP_OUT_OFF_RANGE_ERROR
typedefs_npp, 44
- NPP_OVERFLOW_ERROR
typedefs_npp, 43
- NPP_QUADRANGLE_ERROR
typedefs_npp, 43
- NPP_QUALITY_INDEX_ERROR
typedefs_npp, 43
- NPP_RANGE_ERROR
typedefs_npp, 44
- NPP_RECTANGLE_ERROR
typedefs_npp, 43
- NPP_RESIZE_FACTOR_ERROR
typedefs_npp, 44
- NPP_RESIZE_NO_OPERATION_ERROR
typedefs_npp, 43
- NPP_RND_FINANCIAL
typedefs_npp, 42
- NPP_RND_NEAR
typedefs_npp, 42
- NPP_RND_ZERO
typedefs_npp, 42
- NPP_ROUND_MODE_NOT_SUPPORTED_-
ERROR
typedefs_npp, 43
- NPP_ROUND_NEAREST_TIES_AWAY_-
FROM_ZERO
typedefs_npp, 42
- NPP_ROUND_NEAREST_TIES_TO_EVEN
typedefs_npp, 42
- NPP_ROUND_TOWARD_ZERO
typedefs_npp, 42
- NPP_SCALE_RANGE_ERROR
typedefs_npp, 44
- NPP_SIZE_ERROR
typedefs_npp, 44
- NPP_STEP_ERROR
typedefs_npp, 44
- NPP_STRIDE_ERROR
typedefs_npp, 43
- NPP_SUCCESS
typedefs_npp, 44
- NPP_TEXTURE_BIND_ERROR
typedefs_npp, 43
- NPP_THRESHOLD_ERROR

- typedefs_npp, 44
- NPP_THRESHOLD_NEGATIVE_LEVEL_-
ERROR
typedefs_npp, 44
- NPP_VERTICAL_AXIS
typedefs_npp, 40
- NPP_WRONG_INTERSECTION_QUAD_-
WARNING
typedefs_npp, 44
- NPP_WRONG_INTERSECTION_ROI_ERROR
typedefs_npp, 43
- NPP_WRONG_INTERSECTION_ROI_-
WARNING
typedefs_npp, 44
- NPP_ZC_MODE_NOT_SUPPORTED_ERROR
typedefs_npp, 43
- NPP_ZERO_MASK_VALUE_ERROR
typedefs_npp, 43
- NPP_ALIGN_16, 495
im, 495
re, 496
- NPP_ALIGN_8, 497
im, 497
re, 497, 498
- npp_basic_types
__align__, 48, 49
Npp16s, 47
Npp16sc, 49
Npp16u, 47
Npp16uc, 49
Npp32f, 47
Npp32fc, 47
Npp32s, 47
Npp32sc, 47
Npp32u, 48
Npp32uc, 48
Npp64f, 48
Npp64fc, 48
Npp64s, 48
Npp64sc, 48
Npp64u, 48
Npp8s, 48
Npp8u, 48
Npp8uc, 49
- NPP_MAX_16S
typedefs_npp, 37
- NPP_MAX_16U
typedefs_npp, 37
- NPP_MAX_32S
typedefs_npp, 37
- NPP_MAX_32U
typedefs_npp, 37
- NPP_MAX_64S
typedefs_npp, 37
- NPP_MAX_64U
typedefs_npp, 37
- NPP_MAX_8S
typedefs_npp, 37
- NPP_MAX_8U
typedefs_npp, 37
- NPP_MAXABS_32F
typedefs_npp, 37
- NPP_MAXABS_64F
typedefs_npp, 37
- NPP_MIN_16S
typedefs_npp, 37
- NPP_MIN_16U
typedefs_npp, 38
- NPP_MIN_32S
typedefs_npp, 38
- NPP_MIN_32U
typedefs_npp, 38
- NPP_MIN_64S
typedefs_npp, 38
- NPP_MIN_64U
typedefs_npp, 38
- NPP_MIN_8S
typedefs_npp, 38
- NPP_MIN_8U
typedefs_npp, 38
- NPP_MINABS_32F
typedefs_npp, 38
- NPP_MINABS_64F
typedefs_npp, 38
- NppCmpOp
typedefs_npp, 38
- nppGetGpuComputeCapability
core_npp, 28
- nppGetGpuDeviceProperties
core_npp, 28
- nppGetGpuName
core_npp, 28
- nppGetGpuNumSMs
core_npp, 28
- nppGetLibVersion
core_npp, 28
- nppGetMaxThreadsPerBlock
core_npp, 29
- nppGetMaxThreadsPerSM
core_npp, 29
- nppGetStream
core_npp, 29
- nppGetStreamMaxThreadsPerSM
core_npp, 29
- nppGetStreamNumSMs
core_npp, 29
- NppGpuComputeCapability
typedefs_npp, 39

- NppHintAlgorithm
 - typedefs_npp, 39
- NPPI_BAYER_BGGR
 - typedefs_npp, 40
- NPPI_BAYER_GBRG
 - typedefs_npp, 40
- NPPI_BAYER_GRBG
 - typedefs_npp, 40
- NPPI_BAYER_RGGB
 - typedefs_npp, 40
- NPPI_INTER_CUBIC
 - typedefs_npp, 41
- NPPI_INTER_CUBIC2P_B05C03
 - typedefs_npp, 41
- NPPI_INTER_CUBIC2P_BSPLINE
 - typedefs_npp, 41
- NPPI_INTER_CUBIC2P_CATMULLROM
 - typedefs_npp, 41
- NPPI_INTER_LANCZOS
 - typedefs_npp, 41
- NPPI_INTER_LANCZOS3_ADVANCED
 - typedefs_npp, 41
- NPPI_INTER_LINEAR
 - typedefs_npp, 41
- NPPI_INTER_NN
 - typedefs_npp, 41
- NPPI_INTER_SUPER
 - typedefs_npp, 41
- NPPI_INTER_UNDEFINED
 - typedefs_npp, 41
- NPPI_OP_ALPHA_ATOP
 - typedefs_npp, 39
- NPPI_OP_ALPHA_ATOP_PREMUL
 - typedefs_npp, 40
- NPPI_OP_ALPHA_IN
 - typedefs_npp, 39
- NPPI_OP_ALPHA_IN_PREMUL
 - typedefs_npp, 40
- NPPI_OP_ALPHA_OUT
 - typedefs_npp, 39
- NPPI_OP_ALPHA_OUT_PREMUL
 - typedefs_npp, 40
- NPPI_OP_ALPHA_OVER
 - typedefs_npp, 39
- NPPI_OP_ALPHA_OVER_PREMUL
 - typedefs_npp, 40
- NPPI_OP_ALPHA_PLUS
 - typedefs_npp, 39
- NPPI_OP_ALPHA_PLUS_PREMUL
 - typedefs_npp, 40
- NPPI_OP_ALPHA_PREMUL
 - typedefs_npp, 40
- NPPI_OP_ALPHA_XOR
 - typedefs_npp, 39
- NPPI_OP_ALPHA_XOR_PREMUL
 - typedefs_npp, 40
- NPPI_SMOOTH_EDGE
 - typedefs_npp, 41
- nppiAbs_16s_AC4IR
 - image_abs, 319
- nppiAbs_16s_AC4R
 - image_abs, 319
- nppiAbs_16s_C1IR
 - image_abs, 319
- nppiAbs_16s_C1R
 - image_abs, 320
- nppiAbs_16s_C3IR
 - image_abs, 320
- nppiAbs_16s_C3R
 - image_abs, 320
- nppiAbs_16s_C4IR
 - image_abs, 321
- nppiAbs_16s_C4R
 - image_abs, 321
- nppiAbs_32f_AC4IR
 - image_abs, 321
- nppiAbs_32f_AC4R
 - image_abs, 322
- nppiAbs_32f_C1IR
 - image_abs, 322
- nppiAbs_32f_C1R
 - image_abs, 322
- nppiAbs_32f_C3IR
 - image_abs, 323
- nppiAbs_32f_C3R
 - image_abs, 323
- nppiAbs_32f_C4IR
 - image_abs, 323
- nppiAbs_32f_C4R
 - image_abs, 324
- nppiAbsDiff_16u_C1R
 - image_absdiff, 325
- nppiAbsDiff_32f_C1R
 - image_absdiff, 326
- nppiAbsDiff_8u_C1R
 - image_absdiff, 326
- nppiAbsDiff_8u_C3R
 - image_absdiff, 326
- nppiAbsDiff_8u_C4R
 - image_absdiff, 327
- nppiAbsDiffC_16u_C1R
 - image_absdiffc, 164
- nppiAbsDiffC_32f_C1R
 - image_absdiffc, 164
- nppiAbsDiffC_8u_C1R
 - image_absdiffc, 165
- nppiACTable
 - typedefs_npp, 41

- nppiAdd_16s_AC4IRSfs
image_add, 171
- nppiAdd_16s_AC4RSfs
image_add, 171
- nppiAdd_16s_C1IRSfs
image_add, 172
- nppiAdd_16s_C1RSfs
image_add, 172
- nppiAdd_16s_C3IRSfs
image_add, 173
- nppiAdd_16s_C3RSfs
image_add, 173
- nppiAdd_16s_C4IRSfs
image_add, 173
- nppiAdd_16s_C4RSfs
image_add, 174
- nppiAdd_16sc_AC4IRSfs
image_add, 174
- nppiAdd_16sc_AC4RSfs
image_add, 175
- nppiAdd_16sc_C1IRSfs
image_add, 175
- nppiAdd_16sc_C1RSfs
image_add, 175
- nppiAdd_16sc_C3IRSfs
image_add, 176
- nppiAdd_16sc_C3RSfs
image_add, 176
- nppiAdd_16u_AC4IRSfs
image_add, 177
- nppiAdd_16u_AC4RSfs
image_add, 177
- nppiAdd_16u_C1IRSfs
image_add, 178
- nppiAdd_16u_C1RSfs
image_add, 178
- nppiAdd_16u_C3IRSfs
image_add, 178
- nppiAdd_16u_C3RSfs
image_add, 179
- nppiAdd_16u_C4IRSfs
image_add, 179
- nppiAdd_16u_C4RSfs
image_add, 180
- nppiAdd_32f_AC4IR
image_add, 180
- nppiAdd_32f_AC4R
image_add, 180
- nppiAdd_32f_C1IR
image_add, 181
- nppiAdd_32f_C1R
image_add, 181
- nppiAdd_32f_C3IR
image_add, 182
- nppiAdd_32f_C3R
image_add, 182
- nppiAdd_32f_C4IR
image_add, 182
- nppiAdd_32f_C4R
image_add, 183
- nppiAdd_32fc_AC4IR
image_add, 183
- nppiAdd_32fc_AC4R
image_add, 183
- nppiAdd_32fc_C1IR
image_add, 184
- nppiAdd_32fc_C1R
image_add, 184
- nppiAdd_32fc_C3IR
image_add, 185
- nppiAdd_32fc_C3R
image_add, 185
- nppiAdd_32fc_C4IR
image_add, 185
- nppiAdd_32fc_C4R
image_add, 186
- nppiAdd_32s_C1IRSfs
image_add, 186
- nppiAdd_32s_C1R
image_add, 187
- nppiAdd_32s_C1RSfs
image_add, 187
- nppiAdd_32s_C3IRSfs
image_add, 187
- nppiAdd_32s_C3RSfs
image_add, 188
- nppiAdd_32sc_AC4IRSfs
image_add, 188
- nppiAdd_32sc_AC4RSfs
image_add, 189
- nppiAdd_32sc_C1IRSfs
image_add, 189
- nppiAdd_32sc_C1RSfs
image_add, 189
- nppiAdd_32sc_C3IRSfs
image_add, 190
- nppiAdd_32sc_C3RSfs
image_add, 190
- nppiAdd_8u_AC4IRSfs
image_add, 191
- nppiAdd_8u_AC4RSfs
image_add, 191
- nppiAdd_8u_C1IRSfs
image_add, 192
- nppiAdd_8u_C1RSfs
image_add, 192
- nppiAdd_8u_C3IRSfs
image_add, 192

- nppiAdd_8u_C3RSfs
 image_add, 193
- nppiAdd_8u_C4IRSfs
 image_add, 193
- nppiAdd_8u_C4RSfs
 image_add, 194
- nppiAddC_16s_AC4IRSfs
 image_addc, 58
- nppiAddC_16s_AC4RSfs
 image_addc, 58
- nppiAddC_16s_C1IRSfs
 image_addc, 58
- nppiAddC_16s_C1RSfs
 image_addc, 59
- nppiAddC_16s_C3IRSfs
 image_addc, 59
- nppiAddC_16s_C3RSfs
 image_addc, 59
- nppiAddC_16s_C4IRSfs
 image_addc, 60
- nppiAddC_16s_C4RSfs
 image_addc, 60
- nppiAddC_16sc_AC4IRSfs
 image_addc, 61
- nppiAddC_16sc_AC4RSfs
 image_addc, 61
- nppiAddC_16sc_C1IRSfs
 image_addc, 61
- nppiAddC_16sc_C1RSfs
 image_addc, 62
- nppiAddC_16sc_C3IRSfs
 image_addc, 62
- nppiAddC_16sc_C3RSfs
 image_addc, 63
- nppiAddC_16u_AC4IRSfs
 image_addc, 63
- nppiAddC_16u_AC4RSfs
 image_addc, 63
- nppiAddC_16u_C1IRSfs
 image_addc, 64
- nppiAddC_16u_C1RSfs
 image_addc, 64
- nppiAddC_16u_C3IRSfs
 image_addc, 65
- nppiAddC_16u_C3RSfs
 image_addc, 65
- nppiAddC_16u_C4IRSfs
 image_addc, 65
- nppiAddC_16u_C4RSfs
 image_addc, 66
- nppiAddC_32f_AC4IR
 image_addc, 66
- nppiAddC_32f_AC4R
 image_addc, 66
- nppiAddC_32f_C1IR
 image_addc, 67
- nppiAddC_32f_C1R
 image_addc, 67
- nppiAddC_32f_C3IR
 image_addc, 67
- nppiAddC_32f_C3R
 image_addc, 68
- nppiAddC_32f_C4IR
 image_addc, 68
- nppiAddC_32f_C4R
 image_addc, 68
- nppiAddC_32fc_AC4IR
 image_addc, 69
- nppiAddC_32fc_AC4R
 image_addc, 69
- nppiAddC_32fc_C1IR
 image_addc, 69
- nppiAddC_32fc_C1R
 image_addc, 70
- nppiAddC_32fc_C3IR
 image_addc, 70
- nppiAddC_32fc_C3R
 image_addc, 70
- nppiAddC_32fc_C4IR
 image_addc, 71
- nppiAddC_32fc_C4R
 image_addc, 71
- nppiAddC_32s_C1IRSfs
 image_addc, 72
- nppiAddC_32s_C1RSfs
 image_addc, 72
- nppiAddC_32s_C3IRSfs
 image_addc, 72
- nppiAddC_32s_C3RSfs
 image_addc, 73
- nppiAddC_32sc_AC4IRSfs
 image_addc, 73
- nppiAddC_32sc_AC4RSfs
 image_addc, 73
- nppiAddC_32sc_C1IRSfs
 image_addc, 74
- nppiAddC_32sc_C1RSfs
 image_addc, 74
- nppiAddC_32sc_C3IRSfs
 image_addc, 75
- nppiAddC_32sc_C3RSfs
 image_addc, 75
- nppiAddC_8u_AC4IRSfs
 image_addc, 75
- nppiAddC_8u_AC4RSfs
 image_addc, 76
- nppiAddC_8u_C1IRSfs
 image_addc, 76

- nppiAddC_8u_C1RSfs
 image_addc, [77](#)
- nppiAddC_8u_C3RSfs
 image_addc, [77](#)
- nppiAddC_8u_C3RSfs
 image_addc, [77](#)
- nppiAddC_8u_C4RSfs
 image_addc, [78](#)
- nppiAddC_8u_C4RSfs
 image_addc, [78](#)
- nppiAddProduct_16u32f_C1IMR
 image_addproduct, [198](#)
- nppiAddProduct_16u32f_C1IR
 image_addproduct, [199](#)
- nppiAddProduct_32f_C1IMR
 image_addproduct, [199](#)
- nppiAddProduct_32f_C1IR
 image_addproduct, [200](#)
- nppiAddProduct_8u32f_C1IMR
 image_addproduct, [200](#)
- nppiAddProduct_8u32f_C1IR
 image_addproduct, [200](#)
- nppiAddProduct_8u32f_C1IR
 image_addproduct, [200](#)
- nppiAddSquare_16u32f_C1IMR
 image_addsquare, [195](#)
- nppiAddSquare_16u32f_C1IR
 image_addsquare, [196](#)
- nppiAddSquare_32f_C1IMR
 image_addsquare, [196](#)
- nppiAddSquare_32f_C1IR
 image_addsquare, [196](#)
- nppiAddSquare_8u32f_C1IMR
 image_addsquare, [197](#)
- nppiAddSquare_8u32f_C1IR
 image_addsquare, [197](#)
- nppiAddWeighted_16u32f_C1IMR
 image_addweighted, [202](#)
- nppiAddWeighted_16u32f_C1IR
 image_addweighted, [203](#)
- nppiAddWeighted_32f_C1IMR
 image_addweighted, [203](#)
- nppiAddWeighted_32f_C1IR
 image_addweighted, [204](#)
- nppiAddWeighted_8u32f_C1IMR
 image_addweighted, [204](#)
- nppiAddWeighted_8u32f_C1IR
 image_addweighted, [204](#)
- nppiAlphaComp_16s_AC1R
 image_alphacomp, [487](#)
- nppiAlphaComp_16u_AC1R
 image_alphacomp, [487](#)
- nppiAlphaComp_16u_AC4R
 image_alphacomp, [488](#)
- nppiAlphaComp_32f_AC1R
 image_alphacomp, [488](#)
- nppiAlphaComp_32f_AC4R
 image_alphacomp, [489](#)
- nppiAlphaComp_32s_AC1R
 image_alphacomp, [489](#)
- nppiAlphaComp_32s_AC4R
 image_alphacomp, [489](#)
- nppiAlphaComp_32u_AC1R
 image_alphacomp, [490](#)
- nppiAlphaComp_32u_AC4R
 image_alphacomp, [490](#)
- nppiAlphaComp_8s_AC1R
 image_alphacomp, [491](#)
- nppiAlphaComp_8u_AC1R
 image_alphacomp, [491](#)
- nppiAlphaComp_8u_AC4R
 image_alphacomp, [492](#)
- nppiAlphaCompC_16s_C1R
 image_alphacompc, [472](#)
- nppiAlphaCompC_16u_AC4R
 image_alphacompc, [472](#)
- nppiAlphaCompC_16u_C1R
 image_alphacompc, [473](#)
- nppiAlphaCompC_16u_C3R
 image_alphacompc, [473](#)
- nppiAlphaCompC_16u_C4R
 image_alphacompc, [474](#)
- nppiAlphaCompC_32f_C1R
 image_alphacompc, [474](#)
- nppiAlphaCompC_32s_C1R
 image_alphacompc, [475](#)
- nppiAlphaCompC_32u_C1R
 image_alphacompc, [475](#)
- nppiAlphaCompC_8s_C1R
 image_alphacompc, [476](#)
- nppiAlphaCompC_8u_AC4R
 image_alphacompc, [476](#)
- nppiAlphaCompC_8u_C1R
 image_alphacompc, [477](#)
- nppiAlphaCompC_8u_C3R
 image_alphacompc, [477](#)
- nppiAlphaCompC_8u_C4R
 image_alphacompc, [478](#)
- NppiAlphaOp
 typedefs_npp, [39](#)
- nppiAlphaPremul_16u_AC4IR
 image_alphapremul, [493](#)
- nppiAlphaPremul_16u_AC4R
 image_alphapremul, [493](#)
- nppiAlphaPremul_8u_AC4IR
 image_alphapremul, [494](#)
- nppiAlphaPremul_8u_AC4R
 image_alphapremul, [494](#)
- nppiAlphaPremulC_16u_AC4IR
 image_alphapremulc, [480](#)

- nppiAlphaPremulC_16u_AC4R
 image_alphapremulc, 480
- nppiAlphaPremulC_16u_C1IR
 image_alphapremulc, 481
- nppiAlphaPremulC_16u_C1R
 image_alphapremulc, 481
- nppiAlphaPremulC_16u_C3IR
 image_alphapremulc, 481
- nppiAlphaPremulC_16u_C3R
 image_alphapremulc, 482
- nppiAlphaPremulC_16u_C4IR
 image_alphapremulc, 482
- nppiAlphaPremulC_16u_C4R
 image_alphapremulc, 482
- nppiAlphaPremulC_8u_AC4IR
 image_alphapremulc, 483
- nppiAlphaPremulC_8u_AC4R
 image_alphapremulc, 483
- nppiAlphaPremulC_8u_C1IR
 image_alphapremulc, 483
- nppiAlphaPremulC_8u_C1R
 image_alphapremulc, 484
- nppiAlphaPremulC_8u_C3IR
 image_alphapremulc, 484
- nppiAlphaPremulC_8u_C3R
 image_alphapremulc, 484
- nppiAlphaPremulC_8u_C4IR
 image_alphapremulc, 485
- nppiAlphaPremulC_8u_C4R
 image_alphapremulc, 485
- nppiAnd_16u_AC4IR
 image_and, 432
- nppiAnd_16u_AC4R
 image_and, 432
- nppiAnd_16u_C1IR
 image_and, 432
- nppiAnd_16u_C1R
 image_and, 433
- nppiAnd_16u_C3IR
 image_and, 433
- nppiAnd_16u_C3R
 image_and, 433
- nppiAnd_16u_C4IR
 image_and, 434
- nppiAnd_16u_C4R
 image_and, 434
- nppiAnd_32s_AC4IR
 image_and, 435
- nppiAnd_32s_AC4R
 image_and, 435
- nppiAnd_32s_C1IR
 image_and, 435
- nppiAnd_32s_C1R
 image_and, 436
- nppiAnd_32s_C3IR
 image_and, 436
- nppiAnd_32s_C3R
 image_and, 436
- nppiAnd_32s_C4IR
 image_and, 437
- nppiAnd_32s_C4R
 image_and, 437
- nppiAnd_8u_AC4IR
 image_and, 438
- nppiAnd_8u_AC4R
 image_and, 438
- nppiAnd_8u_C1IR
 image_and, 438
- nppiAnd_8u_C1R
 image_and, 439
- nppiAnd_8u_C3IR
 image_and, 439
- nppiAnd_8u_C3R
 image_and, 439
- nppiAnd_8u_C4IR
 image_and, 440
- nppiAnd_8u_C4R
 image_and, 440
- nppiAndC_16u_AC4IR
 image_andc, 371
- nppiAndC_16u_AC4R
 image_andc, 371
- nppiAndC_16u_C1IR
 image_andc, 371
- nppiAndC_16u_C1R
 image_andc, 372
- nppiAndC_16u_C3IR
 image_andc, 372
- nppiAndC_16u_C3R
 image_andc, 372
- nppiAndC_16u_C4IR
 image_andc, 373
- nppiAndC_16u_C4R
 image_andc, 373
- nppiAndC_32s_AC4IR
 image_andc, 373
- nppiAndC_32s_AC4R
 image_andc, 374
- nppiAndC_32s_C1IR
 image_andc, 374
- nppiAndC_32s_C1R
 image_andc, 374
- nppiAndC_32s_C3IR
 image_andc, 375
- nppiAndC_32s_C3R
 image_andc, 375
- nppiAndC_32s_C4IR
 image_andc, 375

- nppiAndC_32s_C4R
 - image_andc, 376
- nppiAndC_8u_AC4IR
 - image_andc, 376
- nppiAndC_8u_AC4R
 - image_andc, 376
- nppiAndC_8u_C1IR
 - image_andc, 377
- nppiAndC_8u_C1R
 - image_andc, 377
- nppiAndC_8u_C3IR
 - image_andc, 377
- nppiAndC_8u_C3R
 - image_andc, 378
- nppiAndC_8u_C4IR
 - image_andc, 378
- nppiAndC_8u_C4R
 - image_andc, 378
- NppiAxis
 - typedefs_npp, 40
- NppiBayerGridPosition
 - typedefs_npp, 40
- NppiBorderType
 - typedefs_npp, 40
- nppiDCTable
 - typedefs_npp, 41
- NppiDifferentialKernel
 - typedefs_npp, 40
- nppiDiv_16s_AC4IRSfs
 - image_div, 279
- nppiDiv_16s_AC4RSfs
 - image_div, 279
- nppiDiv_16s_C1IRSfs
 - image_div, 280
- nppiDiv_16s_C1RSfs
 - image_div, 280
- nppiDiv_16s_C3IRSfs
 - image_div, 280
- nppiDiv_16s_C3RSfs
 - image_div, 281
- nppiDiv_16s_C4IRSfs
 - image_div, 281
- nppiDiv_16s_C4RSfs
 - image_div, 282
- nppiDiv_16sc_AC4IRSfs
 - image_div, 282
- nppiDiv_16sc_AC4RSfs
 - image_div, 282
- nppiDiv_16sc_C1IRSfs
 - image_div, 283
- nppiDiv_16sc_C1RSfs
 - image_div, 283
- nppiDiv_16sc_C3IRSfs
 - image_div, 284
- nppiDiv_16sc_C3RSfs
 - image_div, 284
- nppiDiv_16sc_C4IRSfs
 - image_div, 284
- nppiDiv_16u_AC4IRSfs
 - image_div, 285
- nppiDiv_16u_AC4RSfs
 - image_div, 285
- nppiDiv_16u_C1IRSfs
 - image_div, 285
- nppiDiv_16u_C1RSfs
 - image_div, 286
- nppiDiv_16u_C3IRSfs
 - image_div, 286
- nppiDiv_16u_C3RSfs
 - image_div, 287
- nppiDiv_16u_C4IRSfs
 - image_div, 287
- nppiDiv_16u_C4RSfs
 - image_div, 287
- nppiDiv_32f_AC4IR
 - image_div, 288
- nppiDiv_32f_AC4R
 - image_div, 288
- nppiDiv_32f_C1IR
 - image_div, 289
- nppiDiv_32f_C1R
 - image_div, 289
- nppiDiv_32f_C3IR
 - image_div, 289
- nppiDiv_32f_C3R
 - image_div, 290
- nppiDiv_32f_C4IR
 - image_div, 290
- nppiDiv_32f_C4R
 - image_div, 290
- nppiDiv_32fc_AC4IR
 - image_div, 291
- nppiDiv_32fc_AC4R
 - image_div, 291
- nppiDiv_32fc_C1IR
 - image_div, 292
- nppiDiv_32fc_C1R
 - image_div, 292
- nppiDiv_32fc_C3IR
 - image_div, 292
- nppiDiv_32fc_C3R
 - image_div, 293
- nppiDiv_32fc_C4IR
 - image_div, 293
- nppiDiv_32fc_C4R
 - image_div, 293
- nppiDiv_32s_C1IRSfs
 - image_div, 294
- nppiDiv_32s_C1R
 - image_div, 294

- nppiDiv_32s_C1RSfs
 image_div, 295
- nppiDiv_32s_C3IRSfs
 image_div, 295
- nppiDiv_32s_C3RSfs
 image_div, 295
- nppiDiv_32sc_AC4IRSfs
 image_div, 296
- nppiDiv_32sc_AC4RSfs
 image_div, 296
- nppiDiv_32sc_C1IRSfs
 image_div, 297
- nppiDiv_32sc_C1RSfs
 image_div, 297
- nppiDiv_32sc_C3IRSfs
 image_div, 298
- nppiDiv_32sc_C3RSfs
 image_div, 298
- nppiDiv_8u_AC4IRSfs
 image_div, 298
- nppiDiv_8u_AC4RSfs
 image_div, 299
- nppiDiv_8u_C1IRSfs
 image_div, 299
- nppiDiv_8u_C1RSfs
 image_div, 300
- nppiDiv_8u_C3IRSfs
 image_div, 300
- nppiDiv_8u_C3RSfs
 image_div, 300
- nppiDiv_8u_C4IRSfs
 image_div, 301
- nppiDiv_8u_C4RSfs
 image_div, 301
- nppiDiv_Round_16s_AC4IRSfs
 image_divround, 305
- nppiDiv_Round_16s_AC4RSfs
 image_divround, 306
- nppiDiv_Round_16s_C1IRSfs
 image_divround, 306
- nppiDiv_Round_16s_C1RSfs
 image_divround, 307
- nppiDiv_Round_16s_C3IRSfs
 image_divround, 307
- nppiDiv_Round_16s_C3RSfs
 image_divround, 307
- nppiDiv_Round_16s_C4IRSfs
 image_divround, 308
- nppiDiv_Round_16s_C4RSfs
 image_divround, 308
- nppiDiv_Round_16u_AC4IRSfs
 image_divround, 309
- nppiDiv_Round_16u_AC4RSfs
 image_divround, 309
- nppiDiv_Round_16u_C1IRSfs
 image_divround, 310
- nppiDiv_Round_16u_C1RSfs
 image_divround, 310
- nppiDiv_Round_16u_C3IRSfs
 image_divround, 311
- nppiDiv_Round_16u_C3RSfs
 image_divround, 311
- nppiDiv_Round_16u_C4IRSfs
 image_divround, 312
- nppiDiv_Round_16u_C4RSfs
 image_divround, 312
- nppiDiv_Round_8u_AC4IRSfs
 image_divround, 313
- nppiDiv_Round_8u_AC4RSfs
 image_divround, 313
- nppiDiv_Round_8u_C1IRSfs
 image_divround, 314
- nppiDiv_Round_8u_C1RSfs
 image_divround, 314
- nppiDiv_Round_8u_C3IRSfs
 image_divround, 315
- nppiDiv_Round_8u_C3RSfs
 image_divround, 315
- nppiDiv_Round_8u_C4IRSfs
 image_divround, 316
- nppiDiv_Round_8u_C4RSfs
 image_divround, 316
- nppiDivC_16s_AC4IRSfs
 image_divc, 143
- nppiDivC_16s_AC4RSfs
 image_divc, 143
- nppiDivC_16s_C1IRSfs
 image_divc, 143
- nppiDivC_16s_C1RSfs
 image_divc, 144
- nppiDivC_16s_C3IRSfs
 image_divc, 144
- nppiDivC_16s_C3RSfs
 image_divc, 144
- nppiDivC_16s_C4IRSfs
 image_divc, 145
- nppiDivC_16s_C4RSfs
 image_divc, 145
- nppiDivC_16sc_AC4IRSfs
 image_divc, 146
- nppiDivC_16sc_AC4RSfs
 image_divc, 146
- nppiDivC_16sc_C1IRSfs
 image_divc, 146
- nppiDivC_16sc_C1RSfs
 image_divc, 147
- nppiDivC_16sc_C3IRSfs
 image_divc, 147

- nppiDivC_16sc_C3RSfs
image_divc, 148
- nppiDivC_16u_AC4IRSfs
image_divc, 148
- nppiDivC_16u_AC4RSfs
image_divc, 148
- nppiDivC_16u_C1IRSfs
image_divc, 149
- nppiDivC_16u_C1RSfs
image_divc, 149
- nppiDivC_16u_C3IRSfs
image_divc, 150
- nppiDivC_16u_C3RSfs
image_divc, 150
- nppiDivC_16u_C4IRSfs
image_divc, 150
- nppiDivC_16u_C4RSfs
image_divc, 151
- nppiDivC_32f_AC4IR
image_divc, 151
- nppiDivC_32f_AC4R
image_divc, 151
- nppiDivC_32f_C1IR
image_divc, 152
- nppiDivC_32f_C1R
image_divc, 152
- nppiDivC_32f_C3IR
image_divc, 152
- nppiDivC_32f_C3R
image_divc, 153
- nppiDivC_32f_C4IR
image_divc, 153
- nppiDivC_32f_C4R
image_divc, 153
- nppiDivC_32fc_AC4IR
image_divc, 154
- nppiDivC_32fc_AC4R
image_divc, 154
- nppiDivC_32fc_C1IR
image_divc, 154
- nppiDivC_32fc_C1R
image_divc, 155
- nppiDivC_32fc_C3IR
image_divc, 155
- nppiDivC_32fc_C3R
image_divc, 155
- nppiDivC_32fc_C4IR
image_divc, 156
- nppiDivC_32fc_C4R
image_divc, 156
- nppiDivC_32s_C1IRSfs
image_divc, 157
- nppiDivC_32s_C1RSfs
image_divc, 157
- nppiDivC_32s_C3IRSfs
image_divc, 157
- nppiDivC_32s_C3RSfs
image_divc, 158
- nppiDivC_32sc_AC4IRSfs
image_divc, 158
- nppiDivC_32sc_AC4RSfs
image_divc, 158
- nppiDivC_32sc_C1IRSfs
image_divc, 159
- nppiDivC_32sc_C1RSfs
image_divc, 159
- nppiDivC_32sc_C3IRSfs
image_divc, 160
- nppiDivC_32sc_C3RSfs
image_divc, 160
- nppiDivC_8u_AC4IRSfs
image_divc, 160
- nppiDivC_8u_AC4RSfs
image_divc, 161
- nppiDivC_8u_C1IRSfs
image_divc, 161
- nppiDivC_8u_C1RSfs
image_divc, 162
- nppiDivC_8u_C3IRSfs
image_divc, 162
- nppiDivC_8u_C3RSfs
image_divc, 162
- nppiDivC_8u_C4IRSfs
image_divc, 163
- nppiDivC_8u_C4RSfs
image_divc, 163
- nppiExp_16s_C1IRSfs
image_exp, 362
- nppiExp_16s_C1RSfs
image_exp, 362
- nppiExp_16s_C3IRSfs
image_exp, 363
- nppiExp_16s_C3RSfs
image_exp, 363
- nppiExp_16u_C1IRSfs
image_exp, 363
- nppiExp_16u_C1RSfs
image_exp, 364
- nppiExp_16u_C3IRSfs
image_exp, 364
- nppiExp_16u_C3RSfs
image_exp, 364
- nppiExp_32f_C1IR
image_exp, 365
- nppiExp_32f_C1R
image_exp, 365
- nppiExp_32f_C3IR
image_exp, 365

- nppiExp_32f_C3R
 - image_exp, 366
- nppiExp_8u_C1RSfs
 - image_exp, 366
- nppiExp_8u_C1RSfs
 - image_exp, 366
- nppiExp_8u_C3RSfs
 - image_exp, 367
- nppiExp_8u_C3RSfs
 - image_exp, 367
- NppiHaarBuffer, 499
 - haarBuffer, 499
 - haarBufferSize, 499
- NppiHaarClassifier_32f, 500
 - classifiers, 500
 - classifierSize, 500
 - classifierStep, 500
 - counterDevice, 500
 - numClassifiers, 500
- NppiHuffmanTableType
 - typedefs_npp, 40
- NppiInterpolationMode
 - typedefs_npp, 41
- nppiLn_16s_C1RSfs
 - image_ln, 355
- nppiLn_16s_C1RSfs
 - image_ln, 355
- nppiLn_16s_C3RSfs
 - image_ln, 356
- nppiLn_16s_C3RSfs
 - image_ln, 356
- nppiLn_16u_C1RSfs
 - image_ln, 356
- nppiLn_16u_C1RSfs
 - image_ln, 357
- nppiLn_16u_C3RSfs
 - image_ln, 357
- nppiLn_16u_C3RSfs
 - image_ln, 357
- nppiLn_32f_C1IR
 - image_ln, 358
- nppiLn_32f_C1R
 - image_ln, 358
- nppiLn_32f_C3IR
 - image_ln, 358
- nppiLn_32f_C3R
 - image_ln, 359
- nppiLn_8u_C1RSfs
 - image_ln, 359
- nppiLn_8u_C1RSfs
 - image_ln, 359
- nppiLn_8u_C3RSfs
 - image_ln, 360
- nppiLn_8u_C3RSfs
 - image_ln, 360
- nppiLShiftC_16u_AC4IR
 - image_lshiftc, 421
- nppiLShiftC_16u_AC4R
 - image_lshiftc, 421
- nppiLShiftC_16u_C1IR
 - image_lshiftc, 421
- nppiLShiftC_16u_C1R
 - image_lshiftc, 422
- nppiLShiftC_16u_C3IR
 - image_lshiftc, 422
- nppiLShiftC_16u_C3R
 - image_lshiftc, 422
- nppiLShiftC_16u_C4IR
 - image_lshiftc, 423
- nppiLShiftC_16u_C4R
 - image_lshiftc, 423
- nppiLShiftC_32s_AC4IR
 - image_lshiftc, 423
- nppiLShiftC_32s_AC4R
 - image_lshiftc, 424
- nppiLShiftC_32s_C1IR
 - image_lshiftc, 424
- nppiLShiftC_32s_C1R
 - image_lshiftc, 424
- nppiLShiftC_32s_C3IR
 - image_lshiftc, 425
- nppiLShiftC_32s_C3R
 - image_lshiftc, 425
- nppiLShiftC_32s_C4IR
 - image_lshiftc, 425
- nppiLShiftC_32s_C4R
 - image_lshiftc, 426
- nppiLShiftC_8u_AC4IR
 - image_lshiftc, 426
- nppiLShiftC_8u_AC4R
 - image_lshiftc, 426
- nppiLShiftC_8u_C1IR
 - image_lshiftc, 427
- nppiLShiftC_8u_C1R
 - image_lshiftc, 427
- nppiLShiftC_8u_C3IR
 - image_lshiftc, 427
- nppiLShiftC_8u_C3R
 - image_lshiftc, 428
- nppiLShiftC_8u_C4IR
 - image_lshiftc, 428
- nppiLShiftC_8u_C4R
 - image_lshiftc, 428
- NppiMaskSize
 - typedefs_npp, 41
- nppiMul_16s_AC4RSfs
 - image_mul, 211
- nppiMul_16s_AC4RSfs

- image_mul, [211](#)
- nppiMul_16s_C1IRSfs
 - image_mul, [212](#)
- nppiMul_16s_C1RSfs
 - image_mul, [212](#)
- nppiMul_16s_C3IRSfs
 - image_mul, [213](#)
- nppiMul_16s_C3RSfs
 - image_mul, [213](#)
- nppiMul_16s_C4IRSfs
 - image_mul, [213](#)
- nppiMul_16s_C4RSfs
 - image_mul, [214](#)
- nppiMul_16sc_AC4IRSfs
 - image_mul, [214](#)
- nppiMul_16sc_AC4RSfs
 - image_mul, [215](#)
- nppiMul_16sc_C1IRSfs
 - image_mul, [215](#)
- nppiMul_16sc_C1RSfs
 - image_mul, [215](#)
- nppiMul_16sc_C3IRSfs
 - image_mul, [216](#)
- nppiMul_16sc_C3RSfs
 - image_mul, [216](#)
- nppiMul_16u_AC4IRSfs
 - image_mul, [217](#)
- nppiMul_16u_AC4RSfs
 - image_mul, [217](#)
- nppiMul_16u_C1IRSfs
 - image_mul, [218](#)
- nppiMul_16u_C1RSfs
 - image_mul, [218](#)
- nppiMul_16u_C3IRSfs
 - image_mul, [218](#)
- nppiMul_16u_C3RSfs
 - image_mul, [219](#)
- nppiMul_16u_C4IRSfs
 - image_mul, [219](#)
- nppiMul_16u_C4RSfs
 - image_mul, [220](#)
- nppiMul_32f_AC4IR
 - image_mul, [220](#)
- nppiMul_32f_AC4R
 - image_mul, [220](#)
- nppiMul_32f_C1IR
 - image_mul, [221](#)
- nppiMul_32f_C1R
 - image_mul, [221](#)
- nppiMul_32f_C3IR
 - image_mul, [222](#)
- nppiMul_32f_C3R
 - image_mul, [222](#)
- nppiMul_32f_C4IR
 - image_mul, [222](#)
- nppiMul_32f_C4R
 - image_mul, [223](#)
- nppiMul_32fc_AC4IR
 - image_mul, [223](#)
- nppiMul_32fc_AC4R
 - image_mul, [223](#)
- nppiMul_32fc_C1IR
 - image_mul, [224](#)
- nppiMul_32fc_C1R
 - image_mul, [224](#)
- nppiMul_32fc_C3IR
 - image_mul, [225](#)
- nppiMul_32fc_C3R
 - image_mul, [225](#)
- nppiMul_32fc_C4IR
 - image_mul, [225](#)
- nppiMul_32fc_C4R
 - image_mul, [226](#)
- nppiMul_32s_C1IRSfs
 - image_mul, [226](#)
- nppiMul_32s_C1R
 - image_mul, [227](#)
- nppiMul_32s_C1RSfs
 - image_mul, [227](#)
- nppiMul_32s_C3IRSfs
 - image_mul, [227](#)
- nppiMul_32s_C3RSfs
 - image_mul, [228](#)
- nppiMul_32sc_AC4IRSfs
 - image_mul, [228](#)
- nppiMul_32sc_AC4RSfs
 - image_mul, [229](#)
- nppiMul_32sc_C1IRSfs
 - image_mul, [229](#)
- nppiMul_32sc_C1RSfs
 - image_mul, [229](#)
- nppiMul_32sc_C3IRSfs
 - image_mul, [230](#)
- nppiMul_32sc_C3RSfs
 - image_mul, [230](#)
- nppiMul_8u_AC4IRSfs
 - image_mul, [231](#)
- nppiMul_8u_AC4RSfs
 - image_mul, [231](#)
- nppiMul_8u_C1IRSfs
 - image_mul, [232](#)
- nppiMul_8u_C1RSfs
 - image_mul, [232](#)
- nppiMul_8u_C3IRSfs
 - image_mul, [232](#)
- nppiMul_8u_C3RSfs
 - image_mul, [233](#)
- nppiMul_8u_C4IRSfs

- image_mul, 233
- nppiMulc_8u_C4RSfs
 - image_mul, 234
- nppiMulC_16s_AC4IRSfs
 - image_mulc, 84
- nppiMulC_16s_AC4RSfs
 - image_mulc, 84
- nppiMulC_16s_C1IRSfs
 - image_mulc, 84
- nppiMulC_16s_C1RSfs
 - image_mulc, 85
- nppiMulC_16s_C3IRSfs
 - image_mulc, 85
- nppiMulC_16s_C3RSfs
 - image_mulc, 85
- nppiMulC_16s_C4IRSfs
 - image_mulc, 86
- nppiMulC_16s_C4RSfs
 - image_mulc, 86
- nppiMulC_16sc_AC4IRSfs
 - image_mulc, 87
- nppiMulC_16sc_AC4RSfs
 - image_mulc, 87
- nppiMulC_16sc_C1IRSfs
 - image_mulc, 87
- nppiMulC_16sc_C1RSfs
 - image_mulc, 88
- nppiMulC_16sc_C3IRSfs
 - image_mulc, 88
- nppiMulC_16sc_C3RSfs
 - image_mulc, 89
- nppiMulC_16u_AC4IRSfs
 - image_mulc, 89
- nppiMulC_16u_AC4RSfs
 - image_mulc, 89
- nppiMulC_16u_C1IRSfs
 - image_mulc, 90
- nppiMulC_16u_C1RSfs
 - image_mulc, 90
- nppiMulC_16u_C3IRSfs
 - image_mulc, 91
- nppiMulC_16u_C3RSfs
 - image_mulc, 91
- nppiMulC_16u_C4IRSfs
 - image_mulc, 91
- nppiMulC_16u_C4RSfs
 - image_mulc, 92
- nppiMulC_32f_AC4IR
 - image_mulc, 92
- nppiMulC_32f_AC4R
 - image_mulc, 92
- nppiMulC_32f_C1IR
 - image_mulc, 93
- nppiMulC_32f_C1R
 - image_mulc, 93
- nppiMulC_32f_C3IR
 - image_mulc, 93
- nppiMulC_32f_C3R
 - image_mulc, 94
- nppiMulC_32f_C4IR
 - image_mulc, 94
- nppiMulC_32f_C4R
 - image_mulc, 94
- nppiMulC_32fc_AC4IR
 - image_mulc, 95
- nppiMulC_32fc_AC4R
 - image_mulc, 95
- nppiMulC_32fc_C1IR
 - image_mulc, 95
- nppiMulC_32fc_C1R
 - image_mulc, 96
- nppiMulC_32fc_C3IR
 - image_mulc, 96
- nppiMulC_32fc_C3R
 - image_mulc, 96
- nppiMulC_32fc_C4IR
 - image_mulc, 97
- nppiMulC_32fc_C4R
 - image_mulc, 97
- nppiMulC_32s_C1IRSfs
 - image_mulc, 98
- nppiMulC_32s_C1RSfs
 - image_mulc, 98
- nppiMulC_32s_C3IRSfs
 - image_mulc, 98
- nppiMulC_32s_C3RSfs
 - image_mulc, 99
- nppiMulC_32sc_AC4IRSfs
 - image_mulc, 99
- nppiMulC_32sc_AC4RSfs
 - image_mulc, 99
- nppiMulC_32sc_C1IRSfs
 - image_mulc, 100
- nppiMulC_32sc_C1RSfs
 - image_mulc, 100
- nppiMulC_32sc_C3IRSfs
 - image_mulc, 101
- nppiMulC_32sc_C3RSfs
 - image_mulc, 101
- nppiMulC_8u_AC4IRSfs
 - image_mulc, 101
- nppiMulC_8u_AC4RSfs
 - image_mulc, 102
- nppiMulC_8u_C1IRSfs
 - image_mulc, 102
- nppiMulC_8u_C1RSfs
 - image_mulc, 103
- nppiMulC_8u_C3IRSfs

image_mulc, 103
nppiMulC_8u_C3RSfs
 image_mulc, 103
nppiMulC_8u_C4IRSfs
 image_mulc, 104
nppiMulC_8u_C4RSfs
 image_mulc, 104
nppiMulCScale_16u_AC4IR
 image_mulcscale, 106
nppiMulCScale_16u_AC4R
 image_mulcscale, 106
nppiMulCScale_16u_C1IR
 image_mulcscale, 107
nppiMulCScale_16u_C1R
 image_mulcscale, 107
nppiMulCScale_16u_C3IR
 image_mulcscale, 107
nppiMulCScale_16u_C3R
 image_mulcscale, 108
nppiMulCScale_16u_C4IR
 image_mulcscale, 108
nppiMulCScale_16u_C4R
 image_mulcscale, 108
nppiMulCScale_8u_AC4IR
 image_mulcscale, 109
nppiMulCScale_8u_AC4R
 image_mulcscale, 109
nppiMulCScale_8u_C1IR
 image_mulcscale, 109
nppiMulCScale_8u_C1R
 image_mulcscale, 110
nppiMulCScale_8u_C3IR
 image_mulcscale, 110
nppiMulCScale_8u_C3R
 image_mulcscale, 110
nppiMulCScale_8u_C4IR
 image_mulcscale, 111
nppiMulCScale_8u_C4R
 image_mulcscale, 111
nppiMulScale_16u_AC4IR
 image_mulscale, 236
nppiMulScale_16u_AC4R
 image_mulscale, 237
nppiMulScale_16u_C1IR
 image_mulscale, 237
nppiMulScale_16u_C1R
 image_mulscale, 237
nppiMulScale_16u_C3IR
 image_mulscale, 238
nppiMulScale_16u_C3R
 image_mulscale, 238
nppiMulScale_16u_C4IR
 image_mulscale, 239
nppiMulScale_16u_C4R
 image_mulscale, 239
nppiMulScale_8u_AC4IR
 image_mulscale, 239
nppiMulScale_8u_AC4R
 image_mulscale, 239
nppiMulScale_8u_C1IR
 image_mulscale, 240
nppiMulScale_8u_C1R
 image_mulscale, 241
nppiMulScale_8u_C3IR
 image_mulscale, 241
nppiMulScale_8u_C3R
 image_mulscale, 241
nppiMulScale_8u_C4IR
 image_mulscale, 242
nppiMulScale_8u_C4R
 image_mulscale, 242
NppiNorm
 typedefs_npp, 41
nppiNormInf
 typedefs_npp, 42
nppiNormL1
 typedefs_npp, 42
nppiNormL2
 typedefs_npp, 42
nppiNot_8u_AC4IR
 image_not, 466
nppiNot_8u_AC4R
 image_not, 467
nppiNot_8u_C1IR
 image_not, 467
nppiNot_8u_C1R
 image_not, 467
nppiNot_8u_C3IR
 image_not, 467
nppiNot_8u_C3R
 image_not, 468
nppiNot_8u_C4IR
 image_not, 468
nppiNot_8u_C4R
 image_not, 468
nppiOr_16u_AC4IR
 image_or, 444
nppiOr_16u_AC4R
 image_or, 444
nppiOr_16u_C1IR
 image_or, 444
nppiOr_16u_C1R
 image_or, 445
nppiOr_16u_C3IR
 image_or, 445
nppiOr_16u_C3R
 image_or, 445
nppiOr_16u_C4IR

- image_or, 446
- nppiOr_16u_C4R
 - image_or, 446
- nppiOr_32s_AC4IR
 - image_or, 447
- nppiOr_32s_AC4R
 - image_or, 447
- nppiOr_32s_C1IR
 - image_or, 447
- nppiOr_32s_C1R
 - image_or, 448
- nppiOr_32s_C3IR
 - image_or, 448
- nppiOr_32s_C3R
 - image_or, 448
- nppiOr_32s_C4IR
 - image_or, 449
- nppiOr_32s_C4R
 - image_or, 449
- nppiOr_8u_AC4IR
 - image_or, 450
- nppiOr_8u_AC4R
 - image_or, 450
- nppiOr_8u_C1IR
 - image_or, 450
- nppiOr_8u_C1R
 - image_or, 451
- nppiOr_8u_C3IR
 - image_or, 451
- nppiOr_8u_C3R
 - image_or, 451
- nppiOr_8u_C4IR
 - image_or, 452
- nppiOr_8u_C4R
 - image_or, 452
- nppiOrC_16u_AC4IR
 - image_orc, 382
- nppiOrC_16u_AC4R
 - image_orc, 382
- nppiOrC_16u_C1IR
 - image_orc, 382
- nppiOrC_16u_C1R
 - image_orc, 383
- nppiOrC_16u_C3IR
 - image_orc, 383
- nppiOrC_16u_C3R
 - image_orc, 383
- nppiOrC_16u_C4IR
 - image_orc, 384
- nppiOrC_16u_C4R
 - image_orc, 384
- nppiOrC_32s_AC4IR
 - image_orc, 384
- nppiOrC_32s_AC4R
 - image_orc, 385
- nppiOrC_32s_C1IR
 - image_orc, 385
- nppiOrC_32s_C1R
 - image_orc, 385
- nppiOrC_32s_C3IR
 - image_orc, 386
- nppiOrC_32s_C3R
 - image_orc, 386
- nppiOrC_32s_C4IR
 - image_orc, 386
- nppiOrC_32s_C4R
 - image_orc, 387
- nppiOrC_8u_AC4IR
 - image_orc, 387
- nppiOrC_8u_AC4R
 - image_orc, 387
- nppiOrC_8u_C1IR
 - image_orc, 388
- nppiOrC_8u_C1R
 - image_orc, 388
- nppiOrC_8u_C3IR
 - image_orc, 388
- nppiOrC_8u_C3R
 - image_orc, 389
- nppiOrC_8u_C4IR
 - image_orc, 389
- nppiOrC_8u_C4R
 - image_orc, 389
- NppiPoint, 501
 - x, 501
 - y, 501
- NppiRect, 502
 - height, 502
 - width, 502
 - x, 502
 - y, 502
- nppiRShiftC_16s_AC4IR
 - image_rshiftc, 405
- nppiRShiftC_16s_AC4R
 - image_rshiftc, 405
- nppiRShiftC_16s_C1IR
 - image_rshiftc, 406
- nppiRShiftC_16s_C1R
 - image_rshiftc, 406
- nppiRShiftC_16s_C3IR
 - image_rshiftc, 406
- nppiRShiftC_16s_C3R
 - image_rshiftc, 407
- nppiRShiftC_16s_C4IR
 - image_rshiftc, 407
- nppiRShiftC_16s_C4R
 - image_rshiftc, 407
- nppiRShiftC_16u_AC4IR

- image_rshiftc, 408
- nppiRShiftC_16u_AC4R
 - image_rshiftc, 408
- nppiRShiftC_16u_C1R
 - image_rshiftc, 408
- nppiRShiftC_16u_C1R
 - image_rshiftc, 409
- nppiRShiftC_16u_C3R
 - image_rshiftc, 409
- nppiRShiftC_16u_C3R
 - image_rshiftc, 409
- nppiRShiftC_16u_C4R
 - image_rshiftc, 410
- nppiRShiftC_16u_C4R
 - image_rshiftc, 410
- nppiRShiftC_32s_AC4IR
 - image_rshiftc, 410
- nppiRShiftC_32s_AC4R
 - image_rshiftc, 411
- nppiRShiftC_32s_C1R
 - image_rshiftc, 411
- nppiRShiftC_32s_C1R
 - image_rshiftc, 411
- nppiRShiftC_32s_C3R
 - image_rshiftc, 412
- nppiRShiftC_32s_C3R
 - image_rshiftc, 412
- nppiRShiftC_32s_C4R
 - image_rshiftc, 412
- nppiRShiftC_32s_C4R
 - image_rshiftc, 413
- nppiRShiftC_8s_AC4IR
 - image_rshiftc, 413
- nppiRShiftC_8s_AC4R
 - image_rshiftc, 413
- nppiRShiftC_8s_C1R
 - image_rshiftc, 414
- nppiRShiftC_8s_C1R
 - image_rshiftc, 414
- nppiRShiftC_8s_C3R
 - image_rshiftc, 414
- nppiRShiftC_8s_C3R
 - image_rshiftc, 415
- nppiRShiftC_8s_C4R
 - image_rshiftc, 415
- nppiRShiftC_8s_C4R
 - image_rshiftc, 415
- nppiRShiftC_8u_AC4IR
 - image_rshiftc, 416
- nppiRShiftC_8u_AC4R
 - image_rshiftc, 416
- nppiRShiftC_8u_C1R
 - image_rshiftc, 416
- nppiRShiftC_8u_C1R
 - image_rshiftc, 417
- nppiRShiftC_8u_C3IR
 - image_rshiftc, 417
- nppiRShiftC_8u_C3R
 - image_rshiftc, 417
- nppiRShiftC_8u_C4IR
 - image_rshiftc, 418
- nppiRShiftC_8u_C4R
 - image_rshiftc, 418
- NppiSize, 503
 - height, 503
 - width, 503
- nppiSqr_16s_AC4IRSfs
 - image_sqr, 331
- nppiSqr_16s_AC4RSfs
 - image_sqr, 331
- nppiSqr_16s_C1IRSfs
 - image_sqr, 331
- nppiSqr_16s_C1RSfs
 - image_sqr, 331
- nppiSqr_16s_C3IRSfs
 - image_sqr, 332
- nppiSqr_16s_C3RSfs
 - image_sqr, 332
- nppiSqr_16s_C4IRSfs
 - image_sqr, 332
- nppiSqr_16s_C4RSfs
 - image_sqr, 333
- nppiSqr_16u_AC4IRSfs
 - image_sqr, 333
- nppiSqr_16u_AC4RSfs
 - image_sqr, 333
- nppiSqr_16u_C1IRSfs
 - image_sqr, 334
- nppiSqr_16u_C1RSfs
 - image_sqr, 334
- nppiSqr_16u_C3IRSfs
 - image_sqr, 335
- nppiSqr_16u_C3RSfs
 - image_sqr, 335
- nppiSqr_16u_C4IRSfs
 - image_sqr, 335
- nppiSqr_16u_C4RSfs
 - image_sqr, 336
- nppiSqr_32f_AC4IR
 - image_sqr, 336
- nppiSqr_32f_AC4R
 - image_sqr, 336
- nppiSqr_32f_C1IR
 - image_sqr, 337
- nppiSqr_32f_C1R
 - image_sqr, 337
- nppiSqr_32f_C3IR
 - image_sqr, 337

- nppiSqr_32f_C3R
 image_sqr, 337
- nppiSqr_32f_C4IR
 image_sqr, 338
- nppiSqr_32f_C4R
 image_sqr, 338
- nppiSqr_8u_AC4IRSfs
 image_sqr, 338
- nppiSqr_8u_AC4RSfs
 image_sqr, 339
- nppiSqr_8u_C1IRSfs
 image_sqr, 339
- nppiSqr_8u_C1RSfs
 image_sqr, 339
- nppiSqr_8u_C3IRSfs
 image_sqr, 340
- nppiSqr_8u_C3RSfs
 image_sqr, 340
- nppiSqr_8u_C4IRSfs
 image_sqr, 340
- nppiSqr_8u_C4RSfs
 image_sqr, 341
- nppiSqrt_16s_AC4IRSfs
 image_sqrt, 344
- nppiSqrt_16s_AC4RSfs
 image_sqrt, 344
- nppiSqrt_16s_C1IRSfs
 image_sqrt, 345
- nppiSqrt_16s_C1RSfs
 image_sqrt, 345
- nppiSqrt_16s_C3IRSfs
 image_sqrt, 346
- nppiSqrt_16s_C3RSfs
 image_sqrt, 346
- nppiSqrt_16u_AC4IRSfs
 image_sqrt, 346
- nppiSqrt_16u_AC4RSfs
 image_sqrt, 347
- nppiSqrt_16u_C1IRSfs
 image_sqrt, 347
- nppiSqrt_16u_C1RSfs
 image_sqrt, 347
- nppiSqrt_16u_C3IRSfs
 image_sqrt, 348
- nppiSqrt_16u_C3RSfs
 image_sqrt, 348
- nppiSqrt_32f_AC4IR
 image_sqrt, 348
- nppiSqrt_32f_AC4R
 image_sqrt, 349
- nppiSqrt_32f_C1IR
 image_sqrt, 349
- nppiSqrt_32f_C1R
 image_sqrt, 349
- nppiSqrt_32f_C3IR
 image_sqrt, 350
- nppiSqrt_32f_C3R
 image_sqrt, 350
- nppiSqrt_32f_C4IR
 image_sqrt, 350
- nppiSqrt_32f_C4R
 image_sqrt, 351
- nppiSqrt_8u_AC4IRSfs
 image_sqrt, 351
- nppiSqrt_8u_AC4RSfs
 image_sqrt, 351
- nppiSqrt_8u_C1IRSfs
 image_sqrt, 352
- nppiSqrt_8u_C1RSfs
 image_sqrt, 352
- nppiSqrt_8u_C3IRSfs
 image_sqrt, 353
- nppiSqrt_8u_C3RSfs
 image_sqrt, 353
- nppiSub_16s_AC4IRSfs
 image_sub, 249
- nppiSub_16s_AC4RSfs
 image_sub, 250
- nppiSub_16s_C1IRSfs
 image_sub, 250
- nppiSub_16s_C1RSfs
 image_sub, 250
- nppiSub_16s_C3IRSfs
 image_sub, 251
- nppiSub_16s_C3RSfs
 image_sub, 251
- nppiSub_16s_C4IRSfs
 image_sub, 252
- nppiSub_16s_C4RSfs
 image_sub, 252
- nppiSub_16sc_AC4IRSfs
 image_sub, 252
- nppiSub_16sc_AC4RSfs
 image_sub, 253
- nppiSub_16sc_C1IRSfs
 image_sub, 253
- nppiSub_16sc_C1RSfs
 image_sub, 254
- nppiSub_16sc_C3IRSfs
 image_sub, 254
- nppiSub_16sc_C3RSfs
 image_sub, 254
- nppiSub_16u_AC4IRSfs
 image_sub, 255
- nppiSub_16u_AC4RSfs
 image_sub, 255
- nppiSub_16u_C1IRSfs
 image_sub, 256

- nppiSub_16u_C1RSfs
 - image_sub, [256](#)
- nppiSub_16u_C3IRSfs
 - image_sub, [257](#)
- nppiSub_16u_C3RSfs
 - image_sub, [257](#)
- nppiSub_16u_C4IRSfs
 - image_sub, [257](#)
- nppiSub_16u_C4RSfs
 - image_sub, [258](#)
- nppiSub_32f_AC4IR
 - image_sub, [258](#)
- nppiSub_32f_AC4R
 - image_sub, [259](#)
- nppiSub_32f_C1IR
 - image_sub, [259](#)
- nppiSub_32f_C1R
 - image_sub, [259](#)
- nppiSub_32f_C3IR
 - image_sub, [260](#)
- nppiSub_32f_C3R
 - image_sub, [260](#)
- nppiSub_32f_C4IR
 - image_sub, [261](#)
- nppiSub_32f_C4R
 - image_sub, [261](#)
- nppiSub_32fc_AC4IR
 - image_sub, [261](#)
- nppiSub_32fc_AC4R
 - image_sub, [262](#)
- nppiSub_32fc_C1IR
 - image_sub, [262](#)
- nppiSub_32fc_C1R
 - image_sub, [263](#)
- nppiSub_32fc_C3IR
 - image_sub, [263](#)
- nppiSub_32fc_C3R
 - image_sub, [263](#)
- nppiSub_32fc_C4IR
 - image_sub, [264](#)
- nppiSub_32fc_C4R
 - image_sub, [264](#)
- nppiSub_32s_C1IRSfs
 - image_sub, [265](#)
- nppiSub_32s_C1R
 - image_sub, [265](#)
- nppiSub_32s_C1RSfs
 - image_sub, [265](#)
- nppiSub_32s_C3IRSfs
 - image_sub, [266](#)
- nppiSub_32s_C3RSfs
 - image_sub, [266](#)
- nppiSub_32s_C4IRSfs
 - image_sub, [267](#)
- nppiSub_32s_C4RSfs
 - image_sub, [267](#)
- nppiSub_32sc_AC4IRSfs
 - image_sub, [268](#)
- nppiSub_32sc_AC4RSfs
 - image_sub, [268](#)
- nppiSub_32sc_C1IRSfs
 - image_sub, [268](#)
- nppiSub_32sc_C1RSfs
 - image_sub, [269](#)
- nppiSub_32sc_C3IRSfs
 - image_sub, [269](#)
- nppiSub_32sc_C3RSfs
 - image_sub, [270](#)
- nppiSub_8u_AC4IRSfs
 - image_sub, [270](#)
- nppiSub_8u_AC4RSfs
 - image_sub, [270](#)
- nppiSub_8u_C1IRSfs
 - image_sub, [271](#)
- nppiSub_8u_C1RSfs
 - image_sub, [271](#)
- nppiSub_8u_C3IRSfs
 - image_sub, [272](#)
- nppiSub_8u_C3RSfs
 - image_sub, [272](#)
- nppiSub_8u_C4IRSfs
 - image_sub, [272](#)
- nppiSub_8u_C4RSfs
 - image_sub, [273](#)
- nppiSubC_16s_AC4IRSfs
 - image_subc, [117](#)
- nppiSubC_16s_AC4RSfs
 - image_subc, [117](#)
- nppiSubC_16s_C1IRSfs
 - image_subc, [117](#)
- nppiSubC_16s_C1RSfs
 - image_subc, [118](#)
- nppiSubC_16s_C3IRSfs
 - image_subc, [118](#)
- nppiSubC_16s_C3RSfs
 - image_subc, [118](#)
- nppiSubC_16s_C4IRSfs
 - image_subc, [119](#)
- nppiSubC_16s_C4RSfs
 - image_subc, [119](#)
- nppiSubC_16sc_AC4IRSfs
 - image_subc, [120](#)
- nppiSubC_16sc_AC4RSfs
 - image_subc, [120](#)
- nppiSubC_16sc_C1IRSfs
 - image_subc, [120](#)
- nppiSubC_16sc_C1RSfs
 - image_subc, [121](#)

- nppiSubC_16sc_C3IRSfs
 image_subc, 121
 nppiSubC_16sc_C3RSfs
 image_subc, 122
 nppiSubC_16u_AC4IRSfs
 image_subc, 122
 nppiSubC_16u_AC4RSfs
 image_subc, 122
 nppiSubC_16u_C1IRSfs
 image_subc, 123
 nppiSubC_16u_C1RSfs
 image_subc, 123
 nppiSubC_16u_C3IRSfs
 image_subc, 124
 nppiSubC_16u_C3RSfs
 image_subc, 124
 nppiSubC_16u_C4IRSfs
 image_subc, 124
 nppiSubC_16u_C4RSfs
 image_subc, 125
 nppiSubC_32f_AC4IR
 image_subc, 125
 nppiSubC_32f_AC4R
 image_subc, 125
 nppiSubC_32f_C1IR
 image_subc, 126
 nppiSubC_32f_C1R
 image_subc, 126
 nppiSubC_32f_C3IR
 image_subc, 126
 nppiSubC_32f_C3R
 image_subc, 127
 nppiSubC_32f_C4IR
 image_subc, 127
 nppiSubC_32f_C4R
 image_subc, 127
 nppiSubC_32fc_AC4IR
 image_subc, 128
 nppiSubC_32fc_AC4R
 image_subc, 128
 nppiSubC_32fc_C1IR
 image_subc, 128
 nppiSubC_32fc_C1R
 image_subc, 129
 nppiSubC_32fc_C3IR
 image_subc, 129
 nppiSubC_32fc_C3R
 image_subc, 129
 nppiSubC_32fc_C4IR
 image_subc, 130
 nppiSubC_32fc_C4R
 image_subc, 130
 nppiSubC_32s_C1IRSfs
 image_subc, 131
 nppiSubC_32s_C1RSfs
 image_subc, 131
 nppiSubC_32s_C3IRSfs
 image_subc, 131
 nppiSubC_32s_C3RSfs
 image_subc, 132
 nppiSubC_32sc_AC4IRSfs
 image_subc, 132
 nppiSubC_32sc_AC4RSfs
 image_subc, 132
 nppiSubC_32sc_C1IRSfs
 image_subc, 133
 nppiSubC_32sc_C1RSfs
 image_subc, 133
 nppiSubC_32sc_C3IRSfs
 image_subc, 134
 nppiSubC_32sc_C3RSfs
 image_subc, 134
 nppiSubC_8u_AC4IRSfs
 image_subc, 134
 nppiSubC_8u_AC4RSfs
 image_subc, 135
 nppiSubC_8u_C1IRSfs
 image_subc, 135
 nppiSubC_8u_C1RSfs
 image_subc, 136
 nppiSubC_8u_C3IRSfs
 image_subc, 136
 nppiSubC_8u_C3RSfs
 image_subc, 136
 nppiSubC_8u_C4IRSfs
 image_subc, 137
 nppiSubC_8u_C4RSfs
 image_subc, 137
 nppiXor_16u_AC4IR
 image_xor, 456
 nppiXor_16u_AC4R
 image_xor, 456
 nppiXor_16u_C1IR
 image_xor, 456
 nppiXor_16u_C1R
 image_xor, 457
 nppiXor_16u_C3IR
 image_xor, 457
 nppiXor_16u_C3R
 image_xor, 457
 nppiXor_16u_C4IR
 image_xor, 458
 nppiXor_16u_C4R
 image_xor, 458
 nppiXor_32s_AC4IR
 image_xor, 459
 nppiXor_32s_AC4R
 image_xor, 459

- nppiXor_32s_C1IR
 - image_xor, 459
- nppiXor_32s_C1R
 - image_xor, 460
- nppiXor_32s_C3IR
 - image_xor, 460
- nppiXor_32s_C3R
 - image_xor, 460
- nppiXor_32s_C4IR
 - image_xor, 461
- nppiXor_32s_C4R
 - image_xor, 461
- nppiXor_8u_AC4IR
 - image_xor, 462
- nppiXor_8u_AC4R
 - image_xor, 462
- nppiXor_8u_C1IR
 - image_xor, 462
- nppiXor_8u_C1R
 - image_xor, 463
- nppiXor_8u_C3IR
 - image_xor, 463
- nppiXor_8u_C3R
 - image_xor, 463
- nppiXor_8u_C4IR
 - image_xor, 464
- nppiXor_8u_C4R
 - image_xor, 464
- nppiXorC_16u_AC4IR
 - image_xorc, 393
- nppiXorC_16u_AC4R
 - image_xorc, 393
- nppiXorC_16u_C1IR
 - image_xorc, 393
- nppiXorC_16u_C1R
 - image_xorc, 394
- nppiXorC_16u_C3IR
 - image_xorc, 394
- nppiXorC_16u_C3R
 - image_xorc, 394
- nppiXorC_16u_C4IR
 - image_xorc, 395
- nppiXorC_16u_C4R
 - image_xorc, 395
- nppiXorC_32s_AC4IR
 - image_xorc, 395
- nppiXorC_32s_AC4R
 - image_xorc, 396
- nppiXorC_32s_C1IR
 - image_xorc, 396
- nppiXorC_32s_C1R
 - image_xorc, 396
- nppiXorC_32s_C3IR
 - image_xorc, 397
- nppiXorC_32s_C3R
 - image_xorc, 397
- nppiXorC_32s_C4IR
 - image_xorc, 397
- nppiXorC_32s_C4R
 - image_xorc, 398
- nppiXorC_8u_AC4IR
 - image_xorc, 398
- nppiXorC_8u_AC4R
 - image_xorc, 398
- nppiXorC_8u_C1IR
 - image_xorc, 399
- nppiXorC_8u_C1R
 - image_xorc, 399
- nppiXorC_8u_C3IR
 - image_xorc, 399
- nppiXorC_8u_C3R
 - image_xorc, 400
- nppiXorC_8u_C4IR
 - image_xorc, 400
- nppiXorC_8u_C4R
 - image_xorc, 400
- NppLibraryVersion, 504
 - build, 504
 - major, 504
 - minor, 504
- NppRoundMode
 - typedefs_npp, 42
- nppSetStream
 - core_npp, 29
- NppStatus
 - typedefs_npp, 42
- NppsZCType
 - typedefs_npp, 44
- nppZCC
 - typedefs_npp, 45
- nppZCR
 - typedefs_npp, 45
- nppZCXor
 - typedefs_npp, 45
- numClassifiers
 - NppiHaarClassifier_32f, 500
- Or, 442
- OrC, 380
- re
 - NPP_ALIGN_16, 496
 - NPP_ALIGN_8, 497, 498
- RShiftC, 402
- Sqr, 328
- Sqrt, 342
- Sub, 244

SubC, 112

typedefs_npp

NPP_AFFINE_QUAD_INCORRECT_ -
WARNING, 44

NPP_ALG_HINT_ACCURATE, 39

NPP_ALG_HINT_FAST, 39

NPP_ALG_HINT_NONE, 39

NPP_ALIGNMENT_ERROR, 43

NPP_ANCHOR_ERROR, 43

NPP_BAD_ARGUMENT_ERROR, 44

NPP_BORDER_CONSTANT, 40

NPP_BORDER_MIRROR, 40

NPP_BORDER_NONE, 40

NPP_BORDER_REPLICATE, 40

NPP_BORDER_UNDEFINED, 40

NPP_BORDER_WRAP, 40

NPP_BOTH_AXIS, 40

NPP_CHANNEL_ERROR, 43

NPP_CHANNEL_ORDER_ERROR, 43

NPP_CMP_EQ, 39

NPP_CMP_GREATER, 39

NPP_CMP_GREATER_EQ, 39

NPP_CMP_LESS, 38

NPP_CMP_LESS_EQ, 38

NPP_COEFFICIENT_ERROR, 43

NPP_COI_ERROR, 43

NPP_CONTEXT_MATCH_ERROR, 44

NPP_CORRUPTED_DATA_ERROR, 43

NPP_CUDA_1_0, 39

NPP_CUDA_1_1, 39

NPP_CUDA_1_2, 39

NPP_CUDA_1_3, 39

NPP_CUDA_2_0, 39

NPP_CUDA_2_1, 39

NPP_CUDA_3_0, 39

NPP_CUDA_3_2, 39

NPP_CUDA_3_5, 39

NPP_CUDA_3_7, 39

NPP_CUDA_5_0, 39

NPP_CUDA_5_2, 39

NPP_CUDA_5_3, 39

NPP_CUDA_6_0, 39

NPP_CUDA_KERNEL_EXECUTION_ -
ERROR, 43

NPP_CUDA_NOT_CAPABLE, 39

NPP_CUDA_UNKNOWN_VERSION, 39

NPP_DATA_TYPE_ERROR, 44

NPP_DIVIDE_BY_ZERO_ERROR, 44

NPP_DIVIDE_BY_ZERO_WARNING, 44

NPP_DIVISOR_ERROR, 43

NPP_DOUBLE_SIZE_WARNING, 44

NPP_ERROR, 44

NPP_ERROR_RESERVED, 44

NPP_FFT_FLAG_ERROR, 44

NPP_FFT_ORDER_ERROR, 44

NPP_FILTER_SCHARR, 40

NPP_FILTER_SOBEL, 40

NPP_HAAR_CLASSIFIER_PIXEL_ -
MATCH_ERROR, 43

NPP_HISTOGRAM_NUMBER_OF_ -
LEVELS_ERROR, 43

NPP_HORIZONTAL_AXIS, 40

NPP_INTERPOLATION_ERROR, 44

NPP_INVALID_DEVICE_POINTER_ -
ERROR, 43

NPP_INVALID_HOST_POINTER_ERROR,
43

NPP_LUT_NUMBER_OF_LEVELS_ -
ERROR, 43

NPP_LUT_PALETTE_BITSIZE_ERROR, 43

NPP_MASK_SIZE_11_X_11, 41

NPP_MASK_SIZE_13_X_13, 41

NPP_MASK_SIZE_15_X_15, 41

NPP_MASK_SIZE_1_X_3, 41

NPP_MASK_SIZE_1_X_5, 41

NPP_MASK_SIZE_3_X_1, 41

NPP_MASK_SIZE_3_X_3, 41

NPP_MASK_SIZE_5_X_1, 41

NPP_MASK_SIZE_5_X_5, 41

NPP_MASK_SIZE_7_X_7, 41

NPP_MASK_SIZE_9_X_9, 41

NPP_MASK_SIZE_ERROR, 43

NPP_MEMCPY_ERROR, 43

NPP_MEMFREE_ERROR, 43

NPP_MEMORY_ALLOCATION_ERR, 44

NPP_MEMSET_ERROR, 43

NPP_MIRROR_FLIP_ERROR, 44

NPP_MISALIGNED_DST_ROI_WARNING,
44

NPP_MOMENT_00_ZERO_ERROR, 44

NPP_NO_ERROR, 44

NPP_NO_MEMORY_ERROR, 44

NPP_NO_OPERATION_WARNING, 44

NPP_NOT_EVEN_STEP_ERROR, 43

NPP_NOT_IMPLEMENTED_ERROR, 44

NPP_NOT_SUFFICIENT_COMPUTE_ -
CAPABILITY, 43

NPP_NOT_SUPPORTED_MODE_ERROR,
43

NPP_NULL_POINTER_ERROR, 44

NPP_NUMBER_OF_CHANNELS_ERROR,
43

NPP_OUT_OFF_RANGE_ERROR, 44

NPP_OVERFLOW_ERROR, 43

NPP_QUADRANGLE_ERROR, 43

NPP_QUALITY_INDEX_ERROR, 43

NPP_RANGE_ERROR, 44

- NPP_RECTANGLE_ERROR, 43
- NPP_RESIZE_FACTOR_ERROR, 44
- NPP_RESIZE_NO_OPERATION_ERROR, 43
- NPP_RND_FINANCIAL, 42
- NPP_RND_NEAR, 42
- NPP_RND_ZERO, 42
- NPP_ROUND_MODE_NOT_SUPPORTED_ERROR, 43
- NPP_ROUND_NEAREST_TIES_AWAY_FROM_ZERO, 42
- NPP_ROUND_NEAREST_TIES_TO_EVEN, 42
- NPP_ROUND_TOWARD_ZERO, 42
- NPP_SCALE_RANGE_ERROR, 44
- NPP_SIZE_ERROR, 44
- NPP_STEP_ERROR, 44
- NPP_STRIDE_ERROR, 43
- NPP_SUCCESS, 44
- NPP_TEXTURE_BIND_ERROR, 43
- NPP_THRESHOLD_ERROR, 44
- NPP_THRESHOLD_NEGATIVE_LEVEL_ERROR, 44
- NPP_VERTICAL_AXIS, 40
- NPP_WRONG_INTERSECTION_QUAD_WARNING, 44
- NPP_WRONG_INTERSECTION_ROI_ERROR, 43
- NPP_WRONG_INTERSECTION_ROI_WARNING, 44
- NPP_ZC_MODE_NOT_SUPPORTED_ERROR, 43
- NPP_ZERO_MASK_VALUE_ERROR, 43
- NPPI_BAYER_BGGR, 40
- NPPI_BAYER_GBRG, 40
- NPPI_BAYER_GRBG, 40
- NPPI_BAYER_RGGB, 40
- NPPI_INTER_CUBIC, 41
- NPPI_INTER_CUBIC2P_B05C03, 41
- NPPI_INTER_CUBIC2P_BSPLINE, 41
- NPPI_INTER_CUBIC2P_CATMULLROM, 41
- NPPI_INTER_LANCZOS, 41
- NPPI_INTER_LANCZOS3_ADVANCED, 41
- NPPI_INTER_LINEAR, 41
- NPPI_INTER_NN, 41
- NPPI_INTER_SUPER, 41
- NPPI_INTER_UNDEFINED, 41
- NPPI_OP_ALPHA_ATOP, 39
- NPPI_OP_ALPHA_ATOP_PREMUL, 40
- NPPI_OP_ALPHA_IN, 39
- NPPI_OP_ALPHA_IN_PREMUL, 40
- NPPI_OP_ALPHA_OUT, 39
- NPPI_OP_ALPHA_OUT_PREMUL, 40
- NPPI_OP_ALPHA_OVER, 39
- NPPI_OP_ALPHA_OVER_PREMUL, 40
- NPPI_OP_ALPHA_PLUS, 39
- NPPI_OP_ALPHA_PLUS_PREMUL, 40
- NPPI_OP_ALPHA_PREMUL, 40
- NPPI_OP_ALPHA_XOR, 39
- NPPI_OP_ALPHA_XOR_PREMUL, 40
- NPPI_SMOOTH_EDGE, 41
- nppiACTable, 41
- nppiDCTable, 41
- nppiNormInf, 42
- nppiNormL1, 42
- nppiNormL2, 42
- nppZCC, 45
- nppZCR, 45
- nppZCXor, 45
- typedefs_npp
 - NPP_MAX_16S, 37
 - NPP_MAX_16U, 37
 - NPP_MAX_32S, 37
 - NPP_MAX_32U, 37
 - NPP_MAX_64S, 37
 - NPP_MAX_64U, 37
 - NPP_MAX_8S, 37
 - NPP_MAX_8U, 37
 - NPP_MAXABS_32F, 37
 - NPP_MAXABS_64F, 37
 - NPP_MIN_16S, 37
 - NPP_MIN_16U, 38
 - NPP_MIN_32S, 38
 - NPP_MIN_32U, 38
 - NPP_MIN_64S, 38
 - NPP_MIN_64U, 38
 - NPP_MIN_8S, 38
 - NPP_MIN_8U, 38
 - NPP_MINABS_32F, 38
 - NPP_MINABS_64F, 38
 - NppCmpOp, 38
 - NppGpuComputeCapability, 39
 - NppHintAlgorithm, 39
 - NppiAlphaOp, 39
 - NppiAxis, 40
 - NppiBayerGridPosition, 40
 - NppiBorderType, 40
 - NppiDifferentialKernel, 40
 - NppiHuffmanTableType, 40
 - NppiInterpolationMode, 41
 - NppiMaskSize, 41
 - NppiNorm, 41
 - NppRoundMode, 42
 - NppStatus, 42
 - NppsZCType, 44
- width

NppiRect, [502](#)
NppiSize, [503](#)

x

NppiPoint, [501](#)
NppiRect, [502](#)
Xor, [454](#)
XorC, [391](#)

y

NppiPoint, [501](#)
NppiRect, [502](#)